

ESET RESEARCH

No “Game over” for the Winnti Group

The notorious APT group continues to play the video game industry with yet another backdoor

 **Mathieu Tartare**

 **Martin Smolár**

21 May 2020 • 18 min. read



Share Article











 Digital Security
Progress. Protected.

APT Activity Report

IRAN-ALIGNED CYBERATTACKS:
RISE IN DISRUPTIVE OPERATIONS

(eset):research

READ NOW



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

Accept all and close

Manage cookies

In February 2020, we discovered a new, modular backdoor, which we named PipeMon. Persisting as a Print Processor, it was used by the Winnti Group against several video gaming companies that are based in South Korea and Taiwan and develop MMO (Massively Multiplayer Online) games. Video games developed by these companies are available on popular gaming platforms and have thousands of simultaneous players.

In at least one case, the malware operators compromised a victim's build system, which could have led to a supply-chain attack, allowing the attackers to trojanize game executables. In another case, the game servers were compromised, which could have allowed the attackers to, for example, manipulate in-game currencies for financial gain.

The Winnti Group, active since at least 2012, is responsible for high-profile supply-chain attacks against the software industry, leading to the distribution of trojanized software (such as [CCleaner](#), [ASUS LiveUpdate](#) and [multiple video games](#)) that is then used to compromise more victims. Recently, ESET researchers also discovered a [campaign of the Winnti Group targeting several Hong Kong universities](#) with ShadowPad and Winnti malware.

*About the “Winnti Group” naming:
We have chosen to keep the name “Winnti Group” since it’s the name first used to identify it, in 2013, by Kaspersky. Since Winnti is also a malware family, we always write “Winnti Group” when we refer to the malefactors behind the attacks. Since 2013, it has been demonstrated that Winnti is only one of the many malware families used by the Winnti Group.*

Attribution to the Winnti Group

Multiple indicators led us to attribute this campaign to the Winnti Group. Some of the C&C domains used by PipeMon were used by Winnti malware in previous campaigns mentioned in [our white paper on the Winnti Group arsenal](#). Besides, Winnti malware was also found in 2019 at some of the companies that were later compromised with PipeMon.



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

tial harvester) binary
a well-known stolen
during this campaign.

and additional tools is
a [supply-chain attack in](#)
time.

sed in the past to drop

vironment to
modus operandi of

Targeted companies

Companies targeted in this campaign are video game developers, producing MMO games and based in South Korea and Taiwan. In at least one case, the attackers were able to compromise the company's build orchestration server, allowing them to take control of the automated build systems. This could have allowed the attackers to include arbitrary code of their choice in the video game executables.

ESET contacted the affected companies and provided the necessary information to remediate the compromise.

Technical analysis

Two different variants of PipeMon were found at the targeted companies. Only for the more recent variant were we able to identify the first stage which is responsible for installing and persisting PipeMon.

First stage

PipeMon's first stage consists of a password-protected RARSFX executable embedded in the `.rsrc` section of its launcher. The launcher writes the RARSFX to `setup0.exe` in a directory named with a randomly generated, eight-character, ASCII string located in the directory returned by `GetTempPath`. Once written to disk, the RARSFX is executed with `CreateProcess` by providing the decryption password in an argument, as follows:

```
setup0.exe -p*|T/PMR{|T2^LWJ*
```

Note that the password is different with each sample.

The content of the RARSFX is then extracted into `%TMP%\RarSFX0` and consists of the following files:

- `CrLnc.dat` – Encrypted payload
- `Duser.dll` – Used for UAC bypass
- `osksupport.dll` – Used for UAC bypass



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

Initialization

load `PrintDialog.dll`

r at the end of the
urther, not all these
e installer.

s. Its sole purpose is to
.dll checks whether

an argument in the format `-x:n` (where `n` is an integer) was provided: the mode of

operation will be different depending on the presence of `n`. Supported arguments and their corresponding behavior are shown in Table 1. `setup.exe` is executed without arguments by the RARSFX, and checks whether it's running with elevated privileges. If not, it will attempt to obtain such privileges using [token impersonation](#) if the version of Windows is below Windows 7 build 7601; otherwise it will attempt different [UAC bypass techniques](#), allowing installation of the payload loader into one of:


- `C:\Windows\System32\spool\prtprocs\x64\DEment.dll`
- `C:\Windows\System32\spool\prtprocs\x64\EntAppsvc.dll`
- `C:\Windows\System32\spool\prtprocs\x64\Interactive.dll`

depending on the variant. Note that we weren't able to retrieve samples related to `Interactive.dll`.

Table 1. `setup.exe` supported arguments and their corresponding behavior.

Command line argument value	Behavior
-x:0	Load the payload loader.
-x:1	Attempt to enable <code>SeLoadDriverPrivilege</code> for the current process. If successful, attempt to install the payload loader; otherwise, restart <code>setup.exe</code> with the <code>-x:2</code> argument using parent process spoofing.
-x:2	Attempt to enable <code>SeLoadDriverPrivilege</code> for the current process. If successful, attempt to install the payload loader.

This loader is stored encrypted within `setup.dll`, which will decrypt it before writing it to the aforementioned location.



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

Drivers

chosen randomly. This is `setup.dll` registers by setting one of the

```
...nments\Windows
iver =

...vironments\Windows
svc.dll"
```

depending on the variant. Note the typo in `PrintFiiterPipelineSvc` (which has no impact on the Print Processor installation since any name can be used).

After having registered the Print Processor, PipeMon restarts the print spooler service (`spoolsv.exe`). As a result, the malicious print process is loaded when the spooler service starts. Note that the Print Spooler service starts at each PC startup, which ensures persistence across system resets.

This technique is really similar to the [Print Monitor persistence technique](#) (being used by [DePriMon](#), for example) and, to our knowledge, has not been documented previously.

Additionally, the encrypted payload, `CrInc.dat`, extracted from the RARSFX is written to the registry at the following location, depending on the installer:

- HKLM\SOFTWARE\Microsoft\Print\Components\DC20FD7E-4B1B-4B88-8172-61F0BED7D9E8
- HKLM\SOFTWARE\Microsoft\Print\Components\A66F35-4164-45FF-9CB4-69ACAA10E52D

This encrypted registry payload is then loaded, decrypted and executed by the previously registered Print Processor library. The whole PipeMon staging and persistence is shown in Figure 1.




Figure 1. PipeMon staging and persistence



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

...ple named pipes for
..., the name of the

...ere found. Considering
...don't know for sure the
...his first variant of
...t's likely that the same

Original filename

PipeMon is a modular backdoor where each module is a single DLL exporting a function called `IntelLoader` and is loaded using a [reflective loading](#) technique. Each module exhibits different functionalities that are shown in Table 2.

The loader, responsible for loading the main modules (`ManagerMain` and `GuardClient`) is `Win32CmdDll.dll` and is located in the Print Processors directory. The modules are stored encrypted on disk at the same location with inoffensive-looking names such as:

-  `banner.bmp`
-  `certificate.cert`
-  `License.hwp`
-  `JSONDIU7c9djE`
-  `D8JNCKS0DJE`
-  `B0SDFUWEkNCj.logN`

Note that `.hwp` is the extension used by Hangul Word Processor from Hangul Office, which is very popular in South Korea.

The modules are RC4 encrypted and the decryption key `Com!123QasdZ` is hardcoded into each module. `Win32CmdDll.dll` decrypts and injects the `ManagerMain` and `GuardClient` modules. The `ManagerMain` module is responsible for decrypting and injecting the Communication module, while the `GuardClient` module will ensure that the Communication module is running and reload it if necessary. An overview of how PipeMon operates is shown in Figure 2.

`Win32CmdDll.dll` first tries to inject the `ManagerMain` and `GuardClient` modules into a process with one of the following names: `lsass.exe`, `wininit.exe` or `lsmd.exe`. If that fails, it tries to inject into one of the registered windows services processes, excluding processes named `spoolsv.exe`, `ekrn.exe` (ESET), `avp.exe` (Kaspersky) or `dllhost.exe`. As a last option, if everything else failed, it tries to use the processes `taskhost.exe`, `taskhostw.exe` or `explorer.exe`.

The process candidates for Communication module injection must be in the TCP

or an ESTABLISHED state. These conditions are likely used to ensure the process is already communicating with the Internet. The Communication module would seem to be designed to inject into a process if no process meets the above criteria. The process to inject the module is likely belonging to the user (e.g., `taskhost.exe` or `taskhostw.exe`) and `avpui.exe` (Kaspersky).

The Communication module is responsible for establishing a connection with the C&C server.

The Communication module is responsible for establishing a connection with the C&C server.

The Communication module is responsible for establishing a connection with the C&C server.

The Communication module is responsible for establishing a connection with the C&C server.

The Communication module is responsible for establishing a connection with the C&C server.

The Communication module is responsible for establishing a connection with the C&C server.

The Communication module is responsible for establishing a connection with the C&C server.



Your account, your cookies choice

We and our partners use cookies to give you the best online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

Name

Win32CmdDll	Decrypts and loads the ManagerMain and GuardClient modules.	S:\Monitor\Monitor_RAW\Launcher\x64\Release\Win32CmdDll.dll S:\Monitor\Monitor_RAW\libs\x64\Release\Win32CmdDll.dll
GuardClient	Periodically checks whether the Communication module is running and loads it if not.	S:\Monitor\Monitor_RAW\Client\x64\Release\GuardClient.dll
ManagerMain	Loads Communication module when executed. Contains encrypted C&C domain which is passed to the Communication module via named pipe. Can execute several commands based on the data received from the Communication module (mostly system information collecting,	S:\Monitor\Monitor_RAW\Client\x64\Release\ManagerMain.exe



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

Additional modules can be loaded on-demand using dedicated commands (see

below), but unfortunately, we weren't able to discover any of them. The names of these modules are an educated guess based on the named pipes used to communicate with them:

- Screen
- Route
- CMD
- InCmd
- File

Inter-module communication

Inter-module communication is performed via named pipes, using two named pipes per communication channel between each individual module, one for sending and one for receiving. Table 3 lists the communication channels and their corresponding named pipes.

Table 3. PipeMon communication channel and their respective named pipes

Communication channel	Named pipe
Communication, Screen	\\.\pipe\ScreenPipeRead%CNC_DEFINED%
	\\.\pipe\ScreenPipeWrite%CNC_DEFINED%
Communication, Route	\\.\pipe\RoutePipeWriite%B64_TIMESTAMP%
Communication, ManagerMain	\\.\pipe\MainPipeWrite%B64_TIMESTAMP%
	\\.\pipe\MainPipeRead%B64_TIMESTAMP%
GuardClient, ManagerMain	\\.\pipe\MainHeatPipeRead%B64_TIMESTAMP%
Communication, InCmd	\\.\pipe\InCmdPipeWrite%B64_TIMESTAMP%
	\\.\pipe\InCmdPipeRead%B64_TIMESTAMP%



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

Table 4. Example timestamps used with named pipes

%BASE64_TIMESTAMP%	Decoded timestamp
MjAxOTAyMjgxMDE1Mzc=	20190228101537
MjAxOTA1MjEyMzU2MjQ=	20190521235624
MjAxOTExMjE2MjY=	20191121121626





Figure 2. PipeMon IPC scheme (original PipeMon variant)

C&C communication

The Communication module is responsible for managing communications between the C&C server and the other modules via named pipes, similar to the [Winnti arsenal](#).



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

BYTE is_compressed;

```
CMD cmd;
};

struct CMD
{
    QWORD cmd_type;
    DWORD cmd_size;
    DWORD cmd_arg;
    BYTE data[cmd_size - 16];
};

struct beacon_msg
{
    BYTE isCompressed = 0;
    CMD cmd_hdr;
    WCHAR win_version[128];
    WCHAR adapters_addrs[128];
    WCHAR adapters_addrs[64];
    WCHAR local_addr[64];
    WCHAR malware_version[64];
    WCHAR computer_name[64];
}
```

Figure 3. C&C message and beacon formats

To initiate communication with the C&C server, a beacon message is first sent that contains the following information:

- OS version
- physical addresses of connected network adapters concatenated with %B64_TIMESTAMP%
- victim's local IP address
- backdoor version/campaign ID; we've observed the following values
 - "1.1.1.4beat"
 - "1.1.1.4Bata"



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

the ManagerMain
ned pipe. The backdoor
text.
the supported

type	argument	
0x02	0x03	Install the File module
0x03	0x03	Install the CMD module
0x03	0x0B	Install the InCmd module
0x04	0x02	Queue command for the Route module
0x04	0x03	Install the Route module
0x05	*	Send victim’s RDP information to the C&C server
0x06	0x05	Send OS, CPU, PC and time zone information to the C&C server
0x06	0x06	Send network information to the C&C server
0x06	0x07	Send disk drive information to the C&C server
0x07	*	Send running processes information to the C&C server
0x09	*	DLL injection
0x0C	0x15	Send names of "InCmd" pipes and events to the C&C server
0x0C	0x16	Send name of "Route" pipe to the C&C server
0x0C	0x17	Send names of "File" pipes to the C&C server

* The argument supplied for this command type is ignored



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

sion of PipeMon for
ove. While exhibiting an
as likely rewritten from

replaced by a simple
ngs were removed.
now named using
e
only generated string
acters.

Here, only the main loader (i.e. the malicious DLL installed as a Print Processor) is stored as a file on disk; the modules are stored in the registry by the installer (from the `CrLnc.dat` file) and are described in Table 6.

Table 6. Updated modules

Module name	Description
CoreLnc.dll	Loaded by the malicious Print Processor. Responsible only for loading the <code>Core.dll</code> module embedded in its <code>.data</code> section.
Core.dll	Loads the <code>Net.dll</code> module embedded in its <code>.data</code> section. Handles commands from the C&C server and communications between individual modules and the C&C server through named pipes.
Net.dll	New Communication module. Handles the networking.

Module injection is not performed using the reflective loading technique with an export function anymore; custom loader shellcode is used instead and is injected along with the module to be loaded.

The C&C message format was changed as well, and is shown in Figure 4.

```
struct CCMSG
{
    BYTE is_compressed;
    CMD cmd;
};

struct CMD
{
    QWORD cmd_type;
    DWORD cmd_size;
    DWORD cmd_arg;
    BYTE data[cmd_size - 16];
};
```



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

- Name of the registry value
- Campaign identifier
- C&C IP addresses or domain names
- Timestamp (in FILETIME format) corresponding to the date from which to start using a second C&C domain marked with '#' in the configuration.

An example of a configuration dump embedded in the loader DLL is shown in Figure 5. Configurations extracted from several loader DLLs are shown in Table 7.






Table 7. Configuration extracted from several loaders

<div><div></div><div><h3>Your account, your cookies choice</h3><p>We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our Cookie Policy.</p></div></div>	Payload registry name	C&C
	DC20FD7E-4B1B-4B88-8172-61F0BED7D9E8	154.2 ssl2. #clie
	DC20FD7E-4B1B-4B88-8172-61F0BED7D9E8	203.8 ssl2. #clie

		203.8
		DC20FD7E-
		www2.
		4B1B-4B88-
7ca43f3612db0891b2c4c8ccab1543f581d0d10c	kor1	(note
		8172-
		dyn.t
		61F0BED7D9E8
		of dy
		#nmn.
		A66F35-4164-
b02ad3e8b1cf0b78ad9239374d535a0ac57bf27e	tw1	45FF-9CB4-
		ssl.1
		69ACAA10E52D

Stolen code-signing certificate

PipeMon modules and installers are all signed with the same valid code-signing certificate that was likely stolen during a previous campaign of the Winnti Group. The certificate's owner revoked it as soon as they were notified of the issue.



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

and modules before (top)

We found on a sample sharing platform other tools signed with this certificate, such as [HTRan](#), a connection bouncer, the [WinEggDrop](#) port scanner, Netcat, and Mimikatz which may have been used by the attackers as well.

Furthermore, a custom AceHash build signed with a Wemade IO stolen certificate already mentioned in [our previous white paper](#) and usually used by the Winnti Group was found on some machines compromised with PipeMon.

Conclusion

Once again, the Winnti Group has targeted video game developers in Asia with a new modular backdoor signed with a code-signing certificate likely stolen during a previous campaign and sharing some similarities with the PortReuse backdoor. This new implant shows that the Winnti Group is still actively developing new tools using multiple open source projects; they don't rely solely on their flagship backdoors, ShadowPad and the Winnti malware.

We will continue to monitor new activities of the Winnti Group and will publish relevant information on our blog. For any inquiries, contact us at threatintel@eset.com. The IoCs are also available at [our GitHub repository](#).

Indicators of Compromise

ESET detection names

Win64/PipeMon.A
Win64/PipeMon.B
Win64/PipeMon.C
Win64/PipeMon.D
Win64/PipeMon.E

Filenames

100.exe
103.exe
Slack.exe
setup.exe



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

mz64x.exe

- - -

Named pipes

```
\\.\pipe\ScreenPipeRead%CNC_DEFINED%
\\.\pipe\ScreenPipeWrite%CNC_DEFINED%
\\.\pipe\RoutePipeWriite%B64_TIMESTAMP%
\\.\pipe>MainPipeWrite%B64_TIMESTAMP%
\\.\pipe>MainPipeRead%B64_TIMESTAMP%
\\.\pipe>MainHeatPipeRead%B64_TIMESTAMP%
\\.\pipe\InCmdPipeWrite%B64_TIMESTAMP%
\\.\pipe\InCmdPipeRead%B64_TIMESTAMP%
\\.\pipe\FilePipeRead%B64_TIMESTAMP%
\\.\pipe\FilePipeWrite%B64_TIMESTAMP%
\\.\pipe\ComHeatPipeRead%B64_TIMESTAMP%
\\.\pipe\CMDPipeRead
\\.\pipe\CMDPipeWrite
```

Registry

```
HKLM\SYSTEM\ControlSet001\Control\Print\Environments\Windows
x64\Print Processors\PrintFiilterPipelineSvc\Driver =
“DEment.dll”
```

```
HKLM\SYSTEM\CurrentControlSet\Control\Print\Environments\Windows
x64\Print Processors\lltdsvcl\Driver = “EntAppsvc.dll”
```

```
HKLM\SOFTWARE\Microsoft\Print\Components\DC20FD7E-4B1B-4B88-
8172-61F0BED7D9E8
HKLM\SOFTWARE\Microsoft\Print\Components\A66F35-4164-45FF-9CB4-
69ACAA10E52D
```

Samples

First stage

```
4B90E2E2D1DEA7889DC15059E11E11353FA621A6
C7A9DCD4F9B2F26F50E8DD7F96352AEC7C4123FE
```



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

PipeMon encrypted binaries

168101B9B3B512583B3CE6531CFCE6E5FB581409
C887B35EA883F8622F7C48EC9D0427AFE833BF46
44D0A2A43ECC8619DE8DB99C1465DB4E3C8FF995
E17972F1A3C667EEBB155A228278AA3B5F89F560
C03BE8BB8D03BE24A6C5CF2ED14EDFCEFA8E8429
2B0481C61F367A99987B7EC0ADE4B6995425151C

Additional tools

WinEggDrop

AF9C220D177B0B54A790C6CC135824E7C829B681

Mimikatz

4A240EDEF042AE3CE47E8E42C2395DB43190909D

Netcat

751A9CBFFEC28B22105CDCAF073A371DE255F176

HTran

48230228B69D764F71A7BF8C08C85436B503109E

AceHash

D24BBB898A4A301870CAB85F836090B0FC968163

Code-signing certificate SHA-1 thumbprints

745EAC99E03232763F98FB6099F575DFC7BDFAA3
2830DE648BF0A521320036B96CE0D82BEF05994C

C&C domains



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

MITRE ATT&CK techniques

Tactic	ID	Name	Description
Persistence	T1013	Port Monitor	PipeMon uses a persistence technique similar to Port Monitor based on Print Processors.
	T1134	Access Token Manipulation	The PipeMon installer tries to gain administrative privileges using token impersonation.
	T1088	Bypass User Account Control	The PipeMon installer uses UAC bypass techniques to install the payload.
Privilege Escalation	T1502	Parent PID Spoofing	The PipeMon installer uses parent PID spoofing to elevate privileges.
	T1116	Code Signing	PipeMon, its installer and additional tools are signed with stolen code-signing certificates.
	T1027	Obfuscate Files or Information	PipeMon modules are stored encrypted on disk.
Defense			



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

The PipeMon installer modifies the registry to install PipeMon as a Print Processor.

PipeMon injects its modules into various processes using reflective loading.

PipeMon iterates over the running processes to find a suitable injection target.

	TI063	Security Software discovery	PipeMon checks for the presence of ESET and Kaspersky software.
Collection	TI113	Screen Capture	One of the PipeMon modules is likely a screenshotter.
Command and Control	TI043	Commonly Used Ports	PipeMon communicates through port 443.
TI095	Custom Command and Control Protocol	PipeMon communication module uses a custom protocol based on TLS over TCP.	
TI032	Standard Cryptographic Protocol	PipeMon communication is RC4 encrypted.	
TI008	Fallback Channels	The updated PipeMon version uses a fallback channel once a particular date is reached.	

Let us keep you up to date

Sign up for our newsletters



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).

ESET RESEARCH
CloudScout: Evasive
Panda scouting cloud
services

ESET RESEARCH
ESET Research
Podcast:
CosmicBeetle

ESET RESEARCH
Embargo
ransomware:
Rock’n’Rust

Discussion

What do you think?
9 Responses


Upvote


Funny



Love


Surprised


Angry








Sad


0 Comments 1 Login ▼



Start the discussion...

LOG IN WITH



OR SIGN UP WITH DISQUS 



• Share

Best

Newest

Oldest

welivesecurity™

BY 

Award-winning news, views, and insight from the ESET security community

- About us
- Contact us
- Legal Information
- RSS Feed

- ESET
- Privacy Policy
- Manage Cookies



Your account, your cookies choice

We and our partners use cookies to give you the best optimized online experience, analyze our website traffic, and serve you with personalized ads. You can agree to the collection of all cookies by clicking "Accept all and close" or adjust your cookie settings by clicking "Manage cookies". You also have the right to withdraw your consent to cookies anytime. For more information, please see our [Cookie Policy](#).