

Product

▼

Solutions

▼

Resources

▼

Open Source

▼

Enterprise

▼

Pricing

Q

Search

Sign in

Sign up

redcanaryco

/

atomic-red-team

Public

Notifications

Fork2.8k

Star9.7k

<>Code

Issues6

Pull requests5

Actions

Wiki

Security

Insights

atomic-red-team / atomics / T1547.004 / T1547.004.md

Atomic Red Team doc generat...

Generated docs from job=generate-d... 819934c · 2 years ago

History

# T1547.004 - Winlogon Helper DLL

## Description from ATT&CK

Adversaries may abuse features of Winlogon to execute DLLs and/or executables when a user logs in. Winlogon.exe is a Windows component responsible for actions at logon/logoff as well as the secure attention sequence (SAS) triggered by Ctrl-Alt-Delete. Registry entries in HKLM\Software[\Wow6432Node\]\Microsoft\Windows NT\CurrentVersion\Winlogon\ and HKCU\Software\Microsoft\Windows NT\CurrentVersion\Winlogon\ are used to manage additional helper programs and functionalities that support Winlogon.(Citation: Cylance Reg Persistence Sept 2013) Malicious modifications to these Registry keys may cause Winlogon to load and execute malicious DLLs and/or executables. Specifically, the following subkeys have been known to be possibly vulnerable to abuse: (Citation: Cylance Reg Persistence Sept 2013)

- Winlogon\Notify - points to notification package DLLs that handle Winlogon events
- Winlogon\Userinit - points to userinit.exe, the user initialization program executed when a user logs on
- Winlogon\Shell - points to explorer.exe, the system shell executed when a user logs on

Adversaries may take advantage of these features to repeatedly execute malicious code and establish persistence.

## Atomic Tests

- [Atomic Test #1 - Winlogon Shell Key Persistence - PowerShell](#)
- [Atomic Test #2 - Winlogon Userinit Key Persistence - PowerShell](#)
- [Atomic Test #3 - Winlogon Notify Key Logon Persistence - PowerShell](#)

## Atomic Test #1 - Winlogon Shell Key Persistence - PowerShell

PowerShell code to set Winlogon shell key to execute a binary at logon along with explorer.exe.

Upon successful execution, PowerShell will modify a registry value to execute cmd.exe upon logon/logoff.

Page 1 of 3

Files

f339e7d

Go to file

> .github

> atomic\_red\_team

> atomics

- > Indexes
- > T1003.001
- > T1003.002
- > T1003.003
- > T1003.004
- > T1003.005
- > T1003.006
- > T1003.007
- > T1003.008
- > T1003
- > T1006
- > T1007
- > T1010
- > T1012
- > T1013

Supported Platforms: Windows

auto\_generated\_guid: bf9f9d65-ee4d-4c3e-a843-777d04f19c38

Inputs:

Name	Description	Type	Default Value
binary_to_execute	Path of binary to execute	Path	C:\Windows\System32\cmd.exe

Attack Commands: Run with powershell !

```
Set-ItemProperty "HKCU:\Software\Microsoft\Windows NT\CurrentVersion\Win
```

Cleanup Commands:

```
Remove-ItemProperty -Path "HKCU:\Software\Microsoft\Windows NT\CurrentVe
```

## Atomic Test #2 - Winlogon Userinit Key Persistence - PowerShell

PowerShell code to set Winlogon userinit key to execute a binary at logon along with userinit.exe.

Upon successful execution, PowerShell will modify a registry value to execute cmd.exe upon logon/logoff.

Supported Platforms: Windows

atomic-red-team / atomics / T1547.004 / T1547.004.md

↑ Top

PreviewCodeBlame139 lines (70 loc) · 4.68 KBRawCopyDownloadMenu

Name	Description	Type	Default Value
binary_to_execute	Path of binary to execute	Path	C:\Windows\System32\cmd.exe

Attack Commands: Run with powershell !

```
Set-ItemProperty "HKCU:\Software\Microsoft\Windows NT\CurrentVersion\Win
```

Cleanup Commands:


























```
Remove-ItemProperty -Path "HKCU:\Software\Microsoft\Windows NT\CurrentVe
```

## Atomic Test #3 - Winlogon Notify Key Logon Persistence - PowerShell

PowerShell code to set Winlogon Notify key to execute a notification package DLL at logon.

Upon successful execution, PowerShell will modify a registry value to execute atomicNotificationPackage.dll upon logon/logoff.

Page 2 of 3

- >  T1014
- >  T1016
- >  T1018
- >  T1020
- >  T1021.001
- >  T1021.002
- >  T1021.003
- >  T1021.006
- >  T1027.001
- >  T1027.002
- >  T1027.004
- >  T1027
- >  T1030
- >  T1033
- >  T1036.003
- >  T1036.004
- >  T1036.005
- >  T1036.006
- >  T1036
- >  T1037.001
- >  T1037.002
- >  T1037.004
- >  T1037.005
- >  T1039
- >  T1040

Supported Platforms: Windows

auto\_generated\_guid: d40da266-e073-4e5a-bb8b-2b385023e5f9

Inputs:

Name	Description	Type	Default Value
binary_to_execute	Path of notification package to execute	Path	C:\Windows\Temp\atomicNotificationPacka

Attack Commands: Run with powershell!

```
New-Item "HKCU:\Software\Microsoft\Windows NT\CurrentVersion\Winlogon\No
Set-ItemProperty "HKCU:\Software\Microsoft\Windows NT\CurrentVersion\Win
```

Cleanup Commands:

```
Remove-Item "HKCU:\Software\Microsoft\Windows NT\CurrentVersion\Winlogon
```