



Download Now: An Introduction to Exposure Validation E-book



# PICUS



# How to Detect Parent PID (PPID) Spoofing Attacks

Huseyin Can YUCEEL & Eren KARABACAK | January 19, 2022

## The Blue Report 2024

Get a comprehensive analysis of over 136 million cyber attacks and understand the state of threat exposure management.

**DOWNLOAD**

Parent Process ID (PPID) spoofing attacks are commonly used for defense evasion and privilege escalation. Although default Windows security logs are able to detect some

cyberattacks, detecting Parent Process ID spoofing attacks requires utilizing additional log types that are not enabled in default configuration. In this article, we will talk in detail about:

- Process ID and its types
- Event Tracing For Windows (ETW)
- Parent Process ID spoofing attacks and example
- Detection of Parent Process ID spoofing attacks using Kernel-Process Logs

## 1. What is Process ID?

**Process ID (PID)** is a unique number that identifies any process currently running on the operating system. In Windows, **Process ID** can be viewed using various tools and commands such as **tasklist** and **wmic** commands or **Process Explorer** in Sysinternals. In Linux and Unix, the **ps** command lists PIDs. PID can be used to call or kill a process.

When a process spawns another process, it becomes a parent process, and the spawned process becomes a child process. Process IDs of these processes are recorded in event logs. For example, Kernel-Process logs of *Process A* keep three types of PID records:

- Process ID: PID of *Process A*
- Parent Process ID: PID of the parent process of *Process A*
- Execution Process ID: PID of the process that executes *Process A*

### 1.1 Viewing Process ID in Windows

Let's show how to view Process ID in Windows using **tasklist** and **wmic** command-line tools. Also, **Process Explorer** shown in Figure 1 is an easy-to-use alternative to view Process ID.

```
> tasklist /fi "IMAGENAME eq explorer.exe"

Image Name          PID Session Name      Session#  Mem Usage
=====
explorer.exe        4700 Console             1    267,936 K

> tasklist /fi "IMAGENAME eq ProcessExplorer.exe"
```

```
Image Name          PID Session Name      Session#  Mem Usage
=====
ProcessExplorer.exe  4960 Console           1    55,880 K

> wmic process where (processid=14324) get parentprocessid
ParentProcessId
4700
```

Process Explorer - Sysinternals: [www.sysinternals.com](http://www.sysinternals.com) [MSEDGEWIN10\IEUser]

File Options View Process Find Users Help

Process	PID	CPU	Private Bytes	Working Set	Description	Company Name
Registry	88		1,796 K	150,296 K		
System Idle Process	0	98.59	56 K	8 K		
System	4	< 0.01	192 K	124 K		
csrss.exe	408	< 0.01	1,712 K	5,020 K		
wininit.exe	484		1,344 K	6,800 K		
csrss.exe	492	< 0.01	25,844 K	92,740 K		
winlogon.exe	552		2,956 K	12,980 K		
explorer.exe	4700	< 0.01	55,616 K	113,260 K	Windows Explorer	Microsoft Corporation
SecurityHealthSystray.exe	7112		1,776 K	8,760 K	Windows Security notificatio...	Microsoft Corporation
vm3dservice.exe	7316		1,756 K	7,360 K	VMware SVGA Helper Service	VMware, Inc.
vmtoolsd.exe	7528	< 0.01	19,740 K	41,024 K	VMware Tools Core Service	VMware, Inc.
OneDrive.exe	7632		23,124 K	79,832 K	Microsoft OneDrive	Microsoft Corporation
ProcessExplorer.exe	4960	1.54	29,196 K	42,556 K	Sysinternals Process Explorer	Sysinternals - www.sysinte...

Figure 1: Process Explorer

## 2. Event Tracing for Windows

**Event Tracing for Windows (ETW)** is a kernel-level monitoring tool to monitor kernel or application-level logs in real-time [1]. These logs can be used to debug an application or detect performance issues.




Figure 2: Event Tracing Model

**ETW** consists of 3 components;

- **Controllers:** The modules that
  - define size and location of the log file
  - start and stop event tracing sessions
  - enable providers to log events to the session
- **Providers:** The modules that produce event logs
  - generate events
  - produce event logs when enabled by a controller
- **Consumers:** The modules that use the generated event logs

## 2.1. How to Start an Event Tracing Session?

**ETW** structure allows dynamic management of event tracing sessions. Event tracing sessions can be started and managed by built-in controllers such as the logman command and perfmon tool.

### 2.1.1. Starting Event Trace Session with logman

logman is a built-in Windows command-line tool included in the controller group of ETW components. logman can start and control event trace sessions. Let's see some examples of usage of logman.

- List available providers on Windows

```
> logman query providers
```

Provider	GUID
-----	
.NET Common Language Runtime	{E13C0D23-CCBC-4E12-931B-D9CC2EEE27E4}
ACPI Driver Trace Provider	{DAB01D4D-2D48-477D-B1C3-DAAD0CE6F06B}
Active Directory Domain Services: SAM	{8E598056-8993-11D2-819E-0000F875A064}
Active Directory: Kerberos Client	{BBA3ADD2-C229-4CDB-AE2B-57EB6966B0C4}
Active Directory: NetLogon	{F33959B4-DBEC-11D2-895B-00C04F79AB69}
ADODB.1	{04C8A86F-3369-12F8-4769-24E484A9E725}
ADOMD.1	{7EA56435-3F2F-3F63-A829-F0B35B5CAD41}
Application Popup	{47BFA2B7-BD54-4FAC-B70B-29021084CA8F}
Application-Addon-Event-Provider	{A83FA99F-C356-4DED-9FD6-5A5EB8546D68}
ATA Port Driver Tracing Provider	{D08BD885-501E-489A-BAC6-B7D24BFE6BBF}
AuthFw NetShell Plugin	{935F4AE6-845D-41C6-97FA-380DAD429B72}
...	

- List the providers that are currently tracing and working in Windows

```
> logman query -ets
```

Data Collector Set	Type	Status
-----		
Circular Kernel Context Logger	Trace	Running
AppModel	Trace	Running
DiagLog	Trace	Running
Diagtrack-Listener	Trace	Running
EventLog-Application	Trace	Running
EventLog-System	Trace	Running
iclsClient	Trace	Running

iclsProxy	Trace	Running
Microsoft-Windows-Kernel-Process	Trace	Running
SgrmEtwSession	Trace	Running
...		

- Look into details of any provider with their GUID

```
> logman query providers {22FB2CD6-0E7B-422B-A0C7-2FAD1FD0E716}
```

Provider	GUID
-----	
Microsoft-Windows-Kernel-Process	{22FB2CD6-0E7B-422B-A0C7-2FAD1FD0E716}

Value	Keyword	Description
-----		
0x0000000000000010	WINEVENT_KEYWORD_PROCESS	
0x0000000000000020	WINEVENT_KEYWORD_THREAD	
0x0000000000000040	WINEVENT_KEYWORD_IMAGE	
0x0000000000000080	WINEVENT_KEYWORD_CPU_PRIORITY	
0x0000000000000100	WINEVENT_KEYWORD_OTHER_PRIORITY	
0x0000000000000200	WINEVENT_KEYWORD_PROCESS_FREEZE	
0x0000000000000400	WINEVENT_KEYWORD_JOB	
0x0000000000000800	WINEVENT_KEYWORD_ENABLE_PROCESS_TRACING_CALLBACKS	
0x0000000000001000	WINEVENT_KEYWORD_JOB_IO	
0x0000000000002000	WINEVENT_KEYWORD_WORK_ON_BEHALF	
0x0000000000004000	WINEVENT_KEYWORD_JOB_SILO	
0x8000000000000000	Microsoft-Windows-Kernel-Process/Analytic	

Value	Level	Description
-----		
0x04	win:Informational	Information

PID	Image
-----	
0x00000000	

Providers may produce multiple log types categorized with different keywords. When setting up a data collector, log types to be collected are selected using these keywords.

The example log shown below can be retrieved when the WINEVENT\_KEYWORD\_WORK\_ON\_BEHALF keyword from **Microsoft-Windows-Kernel-Process** is assigned to an event trace session

```
-<Event xmlns="http://schemas.microsoft.com/win/2004/08/events/event">
-<System>
  <Provider Name="Microsoft-Windows-Kernel-Process" Guid="{22fb2cd6-0e7b-422b-a0c7-2fad1fd0e716}" />
  <EventID>21</EventID>
  <Version>0</Version>
  <Level>4</Level>
  <Task>18</Task>
  <Opcode>0</Opcode>
  <Keywords>0x8000000000002000</Keywords>
  <TimeCreated SystemTime="2022-01-10T13:01:49.527905100Z" />
  <EventRecordID>20</EventRecordID>
  <Correlation />
  <Execution ProcessID="1068" ThreadID="3716" ProcessorID="1" KernelTime="1" UserTime="1" />
  <Channel>Microsoft-Windows-Kernel-Process/Analytic</Channel>
  <Computer>MSEDGEWIN10</Computer>
  <Security />
</System>
-<EventData>
  <Data Name="OldWorkOnBehalfThreadID">0</Data>
  <Data Name="NewWorkOnBehalfThreadID">1432</Data>
</EventData>
</Event>
```

- Start a new event trace session

```
> logman create trace "Sample-trace" -ets
```

The command completed successfully.

- Assign the provider and select logs to be collected for the new event trace session

```
> logman update Sample-trace -p Microsoft-Windows-Kernel-Process 0x70 -ets
```

The command completed successfully.

```
> logman query Sample-trace -ets
```

Name: Sample-trace

Status: Running

Root Path: C:\

Segment: Off

Schedules: On

Name: Sample-trace\Sample-trace

Type: Trace

Output Location: C:\Sample-trace.etl

Append: Off

Circular: Off

Overwrite: Off

Buffer Size: 8

Buffers Lost: 0

Buffers Written: 2

Buffer Flush Timer: 0

Clock Type: Performance

File Mode: File

Provider:

Name: Microsoft-Windows-Kernel-Process

Provider Guid: {22FB2CD6-0E7B-422B-A0C7-2FAD1FD0E716}

Level: 255

KeywordsAll: 0x0

KeywordsAny: 0x70 (WINEVENT\_KEYWORD\_PROCESS,WINEVENT\_KEYWORD\_THREAD,WINEVENT\_KEYWORD\_IMAGE)

Properties: 64

Filter Type: 0

The command completed successfully.

Event Trace Session logs are recorded in the Output Location in **.etl** format. The logs can be examined in the Event Viewer. Keywords of the collected logs are given as KeywordsAny. In the



example, 0x70 parameter in KeywordsAny represents the sum of the selected keywords' parameter given below.

```
0x000000000000000010 WINEVENT_KEYWORD_PROCESS
0x000000000000000020 WINEVENT_KEYWORD_THREAD
0x000000000000000040 WINEVENT_KEYWORD_IMAGE
```

## 2.1.2. Starting Event Trace Session with Performance Monitor

**Windows Performance Monitor** is a Microsoft Management Console (MMC) snap-in that provides tools for monitoring application and hardware performance in real-time and managing data collections. Event Trace Sessions can be managed by using Data Collector Sets on the Performance Monitor.

Performance Monitor can create new Event Trace Sessions or manage currently running sessions. It can also monitor other providers running Event Trace Sessions using Data Collector Sets.

Let's start an Event Trace Session with Performance Monitor. Microsoft has a similar [guide](#) to start a session [2]. Under the Data Collector Sets and User Defined section,

- Right Click > New > Data Collector Set
- Create manually
- Create Data Logs > Event Data Trace
- Add Providers > Microsoft-Windows-Kernel-Process
- Edit Properties > Add 0x70 Manually

Figure 3: Performance Monitor

### 2.1.3 Viewing collected logs

Recorded Event Trace Session logs can be examined using **Event Viewer**. To view in more detail,

- Enable "Show Analytic and Debug Logs" under the View tab
- Open Saved Log under the Action tab
- Select saved log file In the logman example. The saved log was stored at "C:\Sample-trace.etl".

It should be noted that logs opened in the Event Viewer are not in real-time. If the event trace session is still ongoing, a copy of the log file will be created and the copy will be opened by the Event Viewer. In Figure 4, Sample-trace.etl is opened in Event Viewer and a single log is viewed in XML format.

Figure 4: A sample log examined in Event Viewer

### 3. Parent Process ID Spoofing

**Parent PID Spoofing** is a technique that allows attackers to run processes under any parent process they want. Effectively, the child process can have the Parent Process ID selected by the attackers. This technique enables malicious processes to evade detection methods based

on the parent-child relationship and inherit access tokens from the parent process to elevate privilege.

Let's give examples about defense evasion and privilege escalation using Parent PID spoofing.

- Assume that a malicious payload is delivered using a Word document to create a PowerShell session. In this scenario, PowerShell becomes the child process of winword.exe. However, this is not normal behavior of the Word and is easily detected by defense mechanisms. To evade detection by the defense mechanisms, a payload can be created with a different parent PID of a parent process that usually spawns PowerShell.
- Using the `PROC_THREAD_ATTRIBUTE_PARENT_PROCESS` attribute of `CreateProcess` Win32 API call, a malicious process may inherit the access token of the parent process [3]. If the parent process has a SYSTEM level access token, the malicious process gets a SYSTEM level access token as well.

Parent PID Spoofing attacks are categorized as a sub technique under the T1134 Access Token Manipulation techniques in the MITRE ATT&CK framework [4]. It is a widely used technique and detection of Parent PID spoofing is essential to the secure operation of the assets.

## 4. Detecting Parent PID Spoofing Attacks Using Kernel-Process Logs

So far, we have talked about process ID types, event tracing sessions, log collection, and examination. Let's see how Parent PID spoofing can be detected using Kernel-Process logs step by step in the Windows command line.

### 4.1 Starting an event trace session

Using logman, start an event tracing session and start recording Kernel-Process logs.

```
> logman create trace "Sample-trace" -ets
```

```
The command completed successfully.
```

```
> logman update Sample-trace -p Microsoft-Windows-Kernel-Process 0x70 -ets
```

```
The command completed successfully.
```

## 4.2 Starting a notepad process

Using cmd.exe, start notepad.exe

- Child Process: notepad.exe (PID: 5756)
- Parent Process: cmd.exe (PID: 5428)
- Executing Process: cmd.exe (PID: 5428)

## 4.3 Starting a notepad process with Parent Process ID spoofing

Using [PPID-spoof.ps1](#), start notepad.exe [5].

- Child Process: notepad.exe (PID: 7980)
- Parent Process: winlogon.exe (PID: 548)
- Executing Process: powershell.exe (PID: 6312)

```
> powershell
```

```
PS> .\tasklist /fi "IMAGENAME eq powershell.exe"
```

Image Name	PID	Session Name	Session#	Mem Usage
=====				
powershell.exe	6312	Console	1	72,808 K

```
PS> .\PPID-spoof.ps1
```

```
PS> [MyProcess]::CreateProcessFromParent(548,"C:\Windows\System32\notepad.exe",")
```

```
[+] Got Handle for ppid: 548
```

```
[+] Updated proc attribute list
```

```
[+] Starting C:\Windows\System32\notepad.exe...True - pid: 7980 - Last error: 87
```

```
PS> exit
```

```
> tasklist /fi "IMAGENAME eq winlogon.exe"
```

Image Name	PID	Session Name	Session#	Mem Usage
=====				
winlogon.exe	548	Console	1	11,960 K

```
> tasklist /fi "IMAGENAME eq notepad.exe"
```

Image Name	PID	Session Name	Session#	Mem Usage
------------	-----	--------------	----------	-----------

=====				
-------	--	--	--	--

notepad.exe	7980	Console	1	14,100 K
-------------	------	---------	---	----------

```
> wmic process where (processid=7980) get parentprocessid
```

```
ParentProcessId
```

```
548
```

## 4.4 Examining Event Trace Logs

In the Event Viewer, open the logs recorded.

- Enable "Show Analytic and Debug Logs" under View tab
- Click on Saved Log under the Actions tab
- Open the saved log file at "C:\Sample-trace.etl".

Let's look at the log created for starting notepad.exe without Parent Process ID spoofing. There might be lots of logs collected. So search for the term "Process 5756 started" from the Actions tab.

In this example, we see that Execution Process ID and Parent Process ID are the same. Usually, this is an expected log for starting a process.

```
-<Event xmlns="http://schemas.microsoft.com/win/2004/08/events/event">
-<System>
  <Provider Name="Microsoft-Windows-Kernel-Process" Guid="{22fb2cd6-0e7b-422b-a0c7-2fad1fd0e716}" />
  <EventID>1</EventID>
  <Version>2</Version>
  <Level>4</Level>
  <Task>1</Task>
  <Opcode>1</Opcode>
  <Keywords>0x8000000000000010</Keywords>
  <TimeCreated SystemTime="2022-01-11T06:59:52.449063400Z" />
  <EventRecordID>37682</EventRecordID>
  <Correlation />
  <Execution ProcessID="5428" ThreadID="5636" ProcessorID="0" KernelTime="3" UserTime="1" />
</Channel />
```

```
<Computer>MSEDGEWIN10</Computer>
<Security />
</System>
-<EventData>
  <Data Name="ProcessID">5756</Data>
  <Data Name="CreateTime">2022-01-11T07:00:04.257230300Z</Data>
  <Data Name="ParentProcessID">5428</Data>
  <Data Name="SessionID">1</Data>
  <Data Name="Flags">0</Data>
  <Data Name="ImageName">\Device\HarddiskVolume1\Windows\System32\notepad.exe</Data>
  <Data Name="ImageChecksum">307779</Data>
  <Data Name="TimeStamp">314954348</Data>
  <Data Name="PackageFullName" />
  <Data Name="PackageRelativeAppld" />
</EventData>
</Event>
```

Now, let's look at the log created for starting notepad.exe with Parent Process ID spoofing. Search for the term "Process 7980 started" from the Actions tab.

In this example, we see that Execution Process ID and Parent Process ID **do not match**. This is very unusual for starting a process and very rarely legitimate. However, this mismatch is a key characteristic of Parent PID spoofing attacks. From this Kernel-Process log, we can detect malicious Parent Process ID spoofing attacks.

```
-<Event xmlns="http://schemas.microsoft.com/win/2004/08/events/event">
-<System>
  <Provider Name="Microsoft-Windows-Kernel-Process" Guid="{22fb2cd6-0e7b-422b-a0c7-2fad1fd0e716}" />
  <EventID>1</EventID>
  <Version>2</Version>
  <Level>4</Level>
  <Task>1</Task>
  <Opcode>1</Opcode>
  <Keywords>0x8000000000000010</Keywords>
  <TimeCreated SystemTime="2022-01-11T06:59:30.467709500Z" />
  <EventRecordID>37475</EventRecordID>
  <Correlation />
  <Execution ProcessID="6312" ThreadID="5724" ProcessorID="0" KernelTime="14" UserTime="24" />
  <Channel />
  <Computer>MSEDGEWIN10</Computer>
  <Security />
```

```
</System>
-<EventData>
  <Data Name="ProcessID">7980</Data>
  <Data Name="CreateTime">2022-01-11T06:59:42.276169400Z</Data>
  <Data Name="ParentProcessID">548</Data>
  <Data Name="SessionID">1</Data>
  <Data Name="Flags">0</Data>
  <Data Name="ImageName">\\Device\\HarddiskVolume1\\Windows\\System32\\notepad.exe</Data>
  <Data Name="ImageChecksum">307779</Data>
  <Data Name="TimeDateStamp">314954348</Data>
  <Data Name="PackageFullName" />
  <Data Name="PackageRelativeAppld" />
</EventData>
</Event>
```

## 5. Simulating with Picus

**Picus Threat Library** includes multiple Parent Process ID spoofing attack simulations. These attack simulations test detection and prevention capabilities of your security controls.

### 5.1 Parent Process ID Spoofing Simulation with Picus



## 5.2 Detection with Splunk

In the attack simulation with Picus, we saw that the Parent Process ID spoofing attack was not blocked by the security controls. Splunk search queries can be designed with different methods and logs types to detect Parent Process ID spoofing.

As an example, let's see how we can detect the attack with Splunk using Kernel-Process logs. Since it is possible to detect the attack by comparing Execution PID and Parent PID of a child process, we can devise the following Splunk search query for detection.

```
sourcetype="test-xml" "Event.System.EventID"=1 | eval Parent_ProcessId=mvindex('Event.EventData.Data', 3) | eval  
Process_Name=mvindex('Event.EventData.Data', 10) | eval Result=if('Event.System.Execution{@ProcessID}'=Parent_ProcessId,  
"Not Suspicious","Suspicious") | table Process_Name, Result
```

Figure 5: Parent Process ID Spoofing Detection with Splunk

## References

- [1] "About Event Tracing." [Online]. Available: <https://docs.microsoft.com/en-us/windows/win32/etw/about-event-tracing>.
- [2] "How to: Use Performance Monitor to Collect Event Trace Data." [Online]. Available: <https://docs.microsoft.com/en-us/dynamics365/business-central/dev-itpro/administration/monitor-use-performance-monitor-collect-event-trace-data>.
- [3] "UpdateProcThreadAttribute function (processthreadsapi.h)." [Online]. Available: <https://docs.microsoft.com/en-us/windows/win32/api/processthreadsapi/nf-processthreadsapi-updateprocthreadattribute>.
- [4] "Access Token Manipulation: Parent PID Spoofing." [Online]. Available: <https://attack.mitre.org/techniques/T1134/004/>.
- [5] decoder-it, "GitHub - decoder-it/psgetsystem: getsystem via parent process using ps1 & embedded c#" GitHub. [Online]. Available: <https://github.com/decoder-it/psgetsystem>.

## Share this:

---



EMERGING THREAT

**CVE-2024-47575:  
FortiManager Missing  
Authentication Zero-Day...**

**LEARN MORE** ▶

EMERGING THREAT

**Iranian Cyber Actors' Brute  
Force and Credential Access  
Attacks: CISA Alert AA24-...**

**LEARN MORE** ▶



**Email\***

Email

**SUBSCRIBE NOW**

## Platform

The Security Validation Platform

Security Control Validation

Attack Surface Validation

Cloud Security Validation

Attack Path Validation

Detection Rule Validation

Integrations

## Use Cases

Breach and Attack Simulation

Penetration Testing Automation

Continuous Threat Exposure Management

## Resources

Blog

Purple Academy

Webinars

Reports

Case Studies

Press Releases

Datasheets

Cyberpedia

Events

## Company

About Us

Leadership

Careers

Contact

Customer Support

Trust Center

## Subscribe to Our Newsletter

Email\*

SUBSCRIBE NOW

## Contact Us

[info@picussecurity.com](mailto:info@picussecurity.com)

[Schedule a meeting](#)

© 2024 Copyright. All rights reserved.