.. /Eventvwr.exe

UAC bypass (GUI)

Displays Windows Event Logs in a GUI window.

Paths:

C:\Windows\System32\eventvwr.exe C:\Windows\SysWOW64\eventvwr.exe

Resources:

- https://enigma0x3.net/2016/08/15/fileless-uac-bypass-using-eventwwr-exe-and-registry-hijacking/
- https://github.com/enigma0x3/Misc-PowerShell-Stuff/blob/master/Invoke-EventVwrBypass.ps1
- https://twitter.com/orange_8361/status/1518970259868626944

Acknowledgements:

- Matt Nelson (<u>@enigma0x3</u>)
- Matt Graeber (@mattifestation)
- Orange Tsai (<u>@orange_8361</u>)

Detections:

Sigma:

https://github.com/SigmaHQ/sigma/blob/62d4fd26b05f4d81973e7c8e80d7c1a0c6a29d0e/rules/windows/process_creation/proc_creation_win_uac_bypass_eventvwr.yml

Sigma:

https://github.com/SigmaHQ/sigma/blob/62d4fd26b05f4d81973e7c8e80d7c1a0c6a29d0e/rules/windows/registry/registry_set/registry_set_uac_bypass_eventvwr.yml

• Sigma:

https://github.com/SigmaHQ/sigma/blob/197615345b927682ab7ad7fa3c5f5bb2ed911eed/rules/windows/file/file_e vent/file_event_win_uac_bypass_event/wr.yml

Elastic: https://github.com/elastic/detection-

rules/blob/d31ea6253ea40789b1fc49ade79b7ec92154d12a/rules/windows/privilege_escalation_uac_bypass_event_viewer.toml

• Splunk:

 $\underline{\text{https://github.com/splunk/security_content/blob/86a5b644a44240f01274c8b74d19a435c7dae66e/detections/endpoint/eventvwr_uac_bypass.yml}$

- IOC: eventwwr.exe launching child process other than mmc.exe
- IOC: Creation or modification of the registry value HKCU\Software\Classes\mscfile\shell\open\command

UAC bypass

During startup, eventwwr.exe checks the registry value HKCU\Software\Classes\mscfile\shell\open\command for the location of mmc.exe, which is used to open the eventwwr.msc saved console file. If the location of another binary or script is added to this registry value, it will be executed as a high-integrity process without a UAC prompt being displayed to the user.

eventvwr.exe

Use case: Execute a binary or script as a high-integrity process without a UAC prompt.

Privileges required: User

Operating systems: Windows vista, Windows 7, Windows 8, Windows 8.1, Windows 10

ATT&CK® technique: T1548.002

Tags: Application: GUI

During startup, eventwwr.exe uses .NET deserialization with %LOCALAPPDATA%\Microsoft\EventV~1\RecentViews file. This file can be created using https://github.com/pwntester/ysoserial.net

ysoserial.exe -o raw -f BinaryFormatter - g DataSet -c calc > RecentViews & copy RecentViews
%LOCALAPPDATA%\Microsoft\EventV~1\RecentViews & eventvwr.exe

Use case: Execute a command to bypass security restrictions that limit the use of command-line

interpreters.

Privileges required: Administrator

Operating systems: Windows 7, Windows 8, Windows 8.1, Windows 10

ATT&CK® technique: T1548.002

Tags: Application: GUI