

```
[2] Writing Payload
[+] EventViewer Folder exists
[3] Finally, invoking eventvwr
```

## Working

- i) First, the script adds commands to be run to the fileC:\Windows\Tasks\EventViewerRCE.ps1
  - Stop-Process -name mmc\*: Is used to close Microsoft Management Console.
  - After that the command to be executed is added.
- ii) Then it crafts payload which runs
  C:\Windows\Tasks\EventViewerRCE.ps1 script. The base64
  payload was generated using ysoserial.net:

```
ysoserial.exe -o base64 -f BinaryFormatter -g D; ☐
```

- The base64 output from ysoserial.net is decoded and stored in C:\Windows\Tasks\p4y10ad
- The powershell encoded command decodes to:

```
Set-ExecutionPolicy Bypass -Scope CurrentUser; (
```

- iii) When WriteFile function is executed, it checks if the Event Viewer folder exists in AppData and it it doesn't then we create the folder. Finally storing our base64 decoded payload in RecentViews file under this folder.
- iv) In the end, eventum is executed which then executes our payload.

## Reference

• <a href="https://twitter.com/orange\_8361/status/15189702598686">https://twitter.com/orange\_8361/status/15189702598686</a>
26944

Terms Privacy Security Status Docs Contact Manage cookies Do not share my personal information © 2024 GitHub, Inc.