

🔍 Filter by title

replace

replace

rexec

risetup

rmdir

robocopy

route ws2008

rpcinfo

rpcping

rsh

rundll32

rundll32 printui

rwinsta

sc config

sc create

sc delete

sc query

> schtasks

> scwcmd

> secedit

serverceipoptin

servermanagercmd

serverweroptin

Services for Network File System (NFS)

command reference

set environmental variables

setlocal

setx

sfc

shadow

shift

showmount

shutdown

simulate restore

sort

start


subst

sxstrace

📄 Download PDF

# replace

Article • 02/03/2023 • 8 contributors •

Applies  Windows Server 2025,  Windows Server 2022,  Windows Server 2019,  Windows Server 2016,  Windows 11,  Windows 10,  Azure Stack HCI, versions 23H2 and 22H2

 [Feedback](#)

## In this article

- [Syntax](#)
- [Examples](#)
- [Related links](#)


Replace existing files in a directory. If used with the **/a** option, this command adds new files to a directory instead of replacing existing files.

## Syntax

📄 Copy

```
replace [<drive1>:][<path1><filename> [<drive2>:][<path2>] [/a] [/p] [/r] [/w]
replace [<drive1>:][<path1><filename> [<drive2>:][<path2>] [/p] [/r] [/s] [/w]
```

## Parameters

 **Expand table**

Parameter	Description
<code>[&lt;drive1&gt;:]</code> <code>[&lt;path1&gt;]</code> <code>&lt;filename&gt;</code>	Specifies the location and name of the source file or set of files. The <i>filename</i> option is required, and can include wildcard characters (* and ?).
<code>[&lt;drive2&gt;:]</code> <code>[&lt;path2&gt;]</code>	Specifies the location of the destination file. You can't specify a file name for files you replace. If you don't specify a drive or path, this command uses the current drive and directory as the destination.
<code>/a</code>	Adds new files to the destination directory instead of replacing existing files. You can't use this command-line option with the <i>/s</i> or <i>/u</i> command-line option.
<code>/p</code>	Prompts you for confirmation before replacing a destination file or adding a source file.
<code>/r</code>	Replaces Read-only and unprotected files. If you attempt to replace a Read-only file, but you don't specify <i>/r</i> , an error results and stops the replacement operation.
<code>/w</code>	Waits for you to insert a disk before the search for source files begins. If you don't specify <i>/w</i> , this command begins replacing or adding files immediately after you press ENTER.
<code>/s</code>	Searches all subdirectories in the destination directory and replaces matching files. You can't use <i>/s</i> with the <i>/a</i> command-line option. The command doesn't search subdirectories that are specified in <i>Path1</i> .

/u	Replaces only those files on the destination directory that are older than those in the source directory. You can't use /u with the /a command-line option.
/?	Displays help at the command prompt.

## Remarks

- As this command adds or replaces files, the file names appear on the screen. After this command is done, a summary line is displayed in one of the following formats:

Copy

```
nnn files added
nnn files replaced
no file added
no file replaced
```

- If you're using floppy disks and you need to switch disks while running this command, you can specify the /w command-line option so that this command waits for you to switch the disks.
- You can't use this command to update hidden files or system files.
- The following table shows each exit code and a brief description of its meaning:

Expand table

Exit code	Description
0	This command successfully replaced or added the files.
1	This command encountered an incorrect version of MS-DOS.
2	This command couldn't find the source files.
3	This command couldn't find the source or destination path.
5	The user doesn't have access to the files that you want to replace.
8	There is insufficient system memory to carry out the command.
11	The user used the wrong syntax on the command line.

### Note

You can use the ERRORLEVEL parameter on the **if** command line in a batch program to process exit codes that are returned by this command.

## Examples

To update all the versions of a file named *Phones.cli* (which appear in multiple directories on drive C:), with the latest version of the *Phones.cli* file from a floppy disk in drive A:, type:

Copy

```
replace a:\phones.cli c:\ /s
```

## Related links

- [Command-Line Syntax Key](#)




# Feedback

Was this page helpful?

 Yes

 No

 English (United States)  Your Privacy Choices  Theme 

[Manage cookies](#) [Previous Versions](#) [Blog](#)  [Contribute](#) [Privacy](#)  [Terms of Use](#) [Trademarks](#)  [© Microsoft 2024](#)