

Shenanigans of Scheduled Tasks

August 23rd, 2024 · 12 min read

Updated August 26, 2024

Scheduled Tasks are the automated processes configured to run automatically at a specified time or when certain conditions are met. By eliminating the need for manual intervention, these tasks enable the execution of repetitive or routine tasks while ensuring efficiency and consistency. In Windows, the Task Scheduler service manages and executes these automated tasks, similar to cron jobs on Unix systems. It monitors the conditions for any automated task, be it time or event criteria, and executes the tasks as soon as certain conditions are met. Attackers can also abuse scheduled tasks to persist malicious code or execute unauthorized activities on a compromised system.



Swachchhanda Shrawan Poudel
Security Research

Jump To Section ▼

1. This website

2. [#IABV2_T

3. Task Sched

4. Task Sched

5. Scheduled

6. Hunt of Su

7. Conclusion

Share This Story

https://www.logpoint.com/en/blog/shenanigans-of-scheduled-tasks/


Book a demo

Task Scheduler

1. **This website** uses cookies to enhance your browsing experience, understand how our site is used, and have them help us with our marketing efforts. You can opt out of cookies by clicking on the "Cookiebot" button in the bottom right corner of the page. For more information, please visit our [Privacy Policy](#).
 2. **[#IABV2_T**he website uses cookies to enhance your browsing experience, understand how our site is used, and have them help us with our marketing efforts. You can opt out of cookies by clicking on the "Cookiebot" button in the bottom right corner of the page. For more information, please visit our [Privacy Policy](#).
 3. **Task Scheduler** is a Windows service that manages and executes scheduled tasks. It allows users to create tasks that run automatically at a specified time or when certain conditions are met. Tasks can be created for various purposes, such as running a program, sending an email, or performing a system maintenance task. It operates in the background and can be configured to run tasks on a specific schedule or in response to certain events.
 4. **Task Scheduler** is a Windows service that manages and executes scheduled tasks. It allows users to create tasks that run automatically at a specified time or when certain conditions are met. Tasks can be created for various purposes, such as running a program, sending an email, or performing a system maintenance task. It operates in the background and can be configured to run tasks on a specific schedule or in response to certain events.
 5. **Scheduled Tasks** are automated processes that run on a computer at a specified time or when certain conditions are met. They are used to perform repetitive tasks, such as running a program, sending an email, or performing a system maintenance task. Scheduled tasks can be created for various purposes, such as running a program, sending an email, or performing a system maintenance task.
 6. **Hunt of Scheduled Tasks** is a technique used by attackers to identify and exploit scheduled tasks on a compromised system. It involves searching for tasks that are configured to run automatically and analyzing their properties, such as their schedule, triggers, and actions. This information can be used to identify potential vulnerabilities and exploit them to gain unauthorized access to the system.
 7. **Conclusion**
- Share This Story

https://www.logpoint.com/en/blog/shenanigans-of-scheduled-tasks/

Book a demo



- 5. **Task Scheduler API:** An interface that allows developers to create and manage tasks programmatically. This API may be accessible using scripting languages like PowerShell or custom applications.

More information about Task Scheduler can be found here in Microsoft's official documentation [link](#).

Task Scheduling and Execution in Windows


1. Scheduling a Task


- **User Action:** The Task Scheduler program allows you to create a scheduled task. It includes specifying when the task should execute (for example, at a specific time or upon system startup) and what it should perform (for example, run a script or launch an application).
- **Task Storage:** The job is saved to the Task Scheduler Library and registered in the Windows Registry. These two registries are formed for any new scheduled task created.

1	HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\TASK_NAME
2	HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{GUID}

Similar data is also stored within an extensionless XML file located in the `C:\Windows\System32\Tasks` directory.

2. Monitoring and Preparing for Task Execution





Consent


Details

About


This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.


Necessary




Preferences



Statistics



Marketing



- **Trigger Condition:** When the planned time or event happens (for example, the system boots up or the user logs in), the Task Scheduler service identifies the requirement to execute a task.
- **Task Execution:** The Task Scheduler service gets ready to execute the task:
 - **Launching the Task:** It launches a new process, often `taskhostw.exe` (Task Host Window), in charge of carrying out the specified task.
 - **Running the Action:** The `taskhostw.exe` process then executes the task's action that might involve:
 - **Running a Script:** Launching `cmd.exe` or `powershell.exe` to execute a script.
 - **Starting an Application:** Launching the specified application, for example, `example.exe`.
- **User Context:** The job runs with the user rights set when it was created.

4. Logging and Continuation

- **Task Logging:** After completing the job, the job Scheduler reports the results in the Event Viewer under "Task Scheduler", which includes:
 - **Start and End Times.**
 - **Result of the Task** (success, failure, error codes).
 - **Output or Error Messages.**
- **Ongoing Monitoring:** The Task Scheduler service continues to operate and is ready to handle and execute any more scheduled tasks when triggered.

Scheduled Task for Persistence

Persistence is crucial for the attackers to have a successful attack. It allows them to maintain long-term access to the compromised system, enabling continued carnage and a foothold for more destructive objectives. One of the prevalent and widely used techniques used for persistence is the scheduled task. Adversaries commonly used the scheduled tasks to maintain persistence, execute their malicious payloads at specific times, or perform automatic tasks on compromised devices. Also, scheduled tasks allow the processes to execute with elevated privileges. Furthermore, they try to configure such tasks to run under the guise of legitimate processes, making their foothold ever stronger and making detection difficult. One of the most common tools used in Windows for scheduling such tasks is 'schtasks.exe'.


Schtasks

'**schtasks.exe**' is a Windows command-line application for managing scheduled tasks on local or remote computers, such as creating, removing, editing, executing, and terminating tasks. While it is an essential tool for system administrators, it is also a common choice of attackers to maintain persistence, launch malicious payloads, and carry out illegal operations. We have noticed the utilization of **schtasks**, particularly the use of **/create** command to schedule the task, in a diverse range of threat actor operations and malicious software. Below is the snippet of the command seen in one of the latest samples of *Xworm* to create a new scheduled task.

```
1 schtasks /create /sc minute /mo 1 /tn "Nafifas" /tr "'C:\Users\Admin\AppData\Roaming\svchost\svcho
```

This command creates a scheduled " Nafifas " task that runs every minute. The task executes the file **svchost.exe**located in the **C:\Users\Admin\AppData\Roaming\svchost** directory. It's an expected behavior seen in adversaries to drop their payloads from user-writeable directories like **\AppData\Roaming**. The **/f** flag forces the task's creation, replacing any existing task with the same name. An attacker uses this task to maintain persistence, repeatedly running a potentially malicious executable.

In this instance, the scheduled task is executing the **svchost.exe** process from the **\AppData\Roaming** directory, which is not a usual location for legitimate processes like **svchost.exe**, usually executed from **%SystemRoot%\System32**. The malware attempts to evade detection by posing as a legitimate system process and running from an unusual directory. This strategy helps conceal its activity, making it harder for users and security tools to recognize it as malicious and allowing the malware to maintain its foothold.







Consent

Details

About

This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

<div>Necessary</div> <div></div>	<div>Preferences</div> <div></div>	<div>Statistics</div> <div></div>	<div>Marketing</div> <div></div>
---	---	--	---

In Windows, the **Microsoft-Windows-TaskScheduler/Operational** log is a specific event log within the Windows Event Viewer dedicated to recording detailed operational events for the Task Scheduler service. This log provides comprehensive information about the activities and operations carried out by the Task Scheduler, including task registration, running, termination, and errors. Event ID 200 is generated when a new task action starts and likewise for other actions.


Scheduled Task logs are also available through the **Microsoft-Windows-Security-Auditing** events. To access these logs, you must enable the "**Audit Other Object Access Events**" policy. Once enabled, the following Event IDs are generated:

- **4698**: Scheduled task creation.
- **4699**: Scheduled task deletion.
- **4700**: Scheduled task enabled.
- **4701**: Scheduled task disabled.
- **4702**: Scheduled task updated.

Persistent Tasks from Suspicious Locations


Malware or threat actors frequently drop their payloads in publicly writable directories, utilizing them for initial deployment and persistence. It is crucial to monitor scheduled tasks originating from these specific directories.

```
1 label="Create" label="Process"
2 "process"="*\schtasks.exe" command="*/Create *"
3 (command in ["*\ProgramData\*", " *\Temp\*", " *\Tmp\*", " *\Users\Public\*",
4 " *\Windows\Temp\*", " *\AppData\*", " %AppData%*", " %Temp%*", " %tmp%*"])
```



The management of scheduled tasks' execution on Windows 10 is handled by "svchost.exe" through the command line "C:\\WINDOWS\\system32\\svchost.exe -k netsvcs -p -s Schedule". Before Windows 10 Version 1511, it was executed by taskeng.exe. Analyzing the subprocesses of this particular process enables the detection of any irregular patterns that could indicate the presence of potentially harmful scheduled tasks.

```
1 label="Create" label="Process" ("parent_process"="*\\taskeng.exe")
2 OR ("parent_process"="*\\svchost.exe" parent_command="C:\\WINDOWS\\system32\\svchost.exe -k netsvcs -p
3 "process" IN [ "*:\\ProgramData\\*", ".*:\\Temp\\*", ".*:\\Tmp\\*", ".*:\\Users\\Public\\*",
4 ".*:\\Windows\\Temp\\*", ".*\\AppData\\*", ".*%AppData%*", ".*%Temp%*", ".*%tmp%*"]
```



Cookiebot

by Usercentrics

Consent

Details

About

This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

Necessary

Preferences

Statistics

Marketing

Suspicious Scheduled Programs Execution

Malware or threat actors tend to execute their malicious scripts repeatedly using Windows shell script programs such as cmd, Powershell, Wscript, and Cscript while also abusing the other common LOLBAS. It's also a good idea to look at such execution patterns.

The query below can help detect the creation of such scheduled tasks that execute potentially suspicious programs.

```
1 (label="Create" label="Process" "process"="\"schtasks.exe\" command='\"/Create \"' )
2 OR (norm_id=WinServer "event_id"=4698)
3 command IN [ "\"\\InstallUtil.exe*", "\"\\RUNDLL32.EXE*", "\"\\msiexec.exe*", "\"\\RegSvcs.exe*",
4 "\"\\MSHTA.EXE*", "\"\\Cmd.Exe*", "\"\\PowerShell.EXE*", "\"\\cscript.exe*",
5 "\"\\CONTROL.EXE*", "\"\\RegAsm.exe*", "\"\\REGSVR32.EXE*", "\"\\wscript.exe*",
6 "\"\\Microsoft.Workflow.Compiler.exe*", "\"\\MSBuild.exe*", "\"\\msxsl.exe*"]
```

The above query only detects creation, but we can track svchost.exe, which is associated with scheduling tasks, to detect process execution details.

```
1 label="Create" label="Process" ("parent_process"="*\\taskeng.exe")
2 OR ("parent_process"="*\\svchost.exe" parent_command="C:\\WINDOWS\\system32\\svchost.exe -k netsvcs -p
3 "process" IN [ "\"\\InstallUtil.exe", "\"\\RUNDLL32.EXE", "\"\\msiexec.exe", "\"\\RegSvcs.exe",
4 "\"\\MSHTA.EXE", "\"\\Cmd.Exe", "\"\\PowerShell.EXE", "\"\\cscript.exe",
5 "\"\\CONTROL.EXE", "\"\\RegAsm.exe", "\"\\REGSVR32.EXE", "\"\\wscript.exe",
6 "\"\\Microsoft.Workflow.Compiler.exe", "\"\\MSBuild.exe", "\"\\msxsl.exe"]
```

Alternate via network connection event

Page 4 of 7

In specific campaigns, the malware communicates with an external domain, commonly a Command and Control (C&C) server, to exchange information, including data and instructions. This communication is facilitated through scheduled tasks, enabling the malware to interact with malicious domains, download payloads, or transmit collected data based on the threat actor's requirements. We can look for the URL used in the scheduled task command line.

Scheduled Task File Creation

```
1 label=File label=Create
2 path in ["C:\Windows\System32\Tasks", "C:\Windows\Tasks"]
```

Masqueraded Scheduled Tasks

Cookiebot
by Usercentrics

Consent

Details

About

This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

<div>Necessary</div> <div><input type="checkbox"/></div>	<div>Preferences</div> <div><input checked="" type="checkbox"/></div>	<div>Statistics</div> <div><input checked="" type="checkbox"/></div>	<div>Marketing</div> <div><input checked="" type="checkbox"/></div>
--	---	--	---

Scheduled Task Registry Modification

```
1 HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\TASK_NAME
2 HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{GUID}
```

```
1 norm_id=WindowsSysmon event_id IN [12, 13, 14]
2 target_object="*\\SOFTWARE\\Microsoft\\Windows NT\\CurrentVersion\\Schedule\\TaskCache\\Tree\\*"
```

Scheduled Task via a COM Interface


In a recent campaign of [Latrodectus](#), a unique approach was observed to bypass the usual `schtasks.exe` command-line tool while creating the scheduled tasks. Instead, it was observed leveraging the COM object (`Schedule.Service`) to interact with the Task Scheduler through the `taskschd.dll` module. Since, various legitimate processes also load `taskschd.dll`, merely detecting its use is not enough to identify malicious intent. As malicious payloads are generally dropped in publicly writable directories, examining suspicious processes originating from these paths that load this module could indicate malicious scheduled task creation. Following query is catered to hunt for such events.

```
1 label="Image" label=Load
2 image="*\\taskschd.dll"
3 "process" in ["*\\AppData\\Local\\Temp\\*", "*\\AppData\\Roaming\\*",
4 "*C:\\Users\\Public\\*", "*C:\\Windows\\Temp\\*", "*C:\\Temp\\*", "*\\Downloads\\*",
5 "*\\Desktop\\*"]
```

Logpoint Alerts

In addition to the detection queries mentioned above, you can utilize Logpoint's out-of-the-box alert rules. Activating these alerts can assist in pinpointing any potentially suspicious scheduled tasks within your enterprise system. The following alerts are associated explicitly with suspicious scheduled tasks.

Alert Name
Scheduled Task Creation Detected
Default PowerSploit and Empire Schtasks Persistence



Consent


Details

About


This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you’ve provided to them or that they’ve collected from your use of their services.


Necessary




Preferences



Statistics



Marketing



... persistence. Prior to the deployment of the code to execute the task, the attacker used the task to execute your...
...ent sensor and a network scanner to proactively monitor and mitigation of suspicious activities in their infancy, safeguarding your business operations. Additionally, Logpoint Security Research continuously develops analytics, sharing insights through blog posts like the [Emerging Threats Protection Reports](#). Stay updated by following Logpoint on LinkedIn.


Related Posts



Uncover more resources with Logpoint’s latest release
October 30th, 2024



Latrodectus: The Wrath of Black Widow
October 22nd, 2024



Logpoint and Muninn: Better Together
October 1st, 2024

Case Management

EAL3+ Certificate

Careers at Logpoint

Documentation

+45 7060 6100

Behavior Analytics

Newsletter

Media Room

Community

Cyber Defense Platform

Logpoint in the media

Contact


Pricing

Blog & Webinars

Status

Sizing Calculator









Consent

Details

About

This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

<div>Necessary</div> <div></div>	<div>Preferences</div> <div></div>	<div>Statistics</div> <div></div>	<div>Marketing</div> <div></div>
---	---	--	---