



redcanaryco / atomic-red-team Public

Notifications Fork 2.8k Star 9.7k

<> Code Issues 6 Pull requests 5 Actions Wiki Security Insights

atomic-red-team / atomics / T1124 / T1124.md

139 lines (57 loc) · 3.46 KB

Preview Code Blame Raw Copy Download

T1124 - System Time Discovery

Description from ATT&CK

An adversary may gather the system time and/or time zone from a local or remote system. The system time is set and stored by the Windows Time Service within a domain to maintain time synchronization between systems and services in an enterprise network. (Citation: MSDN System Time) (Citation: Technet Windows Time Service)

System time information may be gathered in a number of ways, such as with [Net](#) on Windows by performing `net time \hostname` to gather the system time on a remote system. The victim's time zone may also be inferred from the current system time or gathered by using `w32tm /tz`. (Citation: Technet Windows Time Service)

This information could be useful for performing other techniques, such as executing a file with a [Scheduled Task/Job](#) (Citation: RSA EU12 They're Inside), or to discover locality information based on time zone to assist in victim targeting (i.e. [System Location Discovery](#)). Adversaries may also use knowledge of system time as part of a time bomb, or delaying execution until a specified date/time.(Citation: AnyRun TimeBomb)

Atomic Tests

- [Atomic Test #1 - System Time Discovery](#)
- [Atomic Test #2 - System Time Discovery - PowerShell](#)
- [Atomic Test #3 - System Time Discovery in macOS](#)
- [Atomic Test #4 - System Time Discovery W32tm as a Delay](#)

Atomic Test #1 - System Time Discovery

Identify the system time. Upon execution, the local computer system time and timezone will be displayed.

Supported Platforms: Windows

auto_generated_guid: 20aba24b-e61f-4b26-b4ce-4784f763ca20

Inputs:

Name	Description	Type	Default Value
computer_name	computer name to query	String	localhost

Attack Commands: Run with `command_prompt` !

```
net time \\#{computer_name}
w32tm /tz
```



Atomic Test #2 - System Time Discovery - PowerShell

Identify the system time via PowerShell. Upon execution, the system time will be displayed.

Supported Platforms: Windows

auto_generated_guid: 1d5711d6-655c-4a47-ae9c-6503c74fa877

Attack Commands: Run with `powershell` !

```
Get-Date
```



Atomic Test #3 - System Time Discovery in macOS

Identify system time. Upon execution, the local computer system time and timezone will be displayed.

Supported Platforms: macOS

auto_generated_guid: f449c933-0891-407f-821e-7916a21a1a6f

Attack Commands: Run with `sh` !

```
date
```



Atomic Test #4 - System Time Discovery W32tm as a Delay

identifies DCRat delay time tactics using w32tm. <https://research.splunk.com/endpoint/b2cc69e7-11ba-42dc-a269-59c069a48870/> <https://blogs.blackberry.com/en/2022/05/dirty-deeds-done-dirt-cheap-russian-rat-offers-backdoor-bargains>

Supported Platforms: Windows

auto_generated_guid: d5d5a6b0-0f92-42d8-985d-47aafa2dd4db

Attack Commands: Run with `command_prompt` !

```
W32tm /stripchart /computer:localhost /period:5 /dataonly /samples:2
```

