



Search site

Analytic Stories

Detections

Playbooks

Data Sources

Blog

About



Table of Contents

- Description
- Search
- Data Source
- Macros Used
- Annotations
- Default Configuration
- Implementation
- Known False Positives
- Associated Analytic Story
- Risk Based Analytics (RBA)
- References
- Detection Testing

Detection: O365 New Federated Domain Added

Updated Date: 2024-05-28

ID: e155876a-6048-11eb-ae93-0242ac130002

Author: Rod Soto, Mauricio Velazco Splunk

Type: TTP

Product: Splunk Enterprise Security

Description

The following analytic identifies the addition of a new federated domain in an Office 365 environment. This behavior is detected by analyzing Office 365 management activity logs, specifically filtering for Workload=Exchange and Operation="Add-FederatedDomain". The addition of a new federated domain is significant as it may indicate unauthorized changes or potential compromises. If confirmed malicious, attackers could establish a backdoor, bypass security measures, or exfiltrate data, leading to data breaches and unauthorized access to sensitive information. Immediate investigation is required to review the details of the added domain and any concurrent suspicious activities.

Search

```
`o365_management_activity` Operation IN ("*add*", "*new*") AND Operation="*domain*"
| stats count values(ModifiedProperties{}.NewValue) as new_value by user user_agent authentication_service action
Workload Operation
| `security_content_ctime(firstTime)`
| `security_content_ctime(lastTime)`
| `o365_new_federated_domain_added_filter`
```

SPL

Data Source

Name	Platform	Sourcetype	Source	Supported App
O365	N/A	'o365:management:activity'	'o365'	N/A

Macros Used

Name	Value
o365_management_activity	sourcetype=o365:management:activity
o365_new_federated_domain_added_filter	search *



o365_new_federated_domain_added_filter is an empty macro by default. It allows the user to filter out any results (false positives) without editing the SPL.

Annotations

- MITRE ATT&CK

+ KILL CHAIN PHASES

+ NIST

+ CIS

- THREAT ACTORS

ID	Technique	Tactic
T1136.003	Cloud Account	Persistence
T1136	Create Account	Persistence

APT29

LAPSUS\$

INDRIK SPIDER

SCATTERED SPIDER

Default Configuration

This detection is configured by default in Splunk Enterprise Security to run with the following settings:

Setting	Value
Disabled	true
Cron Schedule	0 * * * *
Earliest Time	-70m@m
Latest Time	-10m@m
Schedule Window	auto
Creates Notable	Yes
Rule Title	%name%
Rule Description	%description%
Notable Event Fields	user, dest
Creates Risk Event	True

i

This configuration file applies to all detections of type TTP. These detections will use Risk Based Alerting and generate Notable Events.

Implementation

You must install splunk Microsoft Office 365 add-on. This search works with o365:management:activity.

Known False Positives

The creation of a new Federated domain is not necessarily malicious, however these events need to be followed closely, as it may indicate federated credential abuse or backdoor via federated identities at a similar or different cloud provider.

Associated Analytic Story

- Cloud Federated Credential Abuse
- Office 365 Persistence Mechanisms

Risk Based Analytics (RBA)

Risk Message	Risk Score	Impact	Confidence
User \$user\$ has added a new federated domain \$new_value\$	64	80	80

!

The Risk Score is calculated by the following formula: Risk Score = (Impact * Confidence/100). Initial Confidence and Impact is set by the analytic author.

References

- <https://www.fireeye.com/content/dam/fireeye-www/blog/pdfs/wp-m-unc2452-2021-000343-01.pdf>
- <https://www.cisa.gov/uscert/ncas/alerts/aa21-008a>
- https://www.splunk.com/en_us/blog/security/a-golden-saml-journey-solarwinds-continued.html
- <https://blog.sygnia.co/detection-and-hunting-of-golden-saml-attack?hsLang=en>
- <https://o365blog.com/post/aadbackdoor/>

Detection Testing

Test Type	Status	Dataset	Source	Sourcetype
Validation	✔ Passing	N/A	N/A	N/A
Unit	✔ Passing	Dataset	o365	o365:management:activity
Integration	✔ Passing	Dataset	o365	o365:management:activity

Replay any dataset to Splunk Enterprise by using our `replay.py` tool or the [UI](#). Alternatively you can replay a dataset into a [Splunk Attack Range](#)

Source: [Git](#)[Hub](#) | Version: **4**

← Detection: Networ...

Detection: Okta ID... →