We use optional cookies to (i) improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. **Privacy Statement Third-Party Cookies**

Accept Reject Manage cookies

 \oplus



regsvr32

Article • 02/03/2023 • 7 contributors

♦ Feedback

In this article

Syntax

Related links

Registers .dll files as command components in the registry.

Syntax

regsvr32 [/u] [/s] [/n] [/i[:cmdline]] <Dllname>

Parameters

Expand table

Parameter	Description
/u	Unregisters server.
/s	Prevents displaying messages.
/n	Prevents calling DIIRegisterServer . This parameter requires you to also use the /i parameter.
/i: <cmdline></cmdline>	Passes an optional command-line string (<i>cmdline</i>) to DIIInstall . If you use this parameter with the /u parameter, it calls DIIUninstall .
<dllname></dllname>	The name of the .dll file that will be registered.
/?	Displays help at the command prompt.

Examples

To register the .dll for the Active Directory Schema, type:

regsvr32 schmmgmt.dll

Related links

• Command-Line Syntax Key

Feedback

Was this page helpful?





③ English (United States) ✓× Your Privacy Choices ❖ Theme ∨

© Microsoft 2024