



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies



SID Strings

Article • 09/26/2023 • 7 contributors

Feedback

In the [security descriptor definition language](#) (SDDL), [security descriptor string](#) use SID strings for the following components of a *security descriptor*:

- Owner
- Primary group
- The [trustee](#) in an ACE

A SID string in a security descriptor string can use either the standard string representation of a SID (*S-R-I-S-S*) or one of the string constants defined in Sddl.h. For more information about the standard SID string notation, see [SID Components](#).

The following SID string constants for well-known SIDs are defined in Sddl.h. For information about the corresponding *relative IDs* (RIDs), see [Well-known SIDs](#).

 Expand table

SDDL SID string	Constant in Sddl.h	Account alias and comment
"AA"	SDDL_ACCESS_CONTROL_ASSISTANCE_OPS	Access control assistance. The DOMAIN_ALIAS_RID_AA. Server 2008 R2, Windows Server 2003
"AC"	SDDL_ALL_APP_PACKAGES	All applications running on the system. SECURITY_BUILTIN_DOMAIN_RID, Windows 7, Windows Server 2003: Not available
"AN"	SDDL_ANONYMOUS	Anonymous logon. The SECURITY_ANONYMOUS
"AO"	SDDL_ACCOUNT_OPERATORS	Account operators. The DOMAIN_ALIAS_RID_AO
"AP"	SDDL_PROTECTED_USERS	Protected Users . The DOMAIN_GROUP_RID_AP. Windows 8, Windows 2008, Windows Vista
"AU"	SDDL_AUTHENTICATED_USERS	Authenticated users. The SECURITY_AUTHENTICATED_USERS
"BA"	SDDL_BUILTIN_ADMINISTRATORS	Built-in administrators. The DOMAIN_ALIAS_RID_BA
"BG"	SDDL_BUILTIN_GUESTS	Built-in guests. The DOMAIN_ALIAS_RID_BG
"BO"	SDDL_BACKUP_OPERATORS	Backup operators. The DOMAIN_ALIAS_RID_BO
"BU"	SDDL_BUILTIN_USERS	Built-in users. The DOMAIN_ALIAS_RID_BU

"CA"	SDDL_CERT_SERV_ADMINISTRATORS	Certificate publishers. The DOMAIN_GROUP_RID.
"CD"	SDDL_CERTSVC_DCOM_ACCESS	Users who can connect Component Object Model DOMAIN_ALIAS_RID_C 2008, Windows Vista
"CG"	SDDL_CREATOR_GROUP	Creator group. The core SECURITY_CREATOR_G
"CN"	SDDL_CLONEABLE_CONTROLLERS	Cloneable domain controller DOMAIN_GROUP_RID. 2008 R2, Windows 7, Windows Server 2003
"CO"	SDDL_CREATOR_OWNER	Creator owner. The core SECURITY_CREATOR_O
"CY"	SDDL_CRYPTO_OPERATORS	Crypto operators. The DOMAIN_ALIAS_RID_C available.
"DA"	SDDL_DOMAIN_ADMINISTRATORS	Domain administrators DOMAIN_GROUP_RID.
"DC"	SDDL_DOMAIN_COMPUTERS	Domain computers. The DOMAIN_GROUP_RID.
"DD"	SDDL_DOMAIN_DOMAIN_CONTROLLERS	Domain controllers. The DOMAIN_GROUP_RID.
"DG"	SDDL_DOMAIN_GUESTS	Domain guests. The co
"DU"	SDDL_DOMAIN_USERS	Domain users. The cor
"EA"	SDDL_ENTERPRISE_ADMINS	Enterprise administrators DOMAIN_GROUP_RID.
"ED"	SDDL_ENTERPRISE_DOMAIN_CONTROLLERS	Enterprise domain controller SECURITY_SERVER_LO
"EK"	SDDL_ENTERPRISE_KEY_ADMINS	Enterprise key admins. DOMAIN_GROUP_RID. R2, Windows 8.1, Win

		2008 R2, Windows 7, Windows Server 2003
"ER"	SDDL_EVENT_LOG_READERS	Event log readers. The DOMAIN_ALIAS_RID_EVENTLOG_READERS. 2008, Windows Vista and Windows Server 2008: Not available.
"ES"	SDDL_RDS_ENDPOINT_SERVERS	Endpoint servers. The DOMAIN_ALIAS_RID_ENDPOINT_SERVERS. 2008 R2, Windows 7, Windows Server 2003: Not available.
"HA"	SDDL_HYPER_V_ADMINS	Hyper-V administrator. The DOMAIN_ALIAS_RID_HYPER_V_ADMINS. 2008 R2, Windows 7, Windows Server 2003: Not available.
"HI"	SDDL_ML_HIGH	High integrity level. The SECURITY_MANDATORY_HIGH. 2008 R2, Windows 7, Windows Server 2003: Not available.
"HO"	SDDL_USER_MODE_HARDWARE_OPERATORS	Group members may control hardware. The corresponding RID is DOMAIN_ALIAS_RID_USERS. 2008 R2, Windows 7, Windows Server 2003: Not available.
"IS"	SDDL_IIS_USERS	Anonymous Internet user. The DOMAIN_ALIAS_RID_IIS_USERS. 2008 R2, Windows 7, Windows Server 2003: Not available.
"IU"	SDDL_INTERACTIVE	Interactively logged-on user. The type of a process when it was started. The type is LOGON32_LOGON_INTERACTIVE. The SECURITY_INTERACTIVE. 2008 R2, Windows 7, Windows Server 2003: Not available.
"KA"	SDDL_KEY_ADMINS	Domain key admins. The DOMAIN_GROUP_RID_KEY_ADMINS. 2008 R2, Windows 7, Windows Server 2003: Not available.
"LA"	SDDL_LOCAL_ADMIN	Local administrator. The DOMAIN_USER_RID_LOCAL_ADMIN. 2008 R2, Windows 7, Windows Server 2003: Not available.
"LG"	SDDL_LOCAL_GUEST	Local guest. The corresponding RID is DOMAIN_USER_RID_LOCAL_GUEST. 2008 R2, Windows 7, Windows Server 2003: Not available.
"LS"	SDDL_LOCAL_SERVICE	Local service account. The SECURITY_LOCAL_SERVICE. 2008 R2, Windows 7, Windows Server 2003: Not available.

"LU"	SDDL_PERFLOG_USERS	Performance Log users DOMAIN_ALIAS_RID_L
"LW"	SDDL_ML_LOW	Low integrity level. The SECURITY_MANDATOR
"ME"	SDDL_ML_MEDIUM	Medium integrity level. SECURITY_MANDATOR available.
"MP"	SDDL_ML_MEDIUM_PLUS	Medium Plus integrity SECURITY_MANDATOR Windows Vista and W
"MU"	SDDL_PERFMON_USERS	Performance Monitor u DOMAIN_ALIAS_RID_M
"NO"	SDDL_NETWORK_CONFIGURATION_OPS	Network configuration DOMAIN_ALIAS_RID_N
"NS"	SDDL_NETWORK_SERVICE	Network service account SECURITY_NETWORK_S
"NU"	SDDL_NETWORK	Network logon user. Th process when it was lo type is LOGON32_LOG SECURITY_NETWORK_I
"OW"	SDDL_OWNER_RIGHTS	Owner Rights SID. The SECURITY_CREATOR_O available.
"PA"	SDDL_GROUP_POLICY_ADMINS	Group Policy administr DOMAIN_GROUP_RID_P
"PO"	SDDL_PRINTER_OPERATORS	Printer operators. The DOMAIN_ALIAS_RID_P
"PS"	SDDL_PERSONAL_SELF	Principal self. The corre
"PU"	SDDL_POWER_USERS	Power users. The corre DOMAIN_ALIAS_RID_P
"RA"	SDDL_RDS_REMOTE_ACCESS_SERVERS	RDS remote access ser DOMAIN_ALIAS_RID_R

		2008 R2, Windows 7, 'Windows Server 2003
"RC"	SDDL_RESTRICTED_CODE	Restricted code. This is CreateRestrictedToken SECURITY_RESTRICTED
"RD"	SDDL_REMOTE_DESKTOP	Terminal server users. 1 DOMAIN_ALIAS_RID_R
"RE"	SDDL_REPLICATOR	Replicator. The correspo
"RM"	SDDL_RMS__SERVICE_OPERATORS	RMS Service. Available
"RO"	SDDL_ENTERPRISE_RO_DC	Enterprise Read-only d DOMAIN_GROUP_RID. Windows Server 2008 available.
"RS"	SDDL_RAS_SERVERS	RAS servers group. The DOMAIN_ALIAS_RID_R
"RU"	SDDL_ALIAS_PREW2KCOMPACC	Alias to grant permissio with operating systems RID is DOMAIN_ALIAS.
"SA"	SDDL_SCHEMA ADMINISTRATORS	Schema administrators DOMAIN_GROUP_RID.
"SI"	SDDL_ML_SYSTEM	System integrity level. ' SECURITY_MANDATOR available.
"SO"	SDDL_SERVER_OPERATORS	Server operators. The c DOMAIN_ALIAS_RID_S
"SS"	SDDL_SERVICE_ASSERTED	Authentication service SECURITY_AUTHENTIC 2008 R2, Windows 7, 'Windows Server 2003
"SU"	SDDL_SERVICE	Service logon user. This process when it was lo LOGON32_LOGON_SE SECURITY_SERVICE_RID

"SY"	SDDL_LOCAL_SYSTEM	Local system. The corre
"UD"	SDDL_USER_MODE_DRIVERS	User-mode driver. The SECURITY_USERMODE R2, Windows 7, Wind Server 2003: Not avail
"WD"	SDDL_EVERYONE	Everyone. The correspc
"WR"	SDDL_WRITE_RESTRICTED_CODE	Write Restricted code. SECURITY_WRITE_REST available.

The [ConvertSidToStringSid](#) and [ConvertStringSidToSid](#) functions always use the standard SID string notation and do not support SDDL SID string constants.

For more information about well-known SIDs, see [Well-known SIDs](#).

See also

[\[MS-DTYP\]: Security Descriptor Description Language](#)

Feedback

Was this page helpful?

[Provide product feedback](#) | [Get help at Microsoft Q&A](#)

© Microsoft 2024