

Product

▼

Solutions

▼

Resources

▼

Open Source

▼

Enterprise

▼

Pricing

Search

Sign in

Sign up

redcanaryco / atomic-red-team

Public

Notifications

Fork

2.8k

Star

9.7k

<> Code

Issues

6

Pull requests

5

Actions

Wiki

Security

Insights

Files

f339e7d

Go to file

> .github

> atomic_red_team

> atomics

> Indexes

> T1003.001

> T1003.002

> T1003.003

> T1003.004

> T1003.005

> T1003.006

> T1003.007

> T1003.008

> T1003

> T1006

> T1007

> T1010

> T1012

> T1014

> T1016

> T1018

> T1020

> T1021.001

> T1021.002

> T1021.003

> T1021.006

> T1027.001

> T1027.002

> T1027.004

> T1027

> T1030

> T1033

> T1036.003

> T1036.004

> T1036.005

> T1036.006

> T1036

atomic-red-team / atomics / T1574.009 / T1574.009.md

CircleCI Atomic Red Team doc... Generate docs from job=genera...

bc21f59 · 3 years ago

History

PreviewCodeBlame

59 lines (34 loc) · 3.02 KB

Raw

T1574.009 - Path Interception by Unquoted Path

Description from ATT&CK

Adversaries may execute their own malicious payloads by hijacking vulnerable file path references. Adversaries can take advantage of paths that lack surrounding quotations by placing an executable in a higher level directory within the path, so that Windows will choose the adversary's executable to launch.

Service paths (Citation: Microsoft CurrentControlSet Services) and shortcut paths may also be vulnerable to path interception if the path has one or more spaces and is not surrounded by quotation marks (e.g., `C:\unsafe path with space\program.exe` vs. `"C:\safe path with space\program.exe"`). (Citation: Help eliminate unquoted path) (stored in Windows Registry keys) An adversary can place an executable in a higher level directory of the path, and Windows will resolve that executable instead of the intended executable. For example, if the path in a shortcut is `C:\program files\myapp.exe` , an adversary may create a program at `C:\program.exe` that will be run instead of the intended program. (Citation: Windows Unquoted Services) (Citation: Windows Privilege Escalation Guide)

This technique can be used for persistence if executables are called on a regular basis, as well as privilege escalation if intercepted executables are started by a higher privileged process.

Atomic Tests

- [Atomic Test #1 - Execution of program.exe as service with unquoted service path](#)

Atomic Test #1 - Execution of program.exe as service with unquoted service path

When a service is created whose executable path contains spaces and isn’t enclosed within quotes, leads to a vulnerability known as Unquoted Service Path which allows a user to gain SYSTEM privileges. In this case, if an executable program.exe in C:\ exists, C:\program.exe will be executed instead of test.exe in C:\Program Files\subfolder\test.exe.

Supported Platforms: Windows

auto_generated_guid: 2770dea7-c50f-457b-84c4-c40a47460d9f

Inputs:

Page 1 of 2

- >  T1037.001
- >  T1037.002
- >  T1037.004
- >  T1037.005
- >  T1039
- >  T1040

Name	Description	Type	Default Value
service_executable	Path of the executable used for the service and as the hijacked program.exe	Path	PathToAtomicsFolder\T1574.009\bin\Winc

Attack Commands: Run with `command_prompt` ! Elevation Required (e.g. root or admin)

```
copy #{service_executable} "C:\Program Files\windows_service.exe"
copy #{service_executable} "C:\program.exe"
sc create "Example Service" binpath= "C:\Program Files\windows_service.e
sc start "Example Service"
```

Cleanup Commands:

```
sc stop "Example Service" >nul 2>&1
sc delete "Example Service" >nul 2>&1
del "C:\Program Files\windows_service.exe" >nul 2>&1
del "C:\program.exe" >nul 2>&1
del "C:\Time.log" >nul 2>&1
```