



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies



Event Logging (Windows Installer)

Article • 06/24/2022 • 5 contributors

Feedback

[Windows Events](#) provides a standard, centralized way for applications (and the operating system) to record important software and hardware events. The event-logging service stores events from various sources in a single collection called an *event log*. Prior to Windows Vista, you would use either [Event Tracing for Windows](#) (ETW) or [Event Logging](#) to log events. Windows Vista introduced a new eventing model that unifies both ETW and the [Windows Event Log](#) API.


The installer also writes entries into the event log. These record events such as following:

- Success or failure of the installation; removal or repair of a product.
- Errors that occur during product configuration.
- Detection of corrupted configuration data.

If a large amount of information is written, the Event Log file can become full and the installer displays the message, "The Application log file is full."

The installer may write the following entries in the event log. All event log messages have a unique event ID. All general errors authored in the [Error table](#) that are returned for an installation that fails are logged in the Application Event Log with a message ID equal to the Error + 10,000. For example, the error number in the Error table for an installation completed successfully is 1707. The successful installation is logged in the Application Event Log with a message ID of 11707 (1707 + 10,000).

For information about how to enable verbose logging on a user's computer when troubleshooting deployment, see [Windows Installer Best Practices](#).

 Expand table

Event ID	Message	Remarks
1001	Detection of product '%1', feature '%2' failed during request for component '%3'	A warning message. For details, see Searching For a Broken Feature or Component .
1002	Unexpected or missing value (name: '%1', value: '%2') in key '%3'	Error message that there was an unexpected or missing value.
1003	Unexpected or missing subkey '%1' in key '%2'	Error message that there was an unexpected or missing subkey.

1004	Detection of product '%1', feature '%2', component '%3' failed Note: Beginning with Windows Installer version 2.0, this message is: Detection of product '%1', feature '%2', component '%3' failed. The resource '%4' does not exist.	A warning message. See also Searching For a Broken Feature or Component .
1005	Install operation initiated a reboot	Informational message that the installation initiated a reboot of the system.
1006	Verification of the digital signature for cabinet '%1' cannot be performed. WinVerifyTrust is not available on the computer.	Warning message. A cabinet was authored in the MsiDigitalSignature table to have a WinVerifyTrust check performed. This action could not be performed because the computer does not have the proper cryptography DLLs installed.
1007	The installation of %1 is not permitted by software restriction policy. The Windows Installer only allows execution of unrestricted items. The authorization level returned by software restriction policy was %2.	An error message indicating that the administrator has configured software restriction policy to disallow this install.
1008	The installation of %1 is not permitted due to an error in software restriction policy processing. The object cannot be trusted.	An error message indicating that there were problems attempting to verify the package according to software restriction policy.
1012	This version of Windows does not support	Error message indicating that scripts for 64-bit packages can only be executed

	deploying 64-bit packages. The script '%1' is for a 64-bit package.	on a 64-bit computer.
1013	{Unhandled exception report}	Error message for an unhandled exception, this is the report.
1014	Windows Installer proxy information not registered correctly	Error message that proxy information was not registered correctly.
1015	Failed to connect to server. Error: %d	Informational message that the installation failed to connect to server.
1016	Detection of product '%1', feature '%2', component '%3' failed. The resource '%4' in a run-from-source component could not be located because no valid and accessible source could be found.	Warning message. For more information, see Searching for a Broken Feature or Component .
1017	User SID had changed from '%1' to '%2' but the managed app and the user data keys cannot be updated. Error = '%3'.	Error message indicating that an error occurred while attempting to update the user's registration after the user's SID changed.
1018	The application '%1' cannot be installed because it is not compatible with this version of Windows.	Error message indicating that the installation is incompatible with the currently running version of Windows. Contact the manufacturer of the software being installed for an update.
1019	Product: %1 - Update '%2' was successfully removed.	Informational message that the installer has removed the update. Windows Installer 2.0: Not available.

1020	Product: %1 - Update '%2' could not be removed. Error code %3. Additional information is available in the log file %4.	Error message indicating that the installer was unable to remove the update. Additional information is available in the log file. Windows Installer 2.0: Not available.
1021	Product: %1 - Update '%2' could not be removed. Error code %3.	Error message indicating that the installer was unable to remove the update. For information on how to turn on logging, see Enable verbose logging on user's computer when troubleshooting deployment . Windows Installer 2.0: Not available.
1022	Product: %1 - Update '%2' installed successfully.	Informational message that the installer has installed the update successfully. Windows Installer 2.0: Not available.
1023	Product: %1 - Update '%2' could not be installed. Error code %3. Additional information is available in the log file %4.	Error message indicating that the installer was unable to install the update. Additional information is available in the log file. Windows Installer 2.0: Not available.
1024	Product: %1 - Update '%2' could not be installed. Error code %3.	Error message indicating that the installer was unable to install the update. For information on how to turn logging on, see Enable verbose logging on user's computer when troubleshooting deployment . Windows Installer 2.0: Not available.
1025	Product: %1. The file %2 is being used by the following process: Name: %3 , Id %4.	Windows Installer 2.0: Not available.
1026	Windows Installer has determined that its configuration data registry key was not secured properly. The	Warning message. Windows Installer 3.1 and earlier: Not available.

	owner of the key must be either Local System or Builtin\Administrators. The existing key will be deleted and re-created with the appropriate security settings.	
1027	Windows Installer has determined that a registry sub key %1 within its configuration data was not secured properly. The owner of the key must be either Local System or Builtin\Administrators. The existing sub key and all of its contents will be deleted.	Warning message. Windows Installer 3.1 and earlier : Not available.
1028	Windows Installer has determined that its configuration data cache folder was not secured properly. The owner of the key must be either Local System or Builtin\Administrators. The existing folder will be deleted and re-created with the appropriate security settings.	Warning message. Windows Installer 3.1 and earlier : Not available.
1029	Product: %1. Restart required.	Warning message indicating that a system restart is required to complete the installation and the restart has been deferred to a later time. Windows Installer 3.1 and earlier : Not available.
1030	Product: %1. The application tried to install a more recent version of the protected Windows	Warning message indicating that the installation tried to replace a critical file that is protected by Windows Resource Protection . An update of the operating

	file %2. You may need to update your operating system for this application to work correctly. (Package Version: %3, Operating System Protected Version: %4).	system may be required to use this application. Windows Installer 3.1 and earlier : Not available.
1031	Product: %1. The assembly '%2' for component '%3' is in use.	Warning message indicating that the installation tried to update an assembly currently in use. The system must be restarted to complete the update of this assembly. Windows Installer 3.1 and earlier : Not available.
1032	An error occurred while refreshing environment variables updated during the installation of '%1'.	Warning message indicating that some users who are logged on to the computer may need to log off and back on to complete the update of environment variables. Windows Installer 3.1 and earlier : Not available.
1033	Product: %1. Version: %2. Language: %3. Installation completed with status: %4. Manufacturer: %5.	Field 1 - ProductName Field 2 - ProductVersion Field 3 - ProductLanguage Windows Installer 3.1 and earlier : Not available. Field 5 - Manufacturer Windows Installer 4.5 and earlier : Field 5 not available.
1034	Product: %1. Version: %2. Language: %3. Removal completed with status: %4. Manufacturer: %5.	Field 1 - ProductName Field 2 - ProductVersion Field 3 - ProductLanguage Windows Installer 3.1 and earlier : Not available. Field 5 - Manufacturer Windows Installer 4.5 and earlier : Field 5 not available.
1035	Product: %1. Version: %2. Language: %3. Configuration change	Field 1 - ProductName Field 2 - ProductVersion Field 3 - ProductLanguage

	completed with status: %4. Manufacturer: %5.	Field 5 - Manufacturer Windows Installer 4.5 and earlier : Field 5 not available.
1036	Product: %1. Version: %2. Language: %3. Update: %4. Update installation completed with status: %5. Manufacturer: %6.	Field 1 - ProductName Field 2 - ProductVersion Field 3 - ProductLanguage Field 4 - This is the user friendly name if the MsiPatchMetadata Table is present in the patch package. Otherwise, this is the patch code GUID of the patch. Field 5 - Status of update installation. Windows Installer 3.1 and earlier : Not available. Field 6 - Manufacturer Windows Installer 4.5 and earlier : Field 6 not available.
1037	Product: %1. Version: %2. Language: %3. Update: %4. Update removal completed with status: %5. Manufacturer: %6.	Field 1 - ProductName Field 2 - ProductVersion Field 3 - ProductLanguage Field 4 - This is the user friendly name if the MsiPatchMetadata Table is present in the patch package. Otherwise, this is the patch code GUID of the patch. Field 5 - Status of update removal. Windows Installer 3.1 and earlier : Not available. Field 6 - Manufacturer Windows Installer 4.5 and earlier : Field 6 not available.
1038	Product: %1. Version: %2. Language: %3. Reboot required. Reboot Type: %4. Reboot Reason: %5. Manufacturer: %6.	Field 1 - ProductName Field 2 - ProductVersion Field 3 - ProductLanguage Field 4 - A constant indicating the type of restart: msirbRebootImmediate (1) - There was an immediate restart of the computer. msirbRebootDeferred (2) - A user or admin has deferred a required restart of the computer using the UI or REBOOT =ReallySuppress.

		<p>Field 5 - A constant indicating the reason for the restart:</p> <p>msirbRebootUndeterminedReason (0)- Restart required for an unspecified reason.</p> <p>msirbRebootInUseFilesReason (1)- A restart was required to replace files in use.</p> <p>msirbRebootScheduleRebootReason (2)- The package contains a ScheduleReboot action.</p> <p>msirbRebootForceRebootReason (3)- The package contains a ForceReboot action.</p> <p>msirbRebootCustomActionReason (4)- A custom action called the MsiSetMode function.</p> <p>Windows Installer 3.1 and earlier: Not available.</p> <p>Field 6 - Manufacturer</p> <p>Windows Installer 4.5 and earlier: Field 6 not available.</p>
1044	%1 is not Microsoft signed. So, rejecting per the Windows Lockdown Policy.	Error message indicating that binary is not signed by Microsoft and is not allowed as per Windows Lockdown Policy.
10005	The installer has encountered an unexpected error installing this package. This may indicate a problem with this package. The error code is [1]. {{The arguments are: [2], [3], [4]}}	Error message indicating an internal error occurred. The text of this message is based upon the text authored for error 5 in the Error table.
11707	Product [2] – Installation operation completed successfully	Informational message that the installation of the product was successful.

11708	Product [2] – Installation operation failed	Error message that the installation of the product failed.
11728	Product [2] -- Configuration completed successfully.	Informational message that configuration of the product was successful.

You can import localized errors strings for events into your database by using Msidb.exe or [MsiDatabaseImport](#). The SDK includes localized resource strings for each of the languages listed in the [Localizing the Error and ActionText Tables](#) section. If the error strings corresponding to events are not populated, the installer loads localized strings for the language specified by the [ProductLanguage](#) property.


Feedback

Was this page helpful?



 Yes

 No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

 English (United States)

 Your Privacy Choices


 Theme 

[Manage cookies](#)

[Previous Versions](#)

[Blog](#) 

[Contribute](#)

[Privacy](#) 

[Terms of Use](#)

[Trademarks](#) 

© Microsoft 2024