



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking “Manage Cookies” at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies

Microsoft Ignite

Nov 19–22, 2024

Register now >



Learn

Discover ▾

Product documentation ▾

Development languages ▾

Topics ▾



Sign in

Microsoft 365

Solutions and architecture ▾

Apps and services ▾

Training ▾

Resources ▾

Free Account

Version

Windows 11 and Windows Server 2022 PowerShell ▾



Search

Import-PfxCertificate

New-CertificateNotificationTask

New-SelfSignedCertificate

Remove-CertificateEnrollmentPolicyServer

Remove-CertificateNotificationTask

Set-CertificateAutoEnrollmentPolicy

Switch-Certificate

Test-Certificate

> PlatformIdentifier

> PnpDevice

> PrintManagement

> ProcessMitigations

> Provisioning

> RDMgmt

> RemoteAccess

> RemoteDesktopServices

> ScheduledTasks

> SecureBoot

> ServerCore

> ServerManager

> ServerManagerTasks

> ShieldedVmCmdlets

> ShieldedVMDataFile

> ShieldedVMTemplate

> SmbShare

> SmbWitness

> SMISConfig

> SoftwareInventoryLogging

> StartLayout

> Storage

> StorageQoS

> StorageReplica

Learn / Windows / PowerShell / pki /



Import-Certificate

Reference



Feedback

Module: [pki](#)

In this article

[Syntax](#)

[Description](#)

[Examples](#)

[Parameters](#)

[Show 3 more](#)

Imports one or more certificates into a certificate store.

Syntax

PowerShell



Copy

```
Import-Certificate
    [-FilePath] <String>
    [-CertStoreLocation <String>]
    [-WhatIf]
    [-Confirm]
    [<CommonParameters>]
```

Description

The `Import-Certificate` cmdlet imports one or more certificates into a certificate store.

Examples

EXAMPLE 1

PowerShell



Copy

```
$params = @{
    FilePath = 'C:\Users\Xyz\Desktop\BackupCert.cer'
    CertStoreLocation = 'Cert:\CurrentUser\Root'
```

 Download PDF

```
}  
Import-Certificate @params
```

This example imports the certificate from the file into the root store of the current user.

EXAMPLE 2

PowerShellCopy

```
Set-Location -Path cert:\CurrentUser\My  
  
Import-Certificate -Filepath 'C:\files\intermediate.cert'
```

This example imports the certificate from the file into the current store.

EXAMPLE 3

PowerShellCopy


```
$params = @{  
    FilePath = 'C:\Users\Xyz\Desktop\BackupCert.cer'  
    CertStoreLocation = 'Cert:\LocalMachine\Root'  
}  
Import-Certificate @params
```

This example imports the certificate from the file into the root store of the local machine.

Parameters

-CertStoreLocation

Specifies the path to the certificate store where the certificates will be imported. If the path to the certificate store is not specified, then the current store is used. In order to get a list of valid **CertStoreLocation** values, open PowerShell and run `Get-ChildItem Cert:\`.

 Expand table

Type:	String
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-Confirm

Prompts you for confirmation before running the cmdlet.

 Expand table

Type:	SwitchParameter
Aliases:	cf
Position:	Named
Default value:	False

Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-FilePath


Specifies the path to a certificate file to be imported. Acceptable formats include `.sst`, `.p7b`, and `.cert` files. If the file contains multiple certificates, then each certificate will be imported to the destination store. The file must be in `.sst` format to import multiple certificates; otherwise, only the first certificate in the file will be imported.

 Expand table

Type:	String
Aliases:	FullName
Position:	0
Default value:	None
Required:	True
Accept pipeline input:	True
Accept wildcard characters:	False

-WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

 Expand table

Type:	SwitchParameter
Aliases:	wi
Position:	Named
Default value:	False
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

Inputs

String

A **String** containing the file path.


Outputs

X509Certificate2[]

The output is an array of **X509Certificate2[]** objects.

Related Links

- [Get-ChildItem](#) 

- [Set-Location](#) 
- [Export-Certificate](#)
- [System Store Locations](#)

Feedback

Was this page helpful?



 Yes

 No

[Provide product feedback](#) 


 English (United States)

  Your Privacy Choices


 Theme 

Manage cookies


Previous Versions

Blog 

Contribute

Privacy 

Terms of Use

Trademarks 

© Microsoft 2024