

Product

▼

Solutions

▼

Resources

▼

Open Source

▼

Enterprise

▼

Pricing

Q

Search

Sign in

Sign up

redcanaryco

/

atomic-red-team

Public

Notifications

Fork 2.8k

Star 9.7k

<> Code

Issues 6

Pull requests 5

Actions

Wiki

Security

Insights

atomic-red-team / atomics / T1553.005 / T1553.005.md

CircleCI Atomic Red Team doc...

Generate docs from job=genera...

bc21f59 · 3 years ago

History

T1553.005 - Mark-of-the-Web Bypass

Description from ATT&CK

Adversaries may abuse specific file formats to subvert Mark-of-the-Web (MOTW) controls. In Windows, when files are downloaded from the Internet, they are tagged with a hidden NTFS Alternate Data Stream (ADS) named `Zone.Identifier` with a specific value known as the MOTW.(Citation: Microsoft Zone.Identifier 2020) Files that are tagged with MOTW are protected and cannot perform certain actions. For example, starting in MS Office 10, if a MS Office file has the MOTW, it will open in Protected View. Executables tagged with the MOTW will be processed by Windows Defender SmartScreen that compares files with an allowlist of well-known executables. If the file in not known/trusted, SmartScreen will prevent the execution and warn the user not to run it.(Citation: Beek Use of VHD Dec 2020)(Citation: Outflank MotW 2020)(Citation: Intezer Russian APT Dec 2020) Adversaries may abuse container files such as compressed/archive (.arj, .gzip) and/or disk image (.iso, .vhd) file formats to deliver malicious payloads that may not be tagged with MOTW. Container files downloaded from the Internet will be marked with MOTW but the files within may not inherit the MOTW after the container files are extracted and/or mounted. MOTW is a NTFS feature and many container files do not support NTFS alternative data streams. After a container file is extracted and/or mounted, the files contained within them may be treated as local files on disk and run without protections.(Citation: Beek Use of VHD Dec 2020)(Citation: Outflank MotW 2020)

Atomic Tests

Atomic Test #1 - Mount ISO image

Atomic Test #2 - Mount an ISO image and run executable from the ISO

Atomic Test #3 - Remove the Zone.Identifier alternate data stream

Atomic Test #1 - Mount ISO image

Mounts ISO image downloaded from internet to evade Mark-of-the-Web. Upon successful execution, powershell will download the .iso from the Atomic Red Team repo, and mount the image. The provided sample ISO simply has a Reports shortcut file in it. Reference: https://www.microsoft.com/security/blog/2021/05/27/new-sophisticated-email-based-attack-from-nobelium/

Supported Platforms: Windows

auto_generated_guid: 002cca30-4778-4891-878a-aaffcfa502fa

Page 1 of 4

Files

f339e7d

Go to file

> .github

> atomic_red_team

> atomics

- > Indexes
- > T1003.001
- > T1003.002
- > T1003.003
- > T1003.004
- > T1003.005
- > T1003.006
- > T1003.007
- > T1003.008
- > T1003
- > T1006
- > T1007
- > T1010
- > T1012
- > T1014
- > T1016
- > T1018
- > T1020
- > T1021.001
- > T1021.002
- > T1021.003
- > T1021.006
- > T1027.001
- > T1027.002

Inputs:

Name	Description	Type	Default Value
path_of_iso	Path to ISO file	Path	PathToAtomicsFolder\T1553.005\bin\T1553.005.is

Attack Commands: Run with powershell!

```
Mount-DiskImage -ImagePath "#{path_of_iso}"
```

Cleanup Commands:

```
Dismount-DiskImage -ImagePath "#{path_of_iso}" | Out-Null
```

Dependencies: Run with powershell!

Description: T1553.005.iso must exist on disk at specified location (#{path_of_iso})

Check Prereq Commands:

atomic-red-team / atomics / T1553.005 / T1553.005.md ↑ Top

PreviewCodeBlame172 lines (102 loc) · 6.59 KBRawCopyDownloadMenu

Get Prereq Commands:

```
New-Item -Type Directory (split-path #{path_of_iso}) -ErrorAction ignore
Invoke-WebRequest https://raw.githubusercontent.com/redcanaryco/atomic-r
```

Atomic Test #2 - Mount an ISO image and run executable from the ISO

Mounts an ISO image downloaded from internet to evade Mark-of-the-Web and run hello.exe executable from the ISO. Upon successful execution, powershell will download the .iso from the Atomic Red Team repo, mount the image, and run the executable from the ISO image that will open command prompt echoing "Hello, World!". ISO provided by:<https://twitter.com/mattifestation/status/1398323532988399620>
Reference:<https://www.microsoft.com/security/blog/2021/05/27/new-sophisticated-email-based-attack-from-nobelium/>,

Supported Platforms: Windows

auto_generated_guid: 42f22b00-0242-4afc-a61b-0da05041f9cc
















Inputs:

Name	Description	Type	Default Value
path_of_iso	Path to ISO file	Path	PathToAtomicsFolder\T1553.005\bin\FeelTheBurn

Attack Commands: Run with powershell!

```
$keep = Mount-DiskImage -ImagePath "#{path_of_iso}" -StorageType ISO -Ac
$driveLetter = ($keep | Get-Volume).DriveLetter
invoke-item "$($driveLetter):\hello.exe"
```

Cleanup Commands:

- >  T1027.004
- >  T1027
- >  T1030
- >  T1033
- >  T1036.003
- >  T1036.004
- >  T1036.005
- >  T1036.006
- >  T1036
- >  T1037.001
- >  T1037.002
- >  T1037.004
- >  T1037.005
- >  T1039
- >  T1040

```
Dismount-DiskImage -ImagePath "#{path_of_iso}" | Out-Null
Stop-process -name "hello" -Force -ErrorAction ignore
```

Dependencies: Run with powershell!

Description: FeelTheBurn.iso must exist on disk at specified location (#{path_of_iso})

Check Prereq Commands:

```
if (Test-Path #{path_of_iso}) {exit 0} else {exit 1}
```

Get Prereq Commands:

```
New-Item -Type Directory (split-path #{path_of_iso}) -ErrorAction ignore
Invoke-WebRequest https://raw.githubusercontent.com/redcanaryco/atomic-r
```

Atomic Test #3 - Remove the Zone.Identifier alternate data stream

Remove the Zone.Identifier alternate data stream which identifies the file as downloaded from the internet. Removing this allows more freedom in executing scripts in PowerShell and avoids opening files in protected view.

Supported Platforms: Windows

auto_generated_guid: 64b12afc-18b8-4d3f-9eab-7f6cae7c73f9

Inputs:

Name	Description	Type	Default Value
file_to_download	File that will be downloaded to test against.	Url	https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/README.md
file_path	File to have the Zone.Identifier removed.	String	\$env:tmp\ReadMe.md

Attack Commands: Run with powershell!

```
Unblock-File -Path #{file_path}
```

Cleanup Commands:

```
Set-Content -Path #{file_path} -Stream Zone.Identifier -Value '[ZoneTran
```

Dependencies: Run with powershell!

Description: A test file with the Zone.Identifier attribute must be present.

Check Prereq Commands:

```
if (Test-Path #{file_path}) { EXIT 0 } else { EXIT 1 }
```

Get Prereq Commands:

```
Invoke-WebRequest #{file_to_download} -OutFile #{file_path}
Set-Content -Path #{file_path} -Stream Zone.Identifier -Value '[ZoneTran
```

