


🔍 Filter by title

NetrWkstaTransportEnum (Opnum 5)
3.2.4.5
NetrWkstaTransportAdd (Opnum 6)
3.2.4.6
NetrWkstaTransportDel (Opnum 7)
3.2.4.7 NetrUseAdd (Opnum 8)
3.2.4.8 NetrUseGetInfo (Opnum 9)
3.2.4.9 NetrUseDel (Opnum 10)
3.2.4.10 NetrUseEnum (Opnum 11)
3.2.4.11
NetrWorkstationStatisticsGet (Opnum 13)
3.2.4.12
NetrGetJoinInformation (Opnum 20)
› 3.2.4.13 NetrJoinDomain2 (Opnum 22)
3.2.4.14 NetrUnjoinDomain2 (Opnum 23)
3.2.4.15
NetrRenameMachineInDomain2 (Opnum 24)
3.2.4.16 NetrValidateName2 (Opnum 25)
3.2.4.17
NetrGetJoinableOUs2 (Opnum 26)
3.2.4.18
NetrAddAlternateComputerName (Opnum 27)
3.2.4.19

 **Download PDF**

3.2.4.3 NetrWkstaUserEnum (Opnum 2)

Article • 04/27/2022

 [Feedback](#)

The **NetrWkstaUserEnum** method returns details about users who are currently active on a remote computer.

```
unsigned long NetrWkstaUserEnum(  
    [in, string, unique] WKSSVC_IDENTIFY_HANDLE ServerName,  
    [in, out] LPWKSTA_USER_ENUM_STRUCT UserInfo,  
    [in] unsigned long PreferredMaximumLength,  
    [out] unsigned long* TotalEntries,  
    [in, out, unique] unsigned long* ResumeHandle  
);
```

ServerName: A **WKSSVC_IDENTIFY_HANDLE** structure (section 2.2.2.1) that identifies the [server \(2\)](#). The [client](#) MUST map this structure to an [RPC](#) binding [handle](#) ([C706] ↗ sections 4.3.5 and 5.1.5.2). The server MUST ignore this parameter.

UserInfo: A pointer to the buffer to receive the data. The data MUST be returned as a **WKSTA_USER_ENUM_STRUCT** structure (section 2.2.5.14) that contains a **Level** member that specifies the type of structure to return.

PreferredMaximumLength: The number of bytes to allocate for the return data.

TotalEntries: The total number of entries that could have been enumerated if the buffer were big enough to hold all the entries.

ResumeHandle: A pointer that, if specified, and if this method returns ERROR_MORE_DATA, MUST receive an implementation-specific value<34> that can be passed in subsequent calls to this method, to continue with the enumeration of currently logged-on users.

If this parameter is NULL or points to zero, the enumeration MUST start from the beginning of the list of currently logged-on users.

Return Values: When the message processing result matches the description in column two of the following table, this method MUST return one of the following values ([MS-ERREF] section 2.2). The most common error codes are listed in the following table.

 **Expand table**

Value/code	Meaning
NERR_Success 0x00000000	The operation completed successfully.
ERROR_ACCESS_DENIED 0x00000005	Access is denied.
ERROR_INVALID_LEVEL 0x0000007C	The information level is invalid.

ERROR_MORE_DATA	More entries are available. The <i>UserInfo</i> buffer was not large enough to contain all the entries.
0x000000EA	

Any other return value MUST conform to the error code requirements in **Protocol Details** (section 3).

The server (2) SHOULD<35> enforce security measures to verify that the caller has the required permissions to execute this routine. If the server enforces security measures, and the caller does not have the required credentials, the server MUST fail the call with ERROR_ACCESS_DENIED. Specifications for determining the identity of the caller for the purpose of performing an access check are in [MS-RPCE] section 3.3.3.1.3.

If the **Level** member of the **WKSTA_USER_ENUM_STRUCT** structure passed in the *UserInfo* parameter does not equal 0x00000000 or 0x00000001, the server MUST fail the call.

If the **Level** member equals 0x00000000, the server MUST return an array of the names of users currently logged on the computer by filling the **WKSTA_USER_INFO_0_CONTAINER** structure (section 2.2.5.14) in the **WkstaUserInfo** field of the *UserInfo* parameter.

If the **Level** member equals 0x00000001, the server MUST return an array of the names and domain details of each user currently logged on the computer, and a list of **OtherDomains** (section 3.2.1.3) in the computer.

If the *PreferredMaximumLength* parameter equals **MAX_PREFERRED_LENGTH** (section 2.2.1.3), the server MUST return all the requested data. Otherwise, if the *PreferredMaximumLength* is insufficient to hold all the entries, then the server MUST return the maximum number of entries that fit in the *UserInfo* buffer and return ERROR_MORE_DATA.

The following rules specify processing of the *ResumeHandle* parameter:

- If the *ResumeHandle* parameter is either NULL or points to 0x00000000, the enumeration MUST start from the beginning of the list of the currently logged on users.<36>
- If the *ResumeHandle* parameter points to a non-zero value, the server MUST continue enumeration based on the value of *ResumeHandle*. The server is not required to maintain any state between calls to the NetrWkstaUserEnum method.
- If the client specifies a *ResumeHandle*, and if the server returns ERROR_MORE_DATA, the server MUST set the value to which *ResumeHandle* points to an implementation-specific value that allow the server to continue with this enumeration on a subsequent call to this method, with the same value for *ResumeHandle*.

The server is not required to maintain any state between calls to the NetrWkstaUserEnum method. If the server returns NERR_Success or ERROR_MORE_DATA, it MUST set the *TotalEntries* parameter to equal the total number of entries that could have been enumerated from the current resume position.

Additional resources

Events

Nov 20, 12 AM - Nov 22, 12 AM

Join online sessions at Microsoft Ignite created to expand your skills and help you tackle today's complex issues.

[Register now](#)

