



Ransomware

# An Overview of the New Rhysida Ransomware Targeting the Healthcare Sector

In this blog entry, we will provide details on Rhysida, including its targets and what we know about its infection chain.

By: Trend Micro Research

August 09, 2023

Read time: 7 min (1936 words)




Subscribe

*Updated on August 9, 2023, 9:30 a.m. EDT: We updated the entry to include an analysis of current Rhysida ransomware samples' encryption routine.*



*Updated on August 14, 2023, 6:00 a.m. EDT: We updated the entry to include Trend XDR workbench alerts for Rhysida and its components.*

## Introduction

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.



[Paramètres des cookies](#)[Autoriser tous les cookies](#)



RANSOMWARE (RHYSIDA.SM), which emerged in May 2023. In this blog entry, we

will provide details on Rhysida, including its targets and what we know about its infection chain.

## Who is behind the Rhysida ransomware?


Not much is currently known about the threat actors behind Rhysida in terms of origin or affiliations. According to the HC3 alert, Rhysida poses itself as a “cybersecurity team” that offers to assist victims in finding security weaknesses within their networks and system. In fact, the group’s first appearance involved the use of a victim chat support portal.



## Who are Rhysida’s targets?

As mentioned earlier, Rhysida, which was previously known for targeting the education, government, manufacturing, and tech industries, among others — has begun conducting attacks on healthcare and public health organizations. The healthcare industry has seen an **increasing number of ransomware attacks** over the past five years. This includes a recent **incident** involving Prospect Medical Holdings, a California-based healthcare system, that occurred in early August (although the group behind the attack has yet to be named as of writing).


Data from Trend Micro™ Smart Protection Network™ (SPN) shows a similar trend, where detections from May to August 2023 show that its operators are targeting multiple industries rather than focusing on just a single sector.

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

 **Business**






and the United States.




© 2023 TREND MICRO

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

 Business






© 2023 TREND MICRO

Figure 1. The industry and country detection count for Rhysida ransomware based on Trend SPN data from May to August 2023

## How does a Rhysida attack proceed?

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

TREND Micro Business




© 2023 TREND MICRO



Figure 2. The Rhysida ransomware infection chain

Rhysida ransomware usually arrives on a victim's machine via phishing lures, after which Cobalt Strike is used for lateral movement within the system.

Additionally, our telemetry shows that the threat actors execute PsExec to deploy PowerShell scripts and the Rhysida ransomware payload itself. The PowerShell script (g.ps1), detected as Trojan.PS1.SILENTKILL.A, is used by the threat actors to terminate antivirus-related processes and services, delete shadow copies, modify remote desktop protocol (RDP) configurations, and change the active directory (AD) password.

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.





Rhysida ransomware employs a 4096-bit RSA key and AES-CTR for file encryption, which we discuss in detail in a succeeding section. After successful encryption, it appends the .rhysida extension and drops the ransom note CriticalBreachDetected.pdf.

This ransom note is fairly unusual — instead of an outright ransom demand as seen in most ransom notes from other ransomware families, the Rhysida ransom note is presented as an alert from the Rhysida “cybersecurity team” notifying victims that their system has been compromised and their files encrypted. The ransom demand comes in the form of a “unique key” designed to restore encrypted files, which must be paid for by the victim.

## Summary of malware and tools used by Rhysida

- **Malware:** RHYSIDA, SILENTKILL, Cobalt Strike
- **Tools:** PsExec

Initial Access	Phishing	Based on external reports, Rhysida uses phishing lures for initial access
Lateral Movement	PsExec	Microsoft tool used for remote execution
	Cobalt Strike	3 <sup>rd</sup> party tool abused for lateral movement
Defense Evasion	SILENTKILL	Malware deployed to terminate security-related processes and services, delete shadow copies, modify RDP configurations, and change the AD password
Impact	Rhysida ransomware	Ransomware encryption

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

 Business



## A closer look at Rhysida's encryption routine

After analyzing current Rhysida samples, we observed that the ransomware uses **LibTomCrypt**, an open-source cryptographic library, to implement its encryption routine. Figure 3 shows the procedures Rhysida follows when initializing its encryption parameters.

```
if ( !init_prng(&prng, &PRNG_IDX) )  
{  
    for ( thread_i = 0; thread_i < PROCS; ++thread_i )  
    {  
        if ( init_prng(prngs + 17648 * thread_i, PRNG_IDXS + thread_i) )// Initialize ChaCha20 PRNG (Pseudo-Random Number Generator) for each thread  
            goto LABEL_46;  
    }  
    if ( !rsa_import(&PUB_DER, _PUB_DER_LEN, &key) )// Import RSA key  
    {  
        err = register_cipher(&refptr_aes_enc_desc);// Register AES cipher to the list of usable ciphers.  
        if ( !err )  
        {  
            CIPHER = find_cipher("aes");           // Declaration of CIPHER to be used from the list  
            if ( CIPHER != -1 )  
            {  
                err = register_hash(&refptr_chc_desc);// Register CHC Hash Algorithm  
                if ( !err )  
                {  
                    err = chc_register(CIPHER);      // Register AES to CHC Hash  
                    if ( !err )  
                    {  
                        HASH_IDX = find_hash("chc_hash");  
                        if ( HASH_IDX != -1 )  
                        {  
                            _aes_keysize = 32;  
                            err = rijndael_keysize(&_aes_keysize);  
                        }  
                    }  
                }  
            }  
        }  
    }  
}
```

Figure 3. Rhysida's parameters for encryption

Rhysida uses LibTomCrypt's pseudorandom number generator (PRNG) functionalities for key and initialization vector (IV) generation. The *init\_prng* function is used to initialize PRNG functionalities as shown in Figure 4. The same screenshot also shows how the ransomware uses the library's ChaCha20 PRNG functionality.

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

 Business



```
err = chacha20_prng_ready(prng_val); // Check if PRNG is ready
if ( err )
    return 3i64;
for ( i = 0; i <= 39; ++i )
    prng_entr[i] = rand() * (*n + i + 1);
err = chacha20_prng_add_entropy(prng_entr, 40i64, prng_val); // Add Seed/Entropy to PRNG
if ( err )
    return 4i64;
v3 = rand();
v6 = (((v3 >> 31) >> 24) + v3) - (((v3 >> 31) >> 24) + 1;
Block = malloc(v6);
chacha20_prng_read(Block, 8u, prng_val);
free(Block);
```

Figure 4. Rhysida's use of the "init\_prng" function

After the PRNG is initialized, Rhysida then proceeds to import the embedded RSA key and declares the encryption algorithm it will use for file encryption:

- It will use the *register\_cipher* function to "register" the algorithm (in this case, aes), to its table of usable ciphers.
- It will use the *find\_cipher* function to store the algorithm to be used (still aes), in the variable CIPHER.

Afterward, it will proceed to also register and declare aes for its Cipher Hash Construction (CHC) functionalities.

Based on our analysis, Rhysida's encryption routine follows these steps:

1. After it reads file contents for encryption, it will use the initialized PRNG's function, *chacha20\_prng\_read*, to generate both a key and an IV that are unique for each file.
2. It will use the *ctr\_start* function to initialize the cipher that will be used, which is aes (from the variable CIPHER), in counter or CTR mode.
3. The generated key and IV are then encrypted with the *rsa\_encrypt\_key\_ex* function.



En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

 Business



```
chacha20_prng_read(cipher_iv, 32u, prngs + 17648 * thread_n); // Generate Key using chacha20 PRNG
chacha20_prng_read(cipher_iv, 16u, prngs + 17648 * thread_n); // Generate IV using chacha20 PRNG
v27 = ctr_start(CIPHER, cipher_iv, cipher_key, 32u, 14u, 16, ctr); // Initialize CTR Cipher
if ( v27 )
{
    pthread_mutex_unlock(&MUTEX_PRNG);
}
else
{
    v27 = ctr_setiv(cipher_iv);
    Size_4 = 32;
    ElementSize_4 = 4096;
    v27 = rsa_encrypt_key_ex(
        cipher_key,
        0x20ui64,
        Buffer,
        &ElementSize_4,
        "Rhysida-0.1",
        11,
        prngs + 0x44F0 * thread_n,
        PRNG_IDX,
        HASH_IDX,
        2,
        &key); // Encrypt Generated Key
```

Figure 5. Rhysida's encryption routine




## How can organizations protect themselves from Rhysida and other ransomware families?

Although we are still in the process of fully analyzing Rhysida ransomware and its tools, tactics, and procedures (TTPs), the best practices for defending against ransomware attacks still holds true for Rhysida and other ransomware families.

Here are several recommended measures that organizations implement to safeguard their systems from ransomware attacks:

- Create an inventory of assets and data
- Review event and incident logs
- Manage hardware and software configurations.

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.



- Establish a software whitelist permitting only legitimate applications

- Perform routine vulnerability assessments
- Apply patches or virtual patches for operating systems and applications
- Keep software and applications up to date using their latest versions
- Integrate data protection, backup, and recovery protocols
- Enable multifactor authentication (MFA) mechanisms
- Utilize sandbox analysis to intercept malicious emails
- Regularly educate and evaluate employees' security aptitude
- Deploy security tools (such as XDR) which are capable of detecting abuse of legitimate applications

## Indicators of compromise


### Hashes

The indicators of compromise for this entry can be found [here](#).


## MITRE ATT&CK Matrix


Initial Access	T1566 Phishing	Based on external reports, Rhysida uses phishing lures for initial access.
Execution	T1059.003 Command and Scripting Interpreter: Windows Command Shell	It uses cmd.exe to execute commands for execution.
	T1059.001 Command and Scripting Interpreter: PowerShell	It uses PowerShell to create scheduled task named <i>Rhsd</i> pointing to the ransomware.

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

Trend Micro

Business





Defense Evasion	T1070.004 Indicator Removal: File Deletion	Rhysida Ransomware deletes itself after execution. The scheduled task (Rhsd) created would also be deleted after execution.	
	T1070.001 Indicator Removal: Clear Windows Event Logs	It uses wevtutil.exe to clear Windows event logs.	
Discovery	T1083 File and Directory Discovery	It enumerates and looks for files to encrypt in all local drives.	
	T1082 System Information Discovery	Obtains the following information: <ul style="list-style-type: none"><li>• Number of processors</li><li>• System information</li></ul>	
Impact	T1490 Inhibit System Recovery	It executes uses vssadmin to remove volume shadow copies	
	T1486 Data Encrypted for Impact	It uses a 4096-bit RSA key and Cha-cha20 for file encryption.  It avoids encrypting files with the following strings in their file name: <ul style="list-style-type: none"><li>• .bat</li><li>• .bin</li><li>• .cab</li></ul>	

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.



Business



		<ul style="list-style-type: none"><li>• .diagcab</li></ul>	
		<ul style="list-style-type: none"><li>• .diagcfg</li><li>• .diagpkg</li><li>• .drv</li><li>• .dll</li><li>• .exe</li><li>• .hlp</li><li>• .hta</li><li>• .ico</li><li>• .msi</li><li>• .ocx</li><li>• .ps1</li><li>• .psm1</li><li>• .scr</li><li>• .sys</li><li>• .ini</li><li>• .Thumbs.db</li><li>• .url</li><li>• .iso</li></ul>	
		<p>It avoids encrypting files found in the following folders:</p>	
		<ul style="list-style-type: none"><li>• \$Recycle.Bin</li><li>• Boot</li><li>• Documents and Settings</li><li>• PerfLogs</li><li>• ProgramData</li><li>• Recovery</li><li>• System Volume Information</li><li>• Windows</li></ul>	

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.



Business






		<p>It appends the following extension to the file name of the encrypted files:</p> <p><i>.rhysida</i></p> <p>It encrypts all system drives from A to Z.</p> <p>It drops the following ransom note:</p> <p><i>{Encrypted Directory}\CriticalBreachDetected.pdf</i></p>	
	T1491.001 Defacement: Internal Defacement	It changes the desktop wallpaper after encryption and prevents the user from changing it back by modifying the NoChangingWallpaper registry value.	

## Trend Micro Solutions

Trend solutions such as [Apex One](#), [Deep Security](#), [Cloud One Workload Security](#), [Worry-Free Business Security](#), [Deep Discovery Web Inspector](#), [Titanium Internet Security](#), and [Cloud Edge](#) can help protect against attacks employed by the Rhysida ransomware.

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

 | Business



Trend Micro solutions	Detection Patterns / Policies / Rules
<ul style="list-style-type: none"><li>• Trend Micro Apex One</li><li>• Trend Micro Deep Security</li><li>• Trend Micro Titanium Internet Security</li><li>• Trend Micro Cloud One Workload Security</li><li>• Trend Micro Worry-Free Business Security Services</li></ul>	<ul style="list-style-type: none"><li>• Ransom.Win64.RHYSIDA.SM</li><li>• Ransom.Win64.RHYSIDA.THEBBBC</li><li>• Ransom.Win64.RHYSIDA.THFOHBC</li><li>• Trojan.PS1.SILENTKILL.SMAJC</li><li>• Trojan.PS1.SILENTKILL.A</li></ul>
<ul style="list-style-type: none"><li>• Trend Micro Apex One</li><li>• Trend Micro Deep Security</li><li>• Trend Micro Worry-Free Business Security Services</li><li>• Trend Micro Titanium Internet Security</li></ul>	<ul style="list-style-type: none"><li>• RAN4056T</li><li>• RAN4052T</li></ul>
<ul style="list-style-type: none"><li>• Trend Micro Apex One</li><li>• Trend Micro Deep Discovery Web Inspector</li></ul>	<ul style="list-style-type: none"><li>• DDI Rule ID: 597 - "PsExec tool detected"</li><li>• DDI Rule ID: 1847 - "PsExec tool detected - Class 2"</li><li>• DDI Rule ID: 4524 - "Possible Renamed PSEXEC Service - SMB2 (Request)"</li><li>• DDI Rule ID: 4466 - "PsExec Clones - SMB2 (Request)"</li><li>• DDI Rule ID: 4571 - "Possible Suspicious Named Pipe - SMB2 (REQUEST)"</li> <li>• DDI Rule ID: 4570 - "COBALTSTRIKE - DNS(RESPONSE)"</li><li>• DDI Rule ID: 4152 - "COBALTSTRIKE - HTTP (Response)"</li></ul>

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

<div><div><div><div></div><div>TREND</div><div>Micro</div></div><div>Business</div></div><div><div></div><div></div><div></div></div></div>	
	<ul style="list-style-type: none"><li>• DDI Rule ID: 4153 - "COBALTSTRIKE - HTTP (Request) Variant 2"</li><li>• DDI Rule ID: 2341 - "COBALTSTRIKE - HTTP (Request)"</li><li>• DDI Rule ID: 4390 - "CobaltStrike - HTTPS (Request)"</li><li>• DDI Rule ID: 4870 - "COBEACON DEFAULT NAMED PIPE - SMB2 (Request)"</li><li>• DDI Rule ID: 4861 - "COBEACON - DNS (Response) - Variant 3"</li><li>• DDI Rule ID: 4860 - "COBEACON - DNS (Response) - Variant 2"</li><li>• DDI Rule ID: 4391 - "COBEACON - DNS (Response)"</li></ul>
<ul style="list-style-type: none"><li>• Trend Micro Apex One</li><li>• Trend Micro Deep Security</li><li>• Trend Micro Worry-Free Business Security Services</li><li>• Trend Micro Titanium Internet Security</li><li>• Trend Micro Cloud Edge</li></ul>	<ul style="list-style-type: none"><li>• Troj.Win32.TRX.XXPE50FFF071</li></ul>

Trend Micro XDR uses the following workbench alerts to protect customers from Rhysida-related attacks:

### Cobalt Strike

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

Strike		
COBALT C2 Connection	afd1fa1f-b8fc-4979-8bf7-136db80aa264	
Early Indicator of Attack via Cobalt Strike	0ddda3c1-dd25-4975-a4ab-b1fa9065568d	
Lateral Movement of Cobalt Strike Beacon	5c7cdb1d-c9fb-4b1d-b71f-9a916b10b513	
Possible Cobalt Strike Beacon	45ca58cc-671b-42ab-a388-d972ff571d68	
Possible Cobalt Strike Beacon Active Directory Database Dumping	1f103cab-9517-455d-ad08-70eaa05b8f8d	
Possible Cobalt Strike Connection	85c752b8-93c2-4450-81eb-52ec6161088e	
Possible Cobalt Strike Privilege Escalation Behavior	2c997bac-4fc0-43b4-8279-6f2e7cf723ae	
Possible Fileless Cobalt Strike	cf1051ba-5360-4226-8ffb-955fe849db53	

PsExec

Workbench Alert	ID
Possible Credential Access via PSEXESVC Command Execution	0b870a13-e371-4bad-9221-be7ad98f16d7
Possible Powershell Process Injection via PSEXEC	7fe83eb8-f40f-43be-8edd-f6cbc1399ac0
Possible Remote Ransomware Execution via PsExec	47fbd8f3-9fb5-4595-9582-eb82566ead7a
PSEXEC Execution By Process	e011b6b9-bdef-47b7-b823-c29492cab414
Remote Execution of Windows Command Shell via PsExec	b21f4b3e-c692-4eaf-bee0-ece272b69ed0



En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.



Suspicious Mimikatz Credential Dumping via PsExec

8004d0ac-ea48-40dd-aab1-f96c24906ac1


SILENTKILL



Workbench Alert	ID
Possible Disabling of Antivirus Software	64a633e4-e1e3-443a-8a56-7574c022d23f
Suspicious Deletion of Volume Shadow Copy	5707562c-e4bf-4714-90b8-becd19bce8e5

Rhysida

Workbench Alert	ID
Ransom Note Detection (Real-time Scan)	16423703-6226-4564-91f2-3c03f2409843
Ransomware Behavior Detection	6afc8c15-a075-4412-98c1-bb2b25d6e05e
Ransomware Detection (Real-time Scan)	2c5e7584-b88e-4bed-b80c-dfb7ede8626d
Scheduled Task Creation via Command Line	05989746-dc16-4589-8261-6b604cd2e186
System-Defined Event Logs Clearing via Wevtutil	639bd61d-8aee-4538-bc37-c630dd63d80f

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.

 | Business



within their system:

```
processCmd:"powershell.exe*\\*$\?.ps1" OR (objectFilePath:"?:*\??\psexec.exe" AND processCmd:"*cmd.exe*\\??\???.bat")
```

Tags

[Endpoints](#) | [Ransomware](#) | [Research](#) | [Articles, News, Reports](#)

Authors

Trend Micro Research  
Trend Micro


CONTACT US



SUBSCRIBE

Related Articles

[Understanding the Initial Stages of Web Shell and VPN Threats: An MXDR Analysis](#)

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.






 **TREND** MICRO | Business



See all articles >

Experience our unified platform for free

Claim your 30-day trial



Resources

Support

About Trend

Country Headquarters

Trend Micro - United States (US)

225 East John Carpenter Freeway

Suite 1500

Irving, Texas 75062

En cliquant sur « Accepter tous les cookies », vous acceptez le stockage de cookies sur votre appareil pour améliorer la navigation sur le site, analyser son utilisation et contribuer à nos efforts de marketing.



Business



Select a country / region

United States



[Privacy](#) | [Legal](#) | [Accessibility](#) | [Site map](#)

Copyright ©2024 Trend Micro Incorporated. All rights reserved