

🔍 Filter by title

schtasks-delete

schtasks-end

schtasks-query

schtasks-run

> scwcmd

> secedit

serverceipoptin

servermanagercmd

serverweroptin

Services for Network File System (NFS)

command reference

set environmental variables

setlocal

setx

sfc

shadow

shift

showmount

shutdown

simulate restore

sort

start

subst

sxstrace

sysocmgr

systeminfo

takeown

> tapicfg

taskkill

tasklist

tcmssetup

> telnet

tftp

time

timeout

title

tlntadmn

📄 Download PDF

schtasks delete

Article • 02/03/2023 • 3 contributors •

Applies ✔ Windows Server 2025, ✔ Windows Server 2022, ✔ Windows Server 2019, ✔ Windows Server 2016, ✔ Windows 11, ✔ Windows 10, ✔ Azure Stack HCI, versions 23H2 and 22H2

[Feedback](#)

In this article

- Syntax
- Examples
- Related links

Deletes a scheduled task from the schedule. This command doesn't delete the program that the task runs or interrupt a running program.

Syntax

📄 Copy

```
schtasks /delete /tn {<taskname> | *} [/f] [/s <computer> [/u [<domain>\]<user>
```

Parameters

[Expand table](#)

Parameter	Description
/tn {<taskname> *}	Identifies the task to be deleted. If you use the <code>*</code> , this command deletes all tasks scheduled for the computer, not just the tasks scheduled by the current user.
/f	Suppresses the confirmation message. The task is deleted without warning.
/s <computer>	Specifies the name or IP address of a remote computer (with or without backslashes). The default is the local computer.
/u [<domain>]	Runs this command with the permissions of the specified user account. By default, the command runs with the permissions of the current user of the local computer. The specified user account must be a member of the Administrators group on the remote computer. The <code>/u</code> and <code>/p</code> parameters are valid only when you use <code>/s</code> .
/p <password>	Specifies the password of the user account specified in the <code>/u</code> parameter. If you use the <code>/u</code> parameter without the <code>/p</code> parameter or the password argument, schtasks will prompt you for a password. The <code>/u</code> and <code>/p</code> parameters are valid only when you use <code>/s</code> .
/?	Displays help at the command prompt.

Examples

To delete the *Start Mail* task from the schedule of a remote computer.

📄 Copy

```
schtasks /delete /tn Start Mail /s Svr16
```

This command uses the `/s` parameter to identify the remote computer.

To delete all tasks from the schedule of the local computer, including tasks scheduled by other users.

 Copy

```
schtasks /delete /tn * /f
```


This command uses the `/tn *` parameter to represent all tasks on the computer and the `/f` parameter to suppress the confirmation message.


Related links

- [Command-Line Syntax Key](#)
- [schtasks change command](#)
- [schtasks create command](#)
- [schtasks end command](#)
- [schtasks query command](#)
- [schtasks run command](#)

Feedback

Was this page helpful?

 Yes

 No

 English (United States)  Your Privacy Choices  Theme 

[Manage cookies](#) [Previous Versions](#) [Blog](#) [Contribute](#) [Privacy](#) [Terms of Use](#) [Trademarks](#) [© Microsoft 2024](#)