



Next Article:  
Installing atop  
Tool To Monito... →

# How to kill processes on the Linux Desktop with xkill

Last Updated : 27 Jun, 2022 ✨ 💬 ✎ ⋮

**xkill** is a command-line utility that can kill the undesired windows on the user’s screen. Basically, xkill force the X server to close the connection to the client. This utility kills the programs without providing PID with a command. Now let’s see how to install the xkill on the systems.

## Installation of xkill

The xkill utility comes with the package x11-utils.

Therefore, to use xkill first we need to install the x11-

Shell Scripting   Kali Linux   Ubuntu   Red Hat   CentOS   Docker in Linux   Kubernetes in Linux   Linux interview question   Python   R   Java   C   C++

commands to install x11-utils according to your distribution.

For Debian/Kali Linux/Garuda Linux/Ubuntu:

```
apt-get install x11-utils
```

For Arch Linux:


```
pacman -S xorg-xkill
```

For CentOS:

```
yum install xorg-xkill
```

For Fedora:

```
dnf install xorg-xkill
```



## Using xkill command


For using xkill to kill the open window, just run the xkill command. Then your cursor will turn into an X sign. Then right-click on the windows which you have to kill.



← Ads by Google


Send feedback

Why this ad? ▶




### Get a List of open windows

To get a list of all open windows that can be terminated using xkill command, run the following command:




This command will show the list of all open windows with the hostname.




### Exiting without killing windows

To exit from the xkill command without killing any window, press the ctrl+c key.



### The ordinary way of killing process on Linux

Generally, when we want to kill any process on the Linux system, we use the kill command. To kill a process first we should know the PID of the respective process. Then we provide this PID to the kill command as the argument. We can find the PID of a process using the following command:



```
ps -A | grep -i processName
```

```
nishant@CyberBox:~$ ps -A | grep -i gvim
7507 ?        00:00:00 gvim
nishant@CyberBox:~$
```

To kill the process, pass the PID to the kill command.  
For the above example:

```
kill 7507
```

There is a more simple way than passing the PID of the process to kill command to kill the process. pkill is a command using which we can kill the process using the name of the process. For the above example, we can kill gvim with pkill using the following command:


```
pkill gvim
```

pkill is an awesome command, but it is preferred to use the kill command to know more about the killing process.


### Using xkill without using terminal

It is sounding weird to kill one process, we need to start another process. There is any way we can use xkill command without a terminal? yes, we can use xkill command without using the terminal. To access xkill command without using the terminal, we need to bind xkill command with the keyboard shortcut.


Let’s see how we can add xkill command to the keyboard shortcuts. We are going to see how we can bind keys in Gnome 3 desktop environment. Go to setting -> keyboard shortcut. Then you will see the following window:



Scroll down in the above setting window and right-click on the + button icon. After pressing the plus button, you will be prompted to input the command name and command and key binding on which this




command should be launched. Enter the command name and command and keyboard shortcut which you like.




After entering the details, press add button. Now you can use the xkill command without using the terminal. Just press the shortcut you created.


## Do xkill guarantee that closing its communication will kill/abort anything successfully?

xkill command does not give the guarantee that this command will successfully kill or abort the application. This command is simple, to close the connection of the application with the X server. Applications are indeed to terminate when their connection is closed with the X server, but some applications may continue after closing the connection with the X server.

 Comment

More info 

Advertise with us

Next Article 

Installing atop Tool To Monitor the System Process in Linux

## Similar Reads

### How to kill processes on the Linux Desktop with xkill

xkill is a command-line utility that can kill the undesired windows on the user's screen. Basically, xkill force the X server to close the connection to the...

 4 min read

### Installing atop Tool To Monitor the System Process in Linux

atop is an ASCII full-screen interactive performance monitor which is kind of similar to the top command to view the load over a Linux system. The job of...

 7 min read

### How to Find Hidden Processes in Linux

Hidden or unlisted running processes in Linux can indicate issues like misconfigured applications or potential security threats, including malware or...

🕒 5 min read

### Using htop to Monitor System Processes on Linux

htop a Linux tool that is used in process-managing and terminal-based system monitoring. It allows real-time monitoring of processes and perform...

🕒 5 min read

### How to Uninstall / Reinstall Cudo Miner in Linux

Cudo Miner is a popular cryptocurrency mining software for Linux. However, if you no longer need it or want to switch to another solution, you may need t...

🕒 2 min read

### How to Kill Processes by Given Partial Names in Linux

On a Unix system creates a separate environment for a program when it is executed. Everything the system needs to run the program as if there were n...

🕒 4 min read

### How to Kill a Process in Linux | Kill Command

kill command in Linux (located in /bin/kill), is a built-in command which is used to terminate processes manually. kill command sends a signal to a process...

🕒 6 min read

### How to Kill a Detached screen Session in Linux

The screen session is like virtual windows, And in Linux it works like a multiplexer terminal where we can create more than one window and work ...

🕒 3 min read

### How to Kill a Process Running on Particular Port in Linux?

Have you ever tried to launch a web server, database, or application in Linux, only to be stopped by the frustrating “Address already in use” error?...

🕒 6 min read

### How to List Running Processes in Linux | ps Command

As we all know Linux is a multitasking and multi-user system. So, it allows multiple processes to operate simultaneously without interfering with each...

🕒 9 min read

📍 **Corporate & Communications Address:**  
A-143, 7th Floor, Sovereign Corporate Tower, Sector- 136, Noida, Uttar Pradesh (201305)

📍 **Registered Address:**  
K 061, Tower K, Gulshan Vivante Apartment, Sector 137, Noida, Gautam Buddh Nagar, Uttar Pradesh, 201305



Advertise with us

#### Company

About Us  
Legal  
Privacy Policy  
In Media  
Contact Us  
Advertise with us  
GFG Corporate Solution  
Placement  
Training  
Program  
GeeksforGeeks Community

#### Languages

Python  
Java  
C++  
PHP  
GoLang  
SQL  
R Language  
Android Tutorial  
Tutorials Archive

#### DSA

Data Structures  
Algorithms  
DSA for  
Beginners  
Basic DSA  
Problems  
DSA Roadmap  
Top 100 DSA  
Interview  
Problems  
DSA Roadmap by Sandeep Jain  
All Cheat Sheets

#### Data Science & ML

Data Science  
With Python  
Data Science For  
Beginner  
Machine  
Learning  
ML Maths  
Data  
Visualisation  
Pandas  
NumPy  
NLP  
Deep Learning

#### Web Technologies

HTML  
CSS  
JavaScript  
TypeScript  
ReactJS  
NextJS  
Bootstrap  
Web Design

#### Python Tutorial

Python  
Programming  
Examples  
Python Projects  
Python Tkinter  
Web Scrapping  
OpenCV Tutorial  
Python Interview  
Question  
Django

#### Computer Science

Operating Systems

#### DevOps

Git  
Linux  
AWS  
Docker

#### System Design

High Level  
Design  
Low Level Design

#### Inteview Preparation

Competitive  
Programming

#### School Subjects

Mathematics  
Physics  
Chemistry

#### GeeksforGeeks Videos

DSA  
Python  
Java



Computer	Kubernetes	UML Diagrams	Top DS or Algo	Biology	C++
Network	Azure	Interview Guide	for CP	Social Science	Web
Database	GCP	Design Patterns	Company-Wise	English	Development
Management	DevOps	OOAD	Recruitment	Grammar	Data Science
System	Roadmap	System Design	Process	Commerce	CS Subjects
Software		Bootcamp	Company-Wise	World GK	
Engineering		Interview	Preparation		
Digital Logic		Questions	Aptitude		
Design			Preparation		
Engineering			Puzzles		
Maths					
Software					
Development					
Software Testing					