

Sarwent has received little attention from researchers, but this backdoor malware is still being actively developed, with new commands and a focus on RDP.

functionality such as executing PowerShell commands.

- Updates also show a preference for using RDP
- Sarwent has been seen using the same binary signer as at least one TrickBot operator[1]

Background

Sarwent appears to have been actively used since at least 2018 but not a lot has been publicly reported about it during that time period.

Research Insight

Sarwent functionality has historically revolved around being a loader, as shown by the limited number of original commands:

|download| |update| |vnc|

Some other functionality that has remained consistent is its AV(AntiVirus) checking.

```
dd offset str dwservice exe.Text
dd offset _str_avp_exe.Text
dd offset _str_ekrn_exe.Text
dd offset str nprosec exe.Text
dd offset _str_pavfnsvr_exe.Text
dd offset _str_msmpeng_exe.Text
dd offset _str_ccsvchst_exe.Text
dd offset _str_Outpost_AntiVir.Text
                           ; DATA XREF: sul
                            Xmlschematags
dd offset _str_Avira_AntiVirus.Text
dd offset _str_Avast_Internet_.Text
dd offset _str_AVG_AntiVirus.Text
dd offset _str_Dr_Web_AntiViru.Text
dd offset _str_Kaspersky_Inter.Text
dd offset _str_Eset_Nod32_Anti.Text
dd offset _str_Norman_AntiViru.Text
dd offset _str_Panda_AntiVirus.Text
dd offset _str_Microsoft_Secur.Text
dd offset _str_Norton_Internet.Text
                           · DOTO YRFF · Ti
```

Figure 1: AV checks

Recent updates include a minor change to their C2 URI structure[2].

Figure 2: C2 checking update

Also, there has recently been the addition of a number of commands that would normally be seen in malware that focus more on backdoor or RAT like capabilities.

```
|cmd|
|powershell|
|rdp|
```

focus as can be seen in the recent proliferation of services selling access to systems[3].

The 'cmd' and 'powershell' commands are simply commands to be detonated.




Figure 3: Command line detonations

The results are base64 encoded and sent back to the C2 through the matching URL route.




Figure 4: Base64 encode command results

C2 routes for sending responses:

```
/gate/cmd_exec
/gate/powershell_exec
```

The 'rdp' command is a bit different; the code execution looks like it serves to tell the bot to perform a series of tasks:

- Add a new user
- List groups and users
- Punch hole in local firewall

Figure 5: Add new user




Figure 6: List network groups and users

Figure 7: Allow firewall connections on RDP port

This command, then, is more related to setting up the system for RDP access at a later time.

Mitigation & Recommendations

Endpoint:

CommadLine="cmd /c ping localhost & regsvr32 /s *"

Suricata rules:

alert http \$HOME_NET any → \$EXTERNAL_NET any (msg:"Sarwent CMD response Post"; content:"POSt"; http_method; content:"/gate/cmd_exec"; http_uri; classtype:trojan-activity; sid:9000040; rev:1; metadata:author Jason Reaves;)

alert http \$HOME_NET any → \$EXTERNAL_NET any (msg:"Sarwent Powershell response Post"; content:"POST"; http_method; content:"/gate/powershell_exec"; http_uri; classtype:trojan-activity; sid:9000041; rev:1; metadata:author Jason Reaves;)

alert http \$HOME_NET any → \$EXTERNAL_NET any (msg:"Sarwent RDP exec response"; content:"GET"; http_method; content:"/gate/rdp_exec?command="; http_uri; content:"&status="; http_uri; classtype:trojan-activity; sid:9000042; rev:1; metadata:author Jason Reaves;)

alert http \$HOME_NET any → \$EXTERNAL_NET any (msg:"Sarwent update exe response"; content:"GET"; http_method; content:"/gate/update_exec?command="; http_uri; content:"&status="; http_uri; classtype:trojan-activity; sid:9000043; rev:1; metadata:author Jason Reaves;)

alert http \$EXTERNAL_NET any → \$HOME_NET any (msg:"Sarwent update command"; content:"200"; http_stat_code; content:"fHVwZGF0ZX"; startswith; http_server_body; flow:to_client, established; classtype:trojan-activity; sid:9000044; rev:1; metadata:author Jason Reaves;)

http_server_body; flow:to_client, established; classtype:trojan-activity; sid:9000045; rev:1; metadata:author Jason Reaves;)

alert http \$EXTERNAL_NET any → \$HOME_NET any (msg:"Sarwent powershell command"; content:"200"; http_stat_code; content:"fHBvd2Vyc2hlbGx8"; startswith; http_server_body; flow:to_client, established; classtype:trojan-activity; sid:9000046; rev:1; metadata:author Jason Reaves;)

alert http \$EXTERNAL_NET any → \$HOME_NET any (msg:"Sarwent rdp command"; content:"200"; http_stat_code; content:"fHJkcH"; startswith; http_server_body; flow:to_client, established; classtype:trojan-activity; sid:9000047; rev:1; metadata:author Jason Reaves;)

Indicators of Compromise

Download Location:

whatsmyhomeworthlondonontario[.]ca/wp-admin/version.exe beurbn[.]com/install.exe

V2 samples

Hash:

3f7fb64ec24a5e9a8cfb6160fad37d33fed6547c

Domains

seoanalyticsproj.xyz

seoanalyticsproewj.xyz

seoanalyticsprojrts.xyz seoanalyticspro32frghyj.xyz Hash: ab57769dd4e4d4720eedaca31198fd7a68b7ff80 **Domains** vertuozoff.xyz vertuozoff.club vertuozofff.xyz vertuozofff.com vertuozofff.club vertuozoffff.club Hash: d297761f97b2ead98a96b374d5d9dac504a9a134 **Domains** rabbot.xyz terobolt.xyz tebbolt.xyz rubbolt.xyz rubbot.xyz treawot.xyz Hash:

3eeddeadcc34b89fbdd77384b2b97daff4ccf8cc

terobolt.xyz

tebbolt.xyz

rubbolt.xyz

rubbot.xyz

treawot.xyz

Hash:

106f8c7ddbf265fc108a7501b6af292000dd5219

Domains

blognews-journal.com

startprojekt.pw

blognews-joural.com

blognews-joural.best

blognews-joural.info

startprojekt.pro

V1 Samples

Hash:

83b33392e045425e9330a7f009801b53e3ab472a

Domains

212.73.150.246

softfaremiks.icu

Hash:

2979160112ea2de4f4e1b9224085efbbedafb593

Domains

shopstoregame.icu

softfaremiks.icu

shopstoregamese.icu shopstoregamese.com shopstoregames.icu

References

1: https://twitter.com/VK_Intel/status/1228833249536987138

2: https://twitter.com/James_inthe_box/status/1228788661006659584

3: https://twitter.com/VK_Intel/status/1242587625409609731

4: https://github.com/silence-is-best/c2db

MALWARE SARWENT TRICKBOT

SHARE











PDF



in malware reverse-engineering. He has spent the majority of his career tracking threats in the Crimeware domain, including reverse-engineering data structures and algorithms found in malware in order to create automated frameworks for harvesting configuration and botnet data. Previously, he worked as a software developer and unix administrator in the financial industry and also spent six years in the U.S. Army. Jason holds multiple certifications related to reverse-engineering and application exploitation and has published numerous papers on topics such as writing malware scripts pretending to be a bot, unpackers, configuration data harvesters and covert channel utilities. He enjoys long walks in IDA and staring at RFCs for hours.

PREV

Deep Dive Into TrickBot
Executor Module
"mexec": Reversing the
Dropper Variant

NetWalker Ransomware: No Respite, No English Required

RELATED POSTS

By clicking Subscribe, I agree to the use of my personal data in accordance with SentinelOne <u>Privacy Notice</u>. SentinelOne will not sell, trade, lease, or rent your personal data to third parties. This site is protected by reCAPTCHA and the <u>Google Privacy Policy</u> and <u>Terms of Service</u> apply.

RECENT POSTS



Cloud Malware | A Threat Hunter's Guide to Analysis, Techniques and Delivery



China's Influence Ops | Twisting Tales of Volt Typhoon at Home and Abroad

Kryptina RaaS | From Unsellable Cast-Off to Enterprise Ransomware

LABS CATEGORIES

Crimeware

Security Research

Advanced Persistent Threat

Adversary

Sarwent Malware Continues to Evolve With https://www.sentinelone.com/labs/sarwent-mal	n Updated Com lware-continues-	mand Functions - SentineII to-evolve-with-updated-comr	Labs - 31/10/2024 18:2 mand-functions/	27
				=
SIGN UP				
Get notified when we post new content.				
	У Twitter	in LinkedIn		
	- Twitter	Linkedin		
©2024 SentinelOne, All Rights Reserved.				