


[Home](#) [About](#)



[Windows OS Hub](#) / [Windows 10](#) / How to View and Clear RDP Connections History in Windows

March 11, 2024



[Windows 10](#)

[Windows 11](#)

[Windows Server 2019](#)

# How to View and Clear RDP Connections History in Windows

The built-in Windows Remote Desktop Connection client ( `mstsc.exe` ) saves the remote computer name (or IP address) and the username that is used to log in after each successful connection to the remote RDP host. The next time the RDP client starts, the user can select one of the saved connections, and the previous username is automatically inserted. If you are using a public computer or a computer you don't trust, you may want to clear your RDP connection history for security reasons.

## Contents:

- [Delete the History of Remote Desktop Connections on Windows](#)
- [Script to Clear RDP Connection History](#)
- [How to Clear Remote Desktop Bitmap Cache?](#)
- [How to Prevent Windows from Saving RDP Connection History](#)
- [Remove Saved RDP Credentials on Windows](#)



This article describes where Windows stores Remote Desktop connection history and credentials, and how to clear RDP history and logs.

## Delete the History of Remote Desktop Connections on Windows

Windows stores the history of Remote Desktop client connections in several different places, and to completely clear the RDP history you will need to delete the data from all of these places.

### How to Delete RDP Connection History from Registry

1. Open the Registry Editor ( `regedit.exe` ) and go to the reg key  
**HKEY\_CURRENT\_USER\Software\Microsoft\Terminal Server Client;**
2. The **Default** subkey contains history entries for the last *10* RDP connections. The names of the parameters are **MRU0-MRU9** (MRU – Most Recently Used). Their values contain IP addresses/RDP host names. Select all the registry parameters in the key and delete them;

3. Then expand the **Servers** subkey. A list of all previously used RDP hosts and user accounts is stored here. The username is contained in the **UsernameHint** parameter. This username is automatically inserted into the mstsc.exe client window when you connect to this RDP host. The **CertHash** parameter contains the thumbprint of the server's RDP certificate (see: "[Configuring trusted TLS/SSL certificates for RDP](#)");

4. Clear all entries in the Servers registry key. The easiest way to do this is to simply delete the entire Servers reg key, and then re-create it manually.

## Delete the Default.RDP File

Then delete the hidden **Default.rdp** file from the `%userprofile%\Documents` folder in the user profile. This file stores information about the last RDP connection.

## How to View and Clear RDP Event Viewer Logs in Windows

The RDP client also logs each outbound connection to the Event Viewer log (Applications and Services Logs -> Microsoft -> Windows -> TerminalServices-ClientActiveXCore -> **Microsoft-Windows-TerminalServices-**

## RDPClient/Operational).



To list the log for outbound RDP client connections, use the [Get-WinEvent](#) cmdlet to select and filter the events in the Event Viewer:

```
$properties = @(
@{n='TimeStamp';e={$_.TimeCreated}}
@{n='LocalUser';e={$_.UserID}}
@{n='Target RDP host';e={$_.Properties[1].Value}}
)
Get-WinEvent -FilterHashTable @{LogName='Microsoft-Windows-TerminalServices-
RDPClient/Operational';ID='1102'} | Select-Object $properties
```

Learn more about [how to view and analyze RDP connection logs](#).

You can [clear this event log](#) from the Event Viewer console or by using the command:

```
WevtUtil cl Microsoft-Windows-TerminalServices-RDPCClient/Operational
```

## Delete Recent RDP History Entries from the Start Menu and Taskbar

Windows also stores recent remote desktop connections in Jump Lists. If you type `mstsc` in the [Windows search box](#) or right-click on the client in the taskbar, you will see the history of previous RDP connections in the Recent list.

To clear the RDP history in the Start Menu and Jump Lists, clear the Recent Items list by deleting the files in the `%AppData%\Microsoft\Windows\Recent\AutomaticDestinations` directory.

## Script to Clear RDP Connection History

To quickly clear the history of RDP connections in Windows, you can use a batch script. This script will automatically perform the manual actions described above to clear the connection history and the RDP logs.

```
@echo off
reg delete "HKEY_CURRENT_USER\Software\Microsoft\Terminal Server Client\Default" /va /f
reg delete "HKEY_CURRENT_USER\Software\Microsoft\Terminal Server Client\Servers" /f
reg add "HKEY_CURRENT_USER\Software\Microsoft\Terminal Server Client\Servers"
attrib -s -h %userprofile%\documents\Default.rdp
del %userprofile%\documents\Default.rdp
del /f /s /q /a %AppData%\Microsoft\Windows\Recent\AutomaticDestinations
```

A similar PowerShell script to clear all entries in the RDP connection history:

```
Get-ChildItem "HKCU:\Software\Microsoft\Terminal Server Client" -Recurse | Remove-ItemProperty -Name  
UsernameHint -Ea 0  
Remove-Item -Path 'HKCU:\Software\Microsoft\Terminal Server Client\servers' -Recurse 2>&1 | Out-Null  
Remove-ItemProperty -Path 'HKCU:\Software\Microsoft\Terminal Server Client\Default' 'MR*' 2>&1 | Out-  
Null  
$docs = [environment]::getfolderpath("mydocuments") + '\Default.rdp'  
remove-item $docs -Force 2>&1 | Out-Null
```

If you want to automatically clear the RDP history when the user logs off, you can run this code as a [logoff GPO script](#).

## How to Clear Remote Desktop Bitmap Cache?

By default, the mstsc.exe client caches rarely modified areas of the remote desktop as bitmaps (persistent bitmap caching). The RDP client cache can significantly reduce network traffic.

The RDP client cache is stored in **\*.bmc** and **\*.bin** files in the `%LOCALAPPDATA%\Microsoft\Terminal Server Client\Cache` folder.

The RDP cache contains raw bitmaps of the RDP screen in the form of 64×64 pixel tiles. Attackers can use simple PowerShell or Python scripts (easily searched using the *RDP Cached Bitmap Extractor* query) to capture large areas of the remote desktop from cached PNGs.



For security reasons, it is recommended that you clear the RDP cache folder and prevent the RDP client from saving the screen image to the cache. Disable the **Persistent bitmap caching** option on the **Advanced** tab of the Remote Desktop Connection client.

## How to Prevent Windows from Saving RDP Connection History



If you do not want Windows to store the history of RDP connections, you must deny writing to the `HKCU\Software\Microsoft\Terminal Server Client` registry key. The first step is to disable the inheritance of permissions on the specified reg key (Permissions -> Advanced -> Disable inheritance). Then change the ACL of the registry key by selecting the **Deny** for users (but you should be aware that this is an unsupported configuration).

As a result, mstsc.exe is simply not able to write any RDP connection information to the registry.

## Remove Saved RDP Credentials on Windows

The RDP client allows you to store the user's password in the built-in [Windows Credential Manager](#) and automatically connect to a remote host without entering a password.





Learn more about using [saved RDP passwords in Windows](#).

You can delete saved RDP passwords from the Credential Manager window (run the command `rundll32.exe keymgr.dll, KRShowKeyMgr` ). Remove all entries prefixed `TERMSRV\` .

Or you can clear the stored credentials for RDP with the command:

```
For /F "tokens=1,2 delims= " %G in ('cmdkey /list ^| findstr "target=TERMSRV"') do cmdkey /delete %H
```

You can prevent users from saving RDP passwords by enabling the Group Policy option **Network access: Do not allow storage of passwords and credentials for network authentication (under Computer Configuration -> Administrative Templates -> Windows Components -> Desktop Services -> Remote Desktop Connection Client)**.

10 comments | 7

previous post

[MBR2GPT: Converting MBR to GPT Disk in Windows 10](#)

next post

[Keepalived: Configuring High Availability with IP Failover on CentOS/RHEL](#)

## RELATED READING

## 10 COMMENTS

GRAY FOX

Reply

March 17, 2017 - 2:13 pm

Thanks for your post. I was looking to clear the last connection, and deleting the default.rdp file helped in that regard. Thanks again!

ROBERTSON THOMAS

Reply

October 18, 2018 - 12:04 pm

I am still getting the username once I login to the RDP

VAHID

Reply

March 27, 2019 - 2:53 pm

go to "Documents" folder and delete "Default.rdp"



---

TELBUS

Reply

□ April 24, 2019 - 7:06 am

In windows 10 there is still a recent connection list when you search RDP in bottom search bar and it brings the RDP client app in the result. How to clear that too?

---

PIRULO

Reply

□ November 1, 2019 - 1:44 pm

Thanks, it worked.

---

ADM

Reply

□ January 1, 2020 - 9:54 pm

still leaves sum info on the resents on windows 10

---

MAHAIR

Reply

□ June 3, 2020 - 1:18 pm

Is there a way to prevent RDP from caching remote computer name  
I do not want RDP to cache remote computer name at all

---

DNT

Reply

□ February 23, 2021 - 3:50 am

Thanks for publishing this forum. It was very helpful to me.

---

VENKATARANGAN

Reply



📅 July 13, 2021 - 9:54 am

Thanks, the script worked and saved a lot of time

---

PIYUSH

Reply

📅 September 5, 2022 - 8:36 am

Hello,

This batch file does not work on Windows 11. Is there a way to make it work on Windows 11? Please help me out. Please

---

## LEAVE A COMMENT

Your Comment

Name\*

Email\*

Website

☐ NOTIFY ME OF FOLLOWUP COMMENTS VIA E-MAIL. YOU CAN ALSO [SUBSCRIBE](#) WITHOUT COMMENTING.

POST COMMENT

CURRENT YE@R \*

4.4



<https://t.me/woshub>

Join WindowsHub Telegram channel to get the latest updates!

CATEGORIES

☐ [Active Directory](#)

☐ [Group Policies](#)

☐ [Exchange Server](#)

☐ [Microsoft 365](#)

☐ [Azure](#)

☐ [Windows 11](#)

☐ [Windows 10](#)

☐ [Windows Server 2022](#)

☐ [Windows Server 2019](#)

☐ [Windows Server 2016](#)

☐ [PowerShell](#)

☐ [VMWare](#)


☐ [Hyper-V](#)

☐ [Linux](#)

☐ [MS Office](#)

RECENT POSTS

[Remove a Specific Device from the Safely Remove Hardware List on Windows](#)




October 16, 2024




[Disable BitLocker Automatic Drive Encryption in Windows 11](#)

October 16, 2024




[Check the Software Installation/Removal History in Windows](#)

October 8, 2024




[Run PowerShell Scripts on a Schedule with Task Scheduler](#)

October 3, 2024




[Graylog: Centralized Log Collection and Analysis](#)

October 1, 2024




[Disable and Completely Remove Widgets from Taskbar in Windows 11](#)

September 26, 2024




[Configure Kiosk Mode on Windows 11 \(Single or Multi-App\)](#)

September 24, 2024




[How to Cast/Mirror Android Screen to Windows PC](#)

September 11, 2024




[Get Started with Docker on Windows \(WSL2\) without Docker Desktop](#)

September 4, 2024



[Adding Multiple Alternate DNS Names for a Windows Computer](#)

September 3, 2024



FOLLOW US

Your email address:

SUBSCRIBE





---

#### Popular Posts

[How to Download Offline Installer \(APPX/MSIX\) for Microsoft Store App](#)

[Fix: Windows Cannot Connect to a Shared Printer](#)

[How to Disable UAC Prompt for Specific Applications in Windows](#)

[Fix: The Computer Restarted Unexpectedly or Encountered an Unexpected Error on Windows](#)

[How to Clean Up System Volume Information Folder on Windows](#)

@2014 - 2024 - Windows OS  
Hub. All about operating  
systems for sysadmins

[Fixing “Winload.efi is Missing or Contains Errors” in Windows 10](#)  
[Windows Doesn't Automatically Assign Drive Letters](#)



□  
BACK TO TOP