

Product

Solutions

Resources

Open Source


Enterprise

Pricing

Search

Sign in

Sign up

 audibleblink / xordump


Public


Notifications


Fork 2


Star 18

<> Code


 Pull requests


 Actions

 Security

 Insights


main





Go to file








<> Code

 audibleblink

adds pid flag

8857597 · 3 years ago

6 Commits

	.github/workflows	initial commit	3 years ago
	.gitignore	initial commit	3 years ago
	Makefile	initial commit	3 years ago
	go.mod	initial commit	3 years ago
	go.sum	initial commit	3 years ago
	main.go	adds cmdline flag for pid	3 years ago
	readme.md	adds pid flag	3 years ago

README

xordump

Made for use with Atomic Red Team.

Usage of xordump.exe:

```
-in string
    Input file to Xor
-m string
    [ dbghelp | dbgcore | comsvcs ] (default "dbghelp")
-out string
    minidump outfile (default "minidump.dmp")
-process string
    Process to dump (default "lsass.exe")
-pid int
    PID of process. Takes precedence over --process
-x int
    Single Byte Xor Key
```

In some cases, lsass.exe minidump files are signatured by AV and deleted. It's not unusual for the binary that initiated the lsass dump to be left on disk and not treated as malicious.

The dll loaded into this bin for minidumping (dgbhelp) *ALWAYS* writes the minidump to disk, but before this binary closes the file handle, it re-reads the contents into memory, closes the handle and immediately deletes the file.

There may exist a race between Go deleting the minidump file after a `close(handle)` and with AV detecting and deleting the file. In either case, the output is safe in memory and passed to a Xor function which then re-writes the xor'd data to disk, where it can be safely exfilled.

OPSEC consideration If you lose the race, AV may see the dumpfile and say something.

Part of the miniDump and seDebug code written by @C-Sto

About

No description, website, or topics provided.

Readme

Activity

18 stars

5 watching

2 forks

Report repository

Releases 2

Release v0.0.2

Latest

on May 25, 2021

+ 1 release

Packages

No packages published

Languages

Go 92.3%

Makefile 7.7%

Building / Usage

Running `make` should build the windows exe and the shellcode that can be injected. Go 1.16+ is required because of the additional PIE (position independence) flag introduced in 1.15 and `ioutil` deprecation in 1.16.