

We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. Privacy Statement Third-Party Cookies

Accept

Reject

Manage cookies

Microsoft Ignite

Nov 19-22, 2024

Register now >





Learn

Discover V Product documentation V Development languages V

Sign in

Feedback

PowerShell

PowerShell 5.1

Learn / PowerShell / Microsoft.PowerShell.Management /

Overview DSC PowerShellGet Utility modules Module Browser API Browser Resources V

Download PowerShell

Version



Set-ItemProperty

Set-Location

Set-Service Set-TimeZone

Set-Wmilnstance

Show-ControlPanelItem

Show-EventLog

Split-Path

Start-Process

Start-Service

Start-Transaction

Stop-Computer

Stop-Process

Stop-Service

Suspend-Service

Test-ComputerSecureChannel

Test-Connection

Test-Path

Undo-Transaction

Use-Transaction

Wait-Process

Write-EventLog

- > Microsoft.PowerShell.ODataUtils
- > Microsoft.PowerShell.Operation.Validation
- > Microsoft.PowerShell.Security
- > Microsoft.PowerShell.Utility
- > Microsoft.WSMan.Management
- > PSDiagnostics
- > PSReadLine
- > PSScheduledJob
- > PSWorkflow
- > PSWorkflowUtility

Start-Process

Module: Microsoft.PowerShell.Management

In this article

Syntax

Reference

Description

Examples

Parameters

Show 4 more

Starts one or more processes on the local computer.

Syntax

PowerShell Copy Start-Process [-FilePath] <string> [[-ArgumentList] <string[]>] [-Credential <pscredential>] [-WorkingDirectory <string>] [-LoadUserProfile] [-NoNewWindow] [-PassThru] [-RedirectStandardError <string>] [-RedirectStandardInput <string>] [-RedirectStandardOutput <string>] [-WindowStyle <ProcessWindowStyle>] [-Wait] [-UseNewEnvironment] [<CommonParameters>]

```
PowerShell
                                                                          Copy
Start-Process
     [-FilePath] <string>
     [[-ArgumentList] <string[]>]
     [-WorkingDirectory <string>]
     [-PassThru]
     [-Verb <string>]
     [-WindowStyle <ProcessWindowStyle>]
```

Download PDF

```
[-Wait]
[<CommonParameters>]
```

Description

The Start-Process cmdlet starts one or more processes on the local computer. By default, Start-Process creates a new process that inherits all the environment variables that are defined in the current process.

To specify the program that runs in the process, enter an executable file or script file, or a file that can be opened using a program on the computer. If you specify a non-executable file,

Start-Process starts the program that's associated with the file, similar to the Invoke-Item cmdlet.

You can use the parameters of Start-Process to specify options, such as loading a user profile, starting the process in a new window, or using alternate credentials.

Examples

Example 1: Start a process that uses default values

This example starts a process that uses the <code>Sort.exe</code> file in the current folder. The command uses all the default values, including the default window style, working folder, and credentials.

```
PowerShell

Start-Process -FilePath "sort.exe"
```

Example 2: Print a text file

This example starts a process that prints the C:\PS-Test\MyFile.txt file.

```
PowerShell

Start-Process -FilePath "myfile.txt" -WorkingDirectory "C:\PS-Test" -Verb Print
```

Example 3: Start a process to sort items to a new file

This example starts a process that sorts items in the TestSort.txt file and returns the sorted items in the Sorted.txt files. Any errors are written to the SortError.txt file. The UseNewEnvironment parameter specifies that the process runs with its own environment variables.

```
PowerShell

$processOptions = @{
    FilePath = "sort.exe"
    RedirectStandardInput = "TestSort.txt"
    RedirectStandardOutput = "Sorted.txt"
    RedirectStandardError = "SortError.txt"
    UseNewEnvironment = $true
}
Start-Process @processOptions
```

This example uses splatting to pass parameters to the cmdlet. For more information, see about_Splatting.

Example 4: Start a process in a maximized window

This example starts the Notepad.exe process. It maximizes the window and retains the window until the process completes.

```
PowerShell

Start-Process -FilePath "notepad" -Wait -WindowStyle Maximized
```

Example 5: Start PowerShell as an administrator

This example starts PowerShell using the Run as administrator option.

```
PowerShell

Start-Process -FilePath "powershell" -Verb RunAs
```

Example 6: Using different verbs to start a process

This example shows how to find the verbs that can be used when starting a process. The available verbs are determined by the filename extension of the file that runs in the process.

```
PowerShell

$startExe = New-Object System.Diagnostics.ProcessStartInfo -Args powershell.exe
$startExe.verbs

open
runas
runas
runasuser
```

The example uses New-Object to create a **System.Diagnostics.ProcessStartInfo** object for powershell.exe, the file that runs in the PowerShell process. The **Verbs** property of the **ProcessStartInfo** object shows that you can use the **Open** and **RunAs** verbs with powershell.exe, or with any process that runs a .exe file.

Example 7: Specifying arguments to the process

Both commands start the Windows command interpreter, issuing a dir command on the Program Files folder. Because this foldername contains a space, the value needs surrounded with escaped quotes. Note that the first command specifies a string as **ArgumentList**. The second command is a string array.

```
PowerShell

Start-Process -FilePath "$env:comspec" -ArgumentList "/c dir `"%SystemDrive%\Process -FilePath "$env:comspec" -ArgumentList "/c", "dir", "`"%SystemDrive%
```

Parameters

-ArgumentList

Specifies parameters or parameter values to use when this cmdlet starts the process. Arguments can be accepted as a single string with the arguments separated by spaces, or as an array of strings separated by commas. The cmdlet joins the array into a single string with each element of the array separated by a single space.

The outer quotes of the PowerShell strings aren't included when the **ArgumentList** values are passed to the new process. If parameters or parameter values contain a space or quotes, they need to be surrounded with escaped double quotes. For more information, see about_Quoting_Rules.

For the best results, use a single **ArgumentList** value containing all the arguments and any needed quote characters.

Expand table

Type:	String[]
Aliases:	Args
Position:	1
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-Credential

Specifies a user account that has permission to perform this action. By default, the cmdlet uses the credentials of the current user.

Type a user name, such as **User01** or **Domain01\User01**, or enter a **PSCredential** object generated by the **Get-Credential** cmdlet. If you type a user name, you're prompted to enter the password.

Credentials are stored in a PSCredential object and the password is stored as a SecureString.

① Note

For more information about **SecureString** data protection, see <u>How secure is SecureString?</u>.

Expand table

Туре:	PSCredential
Aliases:	RunAs
Position:	Named
Default value:	Current user
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-FilePath

Specifies the optional path and filename of the program that runs in the process. Enter the name of an executable file or of a document, such as a .txt or .doc file, that's associated with a program on the computer. This parameter is required.

If you specify only a filename, use the WorkingDirectory parameter to specify the path.

Expand table

Type:	String
Aliases:	PSPath
Position:	0
Default value:	None
Required:	True
Accept pipeline input:	False
Accept wildcard characters:	False

-LoadUserProfile

Indicates that this cmdlet loads the Windows user profile stored in the HKEY_USERS registry key for the current user.

This parameter doesn't affect the PowerShell profiles. For more information, see about_Profiles.

Expand table

Type:	SwitchParameter
Aliases:	Lup
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-NoNewWindow

Start the new process in the current console window. By default on Windows, PowerShell opens a new window.

You can't use the **NoNewWindow** and **WindowStyle** parameters in the same command.

Expand table

Туре:	SwitchParameter
Aliases:	nnw
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-PassThru

Returns a process object for each process that the cmdlet started. By default, this cmdlet doesn't generate any output.

Expand table	e
--------------	---

Type:	SwitchParameter
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-RedirectStandardError

Specifies a file. This cmdlet sends any errors generated by the process to a file that you specify. Enter the path and filename. By default, the errors are displayed in the console.

Expand table

Туре:	String
Aliases:	RSE
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

$\hbox{-RedirectStandardInput}$

Specifies a file. This cmdlet reads input from the specified file. Enter the path and filename of the input file. By default, the process gets its input from the keyboard.

Expand table

Туре:	String
Aliases:	RSI
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-RedirectStandardOutput

Specifies a file. This cmdlet sends the output generated by the process to a file that you specify. Enter the path and filename. By default, the output is displayed in the console.

Expand table

Туре:	String
Aliases:	RSO
Position:	Named

Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-UseNewEnvironment

Indicates that this cmdlet uses new environment variables specified for the process. By default, the started process runs with the environment variables inherited from the parent process.

Expand table

Type:	SwitchParameter
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-Verb

Specifies a verb to use when this cmdlet starts the process. The verbs that are available are determined by the filename extension of the file that runs in the process.

The following table shows the verbs for some common process file types.

Expand table

File type	Verbs
.cmd	Edit, Open, Print, RunAs, RunAsUser
.exe	Open, RunAs, RunAsUser
.txt	Open, Print, PrintTo
.wav	Open, Play

To find the verbs that can be used with the file that runs in a process, use the New-Object cmdlet to create a **System.Diagnostics.ProcessStartInfo** object for the file. The available verbs are in the **Verbs** property of the **ProcessStartInfo** object. For details, see the examples.

Expand table

Type:	String
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

Indicates that this cmdlet waits for the specified process and its descendants to complete before accepting more input. This parameter suppresses the command prompt or retains the window until the processes finish.

Expand table

Туре:	SwitchParameter
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-WindowStyle

Specifies the state of the window that's used for the new process. The default value is Normal. The acceptable values for this parameter are:

- Normal
- Hidden
- Minimized
- Maximized

You can't use the WindowStyle and NoNewWindow parameters in the same command.

Expand table

Туре:	ProcessWindowStyle
Accepted values:	Normal, Hidden, Minimized, Maximized
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-WorkingDirectory

Specifies the location that the new process should start in. The default is the location of the executable file or document being started. Wildcards aren't supported. The path must not contain characters that would be interpreted as wildcards.

Expand table

Туре:	String
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

Inputs

None

You can't pipe objects to this cmdlet.

Outputs

None

By default, this cmdlet returns no output.

Process

When you use the PassThru parameter, this cmdlet returns a Process object.

Notes

Windows PowerShell includes the following aliases for Start-Process:

- saps
- start

Native commands are executable files installed in the operating system. These executables can be run from any command-line shell, like PowerShell. Usually you run the command exactly as you would in bash or cmd.exe. The Start-Process cmdlet can be used to run any native commands, but should only be used when you need to control how the command is executed.

By default, Start-Process launches a process asynchronously. Control is instantly returned to PowerShell even if the new process is still running.

- On the local system, the launched process lives on independent from the calling process.
- On a remote system, the new process is terminated when the remote session ends, immediately following the Start-Process command. Therefore, you can't use Start-Process in a remote session expecting the launched process to outlive the session.

If you do need to use Start-Process in a remote session, invoke it with the **Wait** parameter. Or you could use other methods to create a new process on the remote system.

When using the **Wait** parameter, Start-Process waits for the process tree (the process and all its descendants) to exit before returning control. This is different than the behavior of the wait-Process cmdlet, which only waits for the specified processes to exit.

On Windows, the most common use case for <code>Start-Process</code> is to use the **Wait** parameter to block progress until the new process exits. On non-Windows system, this is rarely needed since the default behavior for command-line applications is equivalent to <code>Start-Process -Wait</code>.

This cmdlet is implemented using the **Start** method of the **System.Diagnostics.Process** class. For more information about this method, see **Process.Start Method**.

Related Links

- about_Quoting_Rules
- Debug-Process
- Get-Process
- Start-Service
- Stop-Process
- Wait-Process

Collaborate with us on GitHub

The source for this content can be found on GitHub, where you can also create and review issues and pull requests. For more information, see our contributor quide.



PowerShell feedback

PowerShell is an open source project. Select a link to provide feedback:

🖔 Open a documentation issue

Provide product feedback

⑤ English (United States)
✓ Your Privacy Choices
※ Theme ∨