

Version

PowerShell 7.4 (LTS) ▾

🔍 Search

Get-Location

**Get-Process**

Get-PSDrive

Get-PSProvider

Get-Service

Get-TimeZone

Invoke-Item

Join-Path

Move-Item

Move-ItemProperty

New-Item

New-ItemProperty

New-PSDrive

New-Service

Pop-Location

Push-Location

Remove-Item

Remove-ItemProperty

Remove-PSDrive

Remove-Service

Rename-Computer

Rename-Item

Rename-ItemProperty

Resolve-Path

Restart-Computer

Restart-Service

Resume-Service

Set-Clipboard

Set-Content

Set-Item

Set-ItemProperty

Set-Location

Set-Service

📄 Download PDF

# Get-Process

Reference

[Feedback](#)

Module: [Microsoft.PowerShell.Management](#)

## In this article

- [Syntax](#)
- [Description](#)
- [Examples](#)
- [Parameters](#)
- [Show 4 more](#)

Gets the processes that are running on the local computer.

## Syntax

PowerShell 📄 Copy

**Get-Process**  
[[ -Name] <String[]>  
[ -Module]  
[ -FileVersionInfo]  
[<CommonParameters>]

PowerShell 📄 Copy

**Get-Process**  
[[ -Name] <String[]>  
**-IncludeUserName**  
[<CommonParameters>]

PowerShell 📄 Copy

**Get-Process**  
**-Id** <Int32[]>  
[ -Module]  
[ -FileVersionInfo]  
[<CommonParameters>]

PowerShell 📄 Copy

**Get-Process**  
**-Id** <Int32[]>  
**-IncludeUserName**  
[<CommonParameters>]

PowerShell 📄 Copy

**Get-Process**  
**-InputObject** <Process[]>  
[ -Module]  
[ -FileVersionInfo]  
[<CommonParameters>]

PowerShellCopy

```
Get-Process
-InputObject <Process[]>
-IncludeUserName
[<CommonParameters>]
```

## Description

The `Get-Process` cmdlet gets the processes on a local computer.

Without parameters, this cmdlet gets all of the processes on the local computer. You can also specify a particular process by process name or process ID (PID) or pass a process object through the pipeline to this cmdlet.

By default, this cmdlet returns a process object that has detailed information about the process and supports methods that let you start and stop the process. You can also use the parameters of the `Get-Process` cmdlet to get file version information for the program that runs in the process and to get the modules that the process loaded.

## Examples

### Example 1: Get a list of all active processes on the local computer

PowerShellCopy

```
Get-Process
```

This command gets a list of all active processes running on the local computer. For a definition of each column, see the [Notes](#) section.

### Example 2: Get all available data about one or more processes

PowerShellCopy

```
Get-Process winword, explorer | Format-List *
```

This command gets all available data about the Winword and Explorer processes on the computer. It uses the **Name** parameter to specify the processes, but it omits the optional parameter name. The pipeline operator (`|`) passes the data to the `Format-List` cmdlet, which displays all available properties (`*`) of the Winword and Explorer process objects.

You can also identify the processes by their process IDs. For instance, `Get-Process -Id 664, 2060`.

### Example 3: Get all processes with a working set greater than a specified size

PowerShellCopy

```
Get-Process | Where-Object {$_.WorkingSet -gt 20000000}
```

This command gets all processes that have a working set greater than 20 MB. It uses the `Get-Process` cmdlet to get all running processes. The pipeline operator (`|`) passes the process objects to the `Where-Object` cmdlet, which selects only the object with a value greater than 20,000,000 bytes for the **WorkingSet** property.

**WorkingSet** is one of many properties of process objects. To see all of the properties, type `Get-Process | Get-Member`. By default, the values of all amount properties are in bytes, even though the default display lists them in kilobytes and megabytes.

## Example 4: List processes on the computer in groups based on priority

PowerShell

Copy

```
$A = Get-Process
$A | Get-Process | Format-Table -View priority
```

These commands list the processes on the computer in groups based on their priority class. The first command gets all the processes on the computer and then stores them in the `$A` variable.

The second command pipes the **Process** object stored in the `$A` variable to the `Get-Process` cmdlet, then to the `Format-Table` cmdlet, which formats the processes by using the **Priority** view.

The **Priority** view, and other views, are defined in the PS1XML format files in the PowerShell home directory (`$pshome`).

## Example 5: Add a property to the standard Get-Process output display

PowerShell

Copy

```
Get-Process pwsh | Format-Table `
    @{Label = "NPM(K)"; Expression = {[int]($_.NPM / 1024)}},
    @{Label = "PM(K)"; Expression = {[int]($_.PM / 1024)}},
    @{Label = "WS(K)"; Expression = {[int]($_.WS / 1024)}},
    @{Label = "VM(M)"; Expression = {[int]($_.VM / 1MB)}},
    @{Label = "CPU(s)"; Expression = {if ($_.CPU) {$_ .CPU.ToString("N")}}},
    Id, ProcessName, StartTime -AutoSize
```

NPM(K)	PM(K)	WS(K)	VM(M)	CPU(s)	Id	ProcessName	StartTime
143	239540	259384	2366162	22.73	12720	pwsh	12/5/2022 3:21:51 PM
114	61776	104588	2366127	11.45	18336	pwsh	12/5/2022 7:30:53 AM
156	77924	82060	2366185	10.47	18812	pwsh	12/5/2022 7:30:52 AM
85	48216	115192	2366074	1.14	24428	pwsh	12/8/2022 9:14:15 AM

This example retrieves processes from the local computer. The retrieved processes are piped to the `Format-Table` command that adds the **StartTime** property to the standard `Get-Process` output display.

## Example 6: Get version information for a process

PowerShell

Copy

```
Get-Process pwsh -FileVersionInfo
```

ProductVersion	FileVersion	FileName
6.1.2	6.1.2	C:\Program Files\PowerShell\6\pwsh.exe

This command uses the **FileVersionInfo** parameter to get the version information for the `pwsh.exe` file that is the main module for the PowerShell process.

To run this command with processes that you do not own on Windows Vista and later versions of Windows, you must open PowerShell with the **Run as administrator** option.

## Example 7: Get modules loaded with the specified process

PowerShell Copy

```
Get-Process SQL* -Module
```

This command uses the **Module** parameter to get the modules that have been loaded by the process. This command gets the modules for the processes that have names that begin with `SQL`.

To run this command on Windows Vista and later versions of Windows with processes that you do not own, you must start PowerShell with the **Run as administrator** option.

## Example 8: Find the owner of a process

PowerShell Copy

```
Get-Process pwsh -IncludeUserName
```

Handles	WS(K)	CPU(s)	Id	UserName	ProcessName
-----	-----	-----	--	-----	-----
782	132080	2.08	2188	DOMAIN01\user01	pwsh

This command shows how to find the owner of a process. On Windows, the **IncludeUserName** parameter requires elevated user rights (**Run as Administrator**). The output reveals that the owner is `Domain01\user01`.

## Example 9: Use an automatic variable to identify the process hosting the current session

PowerShell Copy

```
Get-Process pwsh
```

NPM(K)	PM(M)	WS(M)	CPU(s)	Id	SI	ProcessName
-----	-----	-----	-----	--	--	-----
83	96.21	105.95	4.33	1192	10	pwsh
79	83.81	117.61	2.16	10580	10	pwsh

```
Get-Process -Id $PID
```

NPM(K)	PM(M)	WS(M)	CPU(s)	Id	SI	ProcessName
-----	-----	-----	-----	--	--	-----
83	96.21	77.53	4.39	1192	10	pwsh

These commands show how to use the `$PID` automatic variable to identify the process that is hosting the current PowerShell session. You can use this method to distinguish the host process from other PowerShell processes that you might want to stop or close.

The first command gets all of the PowerShell processes in the current session.

The second command gets the PowerShell process that is hosting the current session.

## Example 10: Get all processes that have a main window title and display them in a table

PowerShell

Copy

```
Get-Process | Where-Object {$_.mainWindowTitle} | Format-Table Id, Name, mainWir
```

This command gets all the processes that have a main window title, and it displays them in a table with the process ID and the process name.

The `mainWindowTitle` property is just one of many useful properties of the `Process` object that `Get-Process` returns. To view all of the properties, pipe the results of a `Get-Process` command to the `Get-Member` cmdlet `Get-Process | Get-Member`.

## Parameters

### -FileVersionInfo

Indicates that this cmdlet gets the file version information for the program that runs in the process.

On Windows Vista and later versions of Windows, you must open PowerShell with the **Run as administrator** option to use this parameter on processes that you do not own.

Using this parameter is equivalent to getting the `MainModule.FileVersionInfo` property of each process object. When you use this parameter, `Get-Process` returns a `FileVersionInfo` object `System.Diagnostics.FileVersionInfo`, not a process object. So, you cannot pipe the output of the command to a cmdlet that expects a process object, such as `Stop-Process`.

[Expand table](#)

Type:	SwitchParameter
Aliases:	FV, FVI
Position:	Named
Default value:	False
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

### -Id

Specifies one or more processes by process ID (PID). To specify multiple IDs, use commas to separate the IDs. To find the PID of a process, type `Get-Process`.


[Expand table](#)

Type:	Int32[]
Aliases:	PID
Position:	Named
Default value:	None
Required:	True
Accept pipeline input:	True

Accept wildcard characters:	False
-----------------------------	-------

-IncludeUserName


Indicates that the UserName value of the **Process** object is returned with results of the command.

 Expand table

Type:	SwitchParameter
Position:	Named
Default value:	None
Required:	True
Accept pipeline input:	False
Accept wildcard characters:	False

-InputObject

Specifies one or more process objects. Enter a variable that contains the objects, or type a command or expression that gets the objects.

 Expand table

Type:	Process[]
Position:	Named
Default value:	None
Required:	True
Accept pipeline input:	True
Accept wildcard characters:	False


-Module

Indicates that this cmdlet gets the modules that have been loaded by the processes.

On Windows Vista and later versions of Windows, you must open PowerShell with the **Run as administrator** option to use this parameter on processes that you do not own.

This parameter is equivalent to getting the **Modules** property of each process object. When you use this parameter, this cmdlet returns a **ProcessModule** object **System.Diagnostics.ProcessModule**, not a process object. So, you cannot pipe the output of the command to a cmdlet that expects a process object, such as `Stop-Process`.

When you use both the **Module** and **FileVersionInfo** parameters in the same command, this cmdlet returns a **FileVersionInfo** object with information about the file version of all modules.

 Expand table

Type:	SwitchParameter
Position:	Named
Default value:	False
Required:	False

Accept pipeline input:	False
Accept wildcard characters:	False

-Name

Specifies one or more processes by process name. You can type multiple process names (separated by commas) and use wildcard characters. The parameter name (`Name`) is optional.

 Expand table

Type:	<a href="#">String[]</a>
Aliases:	ProcessName
Position:	0
Default value:	None
Required:	False
Accept pipeline input:	True
Accept wildcard characters:	True

# Inputs

Process

You can pipe a process object to this cmdlet.

# Outputs

Process

By default, this cmdlet returns a **System.Diagnostics.Process** object.

FileVersionInfo

If you use the **FileVersionInfo** parameter, this cmdlet returns a **FileVersionInfo** object.

ProcessModule

If you use the **Module** parameter, without the **FileVersionInfo** parameter, this cmdlet returns a **ProcessModule** object.

# Notes

PowerShell includes the following aliases for `Get-Process`:

- All platforms:
  - `gps`
- Windows:
  - `ps`

On computers that are running a 64-bit version of Windows, the 64-bit version of PowerShell gets only 64-bit process modules and the 32-bit version of PowerShell gets only 32-bit process modules.

To get process information from a remote computer, use the `Invoke-Command` cmdlet. For more information, see [Invoke-Command](#).

You can use the properties and methods of the Windows Management Instrumentation (WMI) **Win32\_Process** object in PowerShell. For information, see [Win32\\_Process](#).

The default display of a process is a table that includes the following columns. For a description of all of the properties of process objects, see [Process Properties](#).

- **Handles**: The number of handles that the process has opened.
- **NPM(K)**: The amount of non-paged memory that the process is using, in kilobytes.
- **PM(K)**: The amount of pageable memory that the process is using, in kilobytes.
- **WS(K)**: The size of the working set of the process, in kilobytes. The working set consists of the pages of memory that were recently referenced by the process.
- **VM(M)**: The amount of virtual memory that the process is using, in megabytes. Virtual memory includes storage in the paging files on disk.
- **CPU(s)**: The amount of processor time that the process has used on all processors, in seconds.
- **ID**: The process ID (PID) of the process.
- **ProcessName**: The name of the process. For explanations of the concepts related to processes, see the Glossary in Help and Support Center and the Help for Task Manager.

You can also use the built-in alternate views of the processes available with `Format-Table`, such as **StartTime** and **Priority**, and you can design your own views.

## Related Links

- [Debug-Process](#)
- [Get-Process](#)
- [Start-Process](#)
- [Stop-Process](#)
- [Wait-Process](#)



### Collaborate with us on GitHub

The source for this content can be found on GitHub, where you can also create and review issues and pull requests. For more information, see [our contributor guide](#).



### PowerShell feedback

PowerShell is an open source project. Select a link to provide feedback:



[Open a documentation issue](#)



[Provide product feedback](#)