

 Filter by title

- Authorization
- ▾ About Authorization
- About Authorization
- ▾ Access Control
- Access Control
- C2-level Security
- Access Control Model
- ▾ Security Descriptor Definition Language
- Security Descriptor Definition Language
- Security Descriptor String Format
- Security Descriptor Definition Language for Conditional ACEs.
- ACE Strings
- SID Strings**
- Privileges
- Audit Generation
- Securable Objects
- Low-level Access Control
- Access Control Editor
- Client/Server Access Control
- Access Control for Application Resources
- AppContainer
- Mandatory Integrity Control
- User Account Control
- Using Authorization in C++
- Using Authorization in Script
- Using Authz API
- Authorization Reference
- Microsoft.Interop.Security.AzRoles Assembly

 **Download PDF**

⋮ / [Security and Identity](#) / [Authorization](#) /

SID Strings


Article • 09/26/2023 • [7 contributors](#) [Feedback](#)

In the [security descriptor definition language](#) (SDDL), [security descriptor string](#) use SID strings for the following components of a *security descriptor*:

- Owner
- Primary group
- The [trustee](#) in an ACE

A SID string in a security descriptor string can use either the standard string representation of a SID (*S-R-I-S-S*) or one of the string constants defined in Sddl.h. For more information about the standard SID string notation, see [SID Components](#).

The following SID string constants for well-known SIDs are defined in Sddl.h. For information about the corresponding *relative IDs* (RIDs), see [Well-known SIDs](#).

 **Expand table**

SDDL SID string	Constant in Sddl.h	Account alias and corresponding RID
"AA"	SDDL_ACCESS_CONTROL_ASSISTANCE_OPS	Access control assistance operators. The corresponding RID is DOMAIN_ALIAS_RID_ACCESS_CONTROL_ASSISTANCE_OPS. Windows Server 2008 R2, Windows 7, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022: Not available.
"AC"	SDDL_ALL_APP_PACKAGES	All applications running in an app package context. The corresponding RID is SECURITY_BUILTIN_PACKAGE_ANY_PACKAGE. Windows Server 2012 R2, Windows 7, Windows Server 2008, Windows Server 2016, Windows Server 2019, Windows Server 2022: Not available.
"AN"	SDDL_ANONYMOUS	Anonymous logon. The corresponding RID is SECURITY_ANONYMOUS_LOGON_RID.
"AO"	SDDL_ACCOUNT_OPERATORS	Account operators. The corresponding RID is DOMAIN_ALIAS_RID_ACCOUNT_OPS.
"AP"	SDDL_PROTECTED_USERS	Protected Users . The corresponding RID is DOMAIN_GROUP_RID_PROTECTED_USERS. Windows 8, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022: Not available.
"AU"	SDDL_AUTHENTICATED_USERS	Authenticated users. The corresponding RID is SECURITY_AUTHENTICATED_USER_RID.
"BA"	SDDL_BUILTIN_ADMINISTRATORS	Built-in administrators. The corresponding RID is DOMAIN_ALIAS_RID_ADMINS.
"BG"	SDDL_BUILTIN_GUESTS	Built-in guests. The corresponding RID is DOMAIN_ALIAS_RID_GUESTS.
"BO"	SDDL_BACKUP_OPERATORS	Backup operators. The corresponding RID is DOMAIN_ALIAS_RID_BACKUP_OPS.
"BU"	SDDL_BUILTIN_USERS	Built-in users. The corresponding RID is DOMAIN_ALIAS_RID_USERS.
"CA"	SDDL_CERT_SERV_ADMINISTRATORS	Certificate publishers. The corresponding RID is DOMAIN_GROUP_RID_CERT_ADMINS.

"CD"	SDDL_CERTSVC_DCOM_ACCESS	Users who can connect to certification authorities Component Object Model (DCOM). The corresponding RID is DOMAIN_ALIAS_RID_CERTSVC_DCOM_ACCESS. Windows 2000, Windows Vista and Windows Server 2003: Not available.
"CG"	SDDL_CREATOR_GROUP	Creator group. The corresponding RID is SECURITY_CREATOR_GROUP_RID.
"CN"	SDDL_CLONEABLE_CONTROLLERS	Cloneable domain controllers. The corresponding RID is DOMAIN_GROUP_RID_CLONEABLE_CONTROLLERS. Windows 2000 R2, Windows 7, Windows Server 2008, Windows Server 2003: Not available.
"CO"	SDDL_CREATOR_OWNER	Creator owner. The corresponding RID is SECURITY_CREATOR_OWNER_RID.
"CY"	SDDL_CRYPTO_OPERATORS	Crypto operators. The corresponding RID is DOMAIN_ALIAS_RID_CRYPTO_OPERATORS. Windows 2000: Not available.
"DA"	SDDL_DOMAIN_ADMINISTRATORS	Domain administrators. The corresponding RID is DOMAIN_GROUP_RID_ADMINS.
"DC"	SDDL_DOMAIN_COMPUTERS	Domain computers. The corresponding RID is DOMAIN_GROUP_RID_COMPUTERS.
"DD"	SDDL_DOMAIN_DOMAIN_CONTROLLERS	Domain controllers. The corresponding RID is DOMAIN_GROUP_RID_CONTROLLERS.
"DG"	SDDL_DOMAIN_GUESTS	Domain guests. The corresponding RID is DOMAIN_GROUP_RID_GUESTS.
"DU"	SDDL_DOMAIN_USERS	Domain users. The corresponding RID is DOMAIN_GROUP_RID_USERS.
"EA"	SDDL_ENTERPRISE_ADMINS	Enterprise administrators. The corresponding RID is DOMAIN_GROUP_RID_ENTERPRISE_ADMINS.
"ED"	SDDL_ENTERPRISE_DOMAIN_CONTROLLERS	Enterprise domain controllers. The corresponding RID is SECURITY_SERVER_LOGON_RID.
"EK"	SDDL_ENTERPRISE_KEY_ADMINS	Enterprise key admins. The corresponding RID is DOMAIN_GROUP_RID_ENTERPRISE_KEY_ADMINS. Windows 2000 R2, Windows 8.1, Windows Server 2012, Windows Server 2008 R2, Windows 7, Windows Server 2008, Windows Server 2003: Not available.
"ER"	SDDL_EVENT_LOG_READERS	Event log readers. The corresponding RID is DOMAIN_ALIAS_RID_EVENT_LOG_READERS. Windows 2000, Windows Vista and Windows Server 2003: Not available.
"ES"	SDDL_RDS_ENDPOINT_SERVERS	Endpoint servers. The corresponding RID is DOMAIN_ALIAS_RID_RDS_ENDPOINT_SERVERS. Windows 2000 R2, Windows 7, Windows Server 2008, Windows Server 2003: Not available.
"HA"	SDDL_HYPER_V_ADMINS	Hyper-V administrators. The corresponding RID is DOMAIN_ALIAS_RID_HYPER_V_ADMINS. Windows 2000, Windows 7, Windows Server 2008, Windows Server 2003: Not available.
"HI"	SDDL_ML_HIGH	High integrity level. The corresponding RID is SECURITY_MANDATORY_HIGH_RID. Windows Server 2003: Not available.
"HO"	SDDL_USER_MODE_HARDWARE_OPERATORS	Group members may operate hardware from user mode. The corresponding RID is DOMAIN_ALIAS_RID_USER_MODE_HARDWARE_OPERATORS.
"IS"	SDDL_IIS_USERS	Anonymous Internet users. The corresponding RID is DOMAIN_ALIAS_RID_IUSERS. Windows Server 2003: Not available.
"IU"	SDDL_INTERACTIVE	Interactively logged-on user. This is a group identifier of a process when it was logged on interactively. The type is LOGON32_LOGON_INTERACTIVE. The corresponding RID is SECURITY_INTERACTIVE_RID.

"KA"	SDDL_KEY_ADMINS	Domain key admins. The corresponding RID is DOMAIN_GROUP_RID_KEY_ADMINS. Windows 95, Windows 98, Windows 8.1, Windows Server 2012, Windows 8 R2, Windows 7, Windows Server 2008, Windows Server 2003: Not available.
"LA"	SDDL_LOCAL_ADMIN	Local administrator. The corresponding RID is DOMAIN_USER_RID_ADMIN.
"LG"	SDDL_LOCAL_GUEST	Local guest. The corresponding RID is DOMAIN_L
"LS"	SDDL_LOCAL_SERVICE	Local service account. The corresponding RID is SECURITY_LOCAL_SERVICE_RID.
"LU"	SDDL_PERFLOG_USERS	Performance Log users. The corresponding RID is DOMAIN_ALIAS_RID_LOGGING_USERS.
"LW"	SDDL_ML_LOW	Low integrity level. The corresponding RID is SECURITY_MANDATORY_LOW_RID. Windows Se
"ME"	SDDL_ML_MEDIUM	Medium integrity level. The corresponding RID is SECURITY_MANDATORY_MEDIUM_RID. Window available.
"MP"	SDDL_ML_MEDIUM_PLUS	Medium Plus integrity level. The corresponding R SECURITY_MANDATORY_MEDIUM_PLUS_RID. W Windows Vista and Windows Server 2003: Not .
"MU"	SDDL_PERFMON_USERS	Performance Monitor users. The corresponding R DOMAIN_ALIAS_RID_MONITORING_USERS.
"NO"	SDDL_NETWORK_CONFIGURATION_OPS	Network configuration operators. The corresponc DOMAIN_ALIAS_RID_NETWORK_CONFIGURATIC
"NS"	SDDL_NETWORK_SERVICE	Network service account. The corresponding RID SECURITY_NETWORK_SERVICE_RID.
"NU"	SDDL_NETWORK	Network logon user. This is a group identifier add process when it was logged on across a network. type is LOGON32_LOGON_NETWORK. The corre: SECURITY_NETWORK_RID.
"OW"	SDDL_OWNER_RIGHTS	Owner Rights SID. The corresponding RID is SECURITY_CREATOR_OWNER_RIGHTS_RID. <i>Wind</i> available.
"PA"	SDDL_GROUP_POLICY_ADMINS	Group Policy administrators. The corresponding F DOMAIN_GROUP_RID_POLICY_ADMINS.
"PO"	SDDL_PRINTER_OPERATORS	Printer operators. The corresponding RID is DOMAIN_ALIAS_RID_PRINT_OPS
"PS"	SDDL_PERSONAL_SELF	Principal self. The corresponding RID is SECURITY
"PU"	SDDL_POWER_USERS	Power users. The corresponding RID is DOMAIN_ALIAS_RID_POWER_USERS.
"RA"	SDDL_RDS_REMOTE_ACCESS_SERVERS	RDS remote access servers. The corresponding RI DOMAIN_ALIAS_RID_RDS_REMOTE_ACCESS_SER' 2008 R2, Windows 7, Windows Server 2008, W Windows Server 2003: Not available.
"RC"	SDDL_RESTRICTED_CODE	Restricted code. This is a restricted token created CreateRestrictedToken function. The correspondi SECURITY_RESTRICTED_CODE_RID.
"RD"	SDDL_REMOTE_DESKTOP	Terminal server users. The corresponding RID is DOMAIN_ALIAS_RID_REMOTE_DESKTOP_USERS.
"RE"	SDDL_REPLICATOR	Replicator. The corresponding RID is DOMAIN_AI
"RM"	SDDL_RMS__SERVICE_OPERATORS	RMS Service. Available only in Windows Vista.

"RO"	SDDL_ENTERPRISE_RO_DCs	Enterprise Read-only domain controllers. The corresponding RID is DOMAIN_GROUP_RID_ENTERPRISE_READONLY. Windows Server 2008, Windows Vista and Windows XP : Available. Windows Server 2003 : Not available.
"RS"	SDDL_RAS_SERVERS	RAS servers group. The corresponding RID is DOMAIN_ALIAS_RID_RAS_SERVERS.
"RU"	SDDL_ALIAS_PREW2KCOMPACC	Alias to grant permissions to accounts that use a Windows operating system with operating systems previous to Windows 2000. The corresponding RID is DOMAIN_ALIAS_RID_PREW2KCOMPACC.
"SA"	SDDL_SCHEMA ADMINISTRATORS	Schema administrators. The corresponding RID is DOMAIN_GROUP_RID_SCHEMA_ADMINS.
"SI"	SDDL_ML_SYSTEM	System integrity level. The corresponding RID is SECURITY_MANDATORY_SYSTEM_RID. Windows XP : Available. Windows Server 2008, Windows Vista and Windows 7 : Not available.
"SO"	SDDL_SERVER_OPERATORS	Server operators. The corresponding RID is DOMAIN_ALIAS_RID_SYSTEM_OPS.
"SS"	SDDL_SERVICE_ASSERTED	Authentication service asserted. The corresponding RID is SECURITY_AUTHENTICATION_SERVICE_ASSERTED. Windows Server 2008 R2, Windows 7, Windows Server 2008, Windows Vista and Windows XP : Available. Windows Server 2003 : Not available.
"SU"	SDDL_SERVICE	Service logon user. This is a group identifier added to the process when it was logged as a service. The corresponding RID is LOGON32_LOGON_SERVICE. The corresponding SECURITY_SERVICE_RID.
"SY"	SDDL_LOCAL_SYSTEM	Local system. The corresponding RID is SECURITY_LOCAL_SYSTEM_RID.
"UD"	SDDL_USER_MODE_DRIVERS	User-mode driver. The corresponding RID is SECURITY_USERMODEDRIVERHOST_ID_BASE_RID. Windows Server 2008 R2, Windows 7, Windows Server 2008, Windows Vista and Windows XP : Available. Windows Server 2003 : Not available.
"WD"	SDDL_EVERYONE	Everyone. The corresponding RID is SECURITY_WORLD_RID.
"WR"	SDDL_WRITE_RESTRICTED_CODE	Write Restricted code. The corresponding RID is SECURITY_WRITE_RESTRICTED_CODE_RID. Windows XP : Available. Windows Server 2008, Windows Vista and Windows 7 : Not available.

The [ConvertSidToStringSid](#) and [ConvertStringSidToSid](#) functions always use the standard SID string notation and do not support SDDL SID string constants.

For more information about well-known SIDs, see [Well-known SIDs](#).

See also

[\[MS-DTYP\]: Security Descriptor Description Language](#)

Feedback

Was this page helpful?

Yes

No


[Provide product feedback](#) | [Get help at Microsoft Q&A](#)




Additional resources

[Events](#)

Nov 20, 12 AM - Nov 22, 12 AM

Gain the competitive edge you need with powerful AI and Cloud solutions by attending Microsoft Ignite online.
[Register now](#)

 English (United States)  Your Privacy Choices  Theme 

[Manage cookies](#) [Previous Versions](#) [Blog](#)  [Contribute](#) [Privacy](#)  [Terms of Use](#) [Trademarks](#)  © Microsoft 2024