



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies



# systeminfo

Article • 02/03/2023 • 7 contributors

[Feedback](#)

## In this article

[Syntax](#)

[Examples](#)

[Related links](#)

Displays detailed configuration information about a computer and its operating system, including operating system configuration, security information, product ID, and hardware properties (such as RAM, disk space, and network cards).

## Syntax

```
systeminfo [/s <computer> [/u <domain>\<username> [/p <password> [/fo <format> [/nh] [/?]
```

## Parameters

 Expand table

Parameter	Description
/s <computer>	Specifies the name or IP address of a remote computer (do not use backslashes). The default is the local computer.
/u <domain>\<username>	Runs the command with the account permissions of the specified user account. If /u is not specified, this command uses the permissions of the user who is currently logged on to the computer that is issuing the command.
/p <password>	Specifies the password of the user account that is specified in the /u parameter.
/fo <format>	Specifies the output format with one of the following values: <ul style="list-style-type: none"><li>• <b>TABLE</b> - Displays output in a table.</li><li>• <b>LIST</b> - Displays output in a list.</li><li>• <b>CSV</b> - Displays output in comma-separated values (.csv) format.</li></ul>
/nh	Suppresses column headers in the output. Valid when the /fo parameter is set to TABLE or CSV.
/?	Displays help at the command prompt.

## Examples

To view configuration information for a computer named *Srvmain*, type:

```
systeminfo /s Srvmain /u Administrator /p Password123! /fo TABLE /nh
```

```
systeminfo /s srvmain
```

To remotely view configuration information for a computer named *Srvmain2* that is located on the *Maindom* domain, type:

```
systeminfo /s srvmain2 /u maindom\hiropln
```

To remotely view configuration information (in list format) for a computer named *Srvmain2* that is located on the *Maindom* domain, type:

```
systeminfo /s srvmain2 /u maindom\hiropln /p p@ssW23 /fo lis
```

## Related links


- [Command-Line Syntax Key](#)

## Feedback



Was this page helpful?

 Yes

 No

 English (United States)

 Your Privacy Choices


 Theme 

[Manage cookies](#)

[Previous Versions](#)

[Blog](#) 

[Contribute](#)

[Privacy](#) 

[Terms of Use](#)

[Trademarks](#) 

© Microsoft 2024