

Q

8

Start free trial

Contact Sales

Platform Solutions Customers Resources Pricing Docs

Elastic Docs > Elastic Security Solution [8.15] > Detections and alerts > Prebuilt rule reference

Conhost Spawned By Suspicious Parent Process



Detects when the Console Window Host (conhost.exe) process is spawned by a suspicious parent process, which could be indicative of code injection.

Rule type: eql

Rule indices:

- winlogbeat-*
- logs-endpoint.events.process-*
- logs-windows.sysmon_operational-*
- endgame-*
- logs-m365_defender.event-*
- logs-sentinel_one_cloud_funnel.*

Severity: high

Risk score: 73

Runs every: 5m

Searches indices from: now-9m (Date Math format, see also

Additional look-back time)

Maximum alerts per execution: 100

References:

 https://www.fireeye.com/blog/threatresearch/2017/08/monitoring-windows-console-activitypart-one.html

Tags:

• Domain: Endpoint

OS: Windows

Use Case: Threat Detection

• Tactic: Execution

Tactic: Defense Evasion

Tactic: Privilege Escalation

• Resources: Investigation Guide

• Data Source: Elastic Endgame

Data Source: Elastic Defend

Data Source: Sysmon

• Data Source: Microsoft Defender for Endpoint

• Data Source: SentinelOne

Version: 310

Rule authors:

Elastic

Rule license: Elastic License v2

Investigation guide



Triage and analysis

Investigating Conhost Spawned By Suspicious Parent Process

The Windows Console Host, or conhost.exe, is both the server application for all of the Windows Console APIs as well as the classic Windows user interface for working with command-line applications.

Attackers often rely on custom shell implementations to avoid using built-in command interpreters like cmd.exe and PowerShell.exe and bypass application allowlisting and security features. Attackers commonly inject these implementations into legitimate system processes.

Possible investigation steps

- Investigate the process execution chain (parent process tree) for unknown processes. Examine their executable files for prevalence, whether they are located in expected locations, and if they are signed with valid digital signatures.
- Investigate abnormal behaviors observed by the subject process, such as network connections, registry or file modifications, and any spawned child processes.
- Investigate other alerts associated with the user/host during the past 48 hours.
- Inspect the host for suspicious or abnormal behavior in the alert timeframe.
- Retrieve the parent process executable and determine if it is malicious:
- Use a private sandboxed malware analysis system to perform analysis.
- Observe and collect information about the following activities:
- Attempts to contact external domains and addresses.
- File and registry access, modification, and creation activities.
- Service creation and launch activities.
- Scheduled task creation.

- Use the PowerShell Get-FileHash cmdlet to get the files' SHA-256 hash values.
- Search for the existence and reputation of the hashes in resources like VirusTotal, Hybrid-Analysis, CISCO Talos, Any.run, etc.

False positive analysis

 This activity is unlikely to happen legitimately. Benign true positives (B-TPs) can be added as exceptions if necessary.

Related rules

- Suspicious Process from Conhost 28896382-7d4f-4d50-9b72-67091901fd26
- Suspicious PowerShell Engine ImageLoad 852c1f19-68e8-43a6-9dce-340771fe1be3

Response and remediation

- Initiate the incident response process based on the outcome of the triage.
- Isolate the involved hosts to prevent further postcompromise behavior.
- If the triage identified malware, search the environment for additional compromised hosts.
- Implement temporary network rules, procedures, and segmentation to contain the malware.
- Stop suspicious processes.
- Immediately block the identified indicators of compromise (IoCs).
- Inspect the affected systems for additional malware backdoors like reverse shells, reverse proxies, or droppers that attackers could use to reinfect the system.
- Remove and block malicious artifacts identified during triage.

- Investigate credential exposure on systems compromised or used by the attacker to ensure all compromised accounts are identified. Reset passwords for these accounts and other potentially compromised credentials, such as email, business systems, and web services.
- Run a full antimalware scan. This may reveal additional artifacts left in the system, persistence mechanisms, and malware components.
- Determine the initial vector abused by the attacker and take action to prevent reinfection through the same vector.
- Using the incident response data, update logging and audit policies to improve the mean time to detect (MTTD) and the mean time to respond (MTTR).

Rule query



Framework: MITRE ATT&CKTM

Tactic:

Name: Execution

• ID: TA0002


 Reference URL: https://attack.mitre.org/tactics/TA0002/

Technique:

- Name: Command and Scripting Interpreter
- ID: T1059
- Reference URL: https://attack.mitre.org/techniques/T1059/
- Tactic:
 - Name: Defense Evasion
 - ID: TA0005
 - Reference URL: https://attack.mitre.org/tactics/TA0005/
- Technique:
 - Name: Masquerading
 - ID: T1036
 - Reference URL: https://attack.mitre.org/techniques/T1036/
- Tactic:
 - Name: Privilege Escalation
 - ID: TA0004
 - Reference URL: https://attack.mitre.org/tactics/TA0004/
- Technique:
 - Name: Process Injection
 - ID: T1055
 - Reference URL: https://attack.mitre.org/techniques/T1055/

ElasticON events are back!

Learn about the Elastic Search Al Platform from the experts at our live events.





The Search Al Company

Follow us











About us

About Elastic

Leadership

DE&I

Blog

Newsroom

Join us

Careers

Career portal

Partners

Find a partner

Partner login

Request access

Become a partner

Trust & Security

Trust center

EthicsPoint portal

ECCN report

Ethics email

Investor relations

Investor resources

Governance

Financials

Stock

EXCELLENCE AWARDS

Previous winners

ElasticON Tour

Become a sponsor

All events

Conhost Spawned By Suspicious Parent Process | Elastic Security Solution [8.15] | Elastic - 31/10/2024 17:52 https://www.elastic.co/guide/en/security/current/conhost-spawned-by-suspicious-parent-process.html

<u>Trademarks</u> <u>Terms of Use</u> <u>Privacy</u> <u>Sitemap</u>

© 2024. Elasticsearch B.V. All Rights Reserved

Elastic, Elasticsearch and other related marks are trademarks, logos or registered trademarks of Elasticsearch B.V. in the United States and other countries.

Apache, Apache Lucene, Apache Hadoop, Hadoop, HDFS and the yellow elephant logo are trademarks of the Apache Software Foundation in the United States and/or other countries. All other brand names, product names, or trademarks belong to their respective owners.