



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalised advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking 'Manage Cookies' at the bottom of the page.[Privacy Statement](#)
[Third-Party Cookies](#)

Accept

Reject

Manage cookies



ksetup

Article • 03/02/2023 • 7 contributors

Feedback

In this article

[Syntax](#)

[Related links](#)

Performs tasks related to setting up and maintaining Kerberos protocol and the Key Distribution Center (KDC) to support Kerberos realms. Specifically, this command is used to:

- Change the computer settings for locating Kerberos realms. In non-Microsoft, Kerberos-based implementations, this information is usually kept in the Krb5.conf file. In Windows Server operating systems, it's kept in the registry. You can use this tool to modify these settings. These settings are used by workstations to locate

Kerberos realms and by domain controllers to locate Kerberos realms for cross-realm trust relationships.

- Initialize registry keys that the Kerberos Security Support Provider (SSP) uses to locate a KDC for the Kerberos realm, if the computer is isn't a member of a Windows domain. After configuration, the user of a client computer running the Windows operating system can log on to accounts in the Kerberos realm.
- Search the registry for the domain name of the user's realm and then resolves the name to an IP address by querying a DNS server. The Kerberos protocol can use DNS to locate KDCs by using only the realm name, but it must be specially configured to do so.

Syntax

```
ksetup
[/setrealm <DNSdomainname>]
[/mapuser <principal> <account>]
[/addkdc <realmname> <KDCname>]
[/delkdc <realmname> <KDCname>]
[/addkpasswd <realmname> <KDCPasswordName>]
[/delkpasswd <realmname> <KDCPasswordName>]
[/server <servername>]
[/setcomputerpassword <password>]
[/removerealm <realmname>]
[/domain <domainname>]
[/changepassword <oldpassword> <newpassword>]
[/listrealmflags]
[/setrealmflags <realmname> [sendaddress] [tcpsupported] [de
[/addrealmflags <realmname> [sendaddress] [tcpsupported] [de
[/delrealmflags [sendaddress] [tcpsupported] [delegate] [ncs
[/dumpstate]
[/addhosttorealmmap] <hostname> <realmname>]
[/delhosttorealmmap] <hostname> <realmname>]
[/setenctypeattr] <domainname> {DES-CBC-CRC | DES-CBC-MD5 |
[/getenctypeattr] <domainname>
```

```
[/addenctypeattr] <domainname> {DES-CBC-CRC | DES-CBC-MD5 |
[/delenctypeattr] <domainname>
```

Parameters

 Expand table

Parameter	Description
ksetup setrealm	Makes this computer a member of a Kerberos realm.
ksetup addkdc	Defines a KDC entry for the given realm.
ksetup delkdc	Deletes a KDC entry for the realm.
ksetup addkpasswd	Adds a kpasswd server address for a realm.
ksetup delkpasswd	Deletes a kpasswd server address for a realm.
ksetup server	Allows you to specify the name of a Windows computer on which to apply the changes.
ksetup setcomputerpassword	Sets the password for the computer's domain account (or host principal).
ksetup removerealm	Deletes all information for the specified realm from the registry.
ksetup domain	Allows you to specify a domain (if the <code><domainname></code> hasn't already been set by the <code>/domain</code> parameter).
ksetup changepassword	Allows you to use the kpasswd to change the logged on user's password.
ksetup listrealmflags	Lists the available realm flags that ksetup can detect.
ksetup setrealmflags	Sets realm flags for a specific realm.
ksetup addrealmflags	Adds additional realm flags to a realm.

ksetup delrealmflags	Deletes realm flags from a realm.
ksetup dumpstate	Analyzes the Kerberos configuration on the given computer. Adds a host to realm mapping to the registry.
ksetup addhosttorealmmmap	Adds a registry value to map the host to the Kerberos realm.
ksetup delhosttorealmmmap	Deletes the registry value that mapped the host computer to the Kerberos realm.
ksetup setenctypeattr	Sets one or more encryption types trust attributes for the domain.
ksetup getenctypeattr	Gets the encryption types trust attribute for the domain.
ksetup addenctypeattr	Adds encryption types to the encryption types trust attribute for the domain.
ksetup delenctypeattr	Deletes the encryption types trust attribute for the domain.
/?	Displays Help at the command prompt.

Related links

- [Command-Line Syntax Key](#)

Feedback

Was this page helpful?

 Yes

 No

