



Admin console

Home > Google Workspace > Admin console > Reference

# Admin Audit Activity Events - Security Settings

[Send feedback](#)

This document lists the events and parameters for Security Settings Admin Audit activity events. You can retrieve these events by calling `Activities.list()` with `applicationName=admin`.

## Security Settings

Events of this type are returned with `type=SECURITY_SETTINGS`.

(Context-aware access) Access level assignment changed for an app

Event details
Event name
CHANGE_CAA_APP_ASSIGNMENTS
Parameters
APPLICATION_NAME
string
The application's name.
CAA_ASSIGNMENTS_NEW
string

CAA assignments new.

---

CAA\_ASSIGNMENTS\_OLD

string

CAA assignments old.

---

CAA\_ENFORCEMENT\_ENDPOINTS\_NEW

string

CAA enforcement endpoints new. Possible values:

- **CAA\_WEB\_VERSION**  
CAA enforcement endpoints value type - web version.
- **CAA\_WEB\_VERSION\_AND\_1P\_OAUTH\_CLIENTS**  
CAA enforcement endpoints value type - web version and 1p oauth clients.
- **CAA\_WEB\_VERSION\_AND\_1P\_OAUTH\_CLIENTS\_AND\_APIS**  
CAA enforcement endpoints value type - web version and 1p oauth clients and APIs (without exemptions).
- **CAA\_WEB\_VERSION\_AND\_1P\_OAUTH\_CLIENTS\_AND\_APIS\_WITH\_EXEMPTION**  
CAA enforcement endpoints value type - web version and 1p oauth clients and APIs (with exemptions).
- **CAA\_WEB\_VERSION\_AND\_APIS**  
CAA enforcement endpoints value type - web version and APIs (without exemptions).
- **CAA\_WEB\_VERSION\_AND\_APIS\_WITH\_EXEMPTION**  
CAA enforcement endpoints value type - web version and APIs (with exemptions).
- **WEB\_APP**  
CAA enforcement endpoint type - web app.
- **WEB\_APP\_AND\_1P\_OAUTH\_CLIENTS**  
CAA enforcement endpoint type - web app and 1p oauth clients.

---

CAA\_ENFORCEMENT\_ENDPOINTS\_OLD

string

CAA enforcement endpoints old. Possible values:

- **CAA\_WEB\_VERSION**  
CAA enforcement endpoints value type - web version.
- **CAA\_WEB\_VERSION\_AND\_1P\_OAUTH\_CLIENTS**  
CAA enforcement endpoints value type - web version and 1p oauth clients.

- **CAA\_WEB\_VERSION\_AND\_1P\_OAUTH\_CLIENTS\_AND\_APIS**  
CAA enforcement endpoints value type - web version and 1p oauth clients and APIs (without exemptions).
- **CAA\_WEB\_VERSION\_AND\_1P\_OAUTH\_CLIENTS\_AND\_APIS\_WITH\_EXEMPTION**  
CAA enforcement endpoints value type - web version and 1p oauth clients and APIs (with exemptions).
- **CAA\_WEB\_VERSION\_AND\_APIS**  
CAA enforcement endpoints value type - web version and APIs (without exemptions).
- **CAA\_WEB\_VERSION\_AND\_APIS\_WITH\_EXEMPTION**  
CAA enforcement endpoints value type - web version and APIs (with exemptions).
- **WEB\_APP**  
CAA enforcement endpoint type - web app.
- **WEB\_APP\_AND\_1P\_OAUTH\_CLIENTS**  
CAA enforcement endpoint type - web app and 1p oauth clients.

---

#### GROUP\_NAME

string

Group Name.

---

#### ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

---

#### TARGET\_ENTITY\_NAME

string

CAA Target Entity name.

---

#### TARGET\_ENTITY\_TYPE

string

CAA Target Entity type. Possible values:

- **GROUP**  
A distribution entity label for a Google group.
- **ORG\_UNIT**  
A distribution entity label for an organizational unit.

### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=CHANGE_CAA_APP_ASSIGNMENTS&maxResults=10  
&access_token=YOUR_ACCESS_TOKEN
```

### Admin Console message format

For *{TARGET\_ENTITY\_TYPE}* [*{TARGET\_ENTITY\_NAME}*]:Before:Access level  
[*{CAA\_ASSIGNMENTS\_OLD}*] applied to [*{CAA\_ENFORCEMENT\_ENDPOINTS\_OLD}*]  
of [*{APPLICATION\_NAME}*].After:Access level [*{CAA\_ASSIGNMENTS\_NEW}*]  
applied to [*{CAA\_ENFORCEMENT\_ENDPOINTS\_NEW}*] of [*{APPLICATION\_NAME}*].

All access to unconfigured third-party apps blocked for users under  
18

All third party API access blocked for users under 18.

### Event details

#### Event name

UNDERAGE\_BLOCK\_ALL\_THIRD\_PARTY\_API\_ACCESS

#### Parameters

ORG\_UNIT\_NAME  
string

The organizational unit (OU) name (path).

### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?  
eventName=UNDERAGE_BLOCK_ALL_THIRD_PARTY_API_ACCESS&maxResults=10  
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

All access to unconfigured third-party apps blocked for users under 18  
for *{ORG\_UNIT\_NAME}*

All third party API access blocked

Event details

Event name

BLOCK\_ALL\_THIRD\_PARTY\_API\_ACCESS

Parameters

ORG\_UNIT\_NAME  
string

The organizational unit (OU) name (path).

Sample request

GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=BLOCK\_ALL\_THIRD\_PARTY\_API\_ACCESS  
&maxResults=10&access\_token=*YOUR\_ACCESS\_TOKEN*

Admin Console message format

All third party API Access blocked

All third party API access unblocked

Event details

Event name

UNBLOCK\_ALL\_THIRD\_PARTY\_API\_ACCESS

Parameters

ORG\_UNIT\_NAME  
string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=UNBLOCK_ALL_THIRD_PARTY_API_ACCESS
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

All third party API Access unblocked

Allow 2-Step Verification

Event details

Event name

ALLOW\_STRONG\_AUTHENTICATION

Parameters

DOMAIN\_NAME  
string

The primary domain name.

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous `SETTING_NAME` value that was replaced during this event.

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=ALLOW_STRONG_AUTHENTICATION
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

Allow 2-Step Verification has been set from `{OLD_VALUE}` to `{NEW_VALUE}`  
for `{DOMAIN_NAME}`

Allow Google Sign-in only access to unconfigured third-party apps  
for users under 18

Allow Google Sign-in only third party API access for users under 18.

Event details

Event name

UNDERAGE\_SIGN\_IN\_ONLY\_THIRD\_PARTY\_API\_ACCESS

Parameters

ORG\_UNIT\_NAME  
string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?
```

```
eventName=UNDERAGE_SIGN_IN_ONLY_THIRD_PARTY_API_ACCESS&maxResults=10  
&access_token=YOUR_ACCESS_TOKEN
```

#### Admin Console message format

Allow Google Sign-in only access to unconfigured third-party apps for  
users under 18 for {ORG\_UNIT\_NAME}

## Allow Google Sign-in only third party API access

#### Event details

##### Event name

SIGN\_IN\_ONLY\_THIRD\_PARTY\_API\_ACCESS

##### Parameters

ORG\_UNIT\_NAME  
string

The organizational unit (OU) name (path).

#### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=SIGN_IN_ONLY_THIRD_PARTY_API_ACCESS  
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

#### Admin Console message format

Allow Google Sign-in only third party API access

## API Access Allowed



Event details

Event name

ALLOW\_SERVICE\_FOR\_OAUTH2\_ACCESS

Parameters

OAUTH2\_SERVICE\_NAME

string

OAuth2 service name. Possible values:

- APPS\_SCRIPT  
Apps Script Service name.
- APPS\_SCRIPT\_RUNTIME
- CALENDAR
- CLASSROOM  
Classroom service.
- CLOUD\_BILLING
- CLOUD\_MACHINE\_LEARNING
- CLOUD\_PLATFORM
- CLOUD\_SEARCH  
Cloud search service.
- CONTACTS
- DRIVE
- DRIVE\_HIGH\_RISK
- GMAIL
- GMAIL\_HIGH\_RISK
- GROUPS  
Groups service.
- GSUITE\_ADMIN
- TASKS  
Tasks service.
- VAULT

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=ALLOW_SERVICE_FOR_OAUTH2_ACCESS
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

*{OAUTH2\_SERVICE\_NAME}* API Access is allowed for *{ORG\_UNIT\_NAME}*

## API Access Blocked

Event details

Event name

DISALLOW\_SERVICE\_FOR\_OAUTH2\_ACCESS

Parameters

OAUTH2\_SERVICE\_NAME

string

OAuth2 service name. Possible values:

- APPS\_SCRIPT  
Apps Script Service name.
- APPS\_SCRIPT\_RUNTIME
- CALENDAR
- CLASSROOM  
Classroom service.
- CLOUD\_BILLING

- CLOUD\_MACHINE\_LEARNING
- CLOUD\_PLATFORM
- CLOUD\_SEARCH  
Cloud search service.
- CONTACTS
- DRIVE
- DRIVE\_HIGH\_RISK
- GMAIL
- GMAIL\_HIGH\_RISK
- GROUPS  
Groups service.
- GSUITE\_ADMIN
- TASKS  
Tasks service.
- VAULT

---

#### ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

---

#### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=DISALLOW_SERVICE_FOR_OAUTH2_ACCESS  
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

---

#### Admin Console message format

```
{OAUTH2_SERVICE_NAME} API Access is blocked for {ORG_UNIT_NAME}
```

---

app access settings collection id change.

## Event details

### Event name

CHANGE\_APP\_ACCESS\_SETTINGS\_COLLECTION\_ID

### Parameters

#### DOMAIN\_NAME

string

The primary domain name.

#### NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

#### OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

#### ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

#### SETTING\_NAME

string

The unique name (ID) of the setting that was changed.

## Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=CHANGE_APP_ACCESS_SETTINGS_COLLECTION_ID  
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

## Admin Console message format

App Access Settings Collection for the org unit `{ORG_UNIT_NAME}` has changed from `{OLD_VALUE}` to `{NEW_VALUE}`

## App added to Blocked list

### Event details

#### Event name

ADD\_TO\_BLOCKED\_OAUTH2\_APPS

#### Parameters

##### OAUTH2\_APP\_ID

string

OAuth2 application ID.

##### OAUTH2\_APP\_NAME

string

Name of service.

##### OAUTH2\_APP\_TYPE

string

OAuth2 application type. Possible values:

- ANDROID
- CHROME\_EXTENSION
- IOS
- OAUTH2\_CLIENT

##### ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=ADD_TO_BLOCKED_OAUTH2_APPS&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

*{OAUTH2\_APP\_NAME}* added to Blocked list for *{ORG\_UNIT\_NAME}*

App added to Limited list

Event details

Event name

ADD\_TO\_LIMITED\_OAUTH2\_APPS

Parameters

OAUTH2\_APP\_ID

string

OAuth2 application ID.

OAUTH2\_APP\_NAME

string

Name of service.

OAUTH2\_APP\_TYPE

string

OAuth2 application type. Possible values:

- ANDROID
- CHROME\_EXTENSION

- IOS
- OAUTH2\_CLIENT

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=ADD_TO_LIMITED_OAUTH2_APPS&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

{OAUTH2\_APP\_NAME} added to Limited list for {ORG\_UNIT\_NAME}

App no longer trusted

Event details

Event name

REMOVE\_FROM\_TRUSTED\_OAUTH2\_APPS

Parameters

OAUTH2\_APP\_ID

string

OAuth2 application ID.

OAUTH2\_APP\_NAME

string

Name of service.

0AUTH2\_APP\_TYPE

string

OAuth2 application type. Possible values:

- ANDROID
- CHROME\_EXTENSION
- IOS
- 0AUTH2\_CLIENT

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=REMOVE_FROM_TRUSTED_0AUTH2_APPS
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

{0AUTH2\_APP\_NAME} no longer trusted for {ORG\_UNIT\_NAME}

App removed from Blocked list

Event details

Event name

REMOVE\_FROM\_BLOCKED\_0AUTH2\_APPS

Parameters

0AUTH2\_APP\_ID

string



OAuth2 application ID.

OAuth2\_APP\_NAME

string

Name of service.

OAuth2\_APP\_TYPE

string

OAuth2 application type. Possible values:

- ANDROID
- CHROME\_EXTENSION
- IOS
- OAUTH2\_CLIENT

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=REMOVE_FROM_BLOCKED_OAUTH2_APPS  
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

**{OAuth2\_APP\_NAME}** removed from Blocked list for **{ORG\_UNIT\_NAME}**

App removed from Limited list

Event details

### Event name

REMOVE\_FROM\_LIMITED\_OAUTH2\_APPS

### Parameters

OAUTH2\_APP\_ID

string

OAuth2 application ID.

OAUTH2\_APP\_NAME

string

Name of service.

OAUTH2\_APP\_TYPE

string

OAuth2 application type. Possible values:

- ANDROID
- CHROME\_EXTENSION
- IOS
- OAUTH2\_CLIENT

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=REMOVE_FROM_LIMITED_OAUTH2_APPS  
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

### Admin Console message format

`{OAUTH2_APP_NAME}` removed from Limited list for `{ORG_UNIT_NAME}`

## App trusted

Event details
Event name
ADD_TO_TRUSTED_OAUTH2_APPS
Parameters
OAUTH2_APP_ID
string
OAuth2 application ID.
OAUTH2_APP_NAME
string
Name of service.
OAUTH2_APP_TYPE
string
OAuth2 application type. Possible values:
<ul style="list-style-type: none"><li>• ANDROID</li><li>• CHROME_EXTENSION</li><li>• IOS</li><li>• OAUTH2_CLIENT</li></ul>
ORG_UNIT_NAME
string
The organizational unit (OU) name (path).
Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=ADD_TO_TRUSTED_OAUTH2_APPS&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

*{OAUTH2\_APP\_NAME}* trusted for *{ORG\_UNIT\_NAME}*

## Apps added to Blocked list

### Event details

Event name

MULTIPLE\_ADD\_TO\_BLOCKED\_OAUTH2\_APPS

Parameters

OAUTH2\_NUM\_APPS

integer

Number of OAuth2 apps.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=MULTIPLE_ADD_TO_BLOCKED_OAUTH2_APPS
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

`{OAUTH2_NUM_APPS}` apps added to Blocked list for `{ORG_UNIT_NAME}`

## Apps added to Limited list

### Event details

#### Event name

`MULTIPLE_ADD_TO_LIMITED_OAUTH2_APPS`

#### Parameters

`OAUTH2_NUM_APPS`

`integer`

Number of OAuth2 apps.

`ORG_UNIT_NAME`

`string`

The organizational unit (OU) name (path).

### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=MULTIPLE_ADD_TO_LIMITED_OAUTH2_APPS
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

### Admin Console message format

`{OAUTH2_NUM_APPS}` apps added to Limited list for `{ORG_UNIT_NAME}`

## Apps added to Trusted list

### Event details

Event name

MULTIPLE\_ADD\_TO\_TRUSTED\_OAUTH2\_APPS

Parameters

OAUTH2\_NUM\_APPS

integer

Number of OAuth2 apps.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=MULTIPLE_ADD_TO_TRUSTED_OAUTH2_APPS
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

*{OAUTH2\_NUM\_APPS}* apps added to Trusted list for *{ORG\_UNIT\_NAME}*

## Apps lists bulk upload

Event details

Event name

OAUTH\_APPS\_BULK\_UPLOAD

Parameters

BULK\_UPLOAD\_SUCCESS\_OAUTH\_APPS\_NUMBER

string

Bulk upload successful oauth app number.

**BULK\_UPLOAD\_TOTAL\_OAUTH\_APPS\_NUMBER**

string

Bulk upload total oauth app number.

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=OAUTH_APPS_BULK_UPLOAD&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

*{BULK\_UPLOAD\_SUCCESS\_OAUTH\_APPS\_NUMBER}* of  
*{BULK\_UPLOAD\_TOTAL\_OAUTH\_APPS\_NUMBER}* rows successfully uploaded

## Apps lists bulk upload notification

Event details

Event name

**OAUTH\_APPS\_BULK\_UPLOAD\_NOTIFICATION\_SENT**

Parameters

**USER\_EMAIL**

string

The user's primary email address.

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=OAUTH_APPS_BULK_UPLOAD_NOTIFICATION_SENT
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

Notification of bulk upload for apps list sent to *{USER\_EMAIL}*

## Block On Device Access

Summary message to display in the audit log when device access for OAuth2 apps is blocked.

Event details

Event name

BLOCK\_ON\_DEVICE\_ACCESS

Parameters

OAUTH2\_SERVICE\_NAME

string

OAuth2 service name. Possible values:

- APPS\_SCRIPT  
Apps Script Service name.
- APPS\_SCRIPT\_RUNTIME
- CALENDAR
- CLASSROOM  
Classroom service.
- CLOUD\_BILLING
- CLOUD\_MACHINE\_LEARNING
- CLOUD\_PLATFORM
- CLOUD\_SEARCH  
Cloud search service.
- CONTACTS
- DRIVE



- DRIVE\_HIGH\_RISK
- GMAIL
- GMAIL\_HIGH\_RISK
- GROUPS  
Groups service.
- GSUITE\_ADMIN
- TASKS  
Tasks service.
- VAULT

ORG\_UNIT\_NAME  
string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=BLOCK_ON_DEVICE_ACCESS&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

Block on device {OAUTH2\_SERVICE\_NAME} access for {ORG\_UNIT\_NAME}

Change 2-Step Verification Enrollment Period Duration

Event details

Event name

CHANGE\_TWO\_STEP\_VERIFICATION\_ENROLLMENT\_PERIOD\_DURATION

Parameters

GROUP\_EMAIL

string

The group's primary email address.

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?
eventName=CHANGE_TWO_STEP_VERIFICATION_ENROLLMENT_PERIOD_DURATION
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

2-step verification enrollment period duration for {ORG\_UNIT\_NAME}  
changed from {OLD\_VALUE} to {NEW\_VALUE}

Change 2-Step Verification Frequency

Event details

Event name

CHANGE\_TWO\_STEP\_VERIFICATION\_FREQUENCY

Parameters

GROUP\_EMAIL

string

The group's primary email address.

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=CHANGE_TWO_STEP_VERIFICATION_FREQUENCY
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

2-step verification frequency for {ORG\_UNIT\_NAME} changed from  
{OLD\_VALUE} to {NEW\_VALUE}

Change 2-Step Verification Grace Period Duration

Event details

Event name

CHANGE\_TWO\_STEP\_VERIFICATION\_GRACE\_PERIOD\_DURATION

Parameters

GROUP\_EMAIL

string

The group's primary email address.

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?
eventName=CHANGE_TWO_STEP_VERIFICATION_GRACE_PERIOD_DURATION
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

2-step verification grace period duration for {ORG\_UNIT\_NAME} changed  
from {OLD\_VALUE} to {NEW\_VALUE}

Change 2-Step Verification Start Date

Event details

Event name
CHANGE_TWO_STEP_VERIFICATION_START_DATE
Parameters
GROUP_EMAIL
string
The group's primary email address.
NEW_VALUE
string
The new SETTING_NAME value that was set during this event.
OLD_VALUE
string
The previous SETTING_NAME value that was replaced during this event.
ORG_UNIT_NAME
string
The organizational unit (OU) name (path).
Sample request
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all /applications/admin?eventName=CHANGE_TWO_STEP_VERIFICATION_START_DATE &maxResults=10&access_token=YOUR_ACCESS_TOKEN
Admin Console message format
2-step verification start date has been changed from {OLD_VALUE} to {NEW_VALUE}

## Change Allowed 2-step Verification Methods

## Event details

### Event name

CHANGE\_ALLOWED\_TWO\_STEP\_VERIFICATION\_METHODS

### Parameters

#### ALLOWED\_TWO\_STEP\_VERIFICATION\_METHOD

string

Allowed two-step verification method. Possible values:

- ANY  
A label that targets any distribution.
- ONLY\_SECURITY\_KEY

#### GROUP\_EMAIL

string

The group's primary email address.

#### ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

## Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?  
eventName=CHANGE_ALLOWED_TWO_STEP_VERIFICATION_METHODS&maxResults=10  
&access_token=YOUR_ACCESS_TOKEN
```

## Admin Console message format

2-step verification allowed 2-step verification methods for  
{ORG\_UNIT\_NAME} changed to {ALLOWED\_TWO\_STEP\_VERIFICATION\_METHOD}

## Context Aware Access Enablement

Event details
Event name
TOGGLE_CAA_ENABLEMENT
Parameters
NEW_VALUE string
The new SETTING_NAME value that was set during this event.
Sample request
<pre>GET https://admin.googleapis.com/admin/reports/v1/activity/users/all /applications/admin?eventName=TOGGLE_CAA_ENABLEMENT&amp;maxResults=10 &amp;access_token=YOUR_ACCESS_TOKEN</pre>
Admin Console message format
Context Aware Access has been {NEW_VALUE}.

## Context Aware Access Error Message Change

Event details
Event name
CHANGE_CAA_ERROR_MESSAGE
Parameters
NEW_VALUE string
The new SETTING_NAME value that was set during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=CHANGE_CAA_ERROR_MESSAGE&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

Error message has been changed to [ {NEW\_VALUE} ]. (OrgUnit Name:  
{ORG\_UNIT\_NAME})

## Domain Owned Apps not trusted

Event details

Event name

UNTRUST\_DOMAIN\_OWNED\_OAUTH2\_APPS

Parameters

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=UNTRUST_DOMAIN_OWNED_OAUTH2_APPS
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```



Admin Console message format

Domain Owned Apps removed from trusted list

## Domain Owned Apps trusted

### Event details

Event name

TRUST\_DOMAIN\_OWNED\_OAUTH2\_APPS

Parameters

ORG\_UNIT\_NAME  
string

The organizational unit (OU) name (path).

Sample request

GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=TRUST\_DOMAIN\_OWNED\_OAUTH2\_APPS  
&maxResults=10&access\_token=YOUR\_ACCESS\_TOKEN

Admin Console message format

Domain Owned Apps added to trusted list

## Enable Non-Admin User Password Recovery

### Event details

Event name

ENABLE\_NON\_ADMIN\_USER\_PASSWORD\_RECOVERY

Parameters

GROUP\_EMAIL

string

The group's primary email address.

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=ENABLE_NON_ADMIN_USER_PASSWORD_RECOVERY
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

Enable non-admin user password recovery setting in {ORG\_UNIT\_NAME}  
organization changed from {OLD\_VALUE} to {NEW\_VALUE}

Enforce 2-Step Verification

Event details

Event name

ENFORCE\_STRONG\_AUTHENTICATION

Parameters

DOMAIN\_NAME

string

The primary domain name.

GROUP\_EMAIL

string

The group's primary email address.

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

SETTING\_NAME

string

The unique name (ID) of the setting that was changed.

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=ENFORCE_STRONG_AUTHENTICATION
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

`{SETTING_NAME}` in security settings for your organization changed from `{OLD_VALUE}` to `{NEW_VALUE}`

Error message for restricted OAuth2 apps updated

Summary message to display in the audit log for OAuth2 scope management settings.

Event details

Event name

UPDATE\_ERROR\_MSG\_FOR\_RESTRICTED\_OAUTH2\_APPS

Parameters

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?  
eventName=UPDATE\_ERROR\_MSG\_FOR\_RESTRICTED\_OAUTH2\_APPS&maxResults=10  
&access\_token=YOUR\_ACCESS\_TOKEN

Admin Console message format

Error message for restricted OAuth2 apps for your organization updated  
from **{OLD\_VALUE}** to **{NEW\_VALUE}**

Less Secure Apps Access setting changed

Event details

Event name

WEAK\_PROGRAMMATIC\_LOGIN\_SETTINGS\_CHANGED

Parameters

GROUP\_EMAIL

string

The group's primary email address.

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

Sample request

GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=WEAK\_PROGRAMMATIC\_LOGIN\_SETTINGS\_CHANGED

```
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

```
Setting changed for {ORG_UNIT_NAME} organization unit from {OLD_VALUE}
to {NEW_VALUE}
```

## Session Control Settings Change

Event name for change in session control settings.

Event details
Event name
SESSION_CONTROL_SETTINGS_CHANGE
Parameters
ORG_UNIT_NAME
string
The organizational unit (OU) name (path).
REAUTH_APPLICATION
string
Application for with reauthentication settings apply. Possible values:
<ul style="list-style-type: none"><li>ADMIN_CONSOLE Google admin console.</li><li>CLOUD_ADMIN_TOOLS Google cloud admin tools.</li></ul>
REAUTH_SETTING_NEW
string
Old Session control settings. Possible values:

- **INHERIT**  
Message to represent setting that inherits from its parent org unit.
- **NEVER**  
Message to represent setting that never does reauthentication.

---

#### REAUTH\_SETTING\_OLD

string

Old Session control settings. Possible values:

- **INHERIT**  
Message to represent setting that inherits from its parent org unit.
- **NEVER**  
Message to represent setting that never does reauthentication.

#### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all  
/applications/admin?eventName=SESSION_CONTROL_SETTINGS_CHANGE  
&maxResults=10&access_token=YOUR_ACCESS_TOKEN
```

#### Admin Console message format

```
Session Control Settings updated for {REAUTH_APPLICATION} from  
{REAUTH_SETTING_OLD} to {REAUTH_SETTING_NEW}. (OrgUnit Name:  
{ORG_UNIT_NAME})
```

## Session length changed

#### Event details

Event name

CHANGE\_SESSION\_LENGTH

Parameters

NEW\_VALUE

string

The new SETTING\_NAME value that was set during this event.

OLD\_VALUE

string

The previous SETTING\_NAME value that was replaced during this event.

Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=CHANGE_SESSION_LENGTH&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

Admin Console message format

Session length has been changed from {OLD\_VALUE} to {NEW\_VALUE}

## Unblock on Device Access

Summary message to display in the audit log when device access for OAuth2 apps is unblocked.

Event details

Event name

UNBLOCK\_ON\_DEVICE\_ACCESS

Parameters

OAuth2\_SERVICE\_NAME

string

OAuth2 service name. Possible values:

- APPS\_SCRIPT  
Apps Script Service name.



- APPS\_SCRIPT\_RUNTIME
- CALENDAR
- CLASSROOM  
Classroom service.
- CLOUD\_BILLING
- CLOUD\_MACHINE\_LEARNING
- CLOUD\_PLATFORM
- CLOUD\_SEARCH  
Cloud search service.
- CONTACTS
- DRIVE
- DRIVE\_HIGH\_RISK
- GMAIL
- GMAIL\_HIGH\_RISK
- GROUPS  
Groups service.
- GSUITE\_ADMIN
- TASKS  
Tasks service.
- VAULT

---

#### ORG\_UNIT\_NAME

string

The organizational unit (OU) name (path).

#### Sample request

```
GET https://admin.googleapis.com/admin/reports/v1/activity/users/all
/applications/admin?eventName=UNBLOCK_ON_DEVICE_ACCESS&maxResults=10
&access_token=YOUR_ACCESS_TOKEN
```

#### Admin Console message format

Unblock on device `{OAUTH2_SERVICE_NAME}` access for `{ORG_UNIT_NAME}`

[Send feedback](#)

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see the [Google Developers Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated 2024-08-21 UTC.

Blog

X (Twitter)

Code Samples

Codelabs

Videos

Google Workspace for  
Developers  
Platform overview  
Developer products  
Developer support  
Terms of Service

Tools  
Admin console  
Apps Script Dashboard  
Google Cloud console  
APIs Explorer

Connect  
Blog  
Newsletter  
X (Twitter)  
YouTube

Android  
Chrome  
Firebase

Google Cloud Platform

Google AI

All products

---

[Terms](#) | [Privacy](#)

Sign up for the Google for Developers newsletter

Subscribe

