



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking “Manage Cookies” at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies

Microsoft Ignite

Nov 19–22, 2024

Register now >



Learn

Discover

Product documentation

Development languages

Topics



Sign in

Windows Server

Get started

Failover clustering

Management

Identity and access

Networking

Troubleshooting

Related products



Filter by title

repair boot

replace

rexc

risetup

rmdir

robocopy

route ws2008

rpcinfo

rpcping

rsh

rundll32

rundll32 printui

rwinsta

sc config

sc create

sc delete

sc query

> schtasks

> scwcmd

> secdit

serverceipoptin

servermanagercmd

serverweroptin

Services for Network File System (NFS)

command reference

set environmental variables

setlocal

setx

sfc

shadow

shift

showmount

shutdown

simulate restore

sort

Learn / Windows Server /



replace

Article • 02/03/2023 • 8 contributors •

Applies ☒ Windows Server 2025, ☒ Windows Server 2022, ☒ Windows Server 2019, ☒ Windows Server 2016, ☒ Windows 11, ☒ Windows 10, ☒ Azure Stack HCI, versions 23H2 and 22H2

Feedback

In this article

Syntax

Examples

Related links

Replace existing files in a directory. If used with the `/a` option, this command adds new files to a directory instead of replacing existing files.

Syntax



Copy

```
replace [<drive1>:][<path1><filename> [<drive2>:][<path2>] [/a] [/p] [/r] [/w]
replace [<drive1>:][<path1><filename> [<drive2>:][<path2>] [/p] [/r] [/s] [/w]
```

Parameters



Expand table


Parameter	Description
<code>[<drive1>:]</code> <code>[<path1>]</code> <code><filename></code>	Specifies the location and name of the source file or set of files. The <i>filename</i> option is required, and can include wildcard characters (* and ?).
<code>[<drive2>:]</code> <code>[<path2>]</code>	Specifies the location of the destination file. You can't specify a file name for files you replace. If you don't specify a drive or path, this command uses the current drive and directory as the destination.
<code>/a</code>	Adds new files to the destination directory instead of replacing existing files. You can't use this command-line option with the <code>/s</code> or <code>/u</code> command-line option.
<code>/p</code>	Prompts you for confirmation before replacing a destination file or adding a source file.

 Download PDF

/r	Replaces Read-only and unprotected files. If you attempt to replace a Read-only file, but you don't specify <i>/r</i> , an error results and stops the replacement operation.
/w	Waits for you to insert a disk before the search for source files begins. If you don't specify <i>/w</i> , this command begins replacing or adding files immediately after you press ENTER.
/s	Searches all subdirectories in the destination directory and replaces matching files. You can't use <i>/s</i> with the <i>/a</i> command-line option. The command doesn't search subdirectories that are specified in <i>Path1</i> .
/u	Replaces only those files on the destination directory that are older than those in the source directory. You can't use <i>/u</i> with the <i>/a</i> command-line option.
/?	Displays help at the command prompt.

Remarks

- As this command adds or replaces files, the file names appear on the screen. After this command is done, a summary line is displayed in one of the following formats:

 Copy

```
nnn files added
nnn files replaced
no file added
no file replaced
```

- If you're using floppy disks and you need to switch disks while running this command, you can specify the */w* command-line option so that this command waits for you to switch the disks.
- You can't use this command to update hidden files or system files.
- The following table shows each exit code and a brief description of its meaning:

 Expand table

Exit code	Description
0	This command successfully replaced or added the files.
1	This command encountered an incorrect version of MS-DOS.
2	This command couldn't find the source files.
3	This command couldn't find the source or destination path.
5	The user doesn't have access to the files that you want to replace.
8	There is insufficient system memory to carry out the command.
11	The user used the wrong syntax on the command line.

Note

You can use the ERRORLEVEL parameter on the **if** command line in a batch program to process exit codes that are returned by this command.

Examples

To update all the versions of a file named *Phones.cli* (which appear in multiple directories on drive C:), with the latest version of the *Phones.cli* file from a floppy disk in drive A:, type:

 Copy


```
replace a:\phones.cli c:\ /s
```

Related links

- [Command-Line Syntax Key](#)

Feedback

Was this page helpful? 👍 Yes 👎 No

 English (United States)  Your Privacy Choices  Theme 

[Manage cookies](#) [Previous Versions](#) [Blog](#) [Contribute](#) [Privacy](#) [Terms of Use](#) [Trademarks](#) [© Microsoft 2024](#)