

T1012 - Query Registry

Indicator of Activity (IOA):

- Network:
 - Methods:
 - BaseRegCreateKey
 - BaseRegQueryInfoKey
 - BaseRegSetValue
- Host:
 - Inbound network connection to: System over \pipe\winreg
 - Registry key modifications
 - Sysmon Event ID 12/13
 - Native windows binary to interact with registry remotely: reg.exe (look for ADD/QUERY parameters)
 - Process creation events
 - Remote Registry Service start type changed

Prevention Opportunities:

- Turn off the remote registry service and disable it.
- Modify permissions on sensitive registry keys

RPC Filter Example:

```
filter

add rule layer=um actiontype=permit

add condition field=if_uuid matchtype=equal data=338CD001-2244-31F1-AAAA-9000380010

add condition field=remote_user_token matchtype=equal data=D:(A;;KA;;;DA)

add filter

add rule layer=um actiontype=block

add condition field=if_uuid matchtype=equal data=367ABB81-9844-35F1-AD32-98F0380010

add filter

quit
```

Notes:

MSRPC-to-ATTACK/documents/MS-RRP.md at ddd4608fe8684fcf2fcf9b48c5f0b3c28097f8a3 · jsecurity101/MSRPC-to-ATTACK · GitHub - 31/10/2024 09:07 https://github.com/jsecurity101/MSRPC-to-ATTACK/blob/ddd4608fe8684fcf2fcf9b48c5f0b3c28097f8a3/documents/MS-RRP.md

- By default local administrators can start the remote registry service and interact with the registry remotely.
- If remote registry is an operational need, create a group specific to this action. Apply changes to the registry/rpc filter.

Useful Resources:

• https://car.mitre.org/analytics/CAR-2014-11-005/