


# Hypervisor Jackpotting, Part 2: eCrime Actors Increase Targeting of ESXi Servers with Ransomware














***This is Part 2 of a three-part blog series. Read [Part 1](#) and [Part 3](#).***


- CrowdStrike has observed a significant increase in eCrime actors targeting VMware ESXi hypervisors with ransomware since our February 2021 blog post on *Hypervisor Jackpotting*.
- Many of these adversaries share common tradecraft such as gaining interactive access via SSH, listing and terminating running VM processes prior to encryption, and targeting the **vmfs/volumes** datastore path to encrypt disk volumes and snapshots.
- Several defensive controls, listed later in this blog, should be implemented to mitigate the success or impact of hypervisor jackpotting.

In February 2021, CrowdStrike blogged about *Hypervisor Jackpotting*, a technique that involves targeting VMware ESXi hypervisors with ransomware to increase the scope of impact. CrowdStrike noted that two big game hunting (BGH) adversaries, **CARBON SPIDER** and **SPRITE SPIDER**, were observed utilizing this technique with their respective ransomware variants, *Darkside* and *Defray777*. Since then, CrowdStrike has observed a significant uptrend in hypervisor jackpotting by other adversaries, including **PINCHY SPIDER** and **VIKING SPIDER**. In this blog, we overview each new campaign CrowdStrike has observed targeting ESXi systems and detail defensive controls that can be

## CATEGORIES

	Cloud & Application Security	104
	Counter Adversary Operations	184
	Endpoint Security & XDR	307
	Engineering & Tech	78
	Executive Viewpoint	162
	Exposure Management	84
	From The Front Lines	190
	Identity Protection	37
	Next-Gen SIEM & Log Management	91
	Public Sector	37
	Small Business	8

## CONNECT WITH US



## ABOUT COOKIES ON THIS SITE

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts. [Cookie Notice](#)

## Accept All Cookies

## Reject All

## Cookie Settings



option to specify the target folder (e.g., `/vmfs/`), which is then recursively enumerated. Prior to encryption, the ransomware executes the commands shown in Table 2.

Command
<code>pkill -9 vmx-*</code>
<code>esxcli --formatter=csv --format-param=fields=="WorldID,Displ</code>

Table 2. *REvix* commands

In July 2021, PINCHY SPIDER began distributing *REvix v1.2a*, which added execution of VM termination functionality within a separate thread, and support for additional encryption types. In mid-July 2021, PINCHY SPIDER’s DLS infrastructure went offline, leaving in question the future of these operations.

## VIKING SPIDER and Ragnar Locker

Since June 2021, VIKING SPIDER has deployed *Ragnar Locker’s* ELF binary to ESXi systems via SSH using the native root account. VIKING SPIDER copies the binary to the `/tmp` directory and issues the commands shown in Table 3.

Command	Description
<code>uname -a</code>	Print all system information
<code>esxcli system version get</code>	Display the product identifier
<code>esxcli system hostname get</code>	Display the fully qualified domain name
<code>esxcli system account list</code>	List local user accounts
<code>esxcli --formatter=csv vm process list</code>	List the running VMs
<code>esxcli vm process kill -w &lt;WID&gt; -t soft</code>	Perform a “soft” kill (graceful shutdown) of the VM
<code>esxcli --formatter=csv vm process list</code>	List the running VMs
<code>find /vmfs/volumes/ -type f -name "*.vmdk"</code>	Search for all virtual machine disks
<code>chmod a+x /tmp/&lt;FILENAME&gt;</code>	Add execute permissions to the binary
<code>/tmp/&lt;FILENAME&gt; /vmfs/volumes/&lt;UUID&gt;/</code>	Execute Ragnar Locker on the VM
<code>ps   grep &lt;FILENAME&gt;</code>	Ensure Ragnar Locker is running

## ABOUT COOKIES ON THIS SITE

By clicking “Accept All Cookies”, you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts. [Cookie Notice](#)



# How to Protect Your Cluster

Listed below are CrowdStrike’s top five recommendations that organizations should implement to mitigate the success or impact of hypervisor jackpotting.

- **Avoid direct access to ESXi hosts.** Use the vSphere Client to administer ESXi hosts that are managed by a vCenter Server. Do not access managed hosts directly with the VMware Host Client, and do not change managed hosts from the Direct Console User Interface (DCUI). (***Note:** This is a VMware-specific recommendation.*)
- **If direct access to an ESXi host is necessary, use a hardened jump server with multifactor authentication.** ESXi DCUI access should be limited to a jump server used for only administrative or privileged purposes with full auditing capabilities and multifactor authentication (MFA) enabled.
- **Ensure vCenter is not exposed to the internet over SSH or HTTP.** CrowdStrike has observed adversaries gaining initial access to vCenter using valid accounts or exploiting remote code execution (RCE) vulnerabilities (e.g., CVE-2021-21985). Although these vulnerabilities have been addressed by VMware, these services should not be exposed to the internet to mitigate risk.
- **Ensure ESXi datastore volumes are regularly backed up.** Specifically, virtual machine disk images and snapshots should be backed up daily (more frequently if possible) to an offsite storage provider.
- **If encryption activity is observed, do not shut down the ESXi hosts.** If encryption activity is observed, system administrators may be tempted to reboot or shutdown VMs. Be aware that [ransomware](#) is not able to modify locked files, and if a VM is still powered on, it will be considered locked. As a result, shutting down or rebooting VMs will actually release the lock and allow the ransomware to encrypt the virtual disk files.

Additional ESXi security recommendations are available from [VMware](#) at <https://docs.vmware.com/en/VMware-vSphere/7.0/com.vmware.vsphere.security.doc/GUID-B39474AF-6778-499A-B8AB-E973BE6D4899.html>.


## Conclusion

CrowdStrike has observed a significant uptrend in eCrime campaigns targeting VMware ESXi hypervisors with ransomware to maximize encryption impact across a victim environment. This targeting modus operandi is becoming prevalent, with adversaries developing and deploying ESXi ransomware variants, and in some cases seeking partnership opportunities with other

## ABOUT COOKIES ON THIS SITE

By clicking “Accept All Cookies”, you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts. [Cookie Notice](#)

- To find out how to incorporate intelligence on threat actors into your security strategy, visit the [CROWDSTRIKE FALCON® INTELLIGENCE™ Threat Intelligence page](#).
- Learn about the powerful, cloud-native [CrowdStrike Falcon® platform](#) by visiting the [product webpage](#).
- [Get a full-featured free trial of CrowdStrike Falcon® Prevent™](#) to see for yourself how true next-gen AV performs against today's most sophisticated threats.

 Tweet

 Share




BREACHES **STOP** HERE


START FREE TRIAL

PROTECT AGAINST MALWARE, RANSOMWARE AND FILELESS ATTACKS


Related Content



### CrowdStrike Named a Leader with “Bold Vision” in 2024 Forrester Wave for Cybersecurity Incident Response Services



### How to Defend Employees and Data as Social Engineering Evolves



### The Anatomy of an ALPHA SPIDER Ransomware Attack

## ABOUT COOKIES ON THIS SITE

By clicking “Accept All Cookies”, you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts. [Cookie Notice](#)