

This document is for an insecure version of Django that is no longer supported. Please upgrade to a newer release!

SuspiciousOperation ¶

exception **SuspiciousOperation**[\[source\]](#) ¶

The **SuspiciousOperation** exception is raised when a user has performed an operation that should be considered suspicious from a security perspective, such as tampering with a session cookie. Subclasses of **SuspiciousOperation** include:

- **DisallowedHost**
- **DisallowedModelAdminLookup**
- **DisallowedModelAdminToField**
- **DisallowedRedirect**
- **InvalidSessionKey**
- **RequestDataTooBig**
- **SuspiciousFileOperation**
- **SuspiciousMultipartForm**
- **SuspiciousSession**
- **TooManyFieldsSent**

If a **SuspiciousOperation** exception reaches the WSGI handler level it is logged at the **Error** level and results in a **HttpResponseBadRequest**. See the [logging documentation](#) for more information.

PermissionDenied ¶

exception **PermissionDenied**[\[source\]](#) ¶

The **PermissionDenied** exception is raised when a user does not have permission to perform the action requested.

ViewDoesNotExist ¶

exception **ViewDoesNotExist**[\[source\]](#) ¶

The **ViewDoesNotExist** exception is raised by **django.urls** when a requested view does not exist.

MiddlewareNotUsed ¶

exception **MiddlewareNotUsed**[\[source\]](#) ¶

The **MiddlewareNotUsed** exception is raised when a middleware is not used in the server configuration.

ImproperlyConfigured ¶

exception **ImproperlyConfigured**[\[source\]](#) ¶

The **ImproperlyConfigured** exception is raised when Django is somehow improperly configured – for example, if a value in **settings.py** is incorrect or unparseable.

FieldError ¶

exception **FieldError**[\[source\]](#) ¶

- [Table of contents](#)
- [General Index](#)
- [Python Module Index](#)

You are here:

- [Django 1.11 documentation](#)
 - [API Reference](#)
 - Django Exceptions

Getting help

FAQ

Try the FAQ — it's got answers to many common questions.

[Index](#), [Module Index](#), or [Table of Contents](#)
Handy when looking for specific information.

django-users mailing list

Search for information in the archives of the django-users mailing list, or post a question.

#django IRC channel

Ask a question in the #django IRC channel, or search the IRC logs to see if it's been asked before.

Django Discord Server

Join the Django Discord Community.

Official Django Forum

Join the community on the Django Forum.

Ticket tracker

Report bugs with Django or Django documentation in our ticket tracker.

Download:

Offline (Django 1.11): [HTML](#) | [PDF](#) | [ePub](#)
Provided by [Read the Docs](#).

Getting Help

Language: **en**

Documentation version: **1.11**



This document is for an insecure version of Django that is no longer supported. Please upgrade to a newer release!

- A field in a model clashes with a field of the same name from an abstract base class
- An infinite loop is caused by ordering
- A keyword cannot be parsed from the filter parameters
- A field cannot be determined from a keyword in the query parameters
- A join is not permitted on the specified field
- A field name is invalid
- A query contains invalid order_by arguments

ValidationError ¶

exception **ValidationError**[\[source\]](#) ¶

The **ValidationError** exception is raised when data fails form or model field validation. For more information about validation, see [Form and Field Validation](#), [Model Field Validation](#) and the [Validator Reference](#).

NON_FIELD_ERRORS ¶

NON_FIELD_ERRORS ¶

ValidationErrors that don't belong to a particular field in a form or model are classified as **NON_FIELD_ERRORS**. This constant is used as a key in dictionaries that otherwise map fields to their respective list of errors.

URL Resolver exceptions ¶

URL Resolver exceptions are defined in **django.urls**.

Deprecated since version 1.10:

In older versions, these exceptions are located in **django.core.urlresolvers**. Importing from the old location will continue to work until Django 2.0.

Resolver404 ¶

exception **Resolver404**[\[source\]](#) ¶

The **Resolver404** exception is raised by **resolve()** if the path passed to **resolve()** doesn't map to a view. It's a subclass of **django.http.Http404**.

NoReverseMatch ¶

exception **NoReverseMatch**[\[source\]](#) ¶

The **NoReverseMatch** exception is raised by **django.urls** when a matching URL in your URLconf cannot be identified based on the parameters supplied.

Database Exceptions ¶

Database exceptions may be imported from **django.db**.

Django wraps the standard database exceptions so that your Django code has a guaranteed common implementation of these classes.

exception **Error**[\[source\]](#) ¶

Getting Help

Language: en

Documentation version: 1.11



This document is for an insecure version of Django that is no longer supported. Please upgrade to a newer release!

exception **DatabaseError**[\[source\]](#) 

exception **DataError**[\[source\]](#) 

exception **OperationalError**[\[source\]](#) 

exception **IntegrityError**[\[source\]](#) 

exception **InternalError**[\[source\]](#) 

exception **ProgrammingError**[\[source\]](#) 

exception **NotSupportedError**[\[source\]](#) 

The Django wrappers for database exceptions behave exactly the same as the underlying database exceptions. See [PEP 249](#), the Python Database API Specification v2.0, for further information.

As per [PEP 3134](#), a `__cause__` attribute is set with the original (underlying) database exception, allowing access to any additional information provided. (Note that this attribute is available under both Python 2 and Python 3, although [PEP 3134](#) normally only applies to Python 3. To avoid unexpected differences with Python 3, Django will also ensure that the exception made available via `__cause__` has a usable `__traceback__` attribute.)

Changed in Django 1.10:

The `__traceback__` attribute described above was added.

exception **models.ProtectedError** 

Raised to prevent deletion of referenced objects when using `django.db.models.PROTECT`. **models.ProtectedError** is a subclass of [IntegrityError](#).

Http Exceptions

Http exceptions may be imported from **django.http**.

UnreadablePostError

exception **UnreadablePostError**[\[source\]](#) 

UnreadablePostError is raised when a user cancels an upload.

Transaction Exceptions

Transaction exceptions are defined in **django.db.transaction**.

TransactionManagementError

exception **TransactionManagementError**[\[source\]](#) 

TransactionManagementError is raised for any and all problems related to database transactions.

Testing Framework Exceptions

Exceptions provided by the **django.test** package.

RedirectCycleError

Getting Help

Language: **en**

Documentation version: **1.11**



This document is for an insecure version of Django that is no longer supported. Please upgrade to a newer release!

RedirectCycleError is raised when the test client detects a loop or an overly long chain of redirects.

Python Exceptions ¶

Django raises built-in Python exceptions when appropriate as well. See the Python documentation for further information on the Built-in Exceptions.

◀ `django-admin` and `manage.py`

`File handling` ▶

Learn More

- About Django
- Getting Started with Django
- Team Organization
- Django Software Foundation
- Code of Conduct
- Diversity Statement

Get Involved

- Join a Group
- Contribute to Django
- Submit a Bug
- Report a Security Issue

Get Help

- Getting Help FAQ
- #django IRC channel
- Django Discord
- Official Django Forum

Follow Us

- GitHub
- Twitter
- Fediverse (Mastodon)
- News RSS
- Django Users Mailing List

Support Us

- Sponsor Django
- Corporate membership
- Official merchandise store
- Benevity Workplace Giving Program



Hosting by
In-kind donors

Design by
threespot. & andrevv

© 2005-2024 [Django Software Foundation](#) and individual contributors. Django is a [registered trademark](#) of the Django Software Foundation.

Getting Help

Language: en

Documentation version: 1.11

