

.. /Ttdinject.exe

Execute

Used by Windows 1809 and newer to Debug Time Travel (Underlying call of tttracer.exe)

Paths:

C:\Windows\System32\ttdinject.exe
C:\Windows\Syswow64\ttdinject.exe

Resources:

- <https://twitter.com/Oddvarmoe/status/1196333160470138880>

Acknowledgements:

- Oddvar Moe ([@oddvarmoe](#))
- Maxime Nadeau ([@m_nad0](#))

Detections:

- Sigma:
https://github.com/SigmaHQ/sigma/blob/683b63f8184b93c9564c4310d10c571cbe367e1e/rules/windows/create_remote_thread/create_remote_thread_win_ttdinjec.yml
- Sigma:
https://github.com/SigmaHQ/sigma/blob/7ea6ed3db65e0bd812b051d9bb4ffd27c4c4d0a/rules/windows/process_creation/proc_creation_win_lolbin_ttdinject.yml
- IOC: Parent child relationship. Ttdinject.exe parent for executed command
- IOC: Multiple queries made to the IFEO registry key of an untrusted executable (Ex. "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\payload.exe") from the ttdinject.exe process

Execute

. Execute calc using ttdinject.exe. Requires administrator privileges. A log file will be created in tmp.run. The log file can be changed, but the length (7) has to be updated.

```
TTDInject.exe /ClientParams "7 tmp.run 0 0 0 0 0 0 0 0 0" /Launch "C:/Windows/System32/calc.exe"
```

Use case: Spawn process using other binary
Privileges required: Administrator
Operating systems: Windows 10 2004 and above, Windows 11
ATT&CK® technique: T1127

. Execute calc using ttdinject.exe. Requires administrator privileges. A log file will be created in tmp.run. The log file can be changed, but the length (7) has to be updated.

```
ttdinject.exe /ClientScenario TTDRecorder /ddload 0 /ClientParams "7 tmp.run 0 0 0 0 0 0 0 0 0" /launch  
"C:/Windows/System32/calc.exe"
```

Use case: Spawn process using other binary
Privileges required: Administrator
Operating systems: Windows 10 1909 and below
ATT&CK® technique: T1127