

Product

Solutions

Resources

Open Source

Enterprise

Pricing

Sign in

Sign up

trustedsec / SysmonCommunityGuide

Public

Notifications

Fork

164

Star

1.1k

<> Code

Issues

5

Pull requests

2

Actions

Projects

Security

Insights

Files

adcdfee

Go to file

> Build

> chapters

> media

Sysmon.md

WMI-events.md

clipboard-capture.md

configuration.md

cover.png

create-remote-thread.md

dns-query.md

driver-loading.md

eBPF.md

file-block-exe.md

file-create-time-change.md

file-create.md

file-delete.md

file-stream-creation-hash.md

file_delete_detected.md

image-loading.md

install_linux.md

install_windows.md

metadata.yml

named-pipes.md

network-connections.md

operational-events.md

pandoc.css

process-access.md

process-creation.md

process-events.md

process-tampering.md

process-termination.md

raw-access-read.md

registry-actions.md

sysmon-changelog.md

sysmon-events.md

the-sysmon-driver.md

SysmonCommunityGuide / chapters / file-stream-creation-hash.md

darkoperator

Start update for Sysmon for Linux

523f529 · 3 years ago

History

PreviewCodeBlame

94 lines (61 loc) · 3.76 KB

RawCopyDownload

File Stream Creation Hash

Sysmon will log **EventID 15** for the creation of Alternate Data Streams (ADS). This is an old technique where many vendors already monitor for the creation of ADS on files where the alternate stream is a PE executable. Attackers have changed to use alternate streams to hide information and to store other payloads that are not PE executables (DLL, Scripts). Sysmon will also capture the contents of text streams if they are less 1KB for the purpose of capturing Mark Of The Web (MOTW) streams.

Each record in NTFS on a drive is subdivided into a list of variable length attributes:

- \$STANDARD_INFORMATION
- \$FILE_NAME
- \$DATA
- \$INDEX_ROOT
- \$BITMAP
- \$INDEX_ALLOCATION
- \$ATTRIBUTE_LIST

Alternate Data Streams (ADS) are implemented by having multiple \$Data attributes

- The Default data stream is unnamed
- Alternate streams are named ones.

Since streams that are part of the NTFS structure directories may have an AD, we can use PowerShell to look at a file with the single default unamend :\$DATA stream:

```
PS C:\Users\administrator\Downloads> Get-Item .\Sysmon.zip -Stream * -Force
```

```
PSPath      : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads\Sysmon.zip::$DATA
PSParentPath : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads
PSChildName  : Sysmon.zip::$DATA
PSDrive      : C
PSProvider   : Microsoft.PowerShell.Core\FileSystem
PSIsContainer : False
FileName     : C:\Users\administrator\Downloads\Sysmon.zip
Stream       : :$DATA
Length       : 1733083
```

File with a second named stream:

Page 1 of 3

- what-is-sysmon.md
- examples
- .gitignore
- README.md

```
PS C:\Users\administrator\Downloads> Get-Item .\Sysmon.zip -Stream * -Force

PSPath      : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads\Sysmon.zip::$DATA
PSParentPath : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads
PSChildName  : Sysmon.zip::$DATA
PSDrive      : C
PSProvider   : Microsoft.PowerShell.Core\FileSystem
PSIsContainer : False
FileName     : C:\Users\administrator\Downloads\Sysmon.zip
Stream       : :$DATA
Length       : 1733083

PSPath      : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads\Sysmon.zip:secret
PSParentPath : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads
PSChildName  : Sysmon.zip:secret
PSDrive      : C
PSProvider   : Microsoft.PowerShell.Core\FileSystem
PSIsContainer : False
FileName     : C:\Users\administrator\Downloads\Sysmon.zip
Stream       : secret
Length       : 24
```

Some execution examples:

- Execution Rundll32 example
- Cscript Example
- PowerShell Example

More execution examples at <https://gist.github.com/api0cradle/cdd2d0d0ec9abb686f0e89306e277b8f> by Oddvar Moe

In the case of downloads performed by browsers and email clients in Windows that leverage the urlmon.dll for downloading files they have an identifying stream added with information about the download including the URL and Refferer. This information can be used to track the origing of downloaded files by attackers with a console presense or via a phishing attack.

We can use PowerShell Get-Item and Get-Content cmdlets to check if a Zone.Identifier stream exist and show its content.

```
PS C:\Users\administrator\Downloads> Get-Item -Stream Zone.Identifier .\SysinternalsSuite.zip


PSPath      : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads\Sysintern
alsSuite.zip:Zone.Identifier
PSParentPath : Microsoft.PowerShell.Core\FileSystem::C:\Users\administrator\Downloads
PSChildName  : SysinternalsSuite.zip:Zone.Identifier
PSDrive      : C
PSProvider   : Microsoft.PowerShell.Core\FileSystem
PSIsContainer : False
FileName     : C:\Users\administrator\Downloads\SysinternalsSuite.zip
Stream       : Zone.Identifier
Length       : 167

PS C:\Users\administrator\Downloads> Get-Content -Stream Zone.Identifier .\SysinternalsSuite.zip
[ZoneTransfer]
ZoneId=3
ReferrerUrl=https://docs.microsoft.com/en-us/sysinternals/downloads/
HostUrl=https://download.sysinternals.com/files/SysinternalsSuite.zip
```

The fields for the event:

- RuleName:** Name of rule that triggered the event
- UtcTime:** Time in UTC when event was created
- ProcessGuid:** Process GUID of the process that created the named file stream
- ProcessId:** Process ID used by the OS to identify the process that created the named file stream
- Image:** File path of the process that created the named file stream
- TargetFilename:** Name of the file
- CreationUtcTime:** File download time
- Hash:** Full hash of the file with the algorithms in the HashType field
- Content:** Contents of text streams.

The number of processes that create alternate streams should be low and easily excluded. Mail clients and browsers are the main generators of this event in normal operation to set the Zone attribute; Because of this, a maintenance process is recommended when leveraging these filters.



Since urlmon.dll sets different parts of the stream as the file is downloaded we see normally a total of 6 events as the data is added to the file. This provides important forensic information to track files that an attacker may have delived and correlated with other networks logs.

Example: Exclude common processes that create alternate data streams.

```
<Sysmon schemaversion="4.22">
  <EventFiltering>
    <RuleGroup name="" groupRelation="or">
      <FileCreateStreamHash onmatch="exclude">
        <!--Chrome Web Browser-->
        <Image condition="is">C:\Program Files (x86)\Google\Chrome\Appli
        <!--Edge Download broker-->
        <Image condition="is">C:\Windows\system32\browser_broker.exe</Im
        <!--Internet Explorer-->
        <Image condition="is">C:\Program Files\Internet Explorer\iexplor
        <!--Outlook Client-->
        <Image condition="end with">OUTLOOK.EXE</Image>
      </FileCreateStreamHash>
    </RuleGroup>
  </EventFiltering>
</Sysmon>
```