



Center
for Threat
Informed
Defense

Summitting the Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions
Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work


Acknowledgements

Changelog

[_](#) / [Analytics Repository](#) / Scheduled Task/Job

- https://github.com/SigmaHQ/sigma/blob/c0332a9d96f6c7804fcc85dd706caed889446a62/rules/windows/process_creation/proc_creation_win_schtasks_creation.yml

```
title: Scheduled Task Creation
id: 92626ddd-662c-49e3-ac59-f6535f12d189
status: test
description: Detects the creation of scheduled tasks in u
author: Florian Roth (Nextron Systems)
date: 2019/01/16
modified: 2022/10/09
tags:
  - attack.execution
  - attack.persistence
  - attack.privilege_escalation
  - attack.t1053.005
  - attack.s0111
  - car.2013-08-001
logsource:
  category: process_creation
  product: windows
detection:
  selection:
    Image|endswith: '\schtasks.exe'
    CommandLine|contains: ' /create '
  filter:
    User|contains: # covers many language settings
    - 'AUTHORI'
    - 'AUTORI'
  condition: selection and not filter
fields:
  - CommandLine
  - ParentCommandLine
falsepositives:
  - Administrative activity
  - Software installation
level: low
```



Center
for Threat
Informed
Defense

Summitting the Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

	Application (A)	User-mode (U)	Kernel-mode (K)
Core to (Sub-) Technique (5)			
Core to Part of (Sub-) Technique (4)			
Core to Pre-Existing Tool (3)		EventID: 1 CommandLine contains: '/create'	
Core to Adversary-brought Tool (2)			
Ephemeral (1)		Image endswith: '\\schtasks.exe'	

The original analytic detects on the name of a newly-created process in combination with the commandline argument `/create`. The fields references in this analytic exist in Sysmon EventID 1 and not Windows Event ID 4688 for process creation, therefore we know the intent was to use Sysmon data. We have previously scored Sysmon Event ID 1 as operating in user-mode since it is fired when the Win32 API function CreateProcessA is called.

The schtasks executable can be easily copied and renamed by an adversary, `Image|endswith: '\\schtasks.exe'` therefore it is placed at the Ephemeral level. The commandline argument is more challenging for an



Center
for Threat
Informed
Defense

Summiting the Pyramid

v1.0.0

CONTENTS

Overview
Introduction
Definitions
Model Mapping Pages
Combining Observables
Example Mappings
How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring
Improved Analytic Scoring #1
Improved Analytic Scoring #2

Service Registry Permissions
Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

adversary to evade, since they would likely need the source code to change these arguments. However, since schtasks exists in the OS prior to system compromise and no source code is available, the commandline argument observable is placed at **Core to Pre-existing Tool**. Factoring in StP boolean logic, this analytic ultimately scores at a 1U because an adversary can simply change the Image name and avoid detection.

Note

The filter in an analytic does not affect the overall robustness score since its purpose is to remove false positives. Studying how filters affect scoring is slated for future research.

We can use existing open source research from SpecterOps to make this analytic more robust. The following capability abstraction highlights several different ways adversaries could schedule a task on a system without firing the original analytic, and our original analytic would only detect the circled implementation.

T1053 – Scheduled Tasks				
Tools	schtasks.exe	Task Scheduler (GUI)	Remote Registry	At (Deprecated in Win8) Powershell Register-ScheduledTask
COM Method	ITaskFolder::RegisterTask			ITaskFolder::RegisterTask
Win32 API	CreateFile/RegCreateKey			NetScheduleJobAdd CreateFile/RegCreateKey
Registry	HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree OR HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks			
File	C:\Windows\System32\Tasks OR C:\Windows\Tasks OR C:\Windows\SYSWOW64\Tasks			
RPC Server Code/RPC Server Application	schedsvcs.dll	regsvc.dll	taskcomp.dll	
RPC Interface	ITaskSchedulerServices (86D35949-83C9-4044-B424-DB363231FD0C)	[MS-RRP] (338CD001-2244-31F1-AAAA-900038001003)	[ATSvc] (1FF70682-0A51-30E8-076D-740BE8CEE98B)	
RPC Method	SchRpcRegisterTask, SchRpcEnumTasks	BaseRegCreateKey, BaseRegQueryInfoKey	NetJobAdd*	
Network Protocol	ITaskSchedulerServices	winreg Endpoint: lpipwinreg	atsvc Endpoint: lpipatsvc	WS-Management TCP/5985/5986/Custom Port

Scheduled Task Capability Abstraction - Created by SpecterOps¹

Conversely, defenders can use the capability abstraction to create several different analytics, the most robust of which



Center
for Threat
Informed
Defense

Summitting the Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions
Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

might detect on the invariant registry or file creation activity. As a first attempt at a more robust analytic, we can start with the file creation activity. If we create a scheduled task via the Task Scheduler GUI in a test environment with Sysmon installed, we might expect to generate an Event ID 11: FileCreate.

Level	Date and Time	Source	Event ID	Task Category
Information	6/2/2023 4:56:15 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:56:15 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:55:57 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:53:58 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:08 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:07 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:03 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:02 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:01 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:01 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:01 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:00 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:00 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:00 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:52:00 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:51:59 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:51:59 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:51:59 PM	Sysmon	11	File created (rule: FileC...
Information	6/2/2023 4:51:59 PM	Sysmon	11	File created (rule: FileC...

Event 11, Sysmon

General

Details

Image: C:\windows\system32\svchost.exe
TargetFilename: C:\Windows\System32\Tasks\test_task
CreationUtcTime: 2023-06-02 20:53:58.762

Log Name: Microsoft-Windows-Sysmon/Operational
Source: Sysmon
Event ID: 11
Level: Information

Logged: 6/2/2023 4:53:58 PM
Task Category: File created (rule: FileCreate)
Keywords:

Sysmon Event ID 11: FileCreate

Looks like the hypothesis was correct! An Event ID 11 was generated under the expected `C:\Windows\System32\Tasks` directory.

Note

It is important to note all the false positives. Unfortunately this more robust analytic generates a large amount of false positives and should be combined with other observables or fields to provide context, filter out false positives, and ensure the analytic is not completely ignored by an analyst.



Center
for Threat
Informed
Defense

Summiting the Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements


Changelog

Let's score this new analytic and see if it is more robust than the original. It's tough to tell right now where to place Event ID 11, but fortunately open-source references exist that enumerate Windows APIs and the respective Event IDs that are generated:

- Roberto Rodriguez's [API - To - Event](#)
- Jonny Johnson's [TelemetrySource](#)

These two spreadsheets indicate which Event IDs are generated by user-mode or kernel-mode APIs. An excerpt of Roberto's spreadsheet is below, showing the different APIs that generate a Sysmon Event ID 11: FileCreate.

API Call	EventID	Event Name	Log Provider
CopyFile	11	FileCreate	Microsoft-Windows-Sysmon
CopyFile2	11	FileCreate	Microsoft-Windows-Sysmon
CopyFileEx	11	FileCreate	Microsoft-Windows-Sysmon
CreateFile2	11	FileCreate	Microsoft-Windows-Sysmon
CreateFileA	11	FileCreate	Microsoft-Windows-Sysmon
CreateFileW	11	FileCreate	Microsoft-Windows-Sysmon
MoveFile	11	FileCreate	Microsoft-Windows-Sysmon
NtCreateFile	11	FileCreate	Microsoft-Windows-Sysmon



Center
for Threat
Informed
Defense

Summiting the Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

NtWriteFile	11	FileCreate	Microsoft-Windows-Sysmon
-------------	----	------------	--------------------------

All the relevant APIs are in user-mode, and since the file activity is invariant behavior across all implementations of task scheduling we can score this analytic at 5U.

	Application (A)	User-mode (U)	Kernel-mode (K)
Core to (Sub-) Technique (5)		EventID: 11 TargetFileName contains: - "C:\Windows\System32\Tasks" - "C:\Windows\SYSWOW64\Tasks"	
Core to Part of (Sub-) Technique (4)			
Core to Pre-Existing Tool (3)			
Core to Adversary-brought Tool (2)			
Ephemeral			

So far we have created an analytic using the FileCreate invariant behavior. What if we pivot and use the registry

Center
for Threat
Informed
Defense

III

III

MITRE
ENGUITY™

Summitting the
Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements


Changelog

key? Might the registry key approach score at a higher level? Sysmon EventID 12: RegistryEvent (Object create and delete) should be generated when a registry key is created. Roberto's Event ID to Windows API mapping shows us that Event ID 12 can be generated from kernel-mode APIs, so we can score this analytic as operating in kernel-mode.

API Call	Event ID	Event Name	Log Provider
RegCreateKeyA	12	RegistryEvent (Object create and delete)	Microsoft-Windows-Sysmon
RegCreateKeyEx	12	RegistryEvent (Object create and delete)	Microsoft-Windows-Sysmon
RegCreateKeyExW	12	RegistryEvent (Object create and delete)	Microsoft-Windows-Sysmon
RegCreateKeyW	12	RegistryEvent (Object create and delete)	Microsoft-Windows-Sysmon
ZwCreateKey	12	RegistryEvent (Object create and delete)	Microsoft-Windows-Sysmon

Since the registry key is invariant behavior, the analytic is placed at the Core to Subtechnique level and we can ultimately score it at 5K. It is important to ensure an adversary can't evade our analytic by editing an existing registry key value or an renaming an entire registry key/value pair, so we should also integrate Event IDs 13: (Value Set) and 14: (Key and Value Rename) into our analytic logic.

Page 7 of 9



Center
for Threat
Informed
Defense

Summiting the Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

Filtered: Log: Microsoft-Windows-Sysmon/Operational; Source: ; Event ID: 12. Number of events: 6,471				
Level	Date and Time	Source	Event ID	Task Category
Information	7/13/2023 4:59:00 PM	Sysmon	12	Registry object added ...
Information	7/13/2023 4:57:56 PM	Sysmon	12	Registry object added ...
Information	7/13/2023 4:57:56 PM	Sysmon	12	Registry object added ...
Information	7/13/2023 4:57:56 PM	Sysmon	12	Registry object added ...
Information	7/13/2023 4:57:56 PM	Sysmon	12	Registry object added ...
Information	7/13/2023 4:57:56 PM	Sysmon	12	Registry object added ...
Event 12, Sysmon				
General Details				
Registry object added or deleted: RuleName: technique_id=T1053,technique_name=Scheduled Task EventType: CreateKey UtcTime: 2023-07-13 20:59:00.793 ProcessGuid: {9fd6ec04-60cf-64b0-4100-000000003000} ProcessId: 3520 Image: C:\windows\system32\svchost.exe TargetObject: HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\test_task2 User: NT AUTHORITY\SYSTEM				

	Application (A)	User-mode (U)	Kernel-mode (K)
Core to (Sub-) Technique (5)			EventID: - 12 - 13 - 14 TargetObject contai - “HKLM\SOFTWARE NT\CurrentVersion\ - “HKLM\SOFTWARE NT\CurrentVersion\
Core to Part of (Sub-) Technique (4)			
Core to Pre- Existing Tool (3)			



**Center
for Threat
Informed
Defense**

Summiting the Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

Core to Adversary-brought Tool (2)			
Ephemeral (1)			

Note

It is also possible to implement a similar analytic by placing a SACL on the invariant registry keys and searching for Event IDs 4657 or 4663.

References

[1] <https://posts.specterops.io/abstracting-scheduled-tasks-3b6451f6a1c5>

© Copyright 2023, Center for Threat-Informed Defense.