Search Q

Active Directory Security

Active Directory & Enterprise Security, Methods to Secure Active Directory, Attack Methods & Effective Defenses, PowerShell, Tech Notes, & Geek Trivia...

Home About AD Resources Attack Defense & Detection Contact Mimikatz Presentations

Schema Versions Security Resources SPNs Top Posts

• Windows Server 2016 Technical Preview 3 Download & Release Information

DerbyCon V (2015): Red vs. Blue: Modern Active Directory Attacks & Defense Talk Detail

SEP 10 2015

Sneaky Active Directory Persistence #11: Directory Service Restore Mode

(DSRM)

By Sean Metcalf in ActiveDirectorySecurity, Microsoft Security, Security Conference Presentation/Video, Technical Reference

The content in this post describes a method by which an attacker could persist administrative access to Active Directory after having Domain Admin level rights for 5 minutes.

I presented on this AD persistence method in Las Vegas at DEF CON 23 (2015).

Complete list of Sneaky Active Directory Persistence Tricks posts

The Directory Restore Mode Account

Every Domain Controller has an internal "Break glass" local administrator account to DC called the Directory Services Restore Mode (DSRM) account. The DSRM password set when DC is promoted and is rarely changed. The primary method to change the DSRM password on a Domain Controller involves running the ntdsutil command line tool.

Beginning with hotfix KB961320 on Windows Server 2008, there is now the option to synchronize the DSRM password on a DC with a specific domain account. Note that this must be performed every time the password is changed; it does not create an automatic sync partnership.

Changing the DSRM Account Password:

Run the following command on every DC (or remotely against every DC by replacing "null" with DC name)

- NTDSUTIL
- set dsrm password
- reset password on server null
- <PASSWORD>
- Q

RECENT POSTS

BSides Dublin – The Current State of Microsoft Identity Security:
Common Security Issues and Misconfigurations – Sean Metcalf

DEFCON 2017: Transcript – Hacking the Cloud

Detecting the Elusive: Active Directory Threat Hunting

Detecting Kerberoasting Activity

Detecting Password Spraying with Security Event Auditing

TRIMARC ACTIVE DIRECTORY SECURITY SERVICES

Have concerns about your Active
Directory environment? Trimarc helps
enterprises improve their security
posture.

Find out how... TrimarcSecurity.com

POPULAR POSTS

PowerShell Encoding & Decoding (Base64)

Attack Methods for Gaining Domain Admin Rights in...

Kerberos & KRBTGT: Active Directory's...

Finding Passwords in SYSVOL & Exploiting Group...

Securing Domain Controllers to Improve Active...

Securing Windows Workstations: Developing a Secure Baseline

Detecting Kerberoasting Activity

• Q

Synchronize the DSRM Account Password with a Domain Account (2k8 & newer): In an elevated CMD prompt where you have logged on as a Domain Admin, run:

NTDSUTIL
SET DSRM PASSWORD
SYNC FROM DOMAIN ACCOUNT < your user here>
Q
Q

<u>Using DSRM to Backdoor Active Directory</u>

What's interesting about the DSRM password is that the DSRM account is actually "Administrator". This means that once an attacker has the DSRM password for a Domain Controller (or DCs), it's possible to use this account to logon to the Domain Controller over the network as a local administrator.

We can confirm this with Mimikatz by creating a new AD user with a known password. Set the DSRM acount password sync from the domain user account and compare the hashes.

DSRMTest NTLM Password Hash: 2b391dfc6690cc38547d74b8bd8a5b49 Administrator (500) Local Account NTLM Password Hash: 2b391dfc6690cc38547d74b8bd8a5b49

The second graphic shows a local Administrator account on the DC called "Administrator" with the same password hash as the DSRMTest domain user account.

```
fimikatz(commandline) # privilege::debug
Privilege '20' OK

mimikatz(commandline) # lsadump::lsa /name:DSRMTEst /inject
Domain : ADSECLAB / S-1-5-21-1387203482-2957264255-828990924

RID : 000019ff (6655)
User : DSRMTEst

# Primary
LM :
NTLM : 2b391dfc6690cc38547d74b8bd8a5b49
```

Note: The local SAM file is located here: C:\Windows\System32\config\SAM

Using DSRM Credentials

Once you know the DSRM account password (local Administrator account on the DC), there are a few tricks to how it can be used.

Logging on to a DC with the DSRM account:

- 1. Restart in Directory Services Restore Mode (bcdedit/set safeboot dsrepair)
- 2. Access DSRM without rebooting (Windows Server 2008 and newer)
 - 1. Set the registry key DsrmAdminLogonBehavior to 1

Mimikatz DCSync Usage, Exploitation, and Detection

Scanning for Active Directory Privileges &...

Microsoft LAPS Security & Active Directory LAPS...

CATEGORIES

ActiveDirectorySecurity

Apple Security

Cloud Security

Continuing Education

Entertainment

Exploit

Hacking

Hardware Security

Hypervisor Security

Linux/Unix Security

Malware

Microsoft Security

Mitigation

Network/System Security

PowerShell

RealWorld

Security

Security Conference Presentation/Video

Security Recommendation

Technical Article

Technical Reading

Technical Reference

TheCloud

Vulnerability

TAGS

Active Directory Active

Directory Active Directory Security

ActiveDirectorySecurity

ADReading AD Security ADSecurity Azure

AzureAD DCSync DomainController

GoldenTicket GroupPolicy HyperV Invoke
Mimikatz KB3011780 KDC Kerberos

KerberosHacking KRBTGT LAPS LSASS

- 2. Stop the Active Directory service
- 3. Logon using DSRM credentials on the console.
- 3. Access DSRM without rebooting (Windows Server 2008 and newer)
 - 1. Set the registry key DsrmAdminLogonBehavior to 2
 - 2. Logon using DSRM credentials on the console.

Access DSRM without Rebooting:

PowerShell New-ItemProperty "HKLM:\System\CurrentControlSet\Control\Lsa\" -Name "DsrmAdminLogonBehavior" -Value 2 -PropertyType DWORD

The registry value is located at

HKLM\System\CurrentControlSet\Control\Lsa\DSRMAdminLogonBehavior. Its possible values are:

- 0 (default): You can only use the DSRM administrator account if the DC is started in DSRM.
- 1: You can use the DSRM administrator account to log on if the local AD DS service is stopped.
- 2: You can always use the DSRM administrator account (This setting isn't recommended, because password policies don't apply to the DSRM administrator account).


The capability of DSRM account credential is explored further in the post "Sneaky Active Directory Persistence #13: DSRM Persistence v2".

Using DSRM Credentials over the network

It is possible to use the DSRM Credentials over the network.

When Windows 2000 and Active Directory were released, DSRM being limited to console logon was a good security method. Today, however, there are several methods to logon to a system "at the console":

- 1. Virtualization Client
 - 1. VMWare Remote Console (TCP 903)
 - 2. Hyper-V VM Connection (TCP 5900)
- 2. Out of Band Management (Lights Out, etc)
- 3. Network KVM
- 4. Remote Desktop Client when connecting to the "Console" which is "mstsc/console" prior to Windows Server 2008 and "mstsc/admin" with Windows Server 2008 and newer. Tested on Windows Server 2008 R2. Windows Server 2012R2 seems to refuse DSRM logon via RDP console.



MCM MicrosoftEMET
MicrosoftWindows mimikatz
MS14068 PassTheHash
PowerShell
PowerShellCode PowerShellHacking
PowerShellv5 PowerSploit Presentation
Security SilverTicket SneakyADPersistence
SPN TGS TGT Windows7 Windows10
WindowsServer2008R2
WindowsServer2012
WindowsServer2012R2

Search

BSides Dublin - The Current State of Microsoft Identity Security:
Common Security Issues and Misconfigurations - Sean Metcalf

DEFCON 2017: Transcript - Hacking the Cloud

Detecting the Elusive: Active Directory Threat Hunting

Detecting Kerberoasting Activity

Detecting Password Spraying with Security Event Auditing

Derek on Attacking Read-Only Domain Controllers (RODCs) to Own Active Directory Sean Metcalf on Securing Microsoft Active Directory Federation Server (ADFS) Brad on Securing Microsoft Active Directory Federation Server (ADFS) Joonas on Gathering AD Data with the Active Directory PowerShell Module Sean Metcalf on Gathering AD Data with the Active Directory PowerShell Module





Once logged in as the local DC's DSRM account (DC local admin), we can confirm we are on a DC and that this is the DC's local administrator account. not a domain account.

Further proof that this is not a domain account.

Detection

- Monitor event logs relating to DSRM password change and usage
 - 4794: An attempt was made to set the Directory Services Restore Mode administrator password (requires account management/user management subcategory auditing enabled in 2008 R2 and newer).
- Monitor the registry location and alert on values of 1 or 2
 - HKLM\System\CurrentControlSet\Control\Lsa\DSRMAdminLogonBehavior

References:

- http://blogs.technet.com/b/askds/archive/2009/03/11/ds-restore-mode-password-maintenance.aspx
- https://technet.microsoft.com/en-us/library/cc754363.aspx

August 2019	
March 2019	
February 2019	
October 2018	
August 2018	
May 2018	
January 2018	
November 2017	
August 2017	
June 2017	
May 2017	
February 2017	
January 2017	
November 2016	
October 2016	
September 2016	
August 2016	
July 2016	
June 2016	
April 2016	
March 2016	
February 2016	
January 2016	
December 2015	
November 2015	
October 2015	
September 2015	
August 2015	
July 2015	
June 2015	
May 2015	
April 2015	
March 2015	
February 2015	
January 2015	
December 2014	
November 2014	
October 2014	
September 2014	

- http://policelli.com/blog/archive/2009/03/25/back-to-the-basics-securing-thedirectory-services-restore-mode-account/
- http://windowsitpro.com/en/changing-password-dcs-dsrm-and-recovery-console-administrator-account
- http://windowsitpro.com/windows-server/q-how-do-i-make-directory-services-restore-mode-dsrm-administrator-password-work-my-w
- https://technet.microsoft.com/en-us/library/cc816897(v=ws.10).aspx
- http://blogs.metcorpconsulting.com/tech/?p=501

(Visited 35,149 times, 1 visits today)

ActiveDirectory, ActiveDirectoryAttack,
ActiveDirectorySecurity, ADPersistence, ADSecurity, DEFCON,
DEFCON23, DirectoryServicesRestoreMode,
DirectoryServicesRestoreModePassword, DSRM, DSRMLogon,
DSRMNetworkLogon, DSRMPassword, mimikatz,
SneakyActiveDirectoryPersistence, SneakyADPersistence,
toryAttack



Sean Metcalf

I improve security for enterprises around the world working for TrimarcSecurity.com

Read the About page (top left) for information about me.:) https://adsecurity.org/?page_id=8



August 2014	
July 2014	
June 2014	
May 2014	
April 2014	
March 2014	
February 2014	
July 2013	
November 2012	
March 2012	
February 2012	

February 2012	
CATEGORIES	
ActiveDirectorySecurity	
Apple Security	
Cloud Security	
Continuing Education	
Entertainment	
Exploit	
Hacking	
Hardware Security	
Hypervisor Security	
Linux/Unix Security	
Malware	
Microsoft Security	
Mitigation	
Network/System Security	
PowerShell	
RealWorld	
Security	
Security Conference Presentation/Vide	:O
Security Recommendation	
Technical Article	
Technical Reading	
Technical Reference	
TheCloud	

META	
Login	
Entries feed	
Comments feed	
WordPress.org	

COPYRIGHT

Content Disclaimer: This blog and its contents are provided "AS IS" with no warranties, and they confer no rights. Script samples are provided for informational purposes only and no guarantee is provided as to functionality or suitability. The views shared on this blog reflect those of the authors and do not represent the views of any companies mentioned. Content Ownership: All content posted here is intellectual work and under the current law, the poster owns the copyright © 2011 - 2020.

Content Disclaimer: This blog and its contents are provided "AS IS" with no warranties, and they confer no rights. Script samples are provided for informational purposes only and no guarantee is provided as to functionality or suitability. The views shared on this blog reflect those of the authors and do not represent the views of any companies mentioned.

Made with \heartsuit by Graphene Themes.