

The screenshot shows a mobile application interface for file management. At the top, there is a header bar with a back arrow icon on the left and the title "Files" in the center. Below the header, there is a search bar containing the text "f339e7d" and a magnifying glass icon on the right. Below the search bar, there is a text input field with the placeholder text "Go to file". The main content area displays a list of files and folders. The list starts with a folder icon and the text ".github". Below it is another folder icon and the text "atomic_red_team". Then, there is a folder icon and the text "atomics", which is expanded to show a list of sub-folders. The sub-folders are: "Indexes", "T1003.001", "T1003.002", "T1003.003", "T1003.004", "T1003.005", "T1003.006", "T1003.007", "T1003.008", "T1003", "T1006", "T1007", "T1010", "T1012", "T1014", "T1016", "T1018", "T1020", "T1021.001", "T1021.002", "T1021.003", "T1021.006", "T1027.001", "T1027.002", "T1027.004", "T1027", "T1030", "T1033", "T1036.003", "T1036.004", "T1036.005", "T1036.006", and "T1036". Each folder is represented by a blue folder icon and its name. The list is scrollable, as indicated by the vertical scrollbar on the right side.

atomic-red-team / atomics / T1070.002 / T1070.002.md

...

CircleCI Atomic Red Team doc... Generate docs from job=gener... 36d49de · 3 years ago History

PreviewCodeBlame117 lines (54 loc) · 2.57 KB

RawCopyDownloadMenu

T1070.002 - Clear Linux or Mac System Logs

Description from ATT&CK

Adversaries may clear system logs to hide evidence of an intrusion. macOS and Linux both keep track of system or user-initiated actions via system logs. The majority of native system logging is stored under the `/var/log/` directory. Subfolders in this directory categorize logs by their related functions, such as:(Citation: Linux Logs)

- `/var/log/messages` : General and system-related messages
- `/var/log/secure` or `/var/log/auth.log` : Authentication logs
- `/var/log/utmp` or `/var/log/wtmp` : Login records
- `/var/log/kern.log` : Kernel logs
- `/var/log/cron.log` : Crond logs
- `/var/log/maillog` : Mail server logs
- `/var/log/httpd/` : Web server access and error logs

Atomic Tests

- [Atomic Test #1 - rm -rf](#)
- [Atomic Test #2 - Overwrite Linux Mail Spool](#)
- [Atomic Test #3 - Overwrite Linux Log](#)

Atomic Test #1 - rm -rf







Delete system and audit logs

Supported Platforms: macOS, Linux

auto_generated_guid: 989cc1b1-3642-4260-a809-54f9dd559683

Attack Commands: Run with `sh` ! Elevation Required (e.g. root or admin)

```
sudo rm -rf /private/var/log/system.log*
sudo rm -rf /private/var/audit/*
```

- >  T1037.001
- >  T1037.002
- >  T1037.004
- >  T1037.005
- >  T1039
- >  T1040

Atomic Test #2 - Overwrite Linux Mail Spool

This test overwrites the Linux mail spool of a specified user. This technique was used by threat actor Rocke during the exploitation of Linux web servers.

Supported Platforms: Linux

auto_generated_guid: 1602ff76-ed7f-4c94-b550-2f727b4782d4

Inputs:

Name	Description	Type	Default Value
username	Username of mail spool	String	root

Attack Commands: Run with `bash` !

```
echo 0> /var/spool/mail/#{username}
```

Atomic Test #3 - Overwrite Linux Log

This test overwrites the specified log. This technique was used by threat actor Rocke during the exploitation of Linux web servers.

Supported Platforms: Linux

auto_generated_guid: d304b2dc-90b4-4465-a650-16ddd503f7b5

Inputs:

Name	Description	Type	Default Value
log_path	Path of specified log	Path	/var/log/secure

Attack Commands: Run with `bash` !

```
echo 0> #{log_path}
```