



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies



# Process Security and Access Rights

Article • 01/07/2022 • 8 contributors

[Feedback](#)

The Microsoft Windows security model enables you to control access to process objects. For more information about security, see [Access-Control Model](#).

When a user logs in, the system collects a set of data that uniquely identifies the user during the authentication process, and stores it in an [access token](#). This access token describes the security context of all processes associated with the user. The security context of a process is the set of credentials given to the process or the user account that created the process.

You can use a token to specify the current security context for a process using the [CreateProcessWithTokenW](#) function. You can specify a [security descriptor](#) for a process when you call the [CreateProcess](#), [CreateProcessAsUser](#), or [CreateProcessWithLogonW](#) function. If you specify **NULL**, the process gets a default security descriptor. The ACLs in the default security descriptor for a process come from the primary or impersonation token of the creator.

To retrieve a process's security descriptor, call the [GetSecurityInfo](#) function. To change a process's security descriptor, call the [SetSecurityInfo](#) function.

The valid access rights for process objects include the [standard access rights](#) and some process-specific access rights. The following table lists the standard access rights used by all objects.

 Expand table

Value	Meaning
<b>DELETE</b> (0x00010000L)	Required to delete the object.
<b>READ_CONTROL</b> (0x00020000L)	Required to read information in the security descriptor for the object, not including the information in the SACL. To read or write the SACL, you must request the <b>ACCESS_SYSTEM_SECURITY</b> access right. For more information, see <a href="#">SACL Access Right</a> .
<b>SYNCHRONIZE</b> (0x00100000L)	The right to use the object for synchronization. This enables a thread to wait until the object is in the signaled state.
<b>WRITE_DAC</b> (0x00040000L)	Required to modify the DACL in the security descriptor for the object.
<b>WRITE_OWNER</b> (0x00080000L)	Required to change the owner in the security descriptor for the object.

The following table lists the process-specific access rights.

 Expand table

Value	Meaning
<b>PROCESS_ALL_ACCESS</b> (STANDARD_RIGHTS_REQUIRED (0x000F0000L)   SYNCHRONIZE (0x00100000L)   0xFFFF)	All possible access rights for a process. <b>Server 2003 and Windows XP:</b> 1 <b>PROCESS_ALL_ACCESS</b> flag increments the process's access token. <b>Server 2008 and Windows Vista:</b> 1 compiled for Windows Server 2008. is run on Windows Server 2003 or Windows XP. <b>PROCESS_ALL_ACCESS</b> flag is to be used only if the function specifying this flag fails with the error code <b>ERROR_ACCESS_DENIED</b> . To avoid specifying the minimum set of access rights required for the operation. If <b>PROCESS_ALL_ACCESS</b> is used, set <b>_WIN32_WINNT</b> to the system targeted by your application. <code>#define _WIN32_WINNT _WIN32_WINNT_VISTA</code> more information, see <a href="#">Using the</a>
<b>PROCESS_CREATE_PROCESS</b> (0x0080)	Required to use this process as a parent process with <a href="#">PROC_THREAD_ATTRIBUTE_CREATE_PROCESS</a> .
<b>PROCESS_CREATE_THREAD</b> (0x0002)	Required to create a thread in the process.
<b>PROCESS_DUP_HANDLE</b> (0x0040)	Required to duplicate a handle in the process.
<b>PROCESS_QUERY_INFORMATION</b> (0x0400)	Required to retrieve certain information about the process, such as its token, exit code, and session ID (see <a href="#">OpenProcessToken</a> ).
<b>PROCESS_QUERY_LIMITED_INFORMATION</b> (0x1000)	Required to retrieve certain information about the process (see <a href="#">GetExitCodeProcess</a> , <a href="#">IsProcessInJob</a> , <a href="#">QueryFullProcessInformation</a> ). handle that has the <b>PROCESS_QUERY_INFORMATION</b> access right automatically granted. <b>PROCESS_QUERY_LIMITED_INFORMATION</b> access right. <b>Server 2003 and Windows XP:</b> 1 supported.

PROCESS_SET_INFORMATION (0x0200)	Required to set certain information such as its priority class (see <a href="#">SetPriorityClass</a> ).
PROCESS_SET_QUOTA (0x0100)	Required to set memory limits using <a href="#">SetProcessWorkingSetSize</a> .
PROCESS_SUSPEND_RESUME (0x0800)	Required to suspend or resume a process (see <a href="#">SuspendThread</a> ).
PROCESS_TERMINATE (0x0001)	Required to terminate a process (see <a href="#">TerminateProcess</a> ).
PROCESS_VM_OPERATION (0x0008)	Required to perform an operation on the virtual address space of a process (see <a href="#">VirtualProtect</a> and <a href="#">WriteProcessMemory</a> ).
PROCESS_VM_READ (0x0010)	Required to read memory in a process (see <a href="#">ReadProcessMemory</a> ).
PROCESS_VM_WRITE (0x0020)	Required to write to memory in a process (see <a href="#">WriteProcessMemory</a> ).
SYNCHRONIZE (0x00100000L)	Required to wait for the process to finish (see the <a href="#">wait functions</a> ).

To open a handle to another process and obtain full access rights, you must enable the **SeDebugPrivilege** privilege. For more information, see [Changing Privileges in a Token](#).

The handle returned by the [CreateProcess](#) function has **PROCESS\_ALL\_ACCESS** access to the process object. When you call the [OpenProcess](#) function, the system checks the requested [access rights](#) against the DACL in the process's security descriptor. When you call the [GetCurrentProcess](#) function, the system returns a pseudohandle with the maximum access that the DACL allows to the caller.

You can request the **ACCESS\_SYSTEM\_SECURITY** access right to a process object if you want to read or write the object's SACL. For more information, see [Access-Control Lists \(ACLs\)](#) and [SACL Access Right](#).

### Warning

A process that has some of the access rights noted here can use them to gain other access rights. For example, if process A has a handle to process B with **PROCESS\_DUP\_HANDLE** access, it can duplicate the pseudo handle for process B. This creates a handle that has maximum access to process B. For more information on pseudo handles, see [GetCurrentProcess](#).

## Protected Processes

Windows Vista introduces *protected processes* to enhance support for Digital Rights Management. The system restricts access to protected processes and the threads of protected processes.

The following standard access rights are not allowed from a process to a protected process:

- DELETE
- READ\_CONTROL
- WRITE\_DAC
- WRITE\_OWNER

The following specific access rights are not allowed from a process to a protected process:

- PROCESS\_ALL\_ACCESS
- PROCESS\_CREATE\_PROCESS
- PROCESS\_CREATE\_THREAD
- PROCESS\_DUP\_HANDLE
- PROCESS\_QUERY\_INFORMATION
- PROCESS\_SET\_INFORMATION
- PROCESS\_SET\_QUOTA
- PROCESS\_VM\_OPERATION

- `PROCESS_VM_READ`
- `PROCESS_VM_WRITE`

The `PROCESS_QUERY_LIMITED_INFORMATION` right was introduced to provide access to a subset of the information available through `PROCESS_QUERY_INFORMATION`.

---


## Feedback

Was this page helpful?



 Yes

 No

[Provide product feedback](#)  | [Get help at Microsoft Q&A](#)

 English (United States)

 Your Privacy Choices


 Theme 

[Manage cookies](#)


[Previous Versions](#)

[Blog](#) 

[Contribute](#)

[Privacy](#) 

[Terms of Use](#)

[Trademarks](#) 

© Microsoft 2024