


./ persistence-info.github.io



Recycle Bin COM Extension Handler

Location:

```
>> HKCR\CLSID\{645FF040-5081-101B-9F08-00AA002F954E}\shell\  
>> HKLM\SOFTWARE\Classes\CLSID\{645FF040-5081-101B-9F08-00AA002F954E}\shell\
```

Classification:

Criteria	Value
Permissions	Admin
Security context	User
Persistence type	Registry
Code type	EXE
Launch type	User initiated
Impact	Destructive
OS version	All OS versions
Dependencies	OS only
Toolset	Scriptable

Description:

Adding the “open\command” subkey to the Recycle Bin CLSID and adding a new verb for the “shell” key will execute the value stored in the

“\command” entry.

1. REG ADD “HKEY_LOCAL_MACHINE\SOFTWARE\Classes\CLSID\{645FF040-5081-101B-9F08-00AA002F954E}\shell\open\command” /ve /t REG_SZ /d “calc.exe” /f
2. REG ADD “HKEY_CLASSES_ROOT\CLSID\{645FF040-5081-101B-9F08-00AA002F954E}\shell\open\command” /ve /t REG_SZ /d “calc.exe” /f

References:

- >> <https://www.hexacorn.com/blog/2018/05/28/beyond-good-ol-run-key-part-78-2/>
- >> <https://gitlab.com/ORCA000/recyclebinpersistence>

Credits:

- >> [@Hexacorn](#)
- >> Entry added by [rootisareservedword](#)

See also:

Remarks: