

- Filter by title
- systeminfo

takeown

> tapicfg

taskkill

tasklist

tcmsetup

> telnet

tftp

time

timeout

title

tlntadm

tpmtool

tpmvscmgr

tracert

tracert

tree

tscon

tsdiscon

tsecimp

tskill

tsprof

type

typeperf

tzutil

unlodctr

ver

verifier

verify

vol

> vssadmin

waitfor

> wbadmin

> wdsutil

wecutil

wevtutil

where





 Download PDF

[Learn](#) / [Windows Server](#) /

systeminfo

Article • 02/03/2023 • [7 contributors](#) •

Applies  [Windows Server 2025](#),  [Windows Server 2022](#),  [Windows Server 2019](#),  [Windows Server 2016](#),  [Windows 11](#),  [Windows 10](#),  [Azure Stack HCI, versions 23H2 and 22H2](#)

 [Feedback](#)

In this article

- [Syntax](#)
- [Examples](#)
- [Related links](#)


Displays detailed configuration information about a computer and its operating system, including operating system configuration, security information, product ID, and hardware properties (such as RAM, disk space, and network cards).

Syntax

 Copy

```
systeminfo [/s <computer> [/u <domain>\<username> [/p <password>]]] [/fo {TABLE
```

Parameters

 Expand table

Parameter	Description
/s <computer>	Specifies the name or IP address of a remote computer (do not use backslashes). The default is the local computer.
/u <domain>\<username>	Runs the command with the account permissions of the specified user account. If /u is not specified, this command uses the permissions of the user who is currently logged on to the computer that is issuing the command.
/p <password>	Specifies the password of the user account that is specified in the /u parameter.
/fo <format>	Specifies the output format with one of the following values: <ul style="list-style-type: none">TABLE - Displays output in a table.LIST - Displays output in a list.CSV - Displays output in comma-separated values (.csv) format.
/nh	Suppresses column headers in the output. Valid when the /fo parameter is set to TABLE or CSV.
/?	Displays help at the command prompt.

Examples

To view configuration information for a computer named *Srvmain*, type:

 Copy

```
systeminfo /s srvmain
```

To remotely view configuration information for a computer named *Srvmain2* that is located on the *Maindom* domain, type:

 Copy

```
systeminfo /s srvmain2 /u maindom\hiropln
```

To remotely view configuration information (in list format) for a computer named *Srvmain2* that is located on the *Maindom* domain, type:

 Copy


```
systeminfo /s srvmain2 /u maindom\hiropln /p p@ssW23 /fo list
```


Related links

- [Command-Line Syntax Key](#)

Feedback

Was this page helpful?

 Yes

 No