Product ▾Solutions ▾Resources ▾Open Source ▾Enterprise ▾Pricing

🔍

Sign in

Sign up

📄 MichaelGrafnetter / DSInternals

Public

❤️ Sponsor

🔔 Notifications

🍴 Fork 254

★ Star 1.6k

<> Code

🗨 Issues 33

🔗 Pull requests 1


🎮 Actions

🛡 Security 1

📊 Insights

DSInternals / Src / DSInternals.Common / Data / DPAPI / DPAPIBackupKey.cs

⋮

MichaelGrafnetter Improved DPAPI credential parsing ✖

4efd132 · 7 months ago

🕒 History

📁 Files

🔗 39ee8a6

🔍 Go to file

> .github

> Documentation

> Keys

> Scripts

> Src

> .nuget

> Configuration

> DSInternals.Common.Test

> DSInternals.Common

> ADSI

> AzureAD

> Cryptography

> Data

> DPAPI

DPAPIBackupKey.cs

DPAPIBackupKeyType.cs

DPAPIObject.cs

KdsRootKey.cs

ProtectionKeyIdentifier.cs

RoamedCredential.cs

RoamedCredentialFlags.cs

RoamedCredentialType.cs

> Hello

> Principals

> Schema

```
1 namespace DSInternals.Common.Data
2 {
3     using DSInternals.Common.Cryptography;
4     using System;
5     using System.IO;
6     using System.Security.Cryptography;
7     using System.Security.Cryptography.X509Certificates;
8     using System.Text.RegularExpressions;
9
10    public class DPAPIBackupKey : DPAPIObject
11    {
12        private const int RSACertificateSizeOffset = RSAPrivateKeySizeOffset + sizeof(int);
13        private const int RSAPrivateKeyOffset = RSACertificateSizeOffset + sizeof(int);
14        private const string BackupKeyNameFormat = "G$BCKUPKEY_{0}";
15        private const string BackupKeyDNFormat = "CN=BCKUPKEY_{0} Secret,CN=System,{1}";
16        // Examples:
17        // CN=BCKUPKEY_P Secret,CN=System,DC=contoso,DC=com
18        // CN=BCKUPKEY_PREFERRED Secret,CN=System,DC=contoso,DC=com
19        // CN=BCKUPKEY_PREFERRED Secret\0ACNF:26c8edbb-6b48-4f11-9e13-9ddbcedab5a,CN=System,DC=contoso
20        // CN=BCKUPKEY_ac9e427c-fa85-4b78-8db1-771d94c03bad Secret,CN=System,DC=contoso
21        private const string BackupKeyDNRegex = "CN=BCKUPKEY_(.) Secret(\\\\\\\\0ACNF:[0-9a-fA-F-]{32})";
22        private const string PreferredLegacyKeyPointerName = "P";
23        private const string PreferredRSAKeyPointerName = "PREFERRED";
24        private const string TemporaryKeyContainerName = "DSInternals";
25        private const string RSAKeyFileNameFormat = "ntds_capi_{0}.pvk";
26        private const string RSACertFileNameFormat = "ntds_capi_{0}.cer";
27        private const string RSAP12FileNameFormat = "ntds_capi_{0}.pfx";
28        private const string LegacyKeyFileNameFormat = "ntds_legacy_{0}.key";
29        private const string UnknownKeyFileNameFormat = "ntds_unknown_{0}_{1}.key";
30        private const string KiwiCommandFormat = "REM Add this parameter to at least the following command line: {0}";
31        private const int PVKHeaderSize = 6 * sizeof(int);
32        private const uint PVKHeaderMagic = 0xb0b5f11e;
33        private const uint PVKHeaderVersion = 0;
34        private const uint PVKHeaderKeySpec = 1; // = AT_KEYEXCHANGE
35
36        public DPAPIBackupKey(DirectoryObject dsObject, DirectorySecretDecryptor pek)
37        {
38            // Parameter validation
39            Validator.AssertNotNull(dsObject, "dsObject");
40            Validator.AssertNotNull(pek, "pek");
41            // TODO: Test Object type
42
43            // Decrypt the secret value
44            byte[] encryptedSecret;
45            dsObject.ReadAttribute(CommonDirectoryAttributes.CurrentValue, out encryptedSecret);
46            byte[] decryptedBlob = pek.DecryptSecret(encryptedSecret);
47
48            // Initialize properties
49            this.Initialize(dsObject.DistinguishedName, decryptedBlob);
50        }
51
52        public DPAPIBackupKey(string distinguishedName, byte[] blob)
53        {
54            // Validate the input
55        }
56    }
57
```

📄 DNWithBinary.cs

📄 DSDataRepresentation.cd

📄 DirectoryObject.cs

📄 DistinguishedName.cs

📄 DistinguishedNameCompone...

📄 InstanceType.cs

> 📁 Exceptions

> 📁 Extensions

> 📁 Interop

> 📁 Properties

📄 DSInternals.Common.csproj

📄 DSInternals.Common.nuspec

📄 Validator.cs

📄 packages.config

> 📁 DSInternals.DataStore.Test

> 📁 DSInternals.DataStore

> 📁 DSInternals.PowerShell

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

// validate the input

Validator.AssertNotNullOrWhiteSpace(distinguishedName, "distinguishedName")

Validator.AssertNotNull(blob, "blob");

this.Initialize(distinguishedName, blob);

}

public DPAPIBackupKey(Guid keyId, byte[] blob)

{

Validator.AssertNotNull(blob, "blob");

this.KeyId = keyId;

this.Type = GetKeyType(blob);

this.Data = blob;

}

public override string FilePath

{

get

{

switch(this.Type)

{

case DPAPIBackupKeyType.RSAKey:

// .pvk file

return String.Format(RSAKeyFileNameFormat, this.KeyId);

case DPAPIBackupKeyType.LegacyKey:

// .key file

return String.Format(LegacyKeyFileNameFormat, this.KeyId);

case DPAPIBackupKeyType.Unknown:

// Generate an additional random ID to prevent potential filena

int rnd = new Random().Next();

return String.Format(UnknownKeyFileNameFormat, this.KeyId, rnd)

default:

// Saving pointers or other domain key types to files is not su

return null;

}

}

}

public override string KiwiCommand

{

get

{

return this.Type == DPAPIBackupKeyType.RSAKey ? String.Format(KiwiComma

}

}

public DPAPIBackupKeyType Type

{

get;

private set;

}

public string DistinguishedName

{

get;

private set;

}

public Guid KeyId

{

get;

private set;

}

public override void Save(string directoryPath)

{

// The target directory must exist

Validator.AssertDirectoryExists(directoryPath);

string fullPath;

switch (this.Type)

{

case DPAPIBackupKeyType.RSAKey:

// Parse the public and private keys

int privateKeySize = BitConverter.ToInt32(this.Data, RSAPrivateKeys

```
132         int certificateSize = BitConverter.ToInt32(this.Data, RSACertificateSizeOffset);
133
134         byte[] privateKey = this.Data.Cut(RSAPrivateKeyOffset, privateKeySize);
135         byte[] certificate = this.Data.Cut(RSAPrivateKeyOffset + privateKeySize, certificateSize);
136
137         // Create PVK file
138         fullPath = Path.Combine(directoryPath, this.FilePath);
139         byte[] pvk = EncapsulatePvk(privateKey);
140         File.WriteAllBytes(fullPath, pvk);
141
142         // Create PFX file
143         byte[] pkcs12 = CreatePfx(certificate, privateKey);
144         var pfxFile = String.Format(RSAP12FileNameFormat, this.KeyId);
145         fullPath = Path.Combine(directoryPath, pfxFile);
```

```
227         public static string GetKeyName(Guid keyId)
228         {
229             return String.Format(BackupKeyNameFormat, keyId);
230         }
231
232         public static string GetPreferredRSAKeyPointerDN(string domainDN)
233         {
234             return String.Format(BackupKeyDNFormat, PreferredRSAKeyPointerName, domainDN);
235         }
236
237         public static string GetPreferredLegacyKeyPointerDN(string domainDN)
238         {
239             return String.Format(BackupKeyDNFormat, PreferredLegacyKeyPointerName, domainDN);
240         }
241
242         private static string GetSecretNameFromDN(string distinguishedName)
243         {
244             var match = Regex.Match(distinguishedName, BackupKeyDNRegex);
245             bool success = match.Success && (match.Groups.Count >= 2);
246             return success ? match.Groups[1].Value : null;
247         }
248
249         private static byte[] CreatePfx(byte[] certificate, byte[] privateKey)
250         {
251             // The PFX export only works if the key is stored in a named container
252             var cspParameters = new CspParameters();
253             cspParameters.KeyContainerName = TemporaryKeyContainerName;
254             using (var keyContainer = new RSACryptoServiceProvider(cspParameters))
255             {
256                 // Make the key temporary
257                 keyContainer.PersistKeyInCsp = false;
258                 keyContainer.ImportCspBlob(privateKey);
259                 // Combine the private and public keys
260                 var combinedCertificate = new X509Certificate2(certificate);
261                 combinedCertificate.PrivateKey = keyContainer;
262                 // Convert to binary PFX
263                 return combinedCertificate.Export(X509ContentType.Pfx);
264             }
265         }
266
267         private static byte[] EncapsulatePvk(byte[] privateKey)
268         {
269             // We do a quick and dirty encapsulation of the private key into the PVK format
270             // See: http://www.drh-consultancy.demon.co.uk/pvk.html
271             // TODO: Extract PVK code to a distinct class.
272             int pvkSize = PVKHeaderSize + privateKey.Length;
273             byte[] pvk = new byte[pvkSize];
274
275             using (var stream = new MemoryStream(pvk, true))
276             {
277                 using (var writer = new BinaryWriter(stream))
278                 {
279                     // Write PVK header
280                     writer.Write(PVKHeaderMagic);
```

```
281             writer.Write(PVKHeaderVersion);
282             writer.Write(PVKHeaderKeySpec);
283             writer.Write((int)PrivateKeyEncryptionType.None);
284             writer.Write((int)0); // Size of salt
285             writer.Write(privateKey.Length);
286
287             // Write the actual data
288             writer.Write(privateKey);
289         }
290     }
291
292     return pvk;
293 }
294
295 private static DPAPIBackupKeyType GetKeyType(byte[] blob)
296 {
297     return (DPAPIBackupKeyType)BitConverter.ToInt32(blob, KeyVersionOffset);
298 }
299 }
300 }
```